


Area Coverage Paths

Area Coverage

- How do we get a robot to cover the whole area of an environment ?




Area Coverage

- No simple perfect solution
 - Many algorithms of various complexities
- Main **goals** are:
 - cover all reachable areas of environment
 - minimize amount of overlapping
- Robots are not perfectly accurate, approximate solution is ok
- We will discuss a rectangular grid-based solution
 - will provide an approximation only
 - will not attempt to minimize overlap




We will lay a grid of potential robot locations across the environment and then form a graph to travel along.



Grid Creation

- Overlay a 2D grid (i.e., graph of nodes & edges) of “robot-sized” circles touching adjacently vertically and horizontally:



Grid Creation Pseudocode

- The code for creating the grid is basic:

```
g = an empty graph
```

```
numRows = EnvironmentHeight / ROBOT_DIAMETER
```

```
numCols = EnvironmentWidth / ROBOT_DIAMETER
```

```
nodes = an empty 2D array that is numRows x numCols in size
```

```
FOR each row r DO
```

```
    FOR each column c DO
```

```
        nodes[r][c] = new node centered at that r and c
```

```
        add nodes[r][c] to g
```

```
FOR each row r DO
```

```
    FOR each column c (except the last one) DO
```


```
        add edge in g from add nodes[r][c] to nodes[r][c+1]
```

```
FOR each row r (except the last one) DO
```

```
    FOR each column c DO
```


```
        add edge in g from add nodes[r][c] to nodes[r+1][c]
```

Distance
between
vertices is
robot
diameter.



Grid Reduction

- Remove all vertices that represent robot positions that intersect with any obstacles:



Grid Reduction Pseudocode

- The reduced graph simply requires you to check if a node's circle intersects an obstacle:

```

FOR each node n of the graph DO {
  FOR each obstacle obj in the environment DO {
    IF the n's center lies within the obstacle THEN
      mark n as invalid
    FOR each edge e of obj DO {
      IF distance from n's center to e is <= ROBOT_RADIUS THEN
        mark n as invalid
    }
  }
}
FOR each invalid node n DO
  remove n from the graph
  
```

calculate $t = - \frac{(x_1 - x)(x_2 - x_1) + (y_1 - y)(y_2 - y_1)}{(x_2 - x_1)^2 + (y_2 - y_1)^2}$



IF $(0 \leq t \leq 1)$ THEN

$$d = \frac{|(x_2 - x_1)(y_1 - y) - (y_2 - y_1)(x_1 - x)|}{\sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}}$$

OTHERWISE **d** is the smallest of these two:

$$\sqrt{(x_1 - x)^2 + (y_1 - y)^2}$$

$$\sqrt{(x_2 - x)^2 + (y_2 - y)^2}$$



Spanning Tree


- Compute a *spanning tree* in the graph (shown in red):
 - represents a path that covers all the vertices.

In this example, this is root of the spanning tree.

Many graph edges have been removed

There are many possible spanning trees. This one follows an up, right, down, left ordering traversal.

This algorithm assumes that no object lies between adjacent vertex circles so that robot can travel between them without collision:



Spanning Tree Pseudocode

- Spanning tree can be any traversal of the graph that reaches all nodes. It will depend on which edges are traversed first at each vertex.

By marking a node as "visited", we can avoid processing that node again and this is essential to stop the recursion.

```
computeSpanningTree(G) {
  FOR each node n of graph G DO
    mark n as "not visited"
  startNode = any node in G
  dummyEdge = an edge from startNode to itself
  computeSpanningTreeFrom(startNode, dummyEdge)

  edges = all edges that are not marked as part of tree
  FOR each edge e in edges DO
    remove e from G
}
```

```
computeSpanningTreeFrom(aNode, incomingEdge) {
  IF aNode was already visited THEN
    RETURN


  mark aNode as "visited"
  mark incomingEdge as part of the spanning tree

  FOR each edge e connected to aNode DO
    otherNode = node of edge e that is not aNode
    computeSpanningTreeFrom(otherNode, e)
}
```

The ordering of edges in this example is right, down, left, up.


startNode

Each vertex has its edges in some order. Neighbours are visited in that order.




Various Spanning Trees


Up/Right/Down/Left




Right/Down/Left/Up




Right/Down/Left/Up




Left/Right/Up/Down



Up/Down/Left/Right




Left/Right/Up/Down



Spanning Tree Traversal

- Need to compute a path in the spanning tree, recursively.
- Each edge needs to be travelled on twice, which means that each vertex needs to be added to the path as many times as it has edges.
- Path in this example will have 43 points on it.
- Robot travels from point to point.



Spanning Tree Traversal

- To travel along spanning tree, we need to compute a path:

We build up a **path** in the tree which will represent the ordering of nodes to visit by the robot.

Each time we arrive at a **aNode** that has no previous value set, it is a new node in the path, so add it to the **path**.

Make sure that the path goes back to the previous node.

```
computeSpanningTree(G) {  
    ... Compute spanning as before  
  
    FOR each node n of graph G DO  
        set previous of n to NULL  
        set path to be an empty list  
        dummyEdge = an edge from startNode to itself  
        computeCoveragePathFrom(startNode, dummyEdge)  
    }  
  
    computeCoveragePathFrom(aNode, incomingEdge) {  
        IF previous of aNode is not NULL THEN  
            RETURN  
  
        add aNode's location to the path  
  
        set previous of aNode to node at other end of incomingEdge  
  
        FOR each neighbour neigh of aNode DO {  
            edge = the edge that connects aNode and neigh  
            computeCoveragePathFrom(neigh, edge)  
        }  
        add location of aNode's previous to the path  
    }  
}
```

Instead of "visited" boolean, keep the previous node that is the node's parent in the spanning tree.

We will assume that the robot can travel from its start location to the start node without collision.


path is a global variable

Set **aNode**'s previous to be the other end of the edge that we came in on.

Ensures that we are following spanning tree on way back from recursion.

Spanning Tree Coverage

- Traveling along the spanning tree will cover most of the environment (except around borders of obstacles):




More Efficient Travelling

- Currently, robot travels back to root, but this is not necessary.
- Better if we stop when travelled on each edge once.
- Result is that path is shorter with less points.

Robot stops here now. It does not need to go back to the root node.


Path has only 33 points ... which is 23% shorter!



More Efficient Travelling


- Can shorten even more if we visit the smaller branches before the longer ones.
- Results in less travel since we don't have to travel a second time on the longer branches
- Requires us to visit the shorter branches of the tree first

Path has only 28 points now ... which is 35% shorter than original!



Tree Height

- If we want to visit certain branches of the spanning tree in some specific order (e.g., smallest first), then we need to compute the height of the tree at various nodes.



Computing Tree Height

- Start by assigning heights of 0 to all nodes.
- Then simply traverse all nodes recursively, setting their height to be the height of their maximum child's height

A leaf of the tree has height of zero.

All other nodes have at least a height of 1.

Add the height of the maximum child to **aNode**'s current height in the tree already.

```
computeNodeHeightsFrom(aNode) {  
    mark aNode as visited  
  
    IF aNode has just 1 edge THEN  
        set aNode's height to 0  
    ELSE  
        set aNode's height to 1  
  
    max = 0  
    FOR each edge e of aNode DO {  
        otherNode = node of edge e that is not aNode  
  
        IF otherNode was not yet visited THEN {  
            computeNodeHeightsFrom(otherNode)  
            IF height of otherNode > max THEN  
                max = height of otherNode  
        }  
    }  
    set height of aNode to its current height + max  
}
```

Get all children's heights recursively and keep the maximum.

Traversal By Tree Height

- To traverse according to the branch sizes, we need to sort the neighbouring nodes by height and visit in that order:

Same code as before, but now we get the neighbours and sort them by increasing order of height so that we can visit the smaller branches first.

```
computeCoveragePathFrom(aNode, incomingEdge) {  
    IF previous of aNode is not NULL THEN  
        return  
  
    add aNode's location to the path  
  
    set previous of aNode to node at other end of incomingEdge  
  
    { neighbours = a list of aNode's neighbours  
      sort neighbours by increasing order of their precomputed height  
  
      FOR each neighbour neigh in neighbours DO {  
          edge = the edge that connects aNode and neigh  
          computeCoveragePathFrom(neigh, edge)  
      }  
      add location of aNode's previous to the path  
    }  
}
```



**Start the
Lab ...**