

Modules and Imports



modules and imports

- Import syntax variations
- Namespaces and variable lookups
- `sys.modules` and the import cache
- Module level functionality: `__dir__` and `__getattr__`
- Packages and the filesystem
- Relative import syntax
- Module reloading (how to do it and why not to do it)
- Circular imports, avoiding and fixing
- Executable modules and packages
- `__import__` and `importlib`

Modules

- Every Python source file is a module

```
# foo.py
def grok(a):
    ...
def spam(b):
    ...
```

- The import statement loads and executes a module

```
import foo

a = foo.grok(2)
b = foo.spam('Hello')
...
```

Module Objects

- Modules are objects

```
>>> import foo
>>> foo
<module 'foo' from 'foo.py'>
```

- A namespace for the definitions inside

```
>>> foo.grok(2)
```

- Actually a layer on top of dictionaries (module globals)

```
>>> foo.__dict__['grok']
<function grok at 0x7f733a914670>
```

Special Variables

- A few special variables defined automatically in a module

<code>__file__</code>	<i># Name of the source file</i>
<code>__name__</code>	<i># Name of the module</i>
<code>__doc__</code>	<i># Module docstring</i>

- We can use `__name__` to tell if we have been imported or are running as the main module (the main script or program)

Import Implementation

- Import in a nutshell (pseudocode)

```
import types
```

```
def import_module(name):  
    # locate the module and get source code  
    filename = find_module(name)  
    code = open(filename).read()  
    # Create the enclosing module object  
    mod = types.ModuleType(name)  
    # Run it  
    exec(code, mod.__dict__, mod.__dict__)  
    return mod
```


- Import finds and executes the module source file to create the module object

import Statement

- import executes the entire module

```
# bar.py  
import foo
```

- After the import the module name is a reference to the module object inside the module that did the import



Module Cache

- Each module is loaded only once
- Repeated imports return a reference to the same module object
- `sys.modules` is a dict of all loaded modules

```
>> import sys
>>> list(sys.modules)
['sys', 'builtins', '_frozen_importlib', '_imp',
 '_warnings', '_io', 'marshal', 'posix',
 '_frozen_importlib_external', '_thread', ... ]
```


Import Caching

- Import pseudocode with module caching

```
import types
import sys

def import_module(name):
    # Check for cached module
    if name in sys.modules:
        return sys.modules[name]
    filename = find_module(name)
    code = open(filename).read()
    mod = types.ModuleType(name)
    sys.modules[name] = mod
    exec(code, mod.__dict__, mod.__dict__)
    return mod
```

- There are many more details but this is most of the work
- See the `importlib` module for more

from module import

- Import selected symbols with "from module import ..."

```
# bar.py  
from foo import grok
```

```
grok(2)
```

- Useful for frequently used names
- Slightly faster as it avoids the attribute lookup of "foo.grok"

Note: This doesn't change how import works, the entire source file is still executed and the module cached but you only have references to the specific objects imported

from module import *

- Imports *all* the symbols from a module

```
# bar.py
from foo import *

grok(2)
spam('Hello')
...
```

- "import *" *doesn't* import private names from a module, those that start with an underscore (_)
- Not recommended! Namespace pollution!
- Useful for the interactive interpreter and for namespace packages (__init__.py)

Module Reloading

- Modules can sometimes be reloaded

```
>>> import foo
...
>>> import importlib
>>> importlib.reload(foo)
<module 'foo' from 'foo.py'>
```

- Reloading re-executes the source code over the top of the existing module dictionary

```
# pseudocode
def reload(mod):
    code = open(mod.__file__, 'r').read()
    exec(code, mod.__dict__, mod.__dict__)
    return mod
```

Module Reloading Dangers

- Problem: Existing instances of classes will still have a reference to the old class object
- Problem: Anything imported with "from module import name" will still use the old definition
- Problem: Anything that uses super or does type checks will fail
- Reloading is not for production code but very useful for development where modules change rapidly

Locating Modules

- When looking for modules Python first looks in the same directory as the source file that's executing the import
- If the module isn't found there `sys.path` contains a list of places that Python checks (in order)

```
>>> import sys
>>> sys.path
['', '/usr/lib/python310.zip', '/usr/lib/python3.10',
'/usr/lib/python3.10/lib-dynload',
'/home/michael/.local/lib/python3.10/site-packages',
'/usr/local/lib/python3.10/dist-packages',
'/usr/lib/python3/dist-packages']
```

Module Search Path

- `sys.path` contains the search paths for import
- You can manually adjust it if you need to

```
import sys  
sys.path.append('/project/foo/pyfiles')
```

- Paths can also be added via environment variables

```
$ export PYTHONPATH=/home/user/code
```

- The directory added will now be at the start of `sys.path` when you run Python

Organising Libraries

- It is standard practise for Python libraries to be organised as a hierarchical set of modules that sit under a top level package name

```
packagename  
packagename.foo  
packagename.bar  
packagename.utils  
packagename.utils.spam  
packagename.utils.grok  
packagename.parsers  
packagename.parsers.xml  
packagename.parsers.json  
...
```


Creating a Package

- To create the module library hierarchy, organize files on the filesystem in a directory with the desired structure

```
packagename/  
    foo.py  
    bar.py  
    utils/  
        spam.py  
        grok.py  
    parsers/  
        xml.py  
        json.py  
    ...
```

Creating a Package

- Optionally add `__init__.py` files to each directory

```
packagename/  
    __init__.py  
    foo.py  
    bar.py  
    utils/  
        __init__.py  
        spam.py  
        grok.py  
    parsers/  
        __init__.py  
        xml.py  
        json.py  
  
    ...
```

Using a Package

- You can now import from your package

```
import packagename.foo  
import packagename.parsers.xml  
from packagename.parsers import xml
```

- Almost everything should work as it did before but your import statements can have multiple levels

Fixing Relative Imports

- Relative imports between submodules don't work

spam/

__init__.py

foo.py

bar.py

```
# bar.py
import foo    # import fails
```

- The issue: resolving name clashes between submodules and top level packages

spam/

__init__.py

os.py

bar.py

```
# bar.py
import os    # ??? stdlib?
```

- imports are always "absolute" (from the top level)

Absolute Imports

- One approach: always use absolute imports

```
spam/  
    __init__.py  
    foo.py  
    bar.py
```

- Example:

```
# bar.py  
from spam import foo
```

- Notice the use of the top level package name

Package Relative Imports

- Consider a package

spam/

 __init__.py

 foo.py

 bar.py

 grok/

 __init__.py

 blah.py

- Package relative imports

bar.py

from . import foo

from .foo import name

Imports ./foo.py

Load a specific name

from .grok import blah

Imports ./grok/blah.py

Package Environment

- Packages define a few useful variables

```
__package__      # Name of the enclosing package  
__path__         # Search path for subcomponents
```

- Example:

```
>>> import xml  
>>> xml.__package__  
'xml'  
>>> xml.__path__  
['/usr/local/lib/python3.10/xml']
```

- Useful if code needs to know about its enclosing environment

`__init__.py` Usage

- What are you supposed to do in these files?
- `__init__.py` provides the top level namespace for the package/sub-package
- Main use: stitching together multiple files (the submodules) into a "unified" top-level import

Tip: Don't put lots of code in `__init__.py`, use it to create the namespace, use helpfully named modules for the actual code.

Module Assembly

- Consider two submodules in a package

spam/
foo.py



```
# foo.py  
  
class Foo:  
    ...  
    ...
```

bar.py



```
# bar.py  
  
class Bar:  
    ...  
    ...
```

- Suppose we wanted to combine them for import

Module Assembly

- Combine in `__init__.py`

spam/
 `foo.py`



```
# foo.py  
  
class Foo:  
    ...  
    ...
```

`bar.py`



```
# bar.py  
  
class Bar:  
    ...  
    ...
```

`__init__.py`



```
# __init__.py  
  
from .foo import Foo  
from .bar import Bar
```

Module Assembly

- Users see a single unified top-level package

```
import spam
```

```
foo = spam.Foo()  
bar = spam.Bar()  
...
```

- The internal split across submodules, the implementation details, are hidden from the user

Case Study

- The "asyncio" module
- It's actually a package with many sub-components
- If we look in the `__init__.py` we can see all the submodules that provide the implementation

This relies on each of the submodules having an `__all__` variable.

```
from .base_events import *
from .coroutines import *
from .events import *
from .exceptions import *
from .futures import *
from .locks import *
from .protocols import *
from .runners import *
from .queues import *
...
```

Controlling Exports

- Submodules should define `__all__`

```
# foo.py
```

```
__all__ = ['Foo']
```

```
class Foo:
```

```
    ...
```

```
# bar.py
```

```
__all__ = ['Bar']
```

```
class Bar:
```

```
    ...
```

- This controls 'from module import *'
- Which makes it easier to create `__init__.py`

```
# __init__.py
```

```
from .foo import *
```

```
from .bar import *
```

```
__all__ = [ *foo.__all__, *bar.__all__ ]
```

Module Splitting

- Suppose you have a large module

```
# spam.py
```


```
class Foo:  
    ...  
    ...
```

```
class Bar:  
    ...  
    ...
```

- You want to refactor this into multiple files for sanity
- But you want to keep the external API the same as the single file for backwards compatibility

Module Splitting

- Step 1: turn it into a directory with multiple files



- Split the code across the submodules as you wish
- Fix any dependencies between submodules with appropriate imports (not relative imports!)

Module Splitting

- Step 2: stitch back together in `__init__.py`

spam/
foo.py



```
# foo.py  
  
class Foo:  
    ...  
    ...
```

bar.py



```
# bar.py  
  
class Bar:  
    ...  
    ...
```

`__init__.py`



```
# __init__.py  
  
from .foo import Foo  
from .bar import Bar
```


Circular Imports

- Circular imports are a common problem within submodules, modules that depend on each other

```
# spam/base.py  
  
from . import child  
  
class Base:  
    ...
```

```
# spam/child.py  
  
from .base import Base  
  
class Child(Base):  
    ...
```

- Follow the control-flow
- Definition order matters!

Circular Imports

- Moving the import can fix the problem

```
# spam/base.py
```

```
class Base:
```

```
    ...
```

```
from . import child
```

```
# spam/child.py
```

```
from .base import Base
```

```
class Child(Base):
```

```
    ...
```

- Alternative fixes:
 - An "inner import" inside a function/method
 - Refactoring the shared code into a third module
- Better yet, avoid circular imports!

Main Modules

- `python -m module`
- Runs the specified module as a script

```
spam/  
    __init__.py  
    foo.py  
    bar.py
```

```
$ python -m spam.foo      # runs spam/foo.py
```

- Can be used to ship tools and applications as part of a package
- Many standard library modules can be run this way (e.g. `unittest`, `gzip`, `idlelib`, `timeit`, `asyncio`, `antigravity`, etc)

Main Entry Point

- `__main__.py` designates an entry point
- Makes the package itself executable

spam/

`__init__.py`

`__main__.py`

starting module

`foo.py`

`bar.py`

\$ python -m spam

runs spam/__main__.py

- Can also be done with subpackages, ship multiple tools within a package!