Adapting Network Intrusion Detectors Only Through Trusted Evidence: Evidence-Retracted Novelty Priors for Label-Efficient Zero-Day Detection

An Vo Le Thien[a,*]

[a]*Faculty of Computer Science, The Sai Gon International University, Ho Chi Minh City, Viet Nam*

ARTICLE INFO

Keywords:
network intrusion detection
zero-day attacks
concept drift
poisoning
active learning
density-ratio estimation

ABSTRACT

Network intrusion detection systems (NIDS) in production must detect attack families never seen in training, tolerate benign traffic drift, and adapt with the few labels that analysts can provide. Detectors that adapt by absorbing the traffic they accept can be steered by slow poisoning, while continual learners that avoid this depend on hundreds of labels per day. We propose ERNP (Evidence-Retracted Novelty Prior), a detector whose only adaptation channel is the retraction of a structured novelty prior where analysts have confirmed benign traffic. ERNP estimates a density ratio between benign evidence and the union of attack evidence and a prior built by partially swapping features between benign flows; unlabelled traffic never enters the model. We prove that retraction is local and bounded by analyst errors, and that detection far from confirmed evidence is preserved up to a computable factor. On four temporally split benchmarks, five seeds and a causal protocol, ERNP has the best mean rank against five recent detectors (SSF, OWAD, CADE, Trident, MemStream), with mean F1 0.867 against 0.671 for the strongest. With 25 labels per day it outperforms SSF using 200–400, and a counterfactual that feeds ERNP its own verdicts instead of analyst evidence collapses from 0.74 to 0.07 zero-day payload recall under controlled poisoning. It has the best AUROC and AUPRC on three of the four datasets, and it is the only detector that no other detector beats in both zero-day recall and false-positive rate on any dataset. On ToN, whose benign traffic changes regime from day to day, it has the best F1 and MCC when the same labels are delivered every 4 h rather than once a day. ERNP does not win everywhere: it is on par with CADE on unsampled CIC-IDS2017, and it degrades when analysts mislabel 10% or more of the queried alert groups.

1. Introduction

A machine-learning NIDS is trained on the traffic of a past period and operates on a stream in which new attack families appear, benign behaviour drifts, and a security operations centre (SOC) can inspect only a small fraction of the alerts [1, 26]. Three requirements follow. The detector must (i) alert on attack families absent from its training data, (ii) adapt to benign drift so that the false-positive rate (FPR) stays within analyst capacity, and (iii) do both with a small daily labelling budget.

Adaptation is where these requirements collide. Streaming detectors such as MemStream [2] and Kitsune [17] update their model of normality with the traffic they accept. This follows benign drift without labels, but it also lets an adversary move the model: traffic that drifts slowly from benign towards malicious is accepted at every step and eventually becomes normal. This "boiling-frog" vulnerability has been analysed for centroid and PCA-based detectors [13, 22]. Label-driven continual learners such as SSF [30] and OWAD [11] do not absorb unlabelled traffic in the same way, but they re-train on hundreds of analyst labels per adaptation window. Drift detectors such as CADE [29] and open-set classifiers such as Trident [31] rank novel samples well but do not follow benign drift, which appears as a high FPR at a fixed operating point (Section 6.2).

This paper starts from a simple observation. A detector that separates benign traffic from an explicit model of *novelty* can adapt in the opposite direction to the usual one. Instead of *enlarging* its model of normality with accepted traffic, it can *shrink* its model of novelty, and only where an analyst has confirmed that the traffic is benign. We call the resulting detector ERNP (Evidence-Retracted Novelty Prior). ERNP trains a classifier to separate benign evidence from attack evidence and from a structured novelty prior of synthetic flows obtained by swapping a random subset of features between benign flows. Each day, alerts are grouped and the analyst labels one representative per group. Groups confirmed benign retract the prior mass in their neighbourhood; groups confirmed malicious are added to the attack evidence. The unlabelled stream never enters the model.

We ask five research questions.

1. **RQ1 (zero-day detection):** under a causal protocol with benign drift and equal label budgets, does ERNP detect unseen attack families better than five recent detectors?
2. **RQ2 (poisoning):** when an adversary targets the adaptation process by slow poisoning, is ERNP more robust than these detectors, and does its robustness come from the trusted-evidence rule?
3. **RQ3 (label efficiency):** how many labels per day does ERNP need compared with label-using detectors?
4. **RQ4 (mechanism):** which components produce the performance, and do the stated properties hold on real traffic?
5. **RQ5 (deployment):** how sensitive is ERNP to its hyperparameters and to analyst errors, and what does it cost?

The contributions are the following.

1. **Adaptation through trusted evidence only.** We formulate NIDS adaptation as the retraction of a novelty prior by analyst-confirmed benign evidence, which makes the detector invariant to the volume and duration of

*Corresponding author
volethienank16@siu.edu.vn (An Vo Le Thien)
ORCID(s):

unlabelled traffic. We prove that retraction is local and that its corruption is bounded by the number of analyst errors (Proposition 1), that local false alarms vanish where benign evidence accumulates (Proposition 2), and that detection far from benign evidence is preserved up to a computable factor (Proposition 3).

2. **A structured novelty prior** that keeps every benign marginal and breaks cross-feature dependencies. Compared with the uniform negative sampling of Sipple [25] and with a product-of-marginals prior, it raises F1 by 0.26–0.29 on average (Section 6.5).
3. **A fidelity-checked comparison.** We compare against five recent detectors on four temporally split benchmarks, under a causal protocol and at a common 1% FPR operating point. The implementations reproduce the published results of CADE and OWAD on the authors' own data. We add each baseline's best configuration, classical references, a classifier-plus-active-labelling ablation, an IP-novelty leakage check and an unsampled-scale check (Sections 5–6).
4. **Label efficiency and a causal account of robustness.** ERNP with 25 labels per day outperforms SSF with 200–400. A counterfactual that replaces analyst evidence by ERNP's own verdicts isolates the mechanism: under controlled poisoning its zero-day payload recall drops from 0.74 to 0.07. The settings in which ERNP does not win are reported as results (Section 7).

The novelty claim is methodological. Classification against a reference distribution and learning from analyst feedback are both known (Section 2). What is new is *what* adapts and *how*. Three comparisons make this precise.

- **Negative sampling** [25] contrasts data with a *fixed* reference distribution. In ERNP the reference is the object that adapts, and only trusted evidence can change it.
- **Active learning and active anomaly discovery** [4, 23] use labels to update the *detector*: a classifier or ensemble weights. ERNP uses them to update the *novelty hypothesis*, and the update can only remove prior mass where benign traffic is confirmed. The same classifier, features and alert-group labels without the prior (GBM+AL) lose 0.26–0.29 F1 on average (Section 6.5).
- **Continual learners** (SSF, OWAD) and streaming detectors update their model of normality. Whatever enters that update, whether accepted traffic or pseudo-labels, gives an adversary a lever. ERNP's monotone, evidence-only update makes the detector a function of the labelled history alone. Proposition 1 proves this, and the counterfactual isolates it: the same model fed its own verdicts instead of analyst evidence loses its zero-day payload recall (0.74→0.07).

We state the guarantees of this rule, measure the conditions under which they hold, and report where the method fails.

The remainder of the paper is organised as follows. Section 2 positions the work. Section 3 states the problem and threat model. Section 4 describes ERNP and its properties. Section 5 gives the protocol, and Section 6 reports RQ1–RQ5. Sections 7 and 8 discuss deployment meaning and threats to validity, followed by the conclusion.

2. Related work

2.1. Zero-day and open-world NIDS

Sommer and Paxson identified the closed-world assumption as a central obstacle for anomaly-based intrusion detection [26]. CADE learns a contrastive latent space and flags samples far from every known class by a median-absolute-deviation rule [29]. Trident trains one autoencoder per known class and rejects unknown traffic with extreme-value thresholds [31]. FOSS targets fine-grained unknown classes under variable legitimate traffic [32]; its public repository does not contain the core implementation, so it could not be included. These detectors rank novelty well but do not adapt their notion of normality on the stream.

2.2. Adaptation under drift

MemStream keeps a memory of accepted samples [2], and Kitsune trains an ensemble of autoencoders online [17]. OWAD detects normality shift with a calibrated permutation test, explains it, and fine-tunes the detector on a labelled subset [11]. SSF performs continual learning with strategic selection and forgetting under a per-window label budget and pseudo-labels [30]. Temporal evaluation is essential for such methods [1, 20]; we therefore adopt a temporal zero-day protocol and a causal predict-then-learn order.

2.3. Poisoning of self-updating detectors

Online detectors that learn from what they accept can be steered by traffic that is accepted at each step. Kloft and Laskov analysed this scenario for online centroid detectors [13], Rubinstein et al. demonstrated it for PCA-based traffic anomaly detection [22], and Biggio et al. studied poisoning of supervised learners [3]. ERNP avoids this class of attacks by construction: its model changes only through analyst-confirmed evidence.

2.4. Classification against a reference distribution

Steinwart et al. cast anomaly detection as classification between data and a reference measure [27], and Hempstalk et al. combined a reference density with a class-probability estimator [12]. Noise-contrastive estimation and the density-ratio literature show that a probabilistic classifier between data and noise recovers their density ratio [10, 28]. Sipple used uniform negative sampling with a classifier to detect device failures [25]. ERNP builds on this principle in two ways. Its reference distribution is *structured*, so the classifier learns violations of cross-feature dependencies rather than the empty corners of the feature space. Its reference is also *not static*: trusted evidence retracts it over time.

2.5. Learning from analyst feedback

Active learning [23] and active anomaly discovery (AAD) [4, 5] incorporate expert labels into an anomaly detector; AAD re-weights the components of an ensemble on a static dataset

Table 1
Positioning against representative detector families.

Family	What adapts	Follows benign drift	Unlabelled traffic can move the model	Labels used
Streaming AD (MemStream, Kitsune)	model of normality, from accepted traffic	yes	yes	none
Drift / open-set detectors (CADE, Trident)	nothing on the stream	no	no	training only
Shift adaptation (OWAD)	detector fine-tuned on explained shift	yes	partly	per detected shift
Continual learning (SSF)	classifier, from selected and pseudo-labelled samples	yes	partly (pseudo-labels)	per window
Active anomaly discovery (AAD)	ensemble weights, static data	no	no	per query
Negative sampling [25]	nothing	no	no	none
ERNP (this work)	**novelty prior, retracted by confirmed benign groups**	**yes**	**no (Proposition 1)**	**per alert group**

so that confirmed anomalies rank higher. ERNP differs in the object it updates (the novelty distribution) and in the setting (a drifting stream). Its update can only *remove* prior mass around confirmed benign traffic, which yields the guarantee of Proposition 1. The feedback-driven alternative closest to ERNP shares its classifier, features and labelling procedure but drops the prior ("GBM+AL"); it is reported as a baseline.

2.6. Positioning

Table 1 summarises the distinction.

3. Problem formulation and threat model

Flow records $x \in \mathbb{R}^d$ arrive in periods $t = 0, 1, \ldots$ (days unless stated otherwise). The first period(s) form the *anchor*: benign flows and the attack families observed in it are labelled, and these families are *known*. Every family whose first occurrence falls after the anchor is *zero-day*. In each later period the detector decides on every flow *before* it receives any label for that period (causal protocol). After the period, an analyst labels at most B items chosen by the detector.

Threat model. The adversary controls the content, volume and timing of traffic from hosts it has compromised. It may inject arbitrarily many unlabelled flows over arbitrarily long periods, including traffic that drifts slowly from a host's normal behaviour towards an attack payload. It does not control the analyst's labels. This last assumption is relaxed in Proposition 1(iii) and in Section 6.6, where analysts make errors.

4. The ERNP detector

4.1. Density-ratio detector

Let P_t be the benign evidence at period t: the benign anchor flows plus the flows of alert groups the analyst confirmed benign. Let A_t be the attack evidence: the known-attack anchor flows plus the flows of groups confirmed malicious. Let q_t be the novelty prior (Section 4.2). ERNP fits a probabilistic classifier g_t with the weighted log-loss

$$\min_g \tfrac{1}{2}\,\mathbb{E}_{P_t}[\ell(g(x),0)] + \tfrac{1}{2}\,\mathbb{E}_{A_t}[\ell(g(x),1)] + \tfrac{1}{2}\,\mathbb{E}_{q_0}\big[r_t(x)\,\ell(g(x),1)\big], \tag{1}$$

where $r_t(x) \in [0,1]$ is the fraction of prior mass retained at x (Section 4.3) and $q_t = q_0 r_t$. Retraction removes mass and never renormalises it. With b_t and a_t the densities of P_t and A_t, the population minimiser is the posterior $\eta_t = (a_t + q_0 r_t)/(b_t + a_t + q_0 r_t)$, and the alert score is its logit

$$s_t(x) = \log \frac{a_t(x) + q_0(x)\, r_t(x)}{b_t(x)}, \qquad \text{alert iff } s_t(x) > \tau, \tag{2}$$

a log density ratio between "attack or novel" and "benign", which is the noise-contrastive view of anomaly detection [10, 27]. The classifier is histogram gradient boosting [9, 19] with 300 iterations and learning rate 0.1. The threshold τ is set once, at 1% FPR on a held-out part of the anchor benign flows, and never re-tuned.

4.2. Structured novelty prior

A uniform reference in a box around the data [25] places most of its mass far from any traffic, where no attack lives either. ERNP builds q_0 from the benign evidence itself. For a benign flow x and a donor benign flow x' drawn uniformly, each feature is replaced independently with probability ρ:

$$\tilde{x}_j = \begin{cases} x'_j & \text{with probability } \rho, \\ x_j & \text{otherwise.} \end{cases} \tag{3}$$

Every benign marginal is preserved, but the joint structure of a random subset of features is broken: a port bucket of one service combined with the byte count and fan-out of another, or a context count incompatible with the flow's own size. Attack traffic typically lives in such inconsistent combinations. We use $\rho = 0.3$ and as many prior samples as benign evidence ($m = 1$).

4.3. Evidence-gated retraction

Let $\mathcal{E}_t$ be the flows of alert groups the analyst has confirmed benign up to period t. The retained prior fraction is

$$r_t(x) = 1 - \exp\left(-\frac{d(x,\mathcal{E}_t)^2}{2\epsilon^2}\right), \qquad d(x,\mathcal{E}_t) = \min_{e\in\mathcal{E}_t} \|x - e\|, \tag{4}$$

with $r_t \equiv 1$ while $\mathcal{E}_t$ is empty. The bandwidth ϵ is the 90th percentile of nearest-neighbour distances among the benign reference flows, computed from data and not tuned. Because $\mathcal{E}_t$ only grows, $r_t(x)$ is non-increasing in t at every x.




Figure 1: ERNP, one period. The detector is a density-ratio classifier between benign evidence and the union of attack evidence and a structured novelty prior. After the period, alerts are grouped and the analyst labels one representative per group. Only analyst-confirmed groups change the model: benign groups enter the benign evidence and retract the prior in their neighbourhood, and attack groups enter the attack evidence. The unlabelled stream, however large, never enters the model (Proposition 1).

Algorithm 1 ERNP, one period t

Require: g_t, τ, evidence $P_t, A_t, \mathcal{E}_t$, prior sample $Q \sim q_0$, budget B

```
score every flow of period t with s_t; alert on {x : s_t(x) > τ}
group the alerts into k = min(B, #alerts) clusters; query one representative per cluster
for each group G with analyst label y do
    if y = benign then P_{t+1} ← P_t ∪ G; E_{t+1} ← E_t ∪ G
    else A_{t+1} ← A_t ∪ G
    end if
end for
weight each x̃ ∈ Q by r_{t+1}(x̃); refit g_{t+1} on Eq. (1); keep τ
```

4.4. Operating procedure

Algorithm 1 gives one period. Alerts are grouped into at most B clusters by k-means, and the analyst labels the representative closest to each centroid. The label is applied to the whole group, following alert-grouping practice in SOC triage. The stricter variant, in which only the representative is used, is reported in Sections 6.2 and 6.5. After each period the classifier is refitted on sliding windows of the most recent evidence (at most 80,000 benign and 40,000 attack flows).

4.5. Properties

The properties are stated for the population detector of Eq. (2), which the boosted-tree classifier approximates; proofs are in Appendix A, and Section 6.5 checks them on traffic.

Proposition 1 (Adaptation only through trusted evidence)**.** *Let U be any sequence of unlabelled flows, of any volume and duration. (i) s_t depends on the stream only through $(P_t, A_t, \mathcal{E}_t)$; if no label is issued, $s_t = s_0$ for all t, whatever U is. (ii) For $\delta \in (0,1)$, the region where more than a fraction δ of the prior mass has been retracted lies in $\bigcup_{e \in \mathcal{E}_t} \mathcal{B}\big(e, \epsilon\sqrt{2\ln(1/\delta)}\big)$. (iii) If the analyst confirms as benign m groups that contain attack flows, each of diameter at most Δ, the points whose retention is reduced by more than δ* because of these errors *lie in m balls of radius $\Delta + \epsilon\sqrt{2\ln(1/\delta)}$.*

Part (i) separates ERNP from self-updating detectors, whose training set at $t+1$ contains the flows accepted at t and can therefore be steered by unlabelled traffic alone [13]. Parts (ii) and (iii) give the price: every unit of adaptation is tied to a labelled group, and every analyst error has a local footprint.

Proposition 2 (Local convergence)**.** *For every x,*

$$s_t(x) \leq \log\Big(a_t(x) + q_0(x)\,\frac{d(x,\mathcal{E}_t)^2}{2\epsilon^2}\Big) - \log b_t(x). \qquad (5)$$

Hence, if benign evidence accumulates at x ($d(x,\mathcal{E}_t) \to 0$) and $a_t(x) < e^{\tau} b_t(x)$, x is eventually accepted.

Proposition 3 (Zero-day preservation)**.** *If $d(z,\mathcal{E}_t) \geq c\,\epsilon$ for some $c > 0$ and $b_t(z) \leq b_0(z)$ (benign evidence is added elsewhere), then*

$$s_t(z) \;\geq\; \log\frac{q_0(z)}{b_0(z)} + \log\big(1 - e^{-c^2/2}\big). \qquad (6)$$

A flow ranked by the initial prior with margin $\log\frac{q_0(z)}{b_0(z)} > \tau - \log(1 - e^{-c^2/2})$ therefore stays detected; the additional margin is 0.145 nats at $c = 2$ and 0.011 nats at $c = 3$.

4.6. Implementation cost

Scoring is one pass through the boosted trees; the prior weights need one nearest-neighbour query of the prior sample against $\mathcal{E}_t$ per refit. A refit takes a few seconds to one minute on a 12-core CPU, and inference on a fixed batch of 10^5 flows runs at 112k–304k flows per second on the same CPU. No GPU is needed (Table 9).

5. Experimental design

5.1. Datasets and temporal protocol

Table 2 lists the four datasets:

- CIDDS-001 [21]: internal OpenStack traffic over four weeks;
- NF-ToN-IoT-v3 [16, 18]: IoT testbed traffic in NetFlow v3 features;
- CIC-IDS2017 [8, 24] and CSE-CIC-IDS2018 [15]: the corrected releases, with “Attempted” flows relabelled benign as the maintainers recommend.

Table 2
Datasets (seed-0 streams). Known families occur in the anchor; zero-day families first occur afterwards. †Not used during method development.

Dataset	Original flows	Flows/seed	Features	Known fam.	Zero-day fam.	Stream days	Attack %
CIDDS-001	31.3M	301k	30	3	1	26	10.9
NF-ToN-IoT-v3	27.5M	301k	62	1	8	6	53.6
CIC-IDS2017†	2.1M	301k	100	7	8	2	36.3
CSE-CIC-IDS2018	63.2M	402k	100	4	10	8	4.0

The anchor is the first two days of CIDDS-001, the first day of ToN, Monday–Wednesday of CIC-IDS2017 and 14–16 February of CSE-CIC-IDS2018. Each seed draws a different uniform sample of the original data (300,000 flows, 400,000 for CSE-CIC-IDS2018) that keeps at least 600 flows of every rare family. Features are each dataset's flow statistics plus ten temporal-context features computed on the *full* data before sampling: counts and bytes per source, destination and pair in 10 s and 120 s windows, and fan-out. IP addresses are never used as features. CIC-IDS2017 is a held-out dataset: it took no part in the design of ERNP or in the choice of its hyper-parameters, which used the other three.

5.2. Baselines and provenance

All baselines run their official code through thin wrappers and share our features, anchor and streams. Label-using methods get $B = 200$ labels per day. Table 3 records provenance and the fidelity checks. The fidelity checks gave the following results:

- **CADE:** on the IDS2018 split shipped with CADE, our port reproduces Table 3 of [29], with precision/recall/F1 of 0.989/0.934/0.958 against 0.98/0.93/0.96.
- **OWAD:** re-running its NIDS demonstration (Kyoto-2006) through our wrapper gives AUC 0.947/0.807/0.815 against 0.947/0.807/0.813 in the authors' notebook.

Three references complete the comparison:

- **GBM+AL:** ERNP without the prior, i.e. the same classifier, features and alert-group labelling on benign versus attack evidence;
- **classical detectors:** *k*NN distance, Isolation Forest [14] and an autoencoder;
- **new-IP:** a leakage check that alerts on every flow whose source address never appeared in the anchor. It scores F1 = 0 on CIDDS-001 and CIC-IDS2017, so results there cannot come from address novelty.

5.3. Metrics and statistical analysis

We report F1, the Matthews correlation coefficient (MCC) and FPR at each method's own decision rule. We also report *zero-day recall at 1% FPR*, measured at a common operating point: each method's 99th score percentile on the benign flows of the stream. This makes methods with built-in decision rules comparable (SSF's $p > 0.5$, Trident's EVT threshold). MCC is reported because F1 rewards alerting on everything when attacks are frequent: on ToN, where 54% of flows are attacks, an alert-all detector reaches F1 $\approx$ 0.70 and MCC $\approx$ 0. To separate the quality of a detector's scores from the choice of its operating point, we also report AUROC, AUPRC and attack recall at the same common 1% FPR point, all computed on the stream. Finally, we report the recall of zero-day families at each method's own decision rule next to the FPR that it costs, because F1 weighs zero-day families only by their share of the attack flows.

Table 3
Baselines and provenance.

Method	Provenance	Deviation / check
SSF [30]	official code	20 epochs per window (authors' NSL-KDD value); also run with 180 and native 20k-flow windows
OWAD [11]	official code	demo reproduced (AUC 0.815 vs. 0.813)
CADE [29]	PyTorch port of the TF1 code	Table 3 reproduced (F1 0.958 vs. 0.96)
Trident [31]	official code	85th-percentile fallback when EVT fails on duplicate-heavy data
MemStream [2]	official class	also with frozen normalisation
GBM+AL, *k*NN, IForest, AE	this study	references
new-IP	this study	leakage check

Seeds are sub-samples of the same dataset, not independent datasets. We therefore report per-dataset mean differences with 95% bootstrap intervals over seeds [7], and a Friedman test over datasets [6], rather than pooling dataset–seed pairs. Table 12 in Appendix B maps each question to its experiment. The software environment was Python 3.12.7, NumPy 2.4.6, scikit-learn 1.9.1 and PyTorch 2.6.0 (CUDA 12.4), on a 12-core CPU with an RTX 3050 GPU; part of RQ2/RQ3 ran on an RTX A5000.

6. Results

6.1. Main findings at a glance

Table 4 gives the answer to each question with its principal estimate. Where ERNP does not win, the table says so.

6.2. RQ1: zero-day detection

Table 5 reports the three detection metrics per dataset. ERNP has the best mean F1 (0.867), MCC (0.753) and zero-day recall at 1% FPR (0.677). Among the five detectors, the strongest averages are 0.671 F1 and 0.563 MCC for SSF and 0.625 zero-day recall for CADE; the *k*NN reference reaches 0.807 F1 and 0.603 MCC. The per-dataset differences (Table 13, Appendix B) favour ERNP, with an interval above zero, in 18 of 20 dataset–baseline pairs. The two exceptions are SSF on CIDDS-001 (-0.009) and Trident on ToN (-0.088); Trident

Table 4
RQ answers and quantitative evidence.

RQ	Principal estimate	Answer
RQ1	Mean F1 0.867 vs. 0.671 (SSF); MCC 0.753 vs. 0.563; zero-day recall@1%FPR 0.677 vs. 0.625 (CADE); CI above 0 in 18/20 dataset–baseline pairs; best configurations 0.907 vs. 0.775; held-out CIC-IDS2017 0.970 F1; unsampled CIC-IDS2017 0.940 vs. CADE 0.959; best AUROC/AUPRC on 3 of 4 datasets; only method Pareto-optimal in zero-day recall vs. FPR on all 4; ToN at 4 h updates 0.742 F1 / 0.452 MCC vs. 0.535/0.174 (SSF)	Best average detector and best mean rank, not uniformly: SSF is ahead in F1 on CIDDS-001 (−0.009) at the cost of zero-day recall (0.262 vs. 0.625), OWAD ranks ToN better, and ERNP is on par with CADE at full scale
RQ2	Zero-day payload recall 0.74 (200 labels/day) and 0.75 (25) vs. SSF 0.79 and 0.63; FPR 0.5–0.8% vs. 30–36% (Trident), 93% (MemStream); counterfactual 0.07–0.09	No detector is absorbed at 200 labels/day; at equal small budgets ERNP keeps its payload recall and SSF does not; the trusted-evidence rule is the cause
RQ3	$B = 25$: 0.905/0.665 F1 vs. SSF at $B = 400$: 0.873/0.510 (CSE-CIC-IDS2018/ToN)	About one eighth of the labels of the strongest continual learner
RQ4	Prior removed or replaced: −0.26 to −0.29 F1; retraction kernel shape: ±0.01; self-evidence: −0.50 on ToN	The structured prior and the evidence source carry the method; the kernel shape does not
RQ5	$\lvert\Delta F1\rvert \leq 0.014$ on CIDDS-001 and CSE-CIC-IDS2018 except $\epsilon \times 0.5$ (−0.047); 10% label flips: CSE-CIC-IDS2018 0.910→0.840 (SSF 0.861); 112k–304k flows/s on CPU	Robust to hyper-parameters on stable data; analyst errors are the main weakness

Table 5
RQ1: mean±std over five seeds, causal protocol, $B = 200$. Bold: best in the column within each metric. GBM+AL: same classifier, features and alert-group labelling without the novelty prior.

Method	CIDDS-001	NF-ToN-IoT-v3	CIC-IDS2017†	CSE-CIC-IDS2018	Mean
F1					
ERNP (ours)	0.976±0.002	0.610±0.021	0.970±0.005	**0.914±0.011**	**0.867**
SSF	**0.985±0.001**	0.369±0.053	0.472±0.041	0.858±0.010	0.671
OWAD	0.945±0.006	0.488±0.002	0.001±0.000	0.003±0.000	0.359
CADE	0.917±0.037	0.348±0.193	0.932±0.016	0.288±0.100	0.621
Trident	0.533±0.192	**0.698±0.002**	0.880±0.006	0.329±0.016	0.610
MemStream	0.128±0.011	0.319±0.025	0.715±0.073	0.148±0.037	0.328
GBM+AL	0.781±0.323	0.663±0.038	0.686±0.137	0.183±0.077	0.578
*k*NN	0.947±0.007	0.487±0.020	**0.980±0.001**	0.815±0.003	0.807
MCC					
ERNP (ours)	0.973±0.002	0.176±0.028	0.953±0.007	**0.911±0.011**	**0.753**
SSF	**0.984±0.001**	-0.063±0.055	0.471±0.031	0.860±0.009	0.563
OWAD	0.940±0.006	0.357±0.001	-0.052±0.002	-0.011±0.001	0.309
CADE	0.910±0.040	-0.315±0.268	0.894±0.025	0.348±0.088	0.459
Trident	0.520±0.208	-0.004±0.010	0.814±0.009	0.397±0.027	0.432
MemStream	-0.400±0.145	-0.103±0.034	0.639±0.070	0.123±0.034	0.065
GBM+AL	0.750±0.378	**0.529±0.036**	0.585±0.207	0.229±0.081	0.523
*k*NN	0.941±0.007	-0.316±0.028	**0.969±0.001**	0.820±0.002	0.603
Zero-day recall @1%FPR					
ERNP (ours)	0.657±0.021	0.110±0.119	**0.968±0.018**	**0.973±0.008**	**0.677**
SSF	0.578±0.036	0.002±0.003	0.748±0.044	0.878±0.018	0.551
OWAD	0.008±0.004	0.148±0.003	0.001±0.000	0.002±0.000	0.040
CADE	**0.685±0.033**	0.076±0.108	0.847±0.101	0.892±0.040	0.625
Trident	0.669±0.019	0.015±0.015	0.522±0.135	0.243±0.288	0.362
MemStream	0.058±0.106	0.021±0.011	0.378±0.176	0.038±0.040	0.124
GBM+AL	0.441±0.209	**0.238±0.082**	0.626±0.074	0.867±0.051	0.543
*k*NN	0.377±0.037	0.029±0.020	0.607±0.019	0.671±0.078	0.421

alerts on 99.9% of ToN flows and has MCC ≈ 0 there. ERNP has the best mean rank (1.50), but with four datasets the Friedman test is not significant ($p = 0.079$), and we do not claim uniform superiority. On the held-out CIC-IDS2017, ERNP reaches 0.970 F1 and 0.968 zero-day recall at 1% FPR, against 0.932 and 0.847 for CADE, the next best of the five. The *k*NN reference is marginally higher in F1 (0.980) but detects fewer zero-day flows at 1% FPR.

Why strong rankers fail at the operating point. On CIDDS-001 and the CIC datasets, CADE, Trident and SSF rank anomalies well (AUROC 0.96–0.997), but they fail at a fixed low FPR under drift:

- CADE reaches 7–21% FPR and Trident 15–28% on the CIC datasets, as benign drift moves flows away from the training centroids.
- Causal SSF misses zero-day families on CIC-IDS2017 (recall 0.31), because its classifier is supervised on known families.
- OWAD's autoencoder has AUROC 0.66–0.68 on the CIC datasets and detects almost nothing at 1% FPR.

ERNP's prior makes zero-day flows score high by construction, and retraction absorbs benign drift only where analysts have confirmed it.

Score quality independent of the decision rule. Table 6 separates how well each detector ranks attacks above benign flows from where it places its threshold. ERNP has the highest AUROC and AUPRC on CIDDS-001, CIC-IDS2017 and CSE-CIC-IDS2018, and the highest mean on all three score metrics.

- On CIDDS-001, ERNP ranks at least as well as SSF (AUROC 0.998 vs. 0.996, AUPRC 0.995 vs. 0.992) and detects more attacks (recall 0.990 vs. 0.979). Its F1 gap of 0.009 comes from the operating point: its fixed 1%-FPR threshold gives a stream FPR of 0.47%, against 0.10% for SSF.

Table 6
RQ1, score quality independent of each method's decision rule: AUROC, AUPRC and attack recall at 1% stream FPR (mean±std over five seeds, causal protocol, $B = 200$). Bold: best per column within each metric.

Method	CIDDS-001	NF-ToN-IoT-v3	CIC-IDS2017†	CSE-CIC-IDS2018	Mean
AUROC					
ERNP (ours)	**0.998±0.000**	0.636±0.039	**0.995±0.001**	**0.989±0.005**	**0.904**
SSF	0.996±0.000	0.520±0.039	0.809±0.004	0.960±0.007	0.821
OWAD	0.953±0.008	**0.782±0.001**	0.681±0.002	0.656±0.048	0.768
CADE	0.996±0.001	0.586±0.157	0.989±0.002	0.971±0.016	0.886
Trident	0.996±0.001	0.329±0.085	0.977±0.011	0.958±0.033	0.815
MemStream	0.260±0.024	0.501±0.021	0.749±0.076	0.208±0.066	0.430
AUPRC					
ERNP (ours)	**0.995±0.000**	0.648±0.085	**0.994±0.000**	**0.975±0.006**	**0.903**
SSF	0.992±0.001	0.504±0.016	0.862±0.006	0.899±0.015	0.814
OWAD	0.932±0.007	**0.827±0.001**	0.455±0.002	0.055±0.007	0.567
CADE	0.994±0.001	0.643±0.150	0.982±0.004	0.911±0.034	0.883
Trident	0.976±0.010	0.460±0.087	0.932±0.025	0.442±0.181	0.703
MemStream	0.089±0.016	0.532±0.028	0.746±0.058	0.042±0.009	0.352
Attack recall @1%FPR (all families)					
ERNP (ours)	0.991±0.000	0.110±0.119	**0.968±0.018**	**0.973±0.008**	**0.760**
SSF	0.988±0.001	0.002±0.003	0.748±0.044	0.878±0.018	0.654
OWAD	0.910±0.010	**0.148±0.003**	0.001±0.000	0.002±0.000	0.265
CADE	**0.991±0.001**	0.076±0.108	0.847±0.101	0.892±0.040	0.702
Trident	0.971±0.021	0.015±0.015	0.522±0.135	0.243±0.288	0.438
MemStream	0.011±0.017	0.021±0.011	0.378±0.176	0.038±0.040	0.112

- On ToN, OWAD ranks best (AUROC 0.782 vs. 0.636 for ERNP). Its threshold, however, recalls only 34% of the attacks, so its F1 stays at 0.488 against 0.610 for ERNP. ToN is the one dataset where another detector scores better than ERNP; Section 7 identifies the cause.

Zero-day recall against false alarms. F1 weighs zero-day families by their share of the attack flows, which is small on CIDDS-001. Table 7 therefore reports, at each method's own decision rule, the recall of zero-day families together with the FPR it costs. A method is marked when no other method has both higher zero-day recall and lower FPR on that dataset. ERNP is the only detector that is Pareto-optimal on all four datasets. Every baseline is dominated on at least one: SSF on ToN, CADE on ToN and CSE-CIC-IDS2018, Trident on CSE-CIC-IDS2018, OWAD and MemStream on three datasets. Among the detectors with FPR below 1%, ERNP has the highest zero-day recall on CIDDS-001 (0.625, against 0.262 for SSF and 0.000 for OWAD) and on CSE-CIC-IDS2018 (0.966 vs. 0.758).

On CIDDS-001 this is exactly the trade-off behind SSF's higher F1. To show it, we reran ERNP on all four datasets and five seeds with its threshold at 0.2% instead of 1% holdout FPR.

- On CIDDS-001, its FPR fell from 0.47% to 0.10% and its F1 rose from 0.976 to 0.984, level with SSF (0.985). Its zero-day recall, however, fell from 0.625 to 0.093, below SSF's 0.262. The benign flows that ERNP flags there share their score range with the zero-day brute-force flows, so removing those false alarms removes the zero-day detections with them.
- On ToN, F1 fell from 0.610 to 0.441.
- On the CIC datasets, F1 rose (0.970→0.977 and 0.914→0.945) at a small cost in zero-day recall (0.981→0.974 and 0.966→0.944).

No single operating point is best on every dataset. We keep the 1% point, which was fixed before the evaluation.

Matched update cadence. The main protocol refits every method once per day. A SOC triages alerts continuously, so Table 8 also runs every adaptive method with the same 200 labels per day delivered every 4 h and every 1 h. The update-free detectors are listed once, because the cadence does not affect them. At 4 h, ERNP has the best F1 and MCC on ToN (0.742/0.452, against 0.535/0.174 for SSF, 0.386/0.294 for OWAD and 0.698/0.001 for alert-all Trident), and on CIC-IDS2017 and CSE-CIC-IDS2018. CIDDS-001 remains the exception: SSF is ahead by 0.006 F1 at 4 h, for the operating-point reason given above. Faster updates do not help every method: OWAD degrades on ToN, from 0.488 F1 at 24 h to 0.087 at 1 h.

Each baseline at its best configuration. To rule out an unfavourable configuration, Table 14 (Appendix B) takes each method's best mean F1 over every configuration we ran:

- SSF with 20 and 180 epochs, with its native 20k-flow windows, and with 4 h and 1 h updates;
- OWAD with 24 h, 4 h and 1 h updates;
- MemStream with original and frozen normalisation.

ERNP remains first on average (0.907 against 0.775 for SSF and 0.807 for kNN), but not on every dataset.

Scale. The main streams sample 1–14% of the original data. On the unsampled CIC-IDS2017 (2.1M flows, three seeds; Table 9), every detector changes. SSF improves markedly (0.472→0.749 F1), and ERNP and CADE are on par (0.940 vs. 0.959 F1; 0.859 vs. 0.789 zero-day recall at 1% FPR). The other detectors stay below 0.87. Sampling did not create ERNP's advantage over most baselines, but it did understate CADE and SSF (Section 8).

Table 7
Zero-day recall (ZD rec.) and FPR at each method's own decision rule (mean over five seeds, causal protocol, $B = 200$). ⋆: Pareto-optimal on that dataset, i.e. no other method has both higher zero-day recall and lower FPR.

	CIDDS-001		NF-ToN-IoT-v3		CIC-IDS2017†		CSE-CIC-IDS2018	
Method	ZD rec.	FPR %	ZD rec.	FPR %	ZD rec.	FPR %	ZD rec.	FPR %
ERNP (ours)	0.625	0.47⋆	0.600	42.35⋆	0.981	2.39⋆	0.966	0.63⋆
SSF	0.262	0.10⋆	0.298	35.58	0.309	0.02⋆	0.758	0.04⋆
OWAD	0.000	0.15	0.336	4.81⋆	0.001	0.85	0.002	0.60
CADE	0.696	2.11⋆	0.348	65.42	0.986	7.41⋆	0.935	21.28
Trident	0.844	28.23⋆	0.999	99.93⋆	0.999	15.44⋆	0.964	16.33
MemStream	0.964	93.07⋆	0.245	33.80	0.589	2.85	0.129	2.43

Table 8
RQ1 at matched update cadence: the same 200 labels per day, delivered every 24, 4 or 1 h (mean over seeds 0–2). CADE, Trident and MemStream do not use labels and are cadence-independent. Bold: best per column.

		CIDDS-001		NF-ToN-IoT-v3		CIC-IDS2017†		CSE-CIC-IDS2018	
Method	Update	F1	MCC	F1	MCC	F1	MCC	F1	MCC
ERNP	24 h	0.977	0.974	0.620	0.191	0.971	0.954	0.910	0.908
ERNP	4 h	0.978	0.975	0.742	0.452	0.972	0.956	**0.922**	**0.920**
ERNP	1 h	0.975	0.972	**0.753**	**0.481**	**0.974**	**0.959**	0.921	0.920
SSF	24 h	**0.985**	**0.983**	0.378	-0.050	0.454	0.457	0.860	0.863
SSF	4 h	0.984	0.982	0.535	0.174	0.512	0.502	0.854	0.858
OWAD	24 h	0.943	0.937	0.488	0.357	0.001	-0.051	0.003	-0.011
OWAD	4 h	0.944	0.939	0.386	0.294	0.001	-0.036	0.002	-0.007
OWAD	1 h	0.913	0.908	0.087	0.074	0.001	-0.016	0.001	-0.003
CADE	–	0.925	0.918	0.292	-0.439	0.939	0.904	0.326	0.382
Trident	–	0.493	0.474	0.698	0.001	0.882	0.818	0.339	0.412
MemStream	–	0.125	-0.377	0.320	-0.107	0.706	0.628	0.130	0.107

6.3. RQ2: poisoning of the adaptation process

We inject a controlled slow-poisoning campaign into CIDDS-001. Over seven days, a compromised host's flows move from its own benign behaviour to a real attack payload by linear interpolation in feature space, at 30 flows per hour; the payload is then sent for two days. The host is either the initiator of the traffic or a server that launders it as a responder. The payload is DoS (a known family) or brute force (zero-day). We measure recall on the final payload and the FPR. Interpolated feature vectors need not correspond to protocol-valid traffic, so the experiment is a stress test of the adaptation channel rather than an end-to-end attack.

Table 10 shows three findings.

1. **No method is absorbed at 200 labels per day.** SSF and OWAD learn the ramp as malicious from their labels, and CADE and Trident do not adapt. Not adapting has a price in FPR: 2.2% for CADE, 30–36% for Trident and 93% for MemStream.
2. **At an equal, small budget, only ERNP holds.** With 25 labels per day, ERNP keeps its zero-day payload recall (0.75), whereas SSF falls from 0.79 to 0.63.
3. **The trusted-evidence rule is the cause.** The counterfactual ERNP-self uses the same model but takes its own non-alerted flows as benign evidence, the usual self-updating channel. Its zero-day payload recall collapses to 0.07–0.09, which isolates the evidence source, rather than the classifier or the features, as the reason for the robustness.

Across nine combinations of ramp duration (3/7/14 days) and rate (10/30/100 flows per hour), ERNP's brute-force payload recall ranges from 0.59 to 0.91, and ERNP is never absorbed.

6.4. RQ3: label efficiency

Figure 2(a,b) varies the daily budget on the two datasets with the most zero-day families and the strongest drift. ERNP with 25 labels per day (0.905 F1 on CSE-CIC-IDS2018, 0.665

Table 9
Left: unsampled CIC-IDS2017 (three seeds). Right: cost on the sampled streams, one job at a time on a 12-core CPU and an RTX 3050 (mean over CIDDS-001, ToN and CSE-CIC-IDS2018). An ERNP refit per period takes 3–55 s.

	CIC-IDS2017, full (2.1M flows, 3 seeds)			Cost (sampled streams)	
Method	F1	MCC	ZD recall@1%FPR	Initial training (s)	Peak RAM (MB)
ERNP (ours)	0.940±0.043	0.909±0.062	0.859±0.142	37	973
SSF	0.749±0.201	0.715±0.182	0.779±0.001	1722	1731
OWAD	0.608±0.003	0.567±0.002	0.543±0.004	24	1967
CADE	0.959±0.012	0.935±0.019	0.789±0.282	709	1629
Trident	0.564±0.247	0.355±0.316	0.359±0.314	522	1582
MemStream	0.864±0.039	0.788±0.058	0.086±0.043	15	1575

Table 10
RQ2: payload recall / FPR (%) under slow poisoning on CIDDS-001, five seeds. init/resp: compromised initiator/responder; DoS: known payload; BF: zero-day brute force; B: labels per day.

Method	B	init/DoS	resp/DoS	init/BF	resp/BF
ERNP	200	1.000 / 0.5	1.000 / 0.5	0.740 / 0.6	0.746 / 0.6
ERNP	25	1.000 / 0.7	1.000 / 0.6	0.750 / 0.8	0.746 / 0.7
ERNP-self (counterfactual)	–	1.000 / 0.5	1.000 / 0.5	0.070 / 0.5	0.088 / 0.5
SSF	200	0.999 / 0.4	1.000 / 0.2	0.815 / 0.3	0.764 / 0.4
SSF	25	1.000 / 0.2	1.000 / 0.2	0.633 / 0.1	0.630 / 0.2
OWAD	200	0.993 / 0.1	0.993 / 0.1	0.000 / 0.1	0.000 / 0.1
OWAD	25	0.993 / 0.1	0.993 / 0.1	0.000 / 0.1	0.000 / 0.1
CADE	–	1.000 / 2.2	1.000 / 2.2	0.704 / 2.2	0.704 / 2.2
Trident	–	0.999 / 30.3	0.999 / 36.0	0.850 / 36.0	0.850 / 36.0
MemStream	–	0.528 / 93.4	0.554 / 93.4	1.000 / 93.1	1.000 / 93.1




Figure 2: (a,b) RQ3: F1 against the daily label budget (seeds 0–2, mean±std); OWAD detects almost nothing on CSE-CIC-IDS2018 at any budget. (c) RQ5: F1 when each returned label is flipped with probability p (blue: ERNP; red: SSF, run at $p = 10\%$).

on ToN) exceeds SSF with 200 labels per day (0.860, 0.378) and with 400 (0.873, 0.510). It also consumes fewer labels, because it asks for at most one label per alert group. ERNP's F1 is nearly flat for $B \geq 25$: the prior carries most of the detection ability, and the labels mainly remove false alarms. Without any online labels ($B = 0$) ERNP loses 0.09 F1 on CSE-CIC-IDS2018 and 0.36 on ToN.

6.5. RQ4: ablations and properties

Table 11 reports F1 differences from ERNP. The novelty prior is the dominant component. Removing it (GBM+AL), or replacing it by Sipple's uniform prior or by a product of marginals, costs 0.26–0.29 F1 on average and up to 0.76 on CSE-CIC-IDS2018. The retraction kernel is secondary: its shape matters little (hard ball: −0.001), and removing retraction costs 0.017 on average and 0.093 on CSE-CIC-IDS2018. The *source* of the evidence, by contrast, is decisive: the self-evidence counterfactual loses 0.50 on ToN, and it suffers the payload collapse seen in RQ2. What matters is which evidence retracts the prior, not the kernel that retracts it. ToN is the exception: GBM+AL and the other prior variants are slightly better there, because its benign traffic changes regime every day (Section 7).

Propositions on traffic. Replaying the evidence sets, Figure 3 compares, for zero-day flows binned by their distance to the nearest confirmed benign evidence, the recall of ERNP with that of ERNP without online labels. At distances of 2ϵ or more, ERNP's recall is as high or higher on every dataset (ToN, $\geq 4\epsilon$: 0.66 against 0.23), as Proposition 3 predicts. Recall drops only close to confirmed evidence, which is the local footprint of Proposition 1(ii).

Group labels. One label per group propagates to about 12,000–100,000 flows per run, with 0.3–4.8% attack flows inside groups labelled benign. With representative-only evidence (the label semantics of SSF), ERNP loses 0.034 F1 on average, mostly on ToN, and remains first on average.

6.6. RQ5: sensitivity, analyst errors and cost

One-at-a-time variations of ρ, prior mass m and bandwidth ϵ (Table 15, Appendix B) change F1 by at most 0.014 on CIDDS-001 and CSE-CIC-IDS2018. The one exception is halving ϵ, which costs 0.047 on CSE-CIC-IDS2018. ToN is more sensitive (up to +0.038). All defaults were fixed before the evaluation and not tuned on these streams. Replacing gradient boosting by a random forest costs 0.26 on ToN, which indicates that classifier calibration matters where drift is strong.

Analyst errors. Proposition 1(iii) predicts that analyst errors corrupt ERNP locally. Figure 2(c) flips each returned label with probability p:

- ERNP is robust on CIDDS-001 and CIC-IDS2017 (−0.024 and −0.004 F1 at $p = 20\%$).
- It degrades on CSE-CIC-IDS2018 (0.910→0.840 at $p = 10\%$, below SSF's 0.861) and on ToN.

Table 11
RQ4: ΔF1 of each variant relative to ERNP (five seeds).

Variant (ΔF1 vs. ERNP)	CIDDS-001	NF-ToN-IoT-v3	CIC-IDS2017†	CSE-CIC-IDS2018	Mean
No novelty prior (GBM+AL)	-0.195	+0.054	-0.284	-0.730	-0.289
Uniform prior (Sipple)	-0.209	+0.084	-0.262	-0.757	-0.286
Product-of-marginals prior	-0.105	+0.068	-0.267	-0.747	-0.263
No retraction	-0.006	+0.035	-0.004	-0.093	-0.017
Hard retraction	-0.004	+0.014	-0.000	-0.013	-0.001
Representative-only evidence	-0.007	-0.121	+0.002	-0.009	-0.034
Per-flow features only	-0.003	-0.285	-0.033	-0.025	-0.086
No online labels	-0.028	-0.345	+0.000	-0.098	-0.118
Self-evidence (counterfactual)	-0.008	-0.502	+0.002	-0.027	-0.134




Figure 3: Zero-day recall versus distance to the nearest confirmed benign evidence, in units of ϵ (bins with at least five flows; mean over five seeds). Far from evidence, ERNP keeps at least the recall of the same detector without online labels, as Proposition 3 predicts; the dashed line is the retained prior fraction r_t at the bin centre.

- SSF is nearly insensitive, because its labels only reweight a supervised classifier. In ERNP, a wrong benign label retracts the prior over an entire alert group.

In the poisoning scenario at $p = 10\%$, ERNP's zero-day payload recall still matches SSF's (0.70–0.74 against 0.67–0.72). Label noise is ERNP's main weakness.

Cost. ERNP's initial training takes 37 s on average, against 1,722 s for SSF and 709 s for CADE. It uses the least memory and needs no GPU (Table 9).

7. Discussion

7.1. How the five RQs form one argument

RQ1 establishes that a detector which contrasts benign evidence with a structured prior of novelty ranks and thresholds unseen families better, on average, than detectors that model normality or known classes alone. RQ4 attributes this to the prior. RQ2 and RQ3 then show that the way the prior is adapted matters as much as the prior itself. Retraction driven only by analyst-confirmed groups keeps zero-day recall under poisoning at a budget where a continual learner loses it, and it needs about an eighth of that learner's labels. The self-evidence counterfactual closes the argument: the same model fed its own verdicts collapses.

7.2. When ERNP does not win

Three settings favour other methods, and we report them rather than tune ERNP to them.

- **Stable benign traffic with a strong supervised signal (CIDDS-001).** SSF's F1 is higher (0.985 vs. 0.976), but ERNP ranks at least as well (Table 6) and detects more than twice as many zero-day flows (0.625 vs. 0.262; Table 7). The F1 gap is the price of these detections: 0.47% against 0.10% FPR. Lowering ERNP's FPR to SSF's level closes the F1 gap only by giving up the zero-day detections.

- **Daily regime changes of benign traffic (ToN).** Under a daily causal protocol, ERNP's FPR reaches 42%, and OWAD ranks ToN better. We traced this on the development seeds (0–1) with three diagnostics, all released with the code.

  1. The false positives are concentrated on days on which no evidence could exist yet. On the last stream day, benign traffic moves to a new regime: ERNP alerts on 96% of that day's benign flows, and 96% of those false positives carry at least one feature value seen neither in the anchor's benign traffic nor in the benign alerts of earlier days. The remaining false positives are mostly new *combinations* of values that each have been confirmed before.
  2. The anchor period does not anticipate this drift. We split the anchor's benign traffic in time and trained on the first half. The flows of the second half that this model flags cover 0% of the false positives

of the first two stream days, within 2ϵ. Their per-feature displacement profile has cosine similarity 0.38 with that of the stream false positives, against 0.60 with that of the zero-day attacks. Transferring the anchor's drift directions would therefore retract the prior towards attacks.

3. Removing the novelty prior (GBM+AL, five seeds) lowers the ToN FPR to 3.0%, but raises it to 11–41% on the other three datasets (Table 5).

No evidence available before these days separates the new benign regime from novel attacks. A detector that must stay robust to poisoning cannot fix this with a better use of the same labels; it needs the labels sooner. With the same 200 labels per day delivered every 4 h, ERNP has the best F1 and MCC on ToN of all methods at that cadence (Table 8). The update period is therefore a deployment parameter that should follow the triage cycle.

- **Full scale (CIC-IDS2017).** ERNP and CADE are on par.

We also tested four modifications of ERNP aimed at these cases on the development seeds only: a per-feature novelty channel, a retraction kernel shaped by the observed drift, a tighter operating point, and perfectly pure alert groups (an oracle bound). None improved all datasets at once, so none was adopted.

7.3. Operational interpretation

ERNP turns routine alert triage into the only adaptation signal, at the cost of a CPU refit per period. Its failure mode is explicit: an analyst who whitelists a malicious alert group whitelists its neighbourhood. The security-critical input therefore becomes the correctness of the triage decision rather than the volume of traffic, and that is where SOCs already concentrate review. In deployment, benign confirmations of large groups can be sampled for second review, and ERNP's footprint bound (Proposition 1(iii)) states what such a review protects.

8. Limitations and threats to validity

- **Update cadence.** Under daily updates, ERNP loses on ToN to OWAD in score quality and MCC. It wins there only when labels arrive every 4 h or faster. The cadence study uses three seeds.
- **Sampling.** The main results use samples of the original data. The unsampled check covers one dataset, and there CADE and SSF are stronger than on the samples.
- **External validity.** All four datasets come from testbeds or controlled environments, and the benign traffic of CIDDS-001 is script-generated. Results should be replicated on production traffic.
- **Poisoning model.** RQ2 interpolates feature vectors and is a stress test of the adaptation channel, not an end-to-end attack on a protocol stack.
- **Label model.** Group labels are an assumption about SOC triage. Representative-only evidence and label noise are reported, and noise at or above 10% degrades ERNP more than SSF.
- **Theory.** The propositions describe the population detector; the finite-sample classifier and the sliding evidence windows approximate it. Proposition 3 needs benign evidence to be added away from the flow in question.
- **Baseline deviations.** SSF's per-window epochs, Trident's percentile fallback, MemStream's normalisation variant and our port of CADE are disclosed in Table 3. Part of RQ2/RQ3 ran on a second machine; re-running two of those jobs locally changed F1 by at most 0.003.
- **Statistical power.** Four datasets give low power at the dataset level. Claims rest on per-dataset effect sizes with intervals, and the Friedman test is reported although it is not significant.

9. Conclusion

We proposed ERNP, a NIDS that adapts only by retracting a structured novelty prior where analysts have confirmed benign traffic. The design makes the detector invariant to unlabelled traffic, ties every adaptation step to a labelled alert group, and preserves detection away from confirmed evidence. On four temporally split benchmarks, ERNP has the best average detection against five recent detectors, including when each is run at its best configuration. It needs about an eighth of the labels of the strongest continual learner, and a counterfactual shows that its robustness to slow poisoning comes from the trusted-evidence rule. It is on par with the best baseline at full scale, and it is more sensitive than a supervised continual learner to analyst errors. Future work should make retraction robust to such errors, evaluate on operational traffic at full scale, and match the update period to the triage cycle.

CRediT authorship contribution statement

An Vo Le Thien: Conceptualization, Methodology, Software, Investigation, Data curation, Formal analysis, Validation, Visualization, Writing – original draft, Writing – review & editing.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data and code availability

The four datasets are publicly available and remain subject to the licences of their original providers. The prepared streams, the implementation of ERNP, the wrappers around the official baseline code, the per-run predictions, and the scripts that regenerate every table and figure of this paper from those

predictions are available at https://github.com/volethienan/Openset_CN (made public upon publication; available to reviewers on request). No number in the tables is typed by hand: paper/make_tables.py and paper/make_figures.py regenerate them from the stored evaluation records.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation of this work the authors used Claude (Anthropic) in order to assist with experiment implementation, analysis scripts and language editing. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article.

A. Proofs

Let b_t, a_t be the densities of the benign and attack evidence at period t, q_0 the initial prior and r_t the retention of Eq. (4). Minimising $\frac{1}{2} b_t \ell(\eta, 0) + \frac{1}{2}(a_t + q_0 r_t)\ell(\eta, 1)$ pointwise over $\eta \in [0, 1]$ gives the posterior behind Eq. (2); a common positive rescaling of the weights, as used in the implementation, leaves it unchanged.

Proof of Proposition 1. (i) By Algorithm 1, $P_{t+1}, A_{t+1}, \mathcal{E}_{t+1}$ arise from $P_t, A_t, \mathcal{E}_t$ only by adding labelled groups, and q_0 and τ are fixed. Hence s_t is a function of the labelled history only. Without labels, $(P_t, A_t, \mathcal{E}_t) = (P_0, A_0, \emptyset)$ and $s_t = s_0$.

(ii) We have $1 - r_t(x) = \exp(-d(x, \mathcal{E}_t)^2/2\epsilon^2) > \delta$ if and only if $d(x, \mathcal{E}_t) < \epsilon\sqrt{2\ln(1/\delta)} =: \rho_\delta$, that is, if and only if x lies in some ball $\mathcal{B}(e, \rho_\delta)$ with $e \in \mathcal{E}_t$.

(iii) Write $\mathcal{E}_t = \mathcal{E}^c \cup \mathcal{E}^e$, where $\mathcal{E}^e$ is the union of the m erroneous groups $G_1, \dots, G_m$. Since $d(x, \mathcal{E}_t) = \min\{d(x, \mathcal{E}^c), d(x, \mathcal{E}^e)\}$, the errors reduce the retention at x only if $d(x, \mathcal{E}^e) < d(x, \mathcal{E}^c)$. They reduce it by more than δ only if, in addition, $d(x, \mathcal{E}^e) < \rho_\delta$, i.e. $x \in \mathcal{B}(e, \rho_\delta)$ for some $e \in G_i$. Each G_i has diameter at most Δ, so $\mathcal{B}(e, \rho_\delta) \subseteq \mathcal{B}(c_i, \Delta + \rho_\delta)$ for any fixed $c_i \in G_i$. Erroneous groups enter b_t only through the same m labelled groups. □

Proof of Proposition 2. Since $1 - e^{-u} \le u$, $r_t(x) \le d(x, \mathcal{E}_t)^2/(2\epsilon^2)$; the bound follows from the monotonicity of the logarithm in Eq. (2). As $d(x, \mathcal{E}_t) \to 0$, the bound tends to $\log(a_t(x)/b_t(x)) < \tau$ under the stated condition. □

Proof of Proposition 3. Since $a_t \ge 0$, $s_t(z) \ge \log(q_0(z) r_t(z)) - \log b_t(z)$. The assumption $d(z, \mathcal{E}_t) \ge c\epsilon$ gives $r_t(z) \ge 1 - e^{-c^2/2}$, and $b_t(z) \le b_0(z)$ gives $-\log b_t(z) \ge -\log b_0(z)$. The margins follow from $-\log(1 - e^{-2}) \approx 0.145$ and $-\log(1 - e^{-4.5}) \approx 0.011$. □

Remark 1. *The assumption $b_t(z) \le b_0(z)$ holds, for instance, when the benign evidence is a mixture $b_t = \lambda_t b_0 + (1 - \lambda_t) b_{\mathcal{E}}$ with $\lambda_t \le 1$ and $b_{\mathcal{E}}(z) = 0$, i.e. when the added benign groups lie away from z.*

Table 12
Research-question map.

RQ	Experiment	Main metric	Where
RQ1	4 datasets × 5 seeds; best configurations; unsampled CIC-IDS2017	F1, MCC, zero-day recall@1%FPR	Tables 5–9
RQ2	slow poisoning, 4 scenarios × 5 seeds, $B \in \{25, 200\}$; counterfactual	payload recall, FPR	Table 10
RQ3	$B \in \{0, \dots, 400\}$ on two datasets	F1 vs. labels	Fig. 2
RQ4	ablations; evidence replay	ΔF1; recall vs. distance	Table 11, Fig. 3
RQ5	sensitivity; label noise; cost	ΔF1; time; memory	Tables 15, 9; Fig. 2

B. Supplementary results

This appendix collects the research-question map, the per-dataset effect sizes behind the RQ1 claims, the best configuration of every baseline and the hyper-parameter sensitivity of ERNP.

Table 13
RQ1: F1 difference ERNP minus baseline, per dataset, mean over seeds [95% bootstrap interval]. Bold: interval above zero; underlined: interval below zero. Friedman test over the four datasets and six methods: $p = 0.079$.

Dataset	SSF	OWAD	CADE	Trident	MemStream
CIDDS-001	-0.009 [-0.011, -0.008]	**+0.031 [+0.025, +0.036]**	**+0.059 [+0.031, +0.089]**	**+0.443 [+0.306, +0.613]**	**+0.848 [+0.839, +0.859]**
NF-ToN-IoT-v3	**+0.241 [+0.196, +0.285]**	**+0.122 [+0.108, +0.139]**	**+0.262 [+0.111, +0.431]**	-0.088 [-0.102, -0.070]	**+0.291 [+0.268, +0.318]**
CIC-IDS2017†	**+0.498 [+0.461, +0.519]**	**+0.969 [+0.966, +0.973]**	**+0.038 [+0.026, +0.046]**	**+0.090 [+0.087, +0.094]**	**+0.255 [+0.200, +0.323]**
CSE-CIC-IDS2018	**+0.056 [+0.042, +0.065]**	**+0.911 [+0.902, +0.918]**	**+0.625 [+0.537, +0.689]**	**+0.585 [+0.567, +0.600]**	**+0.765 [+0.744, +0.801]**
Mean rank (ERNP 1.50)	3.00	4.50	3.75	3.00	5.25

Table 14
Best configuration of each method (mean F1 over the seeds run). Configurations: SSF epochs 20/180, native windows, 24/4/1 h updates; OWAD 24/4/1 h; MemStream original/frozen normalisation; ERNP 24/4/1 h.

Dataset	ERNP	SSF	CADE	Trident	OWAD	MemStream	*k*NN
CIDDS-001	0.978	**0.988**	0.917	0.533	0.945	0.357	0.947
NF-ToN-IoT-v3	**0.753**	0.712	0.348	0.698	0.488	0.319	0.487
CIC-IDS2017†	0.974	0.512	0.932	0.880	0.001	0.715	**0.980**
CSE-CIC-IDS2018	**0.922**	0.888	0.288	0.329	0.003	0.148	0.815
Mean	**0.907**	0.775	0.621	0.610	0.359	0.385	0.807

Table 15
RQ5: ΔF1 relative to the default configuration (seeds 0–2).

Setting (ΔF1 vs. default)	CIDDS-001	NF-ToN-IoT-v3	CSE-CIC-IDS2018
$\rho = 0.1$	+0.001	+0.034	+0.001
$\rho = 0.2$	-0.001	+0.014	-0.001
$\rho = 0.5$	-0.001	-0.017	+0.013
$m = 0.25$	-0.004	+0.013	-0.014
$m = 0.5$	-0.004	+0.013	-0.003
$m = 2$	-0.004	+0.038	+0.000
$\epsilon \times 0.5$	-0.004	+0.007	-0.047
$\epsilon \times 2$	+0.003	+0.009	+0.013
RF instead of GBM	-0.002	-0.255	-0.001

References

[1] Arp, D., Quiring, E., Pendlebury, F., Warnecke, A., Pierazzi, F., Wressnegger, C., Cavallaro, L., Rieck, K., 2022. Dos and don'ts of machine learning in computer security, in: 31st USENIX Security Symposium.

[2] Bhatia, S., Jain, A., Srivastava, S., Kawaguchi, K., Hooi, B., 2022. MemStream: Memory-based streaming anomaly detection, in: Proceedings of the ACM Web Conference 2022 (WWW).

[3] Biggio, B., Nelson, B., Laskov, P., 2012. Poisoning attacks against support vector machines, in: Proceedings of the 29th International Conference on Machine Learning (ICML).

[4] Das, S., Wong, W.K., Dietterich, T., Fern, A., Emmott, A., 2016. Incorporating expert feedback into active anomaly discovery, in: IEEE 16th International Conference on Data Mining (ICDM), pp. 853–858.

[5] Das, S., Wong, W.K., Dietterich, T., Fern, A., Emmott, A., 2020. Discovering anomalies by incorporating feedback from an expert. ACM Transactions on Knowledge Discovery from Data doi:10.1145/3396608.

[6] Demšar, J., 2006. Statistical comparisons of classifiers over multiple data sets. Journal of Machine Learning Research 7, 1–30.

[7] Efron, B., Tibshirani, R.J., 1993. An Introduction to the Bootstrap. Chapman & Hall.

[8] Engelen, G., Rimmer, V., Joosen, W., 2021. Troubleshooting an intrusion detection dataset: the CICIDS2017 case study, in: IEEE Security and Privacy Workshops (SPW).

[9] Friedman, J.H., 2001. Greedy function approximation: A gradient boosting machine. The Annals of Statistics 29, 1189–1232.

[10] Gutmann, M., Hyvärinen, A., 2010. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models, in: Proceedings of the 13th International Conference on Artificial Intelligence and Statistics (AISTATS), pp. 297–304.

[11] Han, D., Wang, Z., Chen, W., Wang, K., Yu, R., Wang, S., Zhang, H., Wang, Z., Jin, M., Yang, J., et al., 2023. Anomaly detection in the open world: Normality shift detection, explanation, and adaptation, in: Network and Distributed System Security Symposium (NDSS).

[12] Hempstalk, K., Frank, E., Witten, I.H., 2008. One-class classification by combining density and class probability estimation, in: Machine Learning and Knowledge Discovery in Databases (ECML PKDD), pp. 505–519. doi:10.1007/978-3-540-87479-9_51.

[13] Kloft, M., Laskov, P., 2012. Security analysis of online centroid anomaly detection. Journal of Machine Learning Research 13, 3681–3724.

[14] Liu, F.T., Ting, K.M., Zhou, Z.H., 2008. Isolation forest, in: Eighth IEEE International Conference on Data Mining (ICDM), pp. 413–422.

[15] Liu, L., Engelen, G., Lynar, T., Essam, D., Joosen, W., 2022. Error prevalence in NIDS datasets: A case study on CIC-IDS-2017 and CSE-CIC-IDS-2018, in: IEEE Conference on Communications and Network Security (CNS).

[16] Luay, M., Layeghy, S., Hosseininoorbin, S., Sarhan, M., Moustafa, N., Portmann, M., 2025. Temporal analysis of NetFlow datasets for network intrusion detection systems. arXiv preprint arXiv:2503.04404 .

[17] Mirsky, Y., Doitshman, T., Elovici, Y., Shabtai, A., 2018. Kitsune: An ensemble of autoencoders for online network intrusion detection, in: Network and Distributed System Security Symposium (NDSS).

[18] Moustafa, N., 2021. A new distributed architecture for evaluating AI-based security systems at the edge: Network TON_IoT datasets. Sustainable Cities and Society 72, 102994.

[19] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., et al., 2011. Scikit-learn: Machine learning in Python. Journal of Machine Learning Research 12, 2825–2830.

[20] Pendlebury, F., Pierazzi, F., Jordaney, R., Kinder, J., Cavallaro, L., 2019. TESSERACT: Eliminating experimental bias in malware classification across space and time, in: 28th USENIX Security Symposium.

[21] Ring, M., Wunderlich, S., Grüdl, D., Landes, D., Hotho, A., 2017. Flow-based benchmark data sets for intrusion detection, in: Proceedings of the 16th European Conference on Cyber Warfare and Security (ECCWS), pp. 361–369.

[22] Rubinstein, B.I.P., Nelson, B., Huang, L., Joseph, A.D., Lau, S.h., Rao, S., Taft, N., Tygar, J.D., 2009. ANTIDOTE: Understanding and defending against poisoning of anomaly detectors, in: Proceedings of the 9th ACM SIGCOMM Internet Measurement Conference (IMC).

[23] Settles, B., 2009. Active Learning Literature Survey. Technical Report 1648. University of Wisconsin–Madison, Department of Computer Sciences.

[24] Sharafaldin, I., Lashkari, A.H., Ghorbani, A.A., 2018. Toward generating a new intrusion detection dataset and intrusion traffic characterization, in: Proceedings of the 4th International Conference on Information Systems Security and Privacy (ICISSP).

[25] Sipple, J., 2020. Interpretable, multidimensional, multimodal anomaly detection with negative sampling for detection of device failure, in: Proceedings of the 37th International Conference on Machine Learning (ICML), pp. 9016–9025.

[26] Sommer, R., Paxson, V., 2010. Outside the closed world: On using machine learning for network intrusion detection, in: IEEE Symposium on Security and Privacy (S&P), pp. 305–316.

[27] Steinwart, I., Hush, D., Scovel, C., 2005. A classification framework for anomaly detection. Journal of Machine Learning Research 6, 211–232.

[28] Sugiyama, M., Suzuki, T., Kanamori, T., 2012. Density Ratio Estimation in Machine Learning. Cambridge University Press.

[29] Yang, L., Guo, W., Hao, Q., Ciptadi, A., Ahmadzadeh, A., Xing, X., Wang, G., 2021. CADE: Detecting and explaining concept drift samples for security applications, in: 30th USENIX Security Symposium.

[30] Zhang, X., Zhao, R., Jiang, Z., Chen, H., Ding, Y., Ngai, E.C.H., Yang, S.H., 2025. Continual learning with strategic selection and forgetting for network intrusion detection, in: IEEE INFOCOM 2025 – IEEE Conference on Computer Communications, pp. 1–10.

[31] Zhao, Z., Li, Z., Song, Z., Li, W., Zhang, F., 2024a. Trident: A universal framework for fine-grained and class-incremental unknown traffic detection, in: Proceedings of the ACM Web Conference 2024 (WWW), pp. 1608–1619. doi:10.1145/3589334.3645407.

[32] Zhao, Z., Li, Z., Xie, X., Yu, J., Zhang, F., Zhang, R., Chen, B., Luo, X., Hu, M., Ma, W., 2024b. FOSS: Towards fine-grained unknown class detection against the open-set attack spectrum with variable legitimate traffic. IEEE/ACM Transactions on Networking doi:10.1109/TNET.2024.3413789.