# Topic 7: Introduction to APIs

AI Automation & Workflow Integration Module

## What is an API?

An **API (Application Programming Interface)** allows different software applications to communicate and exchange data. In the modern digital landscape, no application exists in a vacuum. APIs serve as the critical bridges that allow distinct systems—such as your CRM, an AI language model, and your email client—to talk to one another seamlessly without requiring human intervention.




*Figure 1: The Request-Response cycle of a typical RESTful API.*

## The Restaurant Analogy

The easiest way to understand an API is to think of a restaurant. You (the client) are sitting at a table with a menu of choices. The kitchen (the server) is where your food is prepared. However, you do not go into the kitchen to cook the food yourself.

Instead, you rely on the waiter—the API. The waiter takes your specific order (the request), brings it to the kitchen, and then returns to your table with your finished meal (the response). The API abstracts away the complexity of the kitchen, providing you with exactly what you asked for through a standardized interface.

## Core API Building Blocks

To successfully integrate AI models and external software into your workflows, you must understand the fundamental components that make up an API transaction.

### 1. Request and Response

Every API interaction is a two-way street. The **Request** is the package of data and instructions you send to the server (e.g., "Summarize this text"). The **Response** is the server's reply containing the requested data or the result of the operation.

### 2. API Endpoint

An endpoint is the specific digital address (URL) where an API receives requests. Just as a business has different phone extensions for Sales and Support, an API has different endpoints for different functions (e.g., `/v1/chat/completions` vs. `/v1/images/generations`).

### 3. JSON Data

JSON (JavaScript Object Notation) is the standard language APIs use to communicate. It structures data in a highly organized format using "key-value" pairs, making it easy for both humans to read and machines to parse when sending prompts to AI.

### 4. API Keys & Auth

An API Key is a unique, secret token used for **Authentication**. It acts as your digital ID badge, proving to the server that you have authorized access and allowing the provider to track your usage and billing.

### Example: Registration API Request

A registration application sends student details to a backend API. The server validates the request and returns an appropriate response. The JSON payload looks like this:

```
{
  "name": "Aarav Patel",
  "course": "Generative AI",
  "email": "aarav@example.com"
}
```

> **Important Security Notice**
> Students should always use sample information for exercises and must **never expose API keys** in public code repositories. Treat your API keys like highly sensitive passwords.

## HTTP Methods (The Verbs)

When you send a request to an endpoint, you use an HTTP method to tell the server what action you want to perform.

| Method | Action | Typical Use Case in Automation |
|---|---|---|
| **GET** | Retrieve data | Fetching a list of customers from a CRM. |
| **POST** | Create data | Sending a prompt to an AI model to generate text. |
| **PUT** | Replace data | Updating an entire user profile with new information. |
| **PATCH** | Update data | Changing a single field, like a task status to "Done". |
| **DELETE** | Remove data | Deleting a temporary file from cloud storage. |

## Status Codes & Error Responses

After processing your request, the server returns a 3-digit HTTP Status Code. This code immediately tells your automation whether the task succeeded or if an **Error Response** occurred, allowing your workflow to branch logically.

- **2xx (Success):** E.g., *200 OK*. The request was received, understood, and processed successfully.
- **4xx (Client Error):** You made a mistake. Common errors include *401 Unauthorized* (invalid or missing API key) and *429 Too Many Requests* (you hit the provider's rate limit).
- **5xx (Server Error):** E.g., *500 Internal Server Error*. The API provider is experiencing a crash or downtime; your request was valid, but they cannot process it right now.

> **Key Takeaway for Automation**
>
> Modern low-code platforms handle the complex coding of HTTP methods automatically. Your main job is to provide the correct API Key, choose the right endpoint, format your JSON payload correctly, and build logic to handle potential 4xx or 5xx error codes.

# Topic 8: Introduction to Webhooks

AI Automation & Workflow Integration Module

## What is a Webhook?

While an API generally requires your system to actively ask for data, a **webhook** is entirely event-driven. It automatically sends information to a specified URL the moment a particular event occurs. This "push" mechanism makes webhooks incredibly efficient for real-time workflows and automation triggers.

## The Webhook Workflow

1. **Event Occurs:** A specific trigger happens in the source application.

↓

2. **Webhook Sends Data:** The application automatically pushes data to your URL.

↓

3. **Server Receives Request:** Your designated endpoint catches the incoming data.

↓

4. **Validate Event:** The server checks the payload to ensure it is legitimate.

↓

5. **Execute Action:** Your system performs the appropriate downstream task.

### Real-World Example: Payment Status

When a payment provider reports a successful payment, it doesn't wait for you to ask. Instead, it instantly sends an event payload to your application's webhook endpoint. Your order system receives this trigger and immediately updates the order status to "Paid", allowing fulfillment to begin.

### Technical Format

Under the hood, webhooks rely on the exact same architecture as APIs. They commonly use standard

**HTTP POST requests**

to deliver their information, formatting the transmitted data as

**JSON payloads**