

Date:

ID:

Name:

Surname:

Signature:

HLK201 HELICOPTER DESIGN
QUESTIONS SET 2
ROTORCRAFT PERFORMANCE AND CONTROL

Q1. (7 pts) Why does a helicopter require **maximum power in hover**?

- a) Parasite drag is maximum
- b) Translational lift is absent
- c) Profile power is zero
- d) Engine efficiency is lowest

Q2. (8 pts) In forward flight, which blade experiences **higher relative velocity**?

- a) Retreating blade
- b) Advancing blade
- c) Root section
- d) Hub region

Q3. (15 pts) As altitude increases, a helicopter will first lose its ability to:

- a) Fly forward
- b) Hover
- c) Autorotate
- d) Produce lift

Q4. (8 pts) Induced power in hover is: $P_i = T\vartheta_i$

If $T = 15\,000\text{ N}$ and $\vartheta_i = 6\text{ m/s}$, what is P_i ?

- a) 45 kW
- b) 60 kW
- c) 90 kW
- d) 120 kW

Q5. (8 pts)

Which aerodynamic theory treats the rotor as an **actuator disk**?

- a) Blade Element Theory
 - b) Momentum Theory
 - c) CFD
 - d) Lifting Line Theory
-

Q6. (15 pts)

Which quantity **cannot** be obtained from Momentum Theory alone?

- a) Induced velocity
 - b) Induced power
 - c) Thrust
 - d) Blade twist distribution
-

Q7. (8 pts)

Disk loading is defined as:

- a) Power per unit area
 - b) Thrust per unit area
 - c) Torque per unit radius
 - d) Lift per blade
-

Q8. (8 pts)

Which control input mitigates **overturning moment** in forward flight?

- a) Pedals
- b) Throttle
- c) Cyclic
- d) Collective

Q9. (15 pts)

Which power component mainly depends on **rotor blade drag**?

- a) Induced power
 - b) Profile power
 - c) Parasite power
 - d) Excess power
-

Q10. (8 pts)

Why are rotor blades thicker near the root?

- a) To reduce induced power
 - b) To reduce tip Mach number
 - c) To carry higher structural loads
 - d) To reduce parasite drag
-

Q11. (+20 pts – Bonus Question)

At sea level, a helicopter has:

- Available power: $P_{ava,0} = 900 \text{ kW}$
- Required power: $P_{req,0} = 780 \text{ kW}$

At altitude, available power scales with density ratio:

$$P_{ava}(h) = P_{ava,0} \left(\frac{\rho}{\rho_0} \right)$$

Assume at that altitude the density ratio is:

$$\frac{\rho}{\rho_0} = 0.82$$

and required power increases by 6% due to performance degradation:

$$P_{req}(h) = 1.06 P_{req,0}$$

Excess power:

$$P_{exc} = P_{ava} - P_{req}$$

What is the new **excess power**?

a) $P_{exc} \approx -6 \text{ kW}$

b) $P_{exc} \approx 0 \text{ kW}$

c) $P_{exc} \approx +32 \text{ kW}$

d) $P_{exc} \approx +96 \text{ kW}$
