

# Cluster Analysis

---

1. What is Cluster Analysis?
2. Types of Data in Cluster Analysis
3. A Categorization of Major Clustering Methods
4. Partitioning Methods
5. Hierarchical Methods
6. Constraint-Based Clustering
7. Outlier Analysis
8. Summary

## What is Cluster Analysis?

---

- Cluster: a collection of data objects
  - Similar to one another within the same cluster
  - Dissimilar to the objects in other clusters
- Cluster analysis
  - Finding similarities between data according to the characteristics found in the data and grouping similar data objects into clusters
- **Unsupervised learning**: no predefined classes
- Typical applications
  - As a **stand-alone tool** to get insight into data distribution
  - As a **preprocessing step** for other algorithms

## Clustering Applications: Some Examples

---

- Marketing: Help marketers discover distinct groups in their customer bases, and then use this knowledge to develop targeted marketing programs
- Land use: Identification of areas of similar land use in an earth observation database
- Insurance: Identifying groups of motor insurance policy holders with a high average claim cost
- City-planning: Identifying groups of houses according to their house type, value, and geographical location

## Quality: What Is Good Clustering?

---

- A good clustering method will produce high quality clusters with
  - high intra-class similarity
  - low inter-class similarity
- The quality of a clustering result depends on both the similarity measure used by the method and its implementation
- The quality of a clustering method is also measured by its ability to discover some or all of the hidden patterns

## Measure the Quality of Clustering

- Dissimilarity/Similarity metric
  - Similarity is expressed in terms of a distance function, typically metric:  $d(i, j)$
  - The definitions of distance functions are usually rather different for interval-scaled, Boolean, categorical, ordinal ratio, and vector variables
  - Weights should be associated with different variables based on applications and data semantics
- Quality of clustering:
  - There is usually a separate “quality” function that measures the “goodness” of a cluster
  - It is hard to define “similar enough” or “good enough”
    - The answer is typically highly subjective

April 26, 2010

Data Acquisition and Processing

5

## Requirements of Clustering in Data Mining

- Scalability
- Ability to deal with different types of attributes
- Ability to handle dynamic data
- Discovery of clusters with arbitrary shape
- Minimal requirements for domain knowledge to determine input parameters
- Able to deal with noise and outliers
- Insensitive to order of input records
- Incorporation of user-specified constraints
- Interpretability and usability

April 26, 2010

Data Acquisition and Processing

6

## Data Structures

- Data matrix
  - (two modes)

$$\begin{bmatrix} x_{11} & \dots & x_{1f} & \dots & x_{1p} \\ \dots & \dots & \dots & \dots & \dots \\ x_{i1} & \dots & x_{if} & \dots & x_{ip} \\ \dots & \dots & \dots & \dots & \dots \\ x_{n1} & \dots & x_{nf} & \dots & x_{np} \end{bmatrix}$$

- Dissimilarity matrix
  - (one mode)

$$\begin{bmatrix} 0 & & & & \\ d(2,1) & 0 & & & \\ d(3,1) & d(3,2) & 0 & & \\ \vdots & \vdots & \vdots & & \\ d(n,1) & d(n,2) & \dots & \dots & 0 \end{bmatrix}$$

## Type of data in clustering analysis

- Interval-scaled variables
- Binary variables
- Nominal and ordinal
- Vector objects

## Distance Measures for Different Kinds of Data

- Numerical (interval)-based:
  - Minkowski Distance
  - Special cases: Euclidean ( $L_2$ -norm), Manhattan ( $L_1$ -norm)
- Binary variables:
  - symmetric vs. asymmetric (Jaccard coeff.)
- Nominal variables: # of mismatches
- Ordinal variables: treated like interval-based
- Vectors: cosine measure

April 26, 2010

Data Acquisition and Processing

9

## Interval-valued variables

- Standardize data
  - Calculate the mean absolute deviation:
$$s_f = \frac{1}{n}(|x_{1f} - m_f| + |x_{2f} - m_f| + \dots + |x_{nf} - m_f|)$$
where  $m_f = \frac{1}{n}(x_{1f} + x_{2f} + \dots + x_{nf})$
  - Calculate the standardized measurement (*z-score*)
$$z_{if} = \frac{x_{if} - m_f}{s_f}$$
- Using mean absolute deviation is more robust than using standard deviation

April 26, 2010

Data Acquisition and Processing

10

## Similarity and Dissimilarity Between Objects

- Distances are normally used to measure the similarity or dissimilarity between two data objects

- Some popular ones include: *Minkowski distance*:

$$d(i, j) = \sqrt[q]{(|x_{i1} - x_{j1}|^q + |x_{i2} - x_{j2}|^q + \dots + |x_{ip} - x_{jp}|^q)}$$

where  $i = (x_{i1}, x_{i2}, \dots, x_{ip})$  and  $j = (x_{j1}, x_{j2}, \dots, x_{jp})$  are two  $p$ -dimensional data objects, and  $q$  is a positive integer

- If  $q = 1$ ,  $d$  is Manhattan distance

$$d(i, j) = |x_{i1} - x_{j1}| + |x_{i2} - x_{j2}| + \dots + |x_{ip} - x_{jp}|$$

## Similarity and Dissimilarity Between Objects

- If  $q = 2$ ,  $d$  is Euclidean distance:

$$d(i, j) = \sqrt{(|x_{i1} - x_{j1}|^2 + |x_{i2} - x_{j2}|^2 + \dots + |x_{ip} - x_{jp}|^2)}$$

- Properties

- $d(i, j) \geq 0$
- $d(i, i) = 0$
- $d(i, j) = d(j, i)$
- $d(i, j) \leq d(i, k) + d(k, j)$

## Binary Variables

- A contingency table for binary data
 

		Object $j$		
		1	0	sum
Object $i$	1	$a$	$b$	$a+b$
	0	$c$	$d$	$c+d$
sum		$a+c$	$b+d$	$p$
- Distance measure for symmetric binary variables:
 
$$d(i, j) = \frac{b + c}{a + b + c + d}$$
- Distance measure for asymmetric binary variables:
 
$$d(i, j) = \frac{b + c}{a + b + c}$$
- Jaccard coefficient (*similarity* measure for *asymmetric* binary variables):
 
$$sim_{Jaccard}(i, j) = \frac{a}{a + b + c}$$

April 26, 2010

Data Acquisition and Processing

13

## Dissimilarity between Binary Variables

- Example

Name	Gender	Fever	Cough	Test-1	Test-2	Test-3	Test-4
Jack	M	Y	N	P	N	N	N
Mary	F	Y	N	P	N	P	N
Jim	M	Y	P	N	N	N	N

- gender is a symmetric attribute
- the remaining attributes are asymmetric binary
- let the values Y and P be set to 1, and the value N be set to 0

$$d(jack, mary) = \frac{0 + 1}{2 + 0 + 1} = 0.33$$

$$d(jack, jim) = \frac{1 + 1}{1 + 1 + 1} = 0.67$$

$$d(jim, mary) = \frac{1 + 2}{1 + 1 + 2} = 0.75$$

April 26, 2010

Data Acquisition and Processing

14

## Nominal Variables

- A generalization of the binary variable in that it can take more than 2 states, e.g., red, yellow, blue, green
- Simple matching
  - $m$ : # of matches,  $p$ : total # of variables

$$d(i, j) = \frac{p - m}{p}$$

## Ordinal Variables

- An ordinal variable can be discrete or continuous
- Order is important, e.g., rank
- Can be treated like interval-scaled
  - replace  $x_{if}$  by their rank  $r_{if} \in \{1, \dots, M_f\}$
  - map the range of each variable onto  $[0, 1]$  by replacing  $i$ -th object in the  $f$ -th variable by

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

- compute the dissimilarity using methods for interval-scaled variables



## Vector Objects

- Vector objects: keywords in documents
- Broad applications: information retrieval, biologic taxonomy, etc.
- Cosine measure

$$s(\vec{X}, \vec{Y}) = \frac{\vec{X}^t \cdot \vec{Y}}{|\vec{X}| |\vec{Y}|},$$

$\vec{X}^t$  is a transposition of vector  $\vec{X}$ ,  $|\vec{X}|$  is the Euclidean normal of vector  $\vec{X}$ ,

- A variant: Tanimoto coefficient

$$s(\vec{X}, \vec{Y}) = \frac{\vec{X}^t \cdot \vec{Y}}{\vec{X}^t \cdot \vec{X} + \vec{Y}^t \cdot \vec{Y} - \vec{X}^t \cdot \vec{Y}},$$

April 26, 2010

Data Acquisition and Processing

17

## Major Clustering Approaches (I)

- Partitioning approach:
  - Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
  - Typical methods: k-means, k-medoids, CLARANS
- Hierarchical approach:
  - Create a hierarchical decomposition of the set of data (or objects) using some criterion
  - Typical methods: Diana, Agnes, BIRCH, ROCK, CAMELEON
- Density-based approach:
  - Based on connectivity and density functions
  - Typical methods: DBSCAN, OPTICS, DenClue

April 26, 2010

Data Acquisition and Processing

18

## Major Clustering Approaches (II)

- Grid-based approach:
  - based on a multiple-level granularity structure
  - Typical methods: STING, WaveCluster, CLIQUE
- Model-based:
  - A model is hypothesized for each of the clusters and tries to find the best fit of that model to each other
  - Typical methods: EM, SOM, COBWEB
- Frequent pattern-based:
  - Based on the analysis of frequent patterns
  - Typical methods: pCluster
- User-guided or constraint-based:
  - Clustering by considering user-specified or application-specific constraints
  - Typical methods: COD (obstacles), constrained clustering

April 26, 2010

Data Acquisition and Processing

19

## Calculation of Distance between Clusters

- **Single link:** smallest distance between an element in one cluster and an element in the other, i.e.,  $\text{dis}(K_i, K_j) = \min(t_{ip}, t_{jq})$
- **Complete link:** largest distance between an element in one cluster and an element in the other, i.e.,  $\text{dis}(K_i, K_j) = \max(t_{ip}, t_{jq})$
- **Average:** avg distance between an element in one cluster and an element in the other, i.e.,  $\text{dis}(K_i, K_j) = \text{avg}(t_{ip}, t_{jq})$
- **Centroid:** distance between the centroids of two clusters, i.e.,  $\text{dis}(K_i, K_j) = \text{dis}(C_i, C_j)$
- **Medoid:** distance between the medoids of two clusters, i.e.,  $\text{dis}(K_i, K_j) = \text{dis}(M_i, M_j)$ 
  - Medoid: one chosen, centrally located object in the cluster

April 26, 2010

Data Acquisition and Processing

20

## Centroid, Radius and Diameter of a Cluster (for numerical data sets)

- Centroid: the "middle" of a cluster

$$C_m = \frac{\sum_{i=1}^N (t_{ip})}{N}$$

- Radius: square root of average distance from any point of the cluster to its centroid

$$R_m = \sqrt{\frac{\sum_{i=1}^N (t_{ip} - c_m)^2}{N}}$$

- Diameter: square root of average mean squared distance between all pairs of points in the cluster

$$D_m = \sqrt{\frac{\sum_{i=1}^N \sum_{i=1}^N (t_{ip} - t_{iq})^2}{N(N-1)}}$$

April 26, 2010

Data Acquisition and Processing

21

## Partitioning Algorithms: Basic Concept

- Partitioning method: Construct a partition of a database  $D$  of  $n$  objects into a set of  $k$  clusters, s.t., min sum of squared distance

$$\sum_{m=1}^k \sum_{t_{mi} \in K_m} (C_m - t_{mi})^2$$

- Given a  $k$ , find a partition of  $k$  clusters that optimizes the chosen partitioning criterion
  - Global optimal: exhaustively enumerate all partitions
  - Heuristic methods: *k-means* and *k-medoids* algorithms
  - k-means*: Each cluster is represented by the center of the cluster
  - k-medoids* or PAM (Partition around medoids): Each cluster is represented by one of the objects in the cluster

April 26, 2010

Data Acquisition and Processing

22

## The *K-Means* Clustering Method

- Given  $k$ , the *k-means* algorithm is implemented in four steps:
  - Partition objects into  $k$  nonempty subsets
  - Compute seed points as the centroids of the clusters of the current partition (the centroid is the center, i.e., *mean point*, of the cluster)
  - Assign each object to the cluster with the nearest seed point
  - Go back to Step 2, stop when no more new assignment


April 26, 2010

Data Acquisition and Processing

23

## The *K-Means* Clustering Method

### ■ Example



April 26, 2010

Data Acquisition and Processing

24

## Comments on the *K-Means* Method


- Strength: *Relatively efficient*:  $O(tkn)$ , where  $n$  is # objects,  $k$  is # clusters, and  $t$  is # iterations. Normally,  $k, t \ll n$
- Comment: Often terminates at a *local optimum*. The *global optimum* may be found using techniques such as: *deterministic annealing* and *genetic algorithms*
- Weakness
  - Applicable only when *mean* is defined, then what about categorical data?
  - Need to specify  $k$ , the *number* of clusters, in advance
  - Unable to handle noisy data and *outliers*

## Variations of the *K-Means* Method

- A few variants of the *k-means* which differ in
  - Selection of the initial  $k$  means
  - Dissimilarity calculations
  - Strategies to calculate cluster means
- Handling categorical data: *k-modes*
  - Replacing means of clusters with modes
  - Using new dissimilarity measures to deal with categorical objects
  - Using a frequency-based method to update modes of clusters

## What Is the Problem of the K-Means Method?

- The  $k$ -means algorithm is sensitive to outliers!
  - An object with an extremely large value may substantially distort the distribution of the data
- $K$ -Medoids: Instead of taking the mean value of the object in a cluster as a reference point, medoids can be used, which is the most centrally located object in a cluster.



April 26, 2010

Data Acquisition and Processing

27

## The $K$ -Medoids Clustering Method

- Find *representative* objects, called medoids, in clusters
- $PAM$  (Partitioning Around Medoids)
  - starts from an initial set of medoids and iteratively replaces one of the medoids by one of the non-medoids if it improves the total distance of the resulting clustering
  - $PAM$  works effectively for small data sets, but does not scale well for large data sets
- $CLARA$
- $CLARANS$ : Randomized sampling

April 26, 2010

Data Acquisition and Processing

28

## CLARA (Clustering Large Applications)

---

- CLARA (built in 1990)
  - Built in statistical analysis packages, such as S+
- It draws *multiple samples* of the data set, applies *PAM* on each sample, and gives the best clustering as the output
- Strength: deals with larger data sets than *PAM*
- Weakness:
  - Efficiency depends on the sample size
  - A good clustering based on samples will not necessarily represent a good clustering of the whole data set if the sample is biased

April 26, 2010

Data Acquisition and Processing

29

## CLARANS ("Randomized" CLARA)

---

- CLARANS (A Clustering Algorithm based on Randomized Search)
- CLARANS draws sample of neighbors dynamically
- The clustering process can be presented as searching a graph where every node is a potential solution, that is, a set of  $k$  medoids
- If the local optimum is found, CLARANS starts with new randomly selected node in search for a new local optimum
- It is more efficient and scalable than both *PAM* and *CLARA*
- Focusing techniques may further improve its performance


April 26, 2010

Data Acquisition and Processing

30

## Hierarchical Clustering

- Use distance matrix as clustering criteria. This method does not require the number of clusters  $k$  as an input, but needs a termination condition




April 26, 2010

Data Acquisition and Processing

31

## AGNES (Agglomerative Nesting)

- Introduced in 1990
- Implemented in statistical analysis packages, e.g., Splus
- Use the Single-Link method and the dissimilarity matrix
- Merge nodes that have the least dissimilarity
- Go on in a non-descending fashion
- Eventually all nodes belong to the same cluster



April 26, 2010

Data Acquisition and Processing


32



## Dendrogram: Shows How the Clusters are Merged

Decompose data objects into a several levels of nested partitioning (tree of clusters), called a dendrogram.

A clustering of the data objects is obtained by cutting the dendrogram at the desired level, then each connected component forms a cluster.




April 26, 2010

Data Acquisition and Processing

33

## DIANA (Divisive Analysis)

- Introduced in 1990
- Implemented in statistical analysis packages, e.g., Splus
- Inverse order of AGNES
- Eventually each node forms a cluster on its own



April 26, 2010

Data Acquisition and Processing

34

## Extensions to Hierarchical Clustering

- Major weakness of agglomerative clustering methods
  - do not scale well: time complexity of at least  $O(n^2)$ , where  $n$  is the number of total objects
  - can never undo what was done previously
- Integration of hierarchical with distance-based clustering
  - BIRCH (1996): uses CF(Clustering Feature)-tree and incrementally adjusts the quality of sub-clusters
  - ROCK (1999): clustering categorical data by neighbor and link analysis
  - CHAMELEON (1999): hierarchical clustering using dynamic modeling

April 26, 2010

Data Acquisition and Processing

35

## Density-Based Clustering Methods

- Clustering based on density (local cluster criterion), such as density-connected points
- Major features:
  - Discover clusters of arbitrary shape
  - Handle noise
  - One scan
  - Need density parameters as termination condition
- Several interesting studies:
  - DBSCAN
  - OPTICS
  - DENCLUE
  - CLIQUE

April 26, 2010

Data Acquisition and Processing

36

## Grid-Based Clustering Method

---

- Using multi-resolution grid data structure
- Several interesting methods
  - **STING** (a Statistical Information Grid approach)
  - **WaveCluster**
    - A multi-resolution clustering approach using wavelet method
  - **CLIQUE**
    - On high-dimensional data (thus put in the section of clustering high-dimensional data)

April 26, 2010

Data Acquisition and Processing

37

## Model-Based Clustering

---

- What is model-based clustering?
  - Attempt to optimize the fit between the given data and some mathematical model
  - Based on the assumption: Data are generated by a mixture of underlying probability distribution
- Typical methods
  - Statistical approach
    - EM (Expectation maximization), AutoClass
  - Machine learning approach
    - COBWEB, CLASSIT
  - Neural network approach
    - SOM (Self-Organizing Feature Map)


April 26, 2010

Data Acquisition and Processing

38

## Why Constraint-Based Cluster Analysis?

- Need user feedback: Users know their applications the best
- Less parameters but more user-desired constraints, e.g., an ATM allocation problem: obstacle & desired clusters



April 26, 2010

Data Acquisition and Processing

39

## A Classification of Constraints in Cluster Analysis

- Clustering in applications: desirable to have user-guided (i.e., constrained) cluster analysis
- Different constraints in cluster analysis:
  - Constraints on individual objects (do selection first)
    - Cluster on houses worth over \$300K
  - Constraints on distance or similarity functions
    - Weighted functions, obstacles (e.g., rivers, lakes)
  - Constraints on the selection of clustering parameters
    - # of clusters, MinPts, etc.
  - User-specified constraints
    - Contain at least 500 valued customers and 5000 ordinary ones
  - Semi-supervised: giving small training sets as "constraints" or hints

April 26, 2010

Data Acquisition and Processing

40

## What Is Outlier Discovery?


- What are outliers?
  - The set of objects are considerably dissimilar from the remainder of the data
  - Example: Sports: Michael Jordon, Wayne Gretzky, ...
- Problem: Define and find outliers in large data sets
- Applications:
  - Credit card fraud detection
  - Telecom fraud detection
  - Customer segmentation
  - Medical analysis

April 26, 2010

Data Acquisition and Processing

41

## Outlier Discovery: Statistical Approaches



- ✧ Assume a model underlying distribution that generates data set (e.g. normal distribution)
- Use discordancy tests depending on
  - data distribution
  - distribution parameter (e.g., mean, variance)
  - number of expected outliers
- Drawbacks
  - most tests are for single attribute
  - In many cases, data distribution may not be known

April 26, 2010

Data Acquisition and Processing

42

## Outlier Discovery: Distance-Based Approach

- Introduced to counter the main limitations imposed by statistical methods
  - We need multi-dimensional analysis without knowing data distribution
- Distance-based outlier: A  $DB(p, D)$ -outlier is an object  $O$  in a dataset  $T$  such that at least a fraction  $p$  of the objects in  $T$  lies at a distance greater than  $D$  from  $O$
- Algorithms for mining distance-based outliers
  - Index-based algorithm
  - Nested-loop algorithm
  - Cell-based algorithm


April 26, 2010

Data Acquisition and Processing

43

## Density-Based Local Outlier Detection

- Distance-based outlier detection is based on global distance distribution
- It encounters difficulties to identify outliers if data is not uniformly distributed
- Ex.  $C_1$  contains 400 loosely distributed points,  $C_2$  has 100 tightly condensed points, 2 outlier points  $o_1, o_2$
- Distance-based method cannot identify  $o_2$  as an outlier
- Need the concept of local outlier



- Local outlier factor (LOF)
  - Assume outlier is not crisp
  - Each point has a LOF

April 26, 2010

Data Acquisition and Processing

44

## Outlier Discovery: Deviation-Based Approach

---

- Identifies outliers by examining the main characteristics of objects in a group
- Objects that “deviate” from this description are considered outliers
- Sequential exception technique
  - simulates the way in which humans can distinguish unusual objects from among a series of supposedly like objects
- OLAP data cube technique
  - uses data cubes to identify regions of anomalies in large multidimensional data

April 26, 2010

Data Acquisition and Processing

45

## Summary

---

- **Cluster analysis** groups objects based on their **similarity** and has wide applications
- Measure of similarity can be computed for **various types of data**
- Clustering algorithms can be **categorized** into partitioning methods, hierarchical methods, density-based methods, grid-based methods, and model-based methods
- **Outlier detection** and analysis are very useful for fraud detection, etc. and can be performed by statistical, distance-based or deviation-based approaches
- There are still lots of research issues on cluster analysis

April 26, 2010

Data Acquisition and Processing

46