

Composite Pattern

Salih ŞEN



Intent

- Compose objects into tree structures to represent part-whole hierarchies.
- Lets clients treat individual objects and compositions of objects uniformly.




Motivation


- When dealing with tree-structured data, programmers often have to discriminate between a leaf-node and a branch. This makes code more complex, and therefore, error prone.
- The solution is an interface that allows treating complex and primitive objects uniformly.
- The operations you can perform on all the composite objects often have a least common denominator relationship.



Composite Example



Composite Example




Applicability

- Use the Composite pattern when:
 - You want to represent part-whole hierarchies of objects in a tree like structure.
 - You want to be able to handle multiple objects in the same way.
 - You want to add new components to the collection easily.



Structure



Participants

- Component:
 - Declares the interface for objects in the composition.
 - Implements default behavior for the interface common to all classes, as appropriate.
 - Declares an interface for accessing and managing its child components.
 - (Optional) Defines an interface for accessing a component's parent in the recursive structure, and implements it if that's appropriate.



Participants

- Leaf:
 - Represents leaf objects in the composition. A leaf has no children.
 - Defines behavior for primitive objects in the composition.
- Composite:
 - Defines behavior for components having children.
 - Stores child components.
 - Implements child-related operations in the Component interface.



Participants

- Client
 - manipulates objects in the composition through the Componentinterface.

