

UKRAINIAN CATHOLIC UNIVERSITY

MASTER THESIS

Neural architecture search: a probabilistic approach

Author:
Volodymyr LUT

Supervisor:
Yuriy KHOMA

*A thesis submitted in fulfillment of the requirements
for the degree of Master of Science*

in the

Department of Computer Sciences
Faculty of Applied Sciences



APPLIED
SCIENCES
FACULTY ●

Lviv 2020

Declaration of Authorship

I, Volodymyr LUT, declare that this thesis titled, “Neural architecture search: a probabilistic approach” and the work presented in it are my own. I confirm that:

- This work was done wholly or mainly while in candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this is always clearly attributed.
- Where I have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely my own work.
- I have acknowledged all main sources of help.
- Where the thesis is based on work done by myself jointly with others, I have made clear exactly what was done by others and what I have contributed myself.

Signed:

Date:

“It’s inspiring to see how AI is starting to bear fruit that people can actually taste. There is still a long way to go before we are truly an AI-first world, but the more we can work to democratize access to the technology—both in terms of the tools people can use and the way we apply it—the sooner everyone will benefit.”

Sundar Pichai, CEO Alphabet Inc., May 17, 2017

UKRAINIAN CATHOLIC UNIVERSITY

Faculty of Applied Sciences

Master of Science

Neural architecture search: a probabilistic approach

by Volodymyr LUT

Abstract

In this paper we review different approaches to use probabilistic methods in existing AutoML solutions using Reinforcement Learning. We focus on providing additional knowledge about probability distribution provided to Reinforcement Learning agents solving Neural Architecture Search tasks. Based on the results of the research we come with an agent designed to model Neural Architectures for image classification tasks.

Acknowledgements

First of all, I would like to thank my supervisor Mr. Yuriy Khoma and Mr. Vasily Ganishev for all their support, patience and knowledge shared with me during this project.

I would also like to thank all my colleagues in UCU - those who already graduated, who were working on their masters during this year, and those who left UCU - for being a bright lighthouse, which navigated me towards excellence, for showing a good example and for being a strong and supportive community.

Many thanks to the UCU team - to all those people, who build and design the educational system I am proud being a part of, to all those who inspired me, shared their vision and made my time being a masters program student an unforgettable experience. I thank everyone who works every day in the UCU - no matter whether they are responsible for brilliant coffee or brilliant courses and workshops.

Special thanks goes to my friend and business partner Serhii Chepkyi for providing a big support during my studies and also for providing a big help with visual materials for this project.

Last but definitely not least - I would like to thank my closest people and my family - without your eternal love this would not be possible. This was the hardest years in my life and I'm glad and thankful that every second I've felt that I'm not alone.

Contents

Declaration of Authorship	ii
Abstract	iv
Acknowledgements	v
1 Introduction	1
2 Background overview	2
2.1 History	2
2.2 Reinforcement Learning	3
2.2.1 Markov Decision Process	3
2.2.2 Q Learning	3
2.2.3 Exploration and Exploitation problem	3
2.2.4 Epsilon-greedy approach	3
2.2.5 Upper-confidence bound	3
2.3 Image classification problem	3
2.4 Convolutional Neural Networks	3
2.5 Gaussian Distribution	3
3 Proposed approach	4
3.1 Pipeline	4
3.2 RL agent	4
3.2.1 Reward function	4
3.2.2 Exploration and exploitation	4
3.2.3 Gaussian layer	4
3.3 Master CNN	4
3.4 Slave CNN	4
4 Experiments	5
4.1 Datasets	5
4.2 Metrics	5
4.3 Environment and training	5
4.4 Results	5
5 Conclusion	6
Bibliography	7

List of Figures

List of Tables

List of Abbreviations

ML	Machine Learning
AutoML	Automated Machine Learning
NAS	Neural Architecture Search
RL	Reinforcement Learning
MDP	Markov Decision Process
CNN	Convolutional Neural Network
RNN	Recurrent Neural Network

Physical Constants

Speed of Light $c_0 = 2.997\,924\,58 \times 10^8 \text{ m s}^{-1}$ (exact)

List of Symbols

a	distance	m
P	power	W (J s ⁻¹)
ω	angular frequency	rad

*For all the brave people who make it possible for millions of
young Ukrainians to hold books in their hands instead of rifles
and grenades.*

Chapter 1

Introduction

As machine learning provides a huge variety of automation possibilities for different industries the problem of automation of ML industry itself seems natural. For decades ML engineers were pioneers in the new era of computer science research. As a result, the new industry was shaped and this industry requires automation.

AutoML is a general name of automation in routine work of ML engineers including but not limited to data preparation, feature engineering, feature extraction, neural architecture search, hyperparameters selection, etc.

ML is reshaping businesses and other aspects of everyday life worldwide. We believe that everyone would benefit from the democratization of these new tools. Having the ability to run models on portable devices, IoT chips, and other mass-market hardware we treat AutoML as a big move towards in terms of a variety of different applications created.

In recent years AutoML becomes a natural product for almost all big technological companies. Google, Amazon, Salesforce, and others are offering AutoML products that allow non-experts to create their ML solutions.

Still, existing AutoML techniques require lots of computational resources and most of the research in the field is covered by tech giants nowadays.

We are focusing on neural architecture search problems, especially on hyperparameter optimization tasks because historically this problem is solved mainly using exhaustive search techniques, such as grid search. Engineers often follow their empirical knowledge and try to guess optimal parameters to tune models.

We are using the reinforcement learning paradigm since it is performing well in solving NAS problems. RL agents can design better architectures than related hand-designed models in terms of error-rate and efficiency - see Zoph and Le, 2016.

Moreover, we believe that RL could benefit from probabilistic approaches. We are deeply inspired by DeepAR Salinas, Flunkert, and Gasthaus, 2017 used by Amazon to build forecasting models. We show that Gaussian probability distribution could be used to effectively balance the exploration and exploitation of RL agents solving NAS tasks.

Chapter 2

Background overview

2.1 History

The idea of using RL agents to build neural networks is not new, however, there are not so many research projects nowadays. Mostly the reason for this is that most of the research is held by business, and business usually is not optimistic about RL in production.

However, some good progress was made in recent years. In 2015, ResNet becomes a winner of ILSVRC 2015 in image classification, detection, and localization and winner of MS COCO 2015 detection and segmentation. This enormous network contained 152 layers optimized by a lot of professional engineers manually. This process is expensive in terms of time and resources. Image classification contests are constantly showing a growing amount of layers for best-performing networks (AlexNet, 2012 - 8 layers, GoogleNet, 2014 - 22 layers). Resnet has 1.7 million parameters. Each competition is turning researchers more and more towards automation of this work - and this is a place where NAS becomes a new trend.

Barret Zoph and Quoc Le. in Zoph and Le, 2016 used a recurrent network to generate the model descriptions of neural networks and train this RNN via RL agent to maximize the expected accuracy of the generated architectures on a validation set. This paper is one the most cited in this field and our research is heavily based on it.

In 2019, Google researchers developed a family of models, called EfficientNets, which surpass state-of-the-art accuracy with up to 10x better efficiency (smaller and faster) using AutoML - see Tan and Le, 2019.

Amazon has two AutoML products to offer - Amazon SageMaker Autopilot for the creation of the classification and regression machine learning models and Amazon DeepAR for forecasting scalar (one-dimensional) time series using RNN. This paper is also heavily based on the probabilistic approach used in DeepAR because of it's spectacular results.

This section would not be full without the paper which shares a lot in common with this project. RL agent (Q-Learning, epsilon-greedy exploration rate control, finite state space) described in the paper outperformed meta-modeling approaches for network design on image classification tasks Baker et al., 2016.

The interest to the topic becomes even hotter when the NAS benchmark and dataset was introduced by Google Research team Ying et al., 2019

A variety of methods have been proposed to perform NAS, including reinforcement learning, Bayesian optimization with a Gaussian process model, sequential model-based optimization (SMAC), evolutionary search, and gradient descent over the past few years. We see a lot of research potential in this field and we share a big passion for RL paradigm - and that's why this project exists.

2.2 Reinforcement Learning

2.2.1 Markov Decision Process

2.2.2 Q Learning

2.2.3 Exploration and Exploitation problem

2.2.4 Epsilon-greedy approach

2.2.5 Upper-confidence bound

2.3 Image classification problem

2.4 Convolutional Neural Networks

2.5 Gaussian Distribution

Chapter 3

Proposed approach

3.1 Pipeline

3.2 RL agent

3.2.1 Reward function

3.2.2 Exploration and exploitation

3.2.3 Gaussian layer

3.3 Master CNN

3.4 Slave CNN

Chapter 4

Experiments

4.1 Datasets

4.2 Metrics

4.3 Environment and training

4.4 Results

Chapter 5

Conclusion

Bibliography

- Baker, Bowen et al. (2016). “Designing Neural Network Architectures using Reinforcement Learning”. In: *ArXiv abs/1611.02167*.
- Salinas, David, Valentin Flunkert, and Jan Gasthaus (2017). “DeepAR: Probabilistic Forecasting with Autoregressive Recurrent Networks”. In: *arXiv e-prints*, arXiv:1704.04110, arXiv:1704.04110. arXiv: [1704.04110 \[cs.AI\]](#).
- Tan, Mingxing and Quoc V. Le (2019). “EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks”. In: *arXiv e-prints*, arXiv:1905.11946, arXiv:1905.11946. arXiv: [1905.11946 \[cs.LG\]](#).
- Ying, Chris et al. (2019). “NAS-Bench-101: Towards Reproducible Neural Architecture Search”. In: *Proceedings of the 36th International Conference on Machine Learning*. Ed. by Kamalika Chaudhuri and Ruslan Salakhutdinov. Vol. 97. Proceedings of Machine Learning Research. Long Beach, California, USA: PMLR, pp. 7105–7114. URL: <http://proceedings.mlr.press/v97/ying19a.html>.
- Zoph, Barret and Quoc V. Le (2016). “Neural Architecture Search with Reinforcement Learning”. In: *CoRR abs/1611.01578*. arXiv: [1611.01578](#). URL: <http://arxiv.org/abs/1611.01578>.