


李 环黎部 3







		50,000 cycles	Electrical life
60°±2°C, 90~95% RH	Moisture resistance 60°±2°C, 90~95% RH	100,000 cycles	Mechanical life
-20°~+70°C	245°C±5°C 3 Sec. Temperature range -20°~+70°C	245°C±5°C 3 Sec.	Soldering temper
0.25 +0.25 mm	Travel	\leq 100m Ω (MAX)	Contact Resistance
4.3±0.3mm	Free position	≥100MΩ	Insulation resistance $\geq 100 M\Omega$
160±30gf	□peration force	DC12V 0.5A	Rating

<u>△</u>
<u>△</u>
<u>△</u>
<u>△</u>
<u>A</u>
2005.08.25 更新圖框,發圖

吳美玉

CHECKED BY

APPROVED BY

DATE

2005.08.25 PART NO

DTSM-31N

WS0130A

REVISION

DESCRIPION

REVISED BY

TOLEANCES .X±

DRAWN BY

吳美玉

DESIGNED ERIC SCALE

ANGLE ½

|

Д

UNIT mm

PART NAME

DTSM

SPEC DRAWING

DWG NO

C/PLATE	Cover	Terminal	Stem	Case
SUS 304	SUS 301	C2680R-EH (Ag 0.5u)	Stanyl	Stanyl