Advanced Power Electronics Corp.

APE1117A-HF-3

## 1A Low Dropout Positive Voltage Regulators

Features

■ Maximum dropout of 1.5V at full load current

■ Fast transient response

■ Output current limiting

■ Built-in thermal shutdown

■ Available packages: SOT223, TO252, SOT89

■ Good noise rejection

■ Stable with Only 1uF Low ESR Ceramic Capacitor

■ Three-terminal adjustable or fixed 1.5V, 1.8V, 1.9V, 2.5V, 3.3V, 5.0V

■ RoHS-compliant, halogen-free

Typical Applications

■ PC peripherals

■ Communications

Description

The APE1117A is a low dropout positive adjustable or fixed-mode regulator with minimum output current capability of 1A. The product is specifically designed to provide well-regulated supply for low-voltage IC applications such as high-speed bus-termination and low current 3.3V logic supplies. It is also well suited for other applications such as VGA cards.
The APE1117A is guaranteed to have lower than 1.5V dropout at full load current making it ideal to provide well-regulated outputs of 1.25 to 5.0V with 6.4V to 16V input supply.



5V/3.3V using fixed output version

5V/2.5V using adjustable output version

$$\text{Note: } V_o = V_{REF} * (1 + \frac{R_2}{R_1})$$

Ordering information

APE1117A**X**-**XX**-**HF-3TR**

Halogen Free
Tape and reel (3000pcs/reel)

Vout   Blank : Adjustable
15 : 1.5V
18 : 1.8V
19 : 1.9V
25 : 2.5V
33 : 3.3V
50 : 5.0V

Package
K : SOT223
H : TO252
G(R) : SOT89

Example: APE1117AK-33-HF-3TR   3.3V fixed output in RoHS-compliant, halogen free SOT-223 shipped on tape and reel, 3000pcs/reel

## Block Diagram

Pin Configurations

3 PIN SOT223

(Top View)

```
3  Vin
2  Vout
1  Adj (GND)
```

Tab is Vout

3 PIN TO252

(Top View)

```
3  Vin
2  Vout
1  Adj (GND)
```

Tab is Vout

3 PIN SOT89

(Top View)

```
3  Vin
2  Vout
1  Adj (GND)
```

(Top View GR - alternate pin out)

```
3  Vout
2  Vin
1  Adj (GND)
```

Tab is Vout

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.

Pin Descriptions

NAME	I/O	PIN #	FUNCTION
Adj (GND)	I	1	A resistor divider from this pin to the Vout pin and ground sets the adjustable output voltage. (Ground this pin only for Fixed-Mode)
Vout	O	2	The output of the regulator. A capacitor with a minimum value of 1μF 0.01Ω ≤ ESR ≤ 1Ω) must be connected from this pin to ground to ensure stability.
Vin	I	3	The input pin of regulator. A capacitor with a minimum value of 1μF is connected from this pin to ground to ensure that the input voltage does not sag below the minimum dropout voltage during the load transient response. This pin must always be 1.5V higher than Vout in order for the device to regulate properly.

Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Vin	DC Supply Voltage		-0.3 to 16	V
P_D	Power Dissipation	SOT-223	850	mW
		SOT-89	330	mW
		TO-252	1050	mW
T_{ST}	Storage Temperature		-65 to +150	°C
T_{OP}	Operating Junction Temperature Range		0 to +150	°C

Advanced Power Electronics Corp.

APE1117A-HF-3

Electrical Characteristics

| PARAMETER	CONDITIONS		MIN	TYP	MAX	UNIT
Reference Voltage	APE1117A-ADJ	T_J=25°C, (V_{IN}-V_{OUT})=1.5V I_O=10mA	1.225	1.250	1.275	V
Output Voltage	APE1117A-15	I_{OUT} = 10mA, T_J = 25°C, 3V < V_{IN} < 16V	1.470	1.500	1.530	V
	APE1117A-18	I_{OUT} = 10mA, T_J = 25°C, 3.3V < V_{IN} < 16V	1.764	1.800	1.836	V
	APE1117A-19	I_{OUT} = 10mA, T_J = 25°C, 3.3V < V_{IN} < 16V	1.862	1.900	1.938	V
	APE1117A-25	I_{OUT} = 10mA, T_J = 25°C, 4V < V_{IN} < 16V	2.450	2.500	2.550	V
	APE1117A-33	I_{OUT} = 10mA, T_J = 25°C, 4.8V < V_{IN} < 16V	3.235	3.300	3.365	V
	APE1117A-50	I_{OUT} = 10mA, T_J = 25°C, 6.5V < V_{IN} < 16V	4.900	5.000	5.100	V
Line Regulation	APE1117A-XXX	I_O=10mA,V_{OUT}+1.5V<V_{IN}<16V, T_J=25°C			0.5	%
Load Regulation	APE1117A-ADJ	V_{IN}=3.3V,Vadj=0,10mA<Io<1A, T_J=25°C (Note 1,2)			1	%
	APE1117A-15	V_{IN}=3V, 10mA<Io<1A, T_J=25°C (Note 1,2)		12	15	mV
	APE1117A-18	V_{IN}=3.3V, 10mA<Io<1A, T_J=25°C (Note 1,2)		15	18	mV
	APE1117A-19	V_{IN}=3.3V, 10mA<Io<1A, T_J=25°C (Note 1,2)		16	19	mV
	APE1117A-25	V_{IN}=4V, 10mA<Io<1A, T_J=25°C (Note 1,2)		20	25	mV
	APE1117A-33	V_{IN} = 5V, 10mA<Io<1A, T_J=25°C (Note 1,2)		26	33	mV
	APE1117A-50	V_{IN} = 6.5V, 10mA<Io<1A, T_J=25°C (Note 1,2)		40	50	mV
Dropout Voltage (V_{IN}-V_{OUT})	APE1117A-XXX	I_{OUT} = 1A, ΔV_{OUT}= 1%V_{OUT}		1.3	1.5	V
Current Limit	APE1117A-XXX	(V_{IN}-V_{OUT}) = 5V	1. 1			A
Minimum Load Current	APE1117A-XXX	0°C <Tj <125°C		5	10	mA
Thermal Regulation	T_A=25°C, 30ms pulse			0.008	0.04	%/W
Ripple Rejection	f=120Hz, C_{OUT}=25uF Tantalum, I_{OUT}=1A					
	APE1117A-XXX	V_{IN}=V_{OUT}+3V		60	70	dB
Temperature Stability	I_O=10mA			0.5		%
Thermal Shutdown Temperature				150		°C
Thermal Shutdown Temperature Recovery				130		°C
θ_{JA} Thermal Resistance Junction-to-Ambient (No heat sink; no air flow)	SOT89 SOT-223 TO-252			300 117 92		°C/W
θ_{JC} Thermal Resistance Junction-to-Case	SOT89 : Control Circuitry/Power Transistor SOT-223 : Control Circuitry/Power Transistor TO-252 : Control Circuitry/Power Transistor			100 15 10		°C/W
I_Q Quiescent Current	APE1117A-18/25/28 APE1117A-33	VIN < 9V VIN < 12V		5.5 5.5	10 10	mA

Note1: See thermal regulation specifications for changes in output voltage due to heating effects. Line and load regulation are measured at a constant junction temperature by low duty cycle pulse testing. Load regulation is measured at the output lead = 1/18" from the package.

Note2: Line and load regulation are guaranteed up to the maximum power dissipation of 15W. Power dissipation is determined by the difference between input and output differential and the output current. Guaranteed maximum power dissipation will not be available over the full input/output range.

Note3: Quiescent current is defined as the minimum output current required in maintaining regulation. At 12V input/output differential the device is guaranteed to regulate if the output current is greater than 10mA.

©2009 Advanced Power Electronics Corp. USA
www.a-powerusa.com

4/9

Electrical Characteristics (cont.)

Dropout Voltage vs Output Current

Load Regulation vs Temperature

Percent Change in Output Voltage vs Temperature

Line Regulation

Line Transient Response

Load Transient Response

Marking Information

SOT-223

(Top view)

117A-33
YWWSSS

Output Type:
1117A: Adjustable
117A-15: 1.5V
117A-18: 1.8V
117A-19: 1.9V
117A-25: 2.5V
117A-33: 3.3V
117A-50: 5.0V

Y: Year
"9" = 2009
"A" = 2010
"1" = 2011

SSS: Lot code sequence:
001~
WW: Work week 01~52

TO-252

(Top view)

117A-33
YWWSSS

Output Type:
1117A: Adjustable
117A-15: 1.5V
117A-18: 1.8V
117A-19: 1.9V
117A-25: 2.5V
117A-33: 3.3V
117A-50: 5.0V

Logo

SSS: Lot code sequence
001~
WW: Work week: 01~52

Y: Year "9" = 2009
"A" = 2010
"1" = 2011
~

SOT-89

Date Code
Y: Year
"9" = 2009
"A" = 2010

WW: Work week
01~52

X: Lot code sequence
0~9, A~

XXXXX
YWWX

1 2 3

Identification Code
(See the table)

Identification code	Output Type
17AA(R)	Adjustable (R)
17AB(R)	1.5V (R)
17AC(R)	1.8V (R)
17AG(R)	1.9V (R)
17AD(R)	2.5V (R)
17AE(R)	3.3V (R)
17AF(R)	5.0V (R)

Package Dimensions: TO-252

SYMBOLS	Millimeters		
	MIN	NOM	MAX
A2	1.80	2.30	2.80
A3	0.40	0.50	0.60
B1	0.40	0.70	1.00
D	6.00	6.50	7.00
D1	4.80	5.35	5.90
E3	3.50	4.00	4.50
F	2.20	2.63	3.05
F1	0.50	0.85	1.20
E1	5.10	5.70	6.30
E2	0.50	1.10	1.80
e	--	2.30	--
C	0.35	0.50	0.65

1. All dimensions are in millimeters.

2. Dimensions do not include mold protrusions.

R : 0.127~0.381

(0.1mm

Product APE1117A

Output Voltage (See page 6)

117A-XX

LOGO

YWWSSS

Date/lot code (YWWSSS)
Y:Last digit of the year
WW:Work week
SSS: Lot code sequence

Package Dimensions: SOT-223

SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	6.70	7.00	7.30
B	---	2.30	---
C	2.90	3.00	3.10
D	0.60	0.70	0.80
G	0.25	0.30	0.35
E	6.30	6.50	6.70
F	1.40	1.60	1.80
K	0.02	0.06	0.10

1. All dimensions are in millimeters.

2. Dimensions do not include mold protrusions.

Marking Information

Product APE1117A

Output Voltage (See page 6)

117A-XX

YWWSSS

Date/lot code (YWWSSS)

Y:Last digit of the year

WW:Work week

SSS: Lot code sequence

Advanced Power Electronics Corp.

Package Dimensions: SOT-89

SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	4.40	-	4.60
B	4.05	-	4.25
C	1.40	-	1.75
E	2.40	-	2.60
F	0.89	-	1.20
I	0.35	-	0.55
H	----	1.50	----
G	----	3.00	----
J	1.40	-	1.60
K	0.35	-	0.43

1. All dimensions are in millimeters.

2. Dimensions do not include mold protrusions.

Marking Information

XXXXX
YWWS

Product: See table on page 6

Date/lot code (YWWS)
Y:Last digit of the year
WW:Work week
S: Lot code sequence