

FINEL

Generated by Doxygen 1.8.12

Contents

1	Modules Index	1
1.1	Modules List	1
2	File Index	3
2.1	File List	3
3	Module Documentation	5
3.1	mshapefunctions Module Reference	5
3.1.1	Detailed Description	5
3.1.2	Function/Subroutine Documentation	6
3.1.2.1	setint()	6
3.1.2.2	shpf1d()	6
3.1.3	Variable Documentation	6
3.1.3.1	w	7
3.1.3.2	xi	7
3.2	mutilities Module Reference	7
3.2.1	Detailed Description	7
3.2.2	Function/Subroutine Documentation	7
3.2.2.1	f1()	7
3.2.2.2	linspace()	8
3.2.2.3	quad1()	8
3.2.2.4	test_shpf1d()	9
4	File Documentation	11
4.1	src/driver.F90 File Reference	11
4.1.1	Function/Subroutine Documentation	11
4.1.1.1	finel()	11
4.2	src/shapeFunctions.F90 File Reference	12
4.3	src/utilities.F90 File Reference	12
	Index	13

Chapter 1

Modules Index

1.1 Modules List

Here is a list of all modules with brief descriptions:

mshapefunctions	Module for shape functions computations and relate operations	5
mutilities	Module for auxiliar routines	7

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

src/ driver.F90	11
src/ shapeFunctions.F90	12
src/ utilities.F90	12

Chapter 3

Module Documentation

3.1 mshapefunctions Module Reference

Module for shape functions computations and relate operations.

Functions/Subroutines

- subroutine [setint](#)
Gauss quadrature data set routine.
- subroutine [shpf1d](#) (xl, n, psi, dpsl)
Calculates the values of the shape functions and their derivatives.

Variables

- real *8, dimension(4, 4) [xi](#)
Gauss point integration.
- real *8, dimension(4, 4) [w](#)
Gauss weights.

3.1.1 Detailed Description

Module for shape functions computations and relate operations.

Author

Diego T. Volpatto


3.1.2 Function/Subroutine Documentation

3.1.2.1 `setint()`

```
subroutine mshapefunctions::setint ( )
```

Gauss quadrature data set routine.

Here is the caller graph for this function:



3.1.2.2 `shpf1d()`


```
subroutine mshapefunctions::shpf1d (
    real*8 xl,
    integer n,
    real*8, dimension(n) psi,
    real*8, dimension(n) dpsi )
```

Calculates the values of the shape functions and their derivatives.

Parameters

<i>xl</i>	[in] specified value of master element coord
<i>n</i>	[in] number of element nodes
<i>psi</i>	[out] shape function values
<i>dpsi</i>	[out] derivatives shape functions values

Here is the caller graph for this function:



3.1.3 Variable Documentation

3.1.3.1 w

```
real*8, dimension(4,4) mshapefunctions::w
```

Gauss weights.

3.1.3.2 xi

```
real*8, dimension(4,4) mshapefunctions::xi
```

Gauss point integration.

3.2 mutilities Module Reference

Module for auxiliar routines.

Functions/Subroutines

- subroutine [linspace](#) (x1, x2, nintv, x)
Generate points between x1 and x2 equally spaced in x(i). Same idea of numpy subroutine.
- real *8 function [f1](#) (x)
A function to test purpose.
- subroutine [quad1](#) (n, x1, x2)
Subroutine that computes gaussian quadrature of f1.
- subroutine [test_shpf1d](#) (n, nelem, x)
Check if shpf1d works properly.

3.2.1 Detailed Description

Module for auxiliar routines.

Author

Diego T. Volpatto

3.2.2 Function/Subroutine Documentation

3.2.2.1 f1()

```
real*8 function mutilities::f1 (  
    real*8 x )
```

A function to test purpose.

Parameters

<i>x</i>	input coordinate
----------	------------------

Here is the caller graph for this function:

**3.2.2.2 linspace()**

```


subroutine mutilities::linspace (
    real*8 x1,
    real*8 x2,
    integer nintv,
    real*8, dimension(:), allocatable x )
  
```

Generate points between x1 and x2 equally spaced in x(i). Same idea of numpy subroutine.

Parameters

<i>x1</i>	interval lower bound
<i>x2</i>	interval upper bound
<i>nintv</i>	num of intervals
<i>x</i>	vector to assemble the values

Here is the caller graph for this function:

**3.2.2.3 quad1()**

```

subroutine mutilities::quad1 (
    integer n,
  
```

```

real*8 x1,
real*8 x2 )

```

Subroutine that computes gaussian quadrature of f1.

Parameters

<i>n</i>	quadrature order
<i>x1</i>	integral lower bound
<i>x2</i>	integral upper bound

Here is the call graph for this function:



3.2.2.4 test_shpf1d()

```

subroutine mutilities::test_shpf1d (
    integer n,
    integer nelem,
    real*8, dimension(nelem+1) x )

```

Check if shpf1d works properly.


Parameters

<i>n</i>	element node numbers
<i>nelem</i>	num of discrete intervals
<i>x</i>	master element's coordinates

Here is the call graph for this function:



Here is the caller graph for this function:



Chapter 4

File Documentation

4.1 src/driver.F90 File Reference

Functions/Subroutines

- program [finel](#)

A FIN ELeMent program for general purpose problems. The present is based in the book "Finite Elements: An Introduction" wrote by Eric Becker, Graham Carey and Tinsley Oden.

4.1.1 Function/Subroutine Documentation

4.1.1.1 finel()

```
program finel ( )
```

A FIN ELeMent program for general purpose problems. The present is based in the book "Finite Elements: An Introduction" wrote by Eric Becker, Graham Carey and Tinsley Oden.


Due to the evolution of Fortran programming language, the code developed here incorporate several changes comparing to the original given in the book cited before. Modular paradigm was employed, as well a little of derived data structure.

Implementations by Diego T. Volpatto. email: volpatto@lncc.br or dtvolpatto@gmail.com

Author

Diego Tavares Volpatto

Here is the call graph for this function:



4.2 src/shapeFunctions.F90 File Reference

Modules

- module [mshapefunctions](#)
Module for shape functions computations and relate operations.

Functions/Subroutines

- subroutine [mshapefunctions::setint](#)
Gauss quadrature data set routine.
- subroutine [mshapefunctions::shpf1d](#) (xl, n, psi, dpsi)
Calculates the values of the shape functions and their derivatives.

Variables

- real *8, dimension(4, 4) [mshapefunctions::xi](#)
Gauss point integration.
- real *8, dimension(4, 4) [mshapefunctions::w](#)
Gauss weights.

4.3 src/utilities.F90 File Reference

Modules

- module [mutilities](#)
Module for auxiliar routines.

Functions/Subroutines

- subroutine [mutilities::linspace](#) (x1, x2, nintv, x)
Generate points between x1 and x2 equally spaced in x(i). Same idea of numpy subroutine.
- real *8 function [mutilities::f1](#) (x)
A function to test purpose.
- subroutine [mutilities::quad1](#) (n, x1, x2)
Subroutine that computes gaussian quadrature of f1.
- subroutine [mutilities::test_shpf1d](#) (n, nelem, x)
Check if shpf1d works properly.

Index

- driver.F90
 - finel, [11](#)
- f1
 - mutilities, [7](#)
- finel
 - driver.F90, [11](#)
- linspace
 - mutilities, [8](#)
- mshapefunctions, [5](#)
 - setint, [6](#)
 - shpf1d, [6](#)
 - w, [6](#)
 - xi, [7](#)
- mutilities, [7](#)
 - f1, [7](#)
 - linspace, [8](#)
 - quad1, [8](#)
 - test_shpf1d, [9](#)
- quad1
 - mutilities, [8](#)
- setint
 - mshapefunctions, [6](#)
- shpf1d
 - mshapefunctions, [6](#)
- src/driver.F90, [11](#)
- src/shapeFunctions.F90, [12](#)
- src/utilities.F90, [12](#)
- test_shpf1d
 - mutilities, [9](#)
- w
 - mshapefunctions, [6](#)
- xi
 - mshapefunctions, [7](#)