

LONGi

LONGi eHome

LGie-HTL15/20K-HS

Low Voltage Three-Phase Hybrid Inverter



Higher Returns, More Power

With a low start-up voltage of 130V, the system turns on earlier and shuts down later, boosting daily energy harvest.



Leading Efficiency, More Energy

≥97% European efficiency, minimizes energy loss and maximizes usable output.



IP66 Protection, More Reliability

Designed for demanding environments, with protection against rain and dust to support stable long-term operation. Backed by a 10-year warranty.

97%
European Efficiency

130V
Start-up Voltage

20A
Max. Input Current per MPPT

IP66
Ingress Protection

Model	LGie-HTL15K-HS	LGie-HTL20K-HS
PV Input		
Max. input power (W)	30,000	40,000
Starting Voltage (V)	130	130
Max. DC Input Voltage (V)	1000	1000
Rated DC Input Voltage (V)	600	600
MPPT Voltage Range (V)	160-850	160-850
No. of MPP Trackers	4	4
No. of DC Inputs per MPPT	1/1/1/1	1/1/1/1
Max. Input Current (A)	20/20/20/20	20/20/20/20
Max. Short-circuit Current (A)	30/30/30/30	30/30/30/30
Battery		
Battery Type	Lithium battery / Lead-acid battery	
Battery Communication Mode	CAN	
Number of Battery Inputs	2	2
Battery Voltage Range (V)	40-60	40-60
Max. Charge/Discharge Current (A)	160/160	215/215
AC Input and Output (On-Grid)		
Rated Output Power (W)**	15,000	20,000
Max. Output Apparent Power (VA)	16,500	22,000
Max. Input Apparent Power (VA)	22,500	30,000
Rated Output Voltage (V)**	3L/N/PE, 220/230 , 380/400	
Rated AC Frequency (Hz)	50/60	
Max. Output Current (A)	25	33.4
Power Factor	>0.99 (0.8 leading ...0.8 lagging)	
Max. Total Harmonic Distortion	<3% @Rated Output Power	
Output (Back-up)		
Rated Output Power (W)	15,000	20,000
Max. Output Apparent Power (VA)	165,00	22,000
Max. Output Current (A)	25	33.4
Max. Bypass Current(Grid to Backup Load) (A)	34	45
UPS Switching Time(ms)	<10	
Rated Output Voltage (V)	3L/N/PE, 380/400	
Rated AC Frequency (Hz)	50/60	
Peak Output Apparent Power (VA)	30,000 ^① ,10s	40,000 ^① ,10s

Efficiency	
Max. Efficiency	97.6%
European Efficiency	97.0%
Max. Charging and Discharging Efficiency	95%
Protection	
PV Reverse Polarity Protection	Integrated
Insulation Resistance Protection	Integrated
DC Switch	Integrated
Surge Protection	Integrated
Over-temperature Protection	Integrated
Residual Current Protection	Integrated
Islanding Protection	Integrated
AC Over-voltage Protection	Integrated
Overload Protection	Integrated
AC Short-circuit Protection	Integrated

General Data	
Over Voltage Category	DC : II ; AC : II
Dimensions (W*D*H mm)	572*219*782
Weight (kg)	50
Protection Degree	IP66
Topology(Solar/Battery)	Transformerless / High-frequency isolation
Operating Temperature Range (°C)	-25~60
Relative Humidity (%)	0~100
Derating Altitude (m)	3000
Cooling	Intelligent Air Cooling
Display	LCD
Communication	RS485/LAN/Bluetooth/WiFi

① The output power will exceed the rated value only when the power in the PV array is sufficient, and the duration of the overload is relating to the overload power.

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to LONGi.