

LONGi

LONGi eHome

LGie-LV16-H Battery

Low Volatage Battery System



Steady Power for Peak Hours

Supports the start-up of high-power appliances and handles peak household loads with greater confidence.



Premium Cells, Superior Quality

A+ grade LiFePO_4 cells offer excellent consistency, while cobalt-free chemistry supports safer, more reliable long-term operation.



Multi-Layered Protection, Enhanced Safety

An integrated BMS provides coordinated monitoring, early warning, and response for safer operation.

16kWh
Usable Energy Capacity

90%
Depth of Discharge

200A
Charging/Discharging
Current

8000* cycles
Cycle Life

Model	LGie-LV16-H	2×LGie-LV16-H	3×LGie-LV16-H	4×LGie-LV16-H
Usable Energy Capacity [kWh]	16	32	48	64
Battery Module	51.2V 16kWh			
Number of Modules	1	2	3	4
Cell Type	LFP(LiFePO ₄)			
Nominal Voltage [V]	51.2			
Operating Voltage Range [V]	40-58.4			
Max. Charge/Discharge Current [A]	300	400	400	400
Recommend Charge/Discharge Current [A]	200	400	400	400
Continue Discharge Output [kW]	10.24	20.48	20.48	20.48
Dimensions [W*D*H mm]	724*240*710			
Approximate Weight [kg]	121	242	363	484

General Specifications

Recommend Depth of Discharge	90%
LED Indicator	4 LED (SOC: 25%-SOC:100% blue), 2 LED (working green, alarming red)
IP Rating of Enclosure	IP65
Operating Temperature	Charge: 0°C - 50°C / Discharge: -20°C - 50°C
Storage Temperature	0°C - 35°C
Humidity	≤ 95%
Altitude	≤ 4000m
Cycle Life	10 years, 8000* cycles
Installation	Floor-mounted
Communication Port	CAN
Certification	UN38.3, EMC

Module

Battery Type	LFP(LiFePO ₄)	Operating Temperature	Charge: 0°C-50°C Discharge: -20°C-50°C
Nominal Voltage	51.2V	Ingress Protection	IP65
Nominal Capacity	314Ah	Dimension [W / D / H]	724*240*710mm
Usable Energy Capacity	16kWh	Weight Approximate	121kg
Max. Charge / Discharge Current	300A		
Storage Temperature	0°C - 35°C		

*Tested under specific laboratory conditions: 25°C, 0.5C, 70% DOD, 60% EOL.