

LONGi

LONGi eHome

LGie-LV5-H battery

Low Volatage Battery System



Steady Power for Peak Hours

1C continuous discharge delivers stable power to meet peak household loads.



Premium Cells, Superior Quality

A+ grade LiFePO_4 cells offer excellent consistency, while cobalt-free chemistry supports safer, more reliable long-term operation.



Multi-Layered Protection, Enhanced Safety

An integrated BMS provides coordinated monitoring, early warning, and response for safer operation.

5.12kWh
Usable Energy Capacity

90%
Depth of Discharge

1C
Charging/Discharging

8000* cycles
Cycle Life

Model	LGie-LV5-H	2×LGie-LV5-H	3×LGie-LV5-H	4×LGie-LV5-H
Usable Energy Capacity [kWh]	5.12	10.24	15.36	20.48
Battery Module		51.2V 5.12kWh		
Number of Modules	1	2	3	4
Cell Type	LFP(LiFePO ₄)			
Nominal Voltage [V]	51.2			
Operating Voltage Range [V]	40-58.4			
Max. Charge/Discharge Current [A]	100	200	260	260
Continue Discharge Output [kW]	5.12	10.24	13.312	13.312
Dimensions [W*D*H mm]	500*160*660			
Approximate Weight [kg]	49.1	98.2	147.3	196.4

General Specifications

Recommend Depth of Discharge	90%
LED Indicator	4 LED (SOC: 25%-SOC:100% blue), 2 LED (working green, alarming red)
IP Rating of Enclosure	IP65
Operating Temperature	Charge: 0°C - 55°C / Discharge: -20°C - 55°C
Storage Temperature	0°C - 35°C
Humidity	≤ 95%
Altitude	≤ 3000m
Cycle Life	10 years, 8000* cycles
Installation	Floor-mounted
Communication Port	CAN
Certification	UN38.3, EMC

Module

Battery Type	LFP(LiFePO ₄)	Operating Temperature	Charge: 0°C-55°C Discharge: -20°C-55°C
Nominal Voltage	51.2V	Ingress Protection	IP65
Nominal Capacity	100Ah	Dimension [W / D / H]	500*160*660mm
Usable Energy Capacity	5.12kWh	Weight Approximate	49.1kg
Max. Charge / Discharge Current	100A		
Storage Temperature	0°C - 35°C		

*Tested under specific laboratory conditions: 25°C, 0.5C, 70% DOD, 60% EOL.