

LONGi

LONGi eHome

LGie-HSL06/08K-HS

Low Voltage Single Phase Hybrid Inverter



Higher Returns, More Power

With a low start-up voltage of 58V, the system turns on earlier and shuts down later, boosting daily energy harvest.



Leading Efficiency, More Energy

≥97% European efficiency, minimizes energy loss and maximizes usable output.



IP66 Protection, More Reliability

Designed for demanding environments, with protection against rain and dust to support stable long-term operation. Backed by a 10-year warranty.

97%
European Efficiency

58V
Start-up Voltage

20A
Max. Input Current per MPPT

IP66
Ingress Protection

Model	LGie-HSL06K-HS	LGie-HSL08K-HS
PV Input		
Max. input power (W)	12,000	12,000
Start-up Voltage (V)	58	58
Max. DC Input Voltage (V)	600	600
Rated DC Input Voltage (V)	360	360
MPPT Voltage Range (V)	80-550	80-550
No. of MPP Trackers	2	2
No. of DC Inputs per MPPT	1/1	1/1
Max. Input Current (A)	20/20	20/20
Max. Short-circuit Current (A)	25/25	25/25
Battery		
Battery Type	Lithium battery (with BMS)/Lead Acid	
Battery Communication Mode	CAN	
Battery Voltage Range (V)	40-60	40-60
Max. Charge/Discharge Current (A)	120/120	160/160
Output (Grid)		
Rated Output Power (W)**	6,000	8,000
Max. Output Power (W)	6,600	8,800
AC Output Rated Apparent Power (VA)	6,000	8,000
Max. Apparent Power (VA)	6,600	8,800
Rated Output Voltage (V)**	L/N/PE, 220/230	
Rated AC Frequency (Hz)	50/60	
AC Output Rated Current (A)	26.1	34.8
Max. Output Current (A)	30	40
Max. Output Fault Current (A)	80	80
Max. Output Overcurrent Protection (A)	80	80
Power Factor	0.8 leading ...0.8 lagging	
Max. Total Harmonic Distortion	<3% @Rated Output Power	
Output (Back-up)		
Rated Output Power (W)	6,000	8,000
Max. Output Power (W)	6,600	8,800
Back-up Output Rated Apparent Power (VA)	6,000	8,000
Max. Apparent Power (VA)	6,600	8,800
Back-up Output Rated Current (A)	26.1	34.8
Max. Output Current (A)	30	40
UPS Switching Time (ms)	<10	
Rated Output Voltage (V)	L/N/PE, 220/230	
Rated AC Frequency (Hz)	50/60	
Peak Output Apparent Power (VA)	12,000 ^① ,10s	12,000 ^① ,10s
Load Capacity of Motors	4HP	4HP

Efficiency		General Data	
Max. Efficiency	97.6%	Over Voltage Category	DC : II ; AC : II
European Efficiency	97.0%	Dimensions (W*D*H mm)	488*205*374
MPPT Efficiency	99.9%	Weight (kg)	21
Protection		Protection Degree	IP66
DC Reverse Polarity Protection	Integrated	Topology	Transformerless
Insulation Resistance Protection	Integrated	Operating Temperature Range (°C)	-25~60
DC Switch	Integrated	Relative Humidity (%)	0~100
Surge Protection	Integrated	Derating Altitude (m)	3000
Over-temperature Protection	Integrated	Cooling	Intelligent Air Cooling
Residual Current Protection	Integrated	Display	LCD
Islanding Protection	Integrated	Communication	RS485/LAN/WiFi/Bluetooth
AC Over-voltage Protection	Integrated		
Overload Protection	Integrated		
AC Short-circuit Protection	Integrated		

① The output power will exceed the rated value only when the power in the PV array is sufficient, and the duration of the overload is relating to the overload power.

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to LONGi.