

1. (a) `grep 'pat[ao]' teste.txt`
(b) `grep '\bpato\b' teste.txt`
(c) `grep '\bpat\w*os\?\b' teste.txt`
(d) `grep 'eco$' teste.txt`
(e) `grep '^Pin' teste.txt`
(f) `grep '^Pin.*ima\?$' teste.txt`
(g) `grep '?$' teste.txt`
(h) `grep '[!?]$' teste.txt`
(i) `grep ',' teste.txt`
(j) `egrep ',\s*\w+\s*,' teste.txt`
(k) `grep '\*' teste.txt`
(l) `grep '^[^\\*]*\\*[^\n]*$' teste.txt`
(m) `grep '\\.\\. ' teste.txt`
(n) `egrep '(\++|--)' teste.txt`
(o) `egrep '(\++.*--|--.*\++)' teste.txt`

2. Letreco

```
# monta lista de palavras com 5 letras
grep '^[a-z]....$' /usr/share/dict/brazilian >letreco.txt

# A na posicao certa, E nao e' 3a letra, sem I e V
cat letreco.txt | grep 'a.[^e]..' | grep e | grep -v '[iv]'
```

3. `egrep '^[0-9]+[\+|\-|*|/][0-9]+=[0-9]+$' expr-arit-1.txt`
4. `egrep '^\\s*[0-9]+\\s*[\+|\-|*|/]\\s*[0-9]+\\s*=\\s*[0-9]+\\s*$' expr-arit-2.txt`
5. `cat /tmp/foo.html | sed 's/<[^>]*>//g' | grep '\\S'`
6. `cat agenda.txt | sed -E 's/\\b([89][0-9][0-9][0-9])\\-\\/9\\1\\-/'`