Stereo I2S audio for internal Linux computer

Rev B. Connected circuit and footprint draft. Read status.md before fabrication.

Stereo speaker amplifier

File: audio.kicad_sch

Audio harness


File: interface.kicad_sch


Sheet: /
File: stereo-audio.kicad_sch


Title:


Size: A3	Date:	**Rev:**
KiCad E.D.A. 9.0.7		Id: 3/3


MAX98357A, 3.3 V supply, 8-ohm 1 W speakers. Default muted by pull-down on AMP_ENABLE.
3.3 V reduces available output; clipping can still overdrive a speaker. Start volume low.
OUT+ and OUT− are both driven. Never connect speaker terminals to ground.



























Connected schematic; hardware and manufacturing validation pending

Sheet: /Stereo speaker amplifier/ File: audio.kicad_sch		
Title: Stereo speaker amplifier		
Size: A3	Date:	**Rev: B — engineering draft**
KiCad E.D.A. 9.0.7		Id: 2/3

All signals use 3.3 V logic. J3 is a prototype header, not the final internal harness connector.
I2S: 48 kHz, 2 channels, 32-bit slots. Keep clocks paired with ground and traces short.
AMP_ENABLE remains low until valid clocks and zeroed samples are running.

J3
J3



R3
33

R4
33

R5
33

R6
10k

C5
47u 10V



#FLG01
PWR_FLAG

#FLG02
PWR_FLAG

H1
M2

H2
M2

H3
M2

H4
M2

Connected schematic; hardware and manufacturing validation pending

Sheet: /Audio harness/
File: interface.kicad_sch

Title: Audio harness

Size: A3	Date:	**Rev: B — engineering draft**
KiCad E.D.A. 9.0.7		Id: 3/3