




CARDWELL Variable Capacitors



A



B


C



D



E


F


G


H


J


I

(A) Midway Featherweight Capacitors

Straight-line-capacity type. Light in weight, compact (panel space only 3″ x 2¼″), adapted to receivers and 25-watt, or lower, CW transmitters; also portable equipment. Extremely rugged and rigid. Air gap between plates is .031″. Shaft diameter ¼″. Mycalex insulation.

SINGLE CONDENSERS

Cat. No.	Type	Max. Cap.	Min. Cap.	Net Price
18-801	MR-25-BS	25	5	$2.38
18-802	MR-50-BS	50	6	3.00
18-803	MR-70-BS	70	7	3.10
18-804	MR-105-BS	105	8	3.22
18-805	MR-150-BS	150	10	3.56
18-806	MR-260-BS	260	11	3.85
18-807	MR-365-BS	365	14	4.20
18-808	MO-150-BS	150	14	Spec.
18-809	MO-165-BS*	165	15	2.94

*.050″ gap.

DOUBLE CONDENSERS

Cat. No.	Type	Max. Cap. Each	Min. Cap. Each	Net Price
18-810	MR-25-BD	25	5	$3.85
18-811	MR-50-BD	50	6	4.11
18-812	MR-70-BD	70	7	4.32
18-813	MR-100-BD	100	8	4.50
18-814	MR-150-BD	150	9	4.65
18-815	MR-260-BD	260	11	5.25
18-816	MO-180-BD*	180	15	7.07

(B) Featherweight Transmitting Capacitors

A very popular condenser in the amateur experimental and commercial fields. Air gap of .070″ suits it to use in CW transmitters up to 100 watts power or phone transmitters up to 50 watts carrier with 100% modulation. Mycalex insulation.

SINGLE CONDENSERS

Cat. No.	Type	Max. Cap.	Min. Cap.	Net Price
18-817	MT-20-GS	20	5	$2.88
18-818	MT-35-GS	35	6	3.10
18-819	MT-50-GS	50	8	3.45
18-820	MT-70-GS	70	10	3.96
18-821	MT-100-GS	100	12	4.32
18-822	MT-150-GS	150	16	5.31
18-823	MG-35-NS	35	12	5.31

DOUBLE CONDENSERS

Cat. No.	Type	Max. Cap. Each	Min. Cap. Each	Net Price
18-824	MT-20-GD	20	7	$4.90
18-825	MT-35-GD	35	7	5.51
18-826	MT-50-GD	50	9	5.61
18-827	MT-70-GD	70	10	6.18
18-828	MT-100-GD	100	13	7.05

(C) Standard Transmitting Capacitors

Heavy rotor and stator plates, with rounded edges, are buffed and polished insuring minimum corona losses and maximum peak breakdown voltage. A self-cleaning phosphor bronze contact spring accomplishes a perfect rotor connection offering very low RF contact resistance. Mycalex insulated.

SINGLE CONDENSERS

Cat. No.	Type	Max. Cap.	Min. Cap.	Net Price
18-829	XT-220-PS	220	20	$4.41
18-830	XP-90-KS	90	16	3.94
18-831	XP-165-KS	165	22	5.76
18-832	XP-290-KS	290	35	8.40
18-833	XP-330-KS	330	37	9.59
18-834	XG-25-XS	25	8	3.12
18-835	XG-50-XS	50	15	5.74
18-836	XG-110-XS	110	26	8.58
18-837	XC-18-XS	18	8	3.94
18-838	XC-40-XS	40	15	5.74
18-839	XC-100-XS	100	28	9.31
18-840	XD-160-XS	160	28	7.98
18-841	XR-50-PS	50	11	3.05
18-842	XR-100-PS	100	12	3.12
18-843	XR-250-PS	250	13	3.26
18-844	XC-65-XS	65	20	7.53
18-845	XK-55-XS	55	20	8.86

DOUBLE CONDENSERS

Cat. No.	Type	Max. Cap. Sec. Each	Min. Cap. Sec. Each	Net Price
18-846	XR-500-PD	500	18	$8.40
18-847	XT-80-PD	80	11	5.60
18-848	XT-210-PD	210	22	7.70
18-849	XP-90-KD	95	15	6.65
18-850	XP-325-KD	325	38	19.50
18-851	XG-50-XD	50	14	9.45
18-852	XG-110-XD	110	27	15.93
18-853	XC-40-XD	40	14	10.17
18-854	XD-160-XD	160	28	16.84
18-855	XC-75-XD	75	21	13.31

(D) Ultra-High Frequency Transmitting Capacitors

A complete series of efficient, medium-powered transmitting condensers for 5, 10, and 20 meters. No frame or tie rods; aluminum end plates; long, brass, nickel-plated front bearing with ball thrust rear bearing. Insulation is Isolantite. Single-hole mounting, or can be mounted on brackets listed on this page.

SINGLE CONDENSERS

Cat. No.	Type No.	Cap. Range	Net Price
18-856	NP-50-DS†	50-9	$3.10
18-857	NP-75-DS†	75-11.0	3.63
18-858	NP-100-DS†	100-13	4.11
18-859	NP-150-DS†	150-19	5.39
18-860	NG-35-DS‡	35-11	4.06

DOUBLE CONDENSERS

18-861	NT-50-GD*	50-7	5.31
18-862	NP-15-ND*	17-4	5.04
18-863	NP-35-ND†	35-5	5.31
18-864	NP-35-DD†	35-5	4.56
18-865	NP-50-DD†	50-9	5.31
18-866	NP-75-DD†	75-11	6.37
18-867	NA-12-ND†	13-7	13.30

* Air gap .070″ 3000 volt peak.
† Air gap .084″ 4200 volt peak
‡ Air gap .171″ 6000 volt peak.

"M" Mounting Brackets

Made to fit the "N" or "M" type capacitors on this page. Satin-finish aluminum. Supplied with hardware.
Cat. No. 18-916 Net Price . . . 15c

(E) Differential Type Trim-Air Midgets

Small, compact, balancing type capacitor having ideal features of the regular Trim-air. All single-bearing type except EU-140-AB. Mount in single ⅜″ hole.

Cat. No.	Type	Max. Cap.	Min. Cap.	Net Price
18-925	EU-75-AB	75	2.7	$1.89
18-926	EU-100-AB	100	3	1.98
18-927	EU-140-AB	140	5	3.99
18-928	ER-10-AB	10	1.5	1.38
18-929	ER-25-AB	25	2	1.44
18-930	ER-50-AB	50	2.8	1.74

(E) Trim-Air Heavy Duty Specials

Cat. No.	Type	Max. Cap.	Min. Cap.	Net Price
18-931	EU-75-ASP	75	2.7	$2.37
18-932	ER-50-ASP	50	2.8	2.61
18-933	ET-30-ASP	30	4.0	2.43
	DOUBLE			
18-934	EU-140-ADP	*140RSE	5	6.96
18-935	ER-50-ADP	50	2.8	2.88
18-936	ER-50-ADP	*50RSE	2.8	5.22

* Rear Shaft Extension.

(F) Trim Airs

Use of Isolantite insulation makes these condensers excellent for ultra-high-frequency work. Shaft with rotor locking nut. Panel mounting by means of bushing and nut.

Cat. No.	Type No.	Max. Cap.	Min. Cap.	Net Price
18-900	ZU-75-AS	75	2.7	$1.50
18-901	ZU-100-AS	100	3	1.53
18-902	ZU-140-AS*	140	5	2.76
18-903	ZR-10-AS	10	1.2	1.11
18-904	ZR-15-AS	15	1.5	1.14
18-905	ZR-25-AS	25	2	1.26
18-906	ZR-35-AS	35	2.5	1.32
18-907	ZR-50-AS	50	2.8	1.38
18-908	ZR-100-AS	30	4	1.98
18-909	ZT-10-AS	11	3.6	1.29
18-910	ZV-5-TS†	5	1.8	1.11
18-911	ZT-15-AS	15	3	1.35
18-912	ZT-30-AS	30	4	1.65
18-913	ZS-4-SS	4	1.5	1.65
18-914	ZS-7-SS	7	4	1.83

* Double bearing; two end plates.
† Supplied with 2 segment stator for 5 meter circuits.

(G) Dual Trim Airs

Incorporates all of the excellent features of the single Trim-air. Ideal for push-pull exciter unit, portable ultra H.F. gear and laboratory equipment.

Cat. No.	Type No.	Max. Cap.	Min. Cap.	Net Price
18-887	EU-75-AD	75	2.7	$2.88
18-888	EU-100-AD	100	3	3.00
18-889	EU-140-AD	140	5	5.31
18-890	ER-10-AD	10	1.2	2.31
18-891	ER-15-AD	15	1.5	2.31
18-892	ER-25-AD	25	2	2.37
18-893	ER-35-AD	35	2.5	2.58
18-894	ER-50-AD	50	2.8	2.73
18-895	ER-100-AD	100	6.9	4.89
18-896	ET-15-AD	15	3	2.84
18-897	ET-30-AD	30	4	3.18
18-898	ES-4-SD	4	1.5	3.18
18-899	ES-7-SD	7	4	3.54

(H) Trim-Air Bracket

Specially designed bracket for Trim-air condensers, permits mounting on chassis. Insulated from rotor. Very sturdy.
Cat. No. 18-915 Net Price . . . 12c

(I) Cardwell Disc Type Neutralizer

Satin-finish aluminum; fine screw adjustment, no wobble. Knurled thumb-nut for easy locking. Nickel-silver bearing. Glazed steatite insulation.
Cat. No. 18-937 Type ADN Range 1 mmf. to 7 mmf. Net Price $2.65
Cat. No. 18-938 Type BDN Range 3 mmf. to 15 mmf. Net Price $4.45

(J) Neutralizing Capacitors

For new low-capacity tubes. Mycalex insulation.

Cat. No.	Type	Cap.	Net Price
18-868	NA-4-NS†	4-3.25	$3.03
18-869	NA-6-NS*	6-4	3.03
18-870	NA-10-NS*	12-6	3.42
18-871	NA-16-NS*	16-7	4.45

* 6600 volt peak.
† Adjustable peak voltage.