Dual-Gang 922111-2 (~575pF / Section) Variable Capacitor

High-Capacity Dual-Section Air Variable Tuning Capacitor with Shaft Collar

Product Overview

The 922111-2 is a high-capacitance dual-gang air variable capacitor delivering approximately 575 pF per section. It is specifically designed for high-inductance tuning networks, low-frequency RF circuits, antenna matching units (transmatches), and AM/broadcast receiving gear requiring large capacitance swings.

Technical Specifications

Part Number	922111-2
Capacitance Rating	~575 pF per section (Dual-Section / 2-Gang)
Total Capacitance (Parallel)	~1,150 pF combined maximum capacitance
Shaft Attachment	Precision machined aluminum shaft collar with dual brass set screws
Chassis / Shielding	Formed aluminum U-channel frame with underside inspection ports
Insulation	High-Q ceramic / phenolic stator support blocks
Mounting	Chassis mounting bosses with dual machine screws on bottom housing

Key Features & Construction

- Extra high capacitance: 575 pF per section allows wide tuning ratios in low-frequency bands
- Heavy-duty machined aluminum shaft collar with dual set screws for rigid coupling
- Formed aluminum chassis shielding provides mechanical rigidity and dust deflection
- Dual independent stator terminals for push-pull, balanced, or parallel configurations
- High plate count multi-rotor assembly ensuring linear capacitance variation

Mechanical & Mounting Details

- Shaft: Machined aluminum extension collar (1/2 inch OD, 1/4 inch bore) with dual set screws
- Frame dimensions: approx. 3.0 inches wide x 3.25 inches long x 2.75 inches high
- Bottom mounting: Threaded mounting bosses with machine screws
- Access ports: Two circular underside inspection holes for plate alignment inspection