Hammarlund ES-675536-9 / APC Series Variable Air Trimmer

Hammarlund Manufacturing Company, Inc. (New York, NY)

Product Overview

The Hammarlund ES-675536-9 is a precision air dielectric trimmer capacitor manufactured by Hammarlund in New York. Based on the venerable APC/HF series architecture, it utilizes a silicone-treated steatite ceramic base plate, nickel-plated brass stator and rotor plates, and a threaded panel mounting bushing with an extended rotor control shaft.

Technical Specifications

Part / Model Number	ES-675536-9 (APC / HF Series Architectural Line)
Manufacturer	Hammarlund Manufacturing Company, New York, NY
Capacitance Range	Approx. 3.5 pF min to 50 pF max (standard trimmer span)
Nominal Air Gap	0.015 inches (0.38 mm)
Voltage Breakdown	750 to 1,000 Volts Peak (Test Rating)
Insulation	Silicone-treated steatite ceramic base plate (low dielectric loss)
Rotor Wiper	Silver-plated phosphor bronze wiper contact
Plates Material	Precision brass plates, solder-assembled and nickel plated

Key Features & Construction

- Low-loss steatite ceramic substrate impervious to moisture and humidity
- Straight-line capacitance tuning profile across 180 degrees rotation
- Positive contact silver-plated phosphor bronze rotor wiper for stable grounding
- Integrated threaded bushing with hex mounting nut for single-hole panel installation
- Heavy-duty solder lug terminals with attached lead wire

Mechanical & Mounting Details

- Mounting: 5/16-32 or 3/8-32 threaded mounting bushing with hex nut
- Shaft: 1/4 inch diameter slotted rotor shaft for knob or screwdriver adjustment
- Base dimensions: approx. 1.25 x 1.00 inches steatite plate
- Overall depth: approx. 1.75 inches behind panel