E.F. Johnson KS-16471L1 Air Variable Capacitor

E.F. Johnson Company / Western Electric Kearny Specification (KS-16471 L1)

Product Overview

The E.F. Johnson KS-16471L1 is a telecommunications and military-grade air variable capacitor manufactured for Western Electric under Kearny Specification KS-16471. Utilizing Johnson Type L construction, it features dual steatite ceramic end plates joined by rigid metal support rods, providing exceptional mechanical rigidity and thermal stability.

Technical Specifications

Part Number	KS-16471L1 / Johnson Type L (167 Series)
Manufacturer	E.F. Johnson Company (Waseca, Minnesota)
Specification Standard	Western Electric Kearny Specification (KS-16471 List 1)
Capacitance Range	Approx. 5.2 pF min to 75 pF max
Peak Voltage Rating	1,500 Volts Peak RMS
Dielectric & Frame	Grade L-4 or better steatite ceramic end plates with tie-rod construction
Plate Material	Heavy-gauge silver/nickel plated brass/aluminum soldered to support rods

Key Features & Construction

- Heavy-duty steatite ceramic front and rear end plates for bilateral mechanical support
- High voltage withstand capability (1.5 kV peak) for transmitter and carrier applications
- Precision soldered stator plate assemblies for maximum electrical stability
- Beryllium copper / phosphor bronze wiping rotor ground contact for minimal contact resistance
- Manufactured to rigorous Western Electric KS-spec reliability standards

Mechanical & Mounting Details

- Mounting: Threaded bushing for single-hole panel mounting, with chassis tie-points
- Shaft: 1/4 inch precision brass/steel rotor shaft with slotted end
- Dimensions: approx. 1.5 x 1.5 x 3.5 inches overall length
- Terminal: Heavy silver-plated solder lugs on stator support rods