

Python For Data Science Cheat Sheet

Python Basics

Learn More Python for Data Science Interactively at www.datacamp.com



Variables and Data Types

Variable Assignment

```
>>> x=5
>>> x
5
```

Calculations With Variables

>>> x+2 7	Sum of two variables
>>> x-2 3	Subtraction of two variables
>>> x*2 10	Multiplication of two variables
>>> x**2 25	Exponentiation of a variable
>>> x%2 1	Remainder of a variable
>>> x/float(2) 2.5	Division of a variable

Types and Type Conversion

str()	'5', '3.45', 'True'	Variables to strings
int()	5, 3, 1	Variables to integers
float()	5.0, 1.0	Variables to floats
bool()	True, True, True	Variables to booleans

Asking For Help

```
>>> help(str)
```

Strings

```
>>> my_string = 'thisStringIsAwesome'
>>> my_string
'thisStringIsAwesome'
```

String Operations

```
>>> my_string * 2
'thisStringIsAwesomethisStringIsAwesome'
>>> my_string + 'Innit'
'thisStringIsAwesomeInnit'
>>> 'm' in my_string
True
```

Lists

Also see NumPy Arrays

```
>>> a = 'is'
>>> b = 'nice'
>>> my_list = ['my', 'list', a, b]
>>> my_list2 = [[4,5,6,7], [3,4,5,6]]
```

Selecting List Elements

Index starts at 0

Subset

```
>>> my_list[1]
>>> my_list[-3]
```

Select item at index 1
Select 3rd last item

Slice

```
>>> my_list[1:3]
>>> my_list[1:]
>>> my_list[:3]
>>> my_list[:]
```

Select items at index 1 and 2
Select items after index 0
Select items before index 3
Copy my_list

Subset Lists of Lists

```
>>> my_list2[1][0]
>>> my_list2[1][:2]
```

my_list[list][itemOfList]

List Operations

```
>>> my_list + my_list
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']
>>> my_list * 2
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']
>>> my_list2 > 4
True
```

error

List Methods

>>> my_list.index(a)	Get the index of an item
>>> my_list.count(a)	Count an item
>>> my_list.append('!')	Append an item at a time
>>> my_list.remove('!')	Remove an item
>>> del(my_list[0:1])	Remove an item
>>> my_list.reverse()	Reverse the list
>>> my_list.extend('!')	Append an item
>>> my_list.pop(-1)	Remove an item
>>> my_list.insert(0, '!')	Insert an item
>>> my_list.sort()	Sort the list

String Operations

Index starts at 0

```
>>> my_string[3]
>>> my_string[4:9]
```

String Methods

>>> my_string.upper()	String to uppercase
>>> my_string.lower()	String to lowercase
>>> my_string.count('w')	Count String elements
>>> my_string.replace('e', 'i')	Replace String elements
>>> my_string.strip()	Strip whitespaces

Libraries

Import libraries

```
>>> import numpy
>>> import numpy as np
Selective import
>>> from math import pi
```

pandas Data analysis	Machine learning
NumPy Scientific computing	matplotlib 2D plotting

Install Python

ANACONDA Leading open data science platform powered by Python	spyder Free IDE that is included with Anaconda	jupyter Create and share documents with live code, visualizations, text, ...
---	--	---

NumPy Arrays

Also see Lists

```
>>> my_list = [1, 2, 3, 4]
>>> my_array = np.array(my_list)
>>> my_2darray = np.array([[1,2,3], [4,5,6]])
```

Selecting Numpy Array Elements

Index starts at 0

Subset

```
>>> my_array[1]
2
```

Select item at index 1

Slice

```
>>> my_array[0:2]
array([1, 2])
```

Select items at index 0 and 1

Subset 2D Numpy arrays

```
>>> my_2darray[:,0]
array([1, 4])
```

my_2darray[rows, columns]

NumPy Array Operations

```
>>> my_array > 3
array([False, False, False,  True], dtype=bool)
>>> my_array * 2
array([2, 4, 6, 8])
>>> my_array + np.array([5, 6, 7, 8])
array([6, 8, 10, 12])
```

NumPy Array Functions

>>> my_array.shape	Get the dimensions of the array
>>> np.append(other_array)	Append items to an array
>>> np.insert(my_array, 1, 5)	Insert items in an array
>>> np.delete(my_array, [1])	Delete items in an array
>>> np.mean(my_array)	Mean of the array
>>> np.median(my_array)	Median of the array
>>> my_array.corrcoeff()	Correlation coefficient
>>> np.std(my_array)	Standard deviation

DataCamp

Learn Python for Data Science Interactively

np.corrcoef(my_array)

Python For Data Science Cheat Sheet

Jupyter Notebook

Learn More Python for Data Science Interactively at www.DataCamp.com



Saving/Loading Notebooks

Create new notebook

Make a copy of the current notebook

Save current notebook and record checkpoint

Preview of the printed notebook

Close notebook & stop running any scripts

Open an existing notebook

Rename notebook

Revert notebook to a previous checkpoint

Download notebook as

- IPython notebook
- Python
- HTML
- Markdown
- reST
- LaTeX
- PDF

Writing Code And Text

Code and text are encapsulated by 3 basic cell types: markdown cells, code cells, and raw NBConvert cells.

Edit Cells

Cut currently selected cells to clipboard

Paste cells from clipboard above current cell

Paste cells from clipboard on top of current cell

Revert "Delete Cells" invocation

Merge current cell with the one above

Move current cell up

Adjust metadata underlying the current notebook

Remove cell attachments

Paste attachments of current cell

Copy cells from clipboard to current cursor position

Paste cells from clipboard below current cell

Delete current cells

Split up a cell from current cursor position

Merge current cell with the one below

Move current cell down

Find and replace in selected cells

Copy attachments of current cell

Insert image in selected cells

Insert Cells

Add new cell above the current one

Add new cell below the current one

Working with Different Programming Languages

Kernels provide computation and communication with front-end interfaces like the notebooks. There are three main kernels:

IP[y]:
IPython

R
IRkernel

IJ[.]:
IJulia

Installing Jupyter Notebook will automatically install the IPython kernel.

Restart kernel

Restart kernel & run all cells

Restart kernel & run all cells

Interrupt kernel

Interrupt kernel & clear all output

Connect back to a remote notebook

Run other installed kernels

Command Mode:

Edit Mode:

Executing Cells

Run selected cell(s)

Run current cells down and create a new one above

Run all cells above the current cell

Change the cell type of current cell

toggle, toggle scrolling and clear all output

Run current cells down and create a new one below

Run all cells

Run all cells below the current cell

toggle, toggle scrolling and clear current outputs

View Cells

Toggle display of Jupyter logo and filename

Toggle line numbers in cells

Toggle display of toolbar

Toggle display of cell action icons:

- None
- Edit metadata
- Raw cell format
- Slideshow
- Attachments
- Tags

Widgets

Notebook widgets provide the ability to visualize and control changes in your data, often as a control like a slider, textbox, etc.

You can use them to build interactive GUIs for your notebooks or to synchronize stateful and stateless information between Python and JavaScript.

Download serialized state of all widget models in use

Save notebook with interactive widgets

Embed current widgets

1. Save and checkpoint
2. Insert cell below
3. Cut cell
4. Copy cell(s)
5. Paste cell(s) below
6. Move cell up
7. Move cell down
8. Run current cell
9. Interrupt kernel
10. Restart kernel
11. Display characteristics
12. Open command palette
13. Current kernel
14. Kernel status
15. Log out from notebook server

Asking For Help

Walk through a UI tour

Edit the built-in keyboard shortcuts

Description of markdown available in notebook

Python help topics

NumPy help topics

Matplotlib help topics

Pandas help topics

List of built-in keyboard shortcuts

Notebook help topics

Information on unofficial Jupyter Notebook extensions

IPython help topics

SciPy help topics

SymPy help topics

About Jupyter Notebook



Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



NumPy

The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:



NumPy

```
>>> import numpy as np
```

NumPy Arrays

1D array

```
1 2 3
```

2D array

axis 1
axis 0

```
1.5 2 3  
4 5 6
```

3D array

axis 2
axis 1
axis 0

Creating Arrays

```
>>> a = np.array([1,2,3])  
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)  
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]],  
                dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))  
>>> np.ones((2,3,4),dtype=np.int16)  
>>> d = np.arange(10,25,5)  
  
>>> np.linspace(0,2,9)  
  
>>> e = np.full((2,2),7)  
>>> f = np.eye(2)  
>>> np.random.random((2,2))  
>>> np.empty((3,2))
```

Create an array of zeros
Create an array of ones
Create an array of evenly spaced values (step value)
Create an array of evenly spaced values (number of samples)
Create a constant array
Create a 2X2 identity matrix
Create an array with random values
Create an empty array

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)  
>>> np.savez('array.npz', a, b)  
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")  
>>> np.genfromtxt("my_file.csv", delimiter=',')  
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64  
>>> np.float32  
>>> np.complex  
>>> np.bool  
>>> np.object  
>>> np.string_  
>>> np.unicode_
```

Signed 64-bit integer types
Standard double-precision floating point
Complex numbers represented by 128 floats
Boolean type storing TRUE and FALSE values
Python object type
Fixed-length string type
Fixed-length unicode type

Inspecting Your Array

```
>>> a.shape  
>>> len(a)  
>>> b.ndim  
>>> e.size  
>>> b.dtype  
>>> b.dtype.name  
>>> b.astype(int)
```

Array dimensions
Length of array
Number of array dimensions
Number of array elements
Data type of array elements
Name of data type
Convert an array to a different type

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b  
array([[ -0.5,  0. ,  0. ],  
       [ -3. , -3. , -3. ]])  
>>> np.subtract(a,b)  
>>> b + a  
array([[ 2.5,  4. ,  6. ],  
       [ 5. ,  7. ,  9. ]])  
>>> np.add(b,a)  
>>> a / b  
array([[ 0.66666667,  1. ,  1. ],  
       [ 0.25 ,  0.4 ,  0.5 ]])  
>>> np.divide(a,b)  
>>> a * b  
array([[ 1.5,  4. ,  9. ],  
       [ 4. , 10. , 18. ]])  
>>> np.multiply(a,b)  
>>> np.exp(b)  
>>> np.sqrt(b)  
>>> np.sin(a)  
>>> np.cos(b)  
>>> np.log(a)  
>>> e.dot(f)  
array([[ 7. ,  7. ],  
       [ 7. ,  7.]])
```

Subtraction
Subtraction
Addition
Addition
Division
Division
Multiplication
Multiplication
Exponentiation
Square root
Print sines of an array
Element-wise cosine
Element-wise natural logarithm
Dot product

Comparison

```
>>> a == b  
array([[False,  True,  True],  
       [False,  True,  True]], dtype=bool)  
>>> a < 2  
array([[True,  False,  False],  
       [True,  False,  False]], dtype=bool)  
>>> np.array_equal(a, b)
```

Element-wise comparison
Element-wise comparison
Array-wise comparison

Aggregate Functions

```
>>> a.sum()  
>>> a.min()  
>>> b.max(axis=0)  
>>> b.cumsum(axis=1)  
>>> a.mean()  
>>> np.median(b)  
>>> np.correlcoef(a)  
>>> np.std(b)
```

Array-wise sum
Array-wise minimum value
Maximum value of an array row
Cumulative sum of the elements
Mean
Median
Correlation coefficient
Standard deviation

Copying Arrays

```
>>> h = a.view()  
>>> np.copy(a)  
>>> h = a.copy()
```

Create a view of the array with the same data
Create a copy of the array
Create a deep copy of the array

Sorting Arrays

```
>>> a.sort()  
>>> c.sort(axis=0)
```

Sort an array
Sort the elements of an array's axis

Subsetting, Slicing, Indexing

Also see Lists

Subsetting

```
>>> a[2]  
3  
>>> b[1,2]  
6.0
```

Select the element at the 2nd index
Select the element at row 0 column 2 (equivalent to b[1][2])

Slicing

```
>>> a[0:2]  
array([1, 2])  
>>> b[0:2,1]  
array([ 2.,  5.])
```

Select items at index 0 and 1
Select items at rows 0 and 1 in column 1

```
>>> b[:1]  
array([[1.5, 2., 3.]])  
>>> c[1,...]  
array([[ 3.,  2.,  1.],  
       [ 4.,  5.,  6.]])
```

Select all items at row 0 (equivalent to b[0:1, :])
Same as [1, :, :]

Reversed array a

Boolean Indexing

```
>>> a[a<2]  
array([1])
```

Select elements from a less than 2

Fancy Indexing

```
>>> b[[1, 0, 1, 0], [0, 1, 2, 0]]  
array([ 4. ,  2. ,  6. ,  1.5])  
>>> b[[1, 0, 1, 0]][:[0,1,2,0]]  
array([[ 4. ,  5. ,  6. ,  4. ],  
       [ 1.5,  2. ,  3. ,  1.5]])
```

Select elements (1,0), (0,1), (1,2) and (0,0)
Select a subset of the matrix's rows and columns

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)  
>>> i.T
```

Permute array dimensions
Permute array dimensions

Changing Array Shape

```
>>> b.ravel()  
>>> g.reshape(3,-2)
```

Flatten the array
Reshape, but don't change data

Adding/Removing Elements

```
>>> h.resize((2,6))  
>>> np.append(h,g)  
>>> np.insert(a, 1, 5)  
>>> np.delete(a, [1])
```

turn a new array with shape (2,6)
Append items to an array
Insert items in an array
Delete items from an array

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)  
array([ 1,  2,  3, 10, 15, 20])  
>>> np.vstack((a,b))  
array([[ 1. ,  2. ,  3. ],  
       [ 1.5,  2. ,  3. ],  
       [ 4. ,  5. ,  6. ]])  
>>> np.r_[e,f]  
>>> np.hstack((e,f))  
array([[ 7.,  7.,  1.,  0.],  
       [ 7.,  7.,  0.,  1.]])  
>>> np.column_stack((a,d))  
array([[ 1, 10],  
       [ 2, 15],  
       [ 3, 20]])  
>>> np.c_[a,d]
```

Concatenate arrays
Stack arrays vertically (row-wise)
Stack arrays vertically (row-wise)
Stack arrays horizontally (column-wise)
Create stacked column-wise arrays
Create stacked column-wise arrays

Splitting Arrays

```
>>> np.hsplit(a,3)  
[array([1]),array([2]),array([3])]  
>>> np.vsplit(c,2)  
[array([[ 1.5,  2. ,  1. ],  
       [ 4. ,  5. ,  6. ]]),  
 array([[ 3.,  2.,  3.],  
       [ 4. ,  5. ,  6.]])]
```

Split the array horizontally at the 3rd index
Split the array vertically at the 2nd index

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

SciPy - Linear Algebra

Learn More Python for Data Science [Interactively](https://www.datacamp.com) at www.datacamp.com



SciPy

The **SciPy** library is one of the core packages for scientific computing that provides mathematical algorithms and convenience functions built on the NumPy extension of Python.



Interacting With NumPy

Also see NumPy

```
>>> import numpy as np
>>> a = np.array([1,2,3])
>>> b = np.array([(1+5j,2j,3j), (4j,5j,6j)])
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)])
```

Index Tricks all the input arrays must have same number of dimensions

```
>>> np.mgrid[0:5,0:5]
>>> np.ogrid[0:2,0:2]
>>> np.r_[[3,[0]*5,-1:1:10]]
>>> np.c_[b,e]
```

Create a dense meshgrid
Create an open meshgrid
Stack arrays vertically (row-wise)
Create stacked column-wise arrays

Shape Manipulation

```
>>> np.transpose(b)
>>> b.flatten()
>>> np.hstack((b,c))
>>> np.vstack((a,b))
>>> np.hsplit(c,2)
>>> np.vsplit(c,2)
```

Permute array dimensions
Flatten the array
Stack arrays horizontally (column-wise)
Stack arrays vertically (row-wise)
Split the array horizontally at the 2nd index
Split the array vertically at the 2nd index

Polynomials

np.vsplit(c, 2)

```
>>> from numpy import polyld
>>> p = polyld([3,4,5])
```

Create a polynomial object

Vectorizing Functions

```
>>> def myfunc(a):
    if a < 0:
        return a*2
    else:
        return a/2
>>> np.vectorize(myfunc)
```

Vectorize functions

Type Handling

```
>>> np.real(c)
>>> np.imag(c)
>>> np.real_if_close(c,tol=1000)
>>> np.cast['f'](np.pi)
```

Return the real part of the array elements
Return the imaginary part of the array elements
Return a real array if complex parts close to 0
Cast object to a data type

Other Useful Functions

```
>>> np.angle(b,deg=True)
>>> g = np.linspace(0,np.pi,num=5)
>>> g[3:] += np.pi
>>> np.unwrap(g)
>>> np.logspace(0,10,3)
>>> np.select([c<4],[c*2])
>>> misc.factorial(a)
>>> misc.comb(10,3,exact=True)
>>> misc.central_diff_weights(3)
>>> misc.derivative(myfunc,1.0)
```

Return the angle of the complex argument
Create an array of evenly spaced values (number of samples)
Unwrap
Create an array of evenly spaced values (log scale)
from scipy import special
special.factorial()
special.comb()
Compute combinations taken at k time
Weights for Np-point central derivative
Find the n-th derivative of a function at a point

Linear Algebra

You'll use the `linalg` and `sparse` modules. Note that `scipy.linalg` contains and expands on `numpy.linalg`.

```
>>> from scipy import linalg, sparse
```

Creating Matrices

```
>>> A = np.matrix(np.random.random((2,2)))
>>> B = np.asmatrix(b)
>>> C = np.mat(np.random.random((10,5)))
>>> D = np.mat([[3,4], [5,6]])
```

Basic Matrix Routines

Inverse

```
>>> A.I
>>> linalg.inv(A)
>>> A.T
>>> A.H
>>> np.trace(A)
```

Inverse
Inverse
Transpose matrix
Conjugate transposition
Trace

Norm

```
>>> linalg.norm(A)
>>> linalg.norm(A,1)
>>> linalg.norm(A,np.inf)
```

Frobenius norm
L1 norm (max column sum)
L inf norm (max row sum)

Rank

```
>>> np.linalg.matrix_rank(C)
```

Matrix rank

Determinant

```
>>> linalg.det(A)
```

Determinant

Solving linear problems

```
>>> linalg.solve(A,b)
>>> E = np.mat(a).T
>>> linalg.lstsq(D,E)
```

Solver for dense matrices
Solver for dense matrices
Least-squares solution to linear matrix equation

Generalized inverse

```
>>> linalg.pinv(C)
>>> linalg.pinv2(C)
```

Compute the pseudo-inverse of a matrix (least-squares solver)
Compute the pseudo-inverse of a matrix (SVD)

Creating Sparse Matrices

```
>>> F = np.eye(3, k=1)
>>> G = np.mat(np.identity(2))
>>> C[C > 0.5] = 0
>>> H = sparse.csr_matrix(C)
>>> I = sparse.csc_matrix(D)
>>> J = sparse.dok_matrix(A)
>>> E.todense()
>>> sparse.isspmatrix_csc(A)
```

Create a 2x2 identity matrix
Create a 2x2 identity matrix
Compressed Sparse Row matrix
Compressed Sparse Column matrix
Dictionary Of Keys matrix
Sparse matrix to full matrix
Identify sparse matrix

Sparse Matrix Routines

Inverse

```
>>> sparse.linalg.inv(I)
```

Inverse

Norm

```
>>> sparse.linalg.norm(I)
```

Norm

Solving linear problems

```
>>> sparse.linalg.spsolve(H,I)
```

Solver for sparse matrices

Sparse Matrix Functions

```
>>> sparse.linalg.expm(I)
```

Sparse matrix exponential

Asking For Help

```
>>> help(scipy.linalg.diagsvd)
>>> np.info(np.matrix)
```

Matrix Functions

Addition

```
>>> np.add(A,D)
```

Addition

Subtraction

```
>>> np.subtract(A,D)
```

Subtraction

Division

```
>>> np.divide(A,D)
```

Division

Multiplication

```
>>> np.multiply(D,A)
>>> np.dot(A,D)
>>> np.vdot(A,D)
>>> np.inner(A,D)
>>> np.outer(A,D)
>>> np.tensordot(A,D)
>>> np.kron(A,D)
```

Multiplication
Dot product
Vector dot product
Inner product
Outer product
Tensor dot product
Kronecker product

Exponential Functions

```
>>> linalg.expm(A)
>>> linalg.expm2(A)
>>> linalg.expm3(D)
```

Matrix exponential
Matrix exponential (Taylor Series)
Matrix exponential (eigenvalue decomposition)

Logarithm Function

```
>>> linalg.logm(A)
```

Matrix logarithm

Trigonometric Functions

```
>>> linalg.sinm(D)
>>> linalg.cosm(D)
>>> linalg.tanm(A)
```

Matrix sine
Matrix cosine
Matrix tangent

Hyperbolic Trigonometric Functions

```
>>> linalg.sinhm(D)
>>> linalg.coshm(D)
>>> linalg.tanhm(A)
```

Hyperbolic matrix sine
Hyperbolic matrix cosine
Hyperbolic matrix tangent

Matrix Sign Function

```
>>> np.sigm(A)
```

Matrix sign function

Matrix Square Root

```
>>> linalg.sqrtm(A)
```

Matrix square root

Arbitrary Functions

```
>>> linalg.funm(A, lambda x: x*x)
```

Evaluate matrix function

Decompositions

Eigenvalues and Eigenvectors

```
>>> la, v = linalg.eig(A)
>>> l1, l2 = la
>>> v[:,0]
>>> v[:,1]
>>> linalg.eigvals(A)
```

Solve ordinary or generalized eigenvalue problem for square matrix
Unpack eigenvalues
First eigenvector
Second eigenvector
Unpack eigenvalues

Singular Value Decomposition

```
>>> U,s,Vh = linalg.svd(B)
>>> M,N = B.shape
>>> Sig = linalg.diagsvd(s,M,N)
```

Singular Value Decomposition (SVD)
Construct sigma matrix in SVD

LU Decomposition

```
>>> P,L,U = linalg.lu(C)
```

LU Decomposition

Sparse Matrix Decompositions

```
>>> la, v = sparse.linalg.eigs(F,1)
>>> sparse.linalg.svds(H, 2)
```

Eigenvalues and eigenvectors
SVD

DataCamp

Learn Python for Data Science [Interactively](https://www.datacamp.com)



Python For Data Science Cheat Sheet

Pandas Basics

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



Pandas

The **Pandas** library is built on NumPy and provides easy-to-use **data structures** and **data analysis tools** for the Python programming language.



Use the following import convention:

```
>>> import pandas as pd
```

Pandas Data Structures

Series

A **one-dimensional** labeled array capable of holding any data type

a	3
b	-5
c	7
d	4

Index

```
>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])
```

DataFrame

	Country	Capital	Population
0	Belgium	Brussels	11190846
1	India	New Delhi	1303171035
2	Brazil	Brasília	207847528

A **two-dimensional** labeled data structure with columns of potentially different types

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
           'Capital': ['Brussels', 'New Delhi', 'Brasília'],
           'Population': [11190846, 1303171035, 207847528]}
```

```
>>> df = pd.DataFrame(data,
                      columns=['Country', 'Capital', 'Population'])
```

I/O

Read and Write to CSV

```
>>> pd.read_csv('file.csv', header=None, nrows=5)
>>> df.to_csv('myDataFrame.csv')
```

Read and Write to Excel

```
>>> pd.read_excel('file.xlsx')
>>> pd.to_excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')

Read multiple sheets from the same file
>>> xlsx = pd.ExcelFile('file.xls')
>>> df = pd.read_excel(xlsx, 'Sheet1')
```

Asking For Help

```
>>> help(pd.Series.loc)
```

Selection

Also see NumPy Arrays

Getting

```
>>> s['b']
-5

>>> df[1:]
   Country  Capital  Population
1   India  New Delhi  1303171035
2  Brazil  Brasília  207847528
```

Get one element

Get subset of a DataFrame

Selecting, Boolean Indexing & Setting

By Position

```
>>> df.iloc([0], [0])
'Belgium'

>>> df.iat([0], [0])
'Belgium'
```

Select single value by row & column

By Label

```
>>> df.loc([0], ['Country'])
'Belgium'

>>> df.at([0], ['Country'])
'Belgium'
```

Select single value by row & column labels

By Label/Position

```
>>> df.ix[2]
Country      Brazil
Capital      Brasília
Population    207847528
```

Select single row of subset of rows

```
>>> df.ix[:, 'Capital']
0      Brussels
1      New Delhi
2      Brasilia
```

Select a single column of subset of columns

```
>>> df.ix[1, 'Capital']
'New Delhi'
```

Select rows and columns

Boolean Indexing

```
>>> s[~(s > 1)]
>>> s[(s < -1) | (s > 2)]
>>> df[df['Population'] > 1200000000]
```

Series *s* where value is not >1
s where value is <-1 or >2
Use filter to adjust DataFrame

Setting

```
>>> s['a'] = 6
```

Set index *a* of Series *s* to 6

Dropping

```
>>> s.drop(['a', 'c'])
>>> df.drop('Country', axis=1)
```

Drop values from rows (axis=0)
Drop values from columns(axis=1)

Sort & Rank

```
>>> df.sort_index()
>>> df.sort_values(by='Country')
>>> df.rank()
```

Sort by labels along an axis
Sort by the values along an axis
Assign ranks to entries

Retrieving Series/DataFrame Information

Basic Information

```
>>> df.shape
>>> df.index
>>> df.columns
>>> df.info()
>>> df.count()
```

(rows,columns)
Describe index
Describe DataFrame columns
Info on DataFrame
Number of non-NA values

Summary

```
>>> df.sum()
>>> df.cumsum()
>>> df.min()/df.max()
>>> df.idxmin()/df.idxmax()
>>> df.describe()
>>> df.mean()
>>> df.median()
```

Sum of values
Cumulative sum of values
Minimum/maximum values
Minimum/Maximum index value
Summary statistics
Mean of values
Median of values

Applying Functions

```
>>> f = lambda x: x*2
>>> df.apply(f)
>>> df.applymap(f)
```

Apply function
Apply function element-wise

Data Alignment

Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
a      10.0
b      NaN
c       5.0
d       7.0
```

Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill_value=0)
a      10.0
b     -5.0
c       5.0
d       7.0

>>> s.sub(s3, fill_value=2)
>>> s.div(s3, fill_value=4)
>>> s.mul(s3, fill_value=3)
```

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

Scikit-Learn

Learn Python for data science [Interactively](#) at [www.DataCamp.com](#)



Scikit-learn

Scikit-learn is an open source Python library that implements a range of machine learning, preprocessing, cross-validation and visualization algorithms using a unified interface.



A Basic Example

```
>>> from sklearn import neighbors, datasets, preprocessing
>>> from sklearn.model_selection import train_test_split
>>> from sklearn.metrics import accuracy_score
>>> iris = datasets.load_iris()
>>> X, y = iris.data[:, :2], iris.target
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=33)
>>> scaler = preprocessing.StandardScaler().fit(X_train)
>>> X_train = scaler.transform(X_train)
>>> X_test = scaler.transform(X_test)
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
>>> knn.fit(X_train, y_train)
>>> y_pred = knn.predict(X_test)
>>> accuracy_score(y_test, y_pred)
```

Loading The Data

Also see NumPy & Pandas

Your data needs to be numeric and stored as NumPy arrays or SciPy sparse matrices. Other types that are convertible to numeric arrays, such as Pandas DataFrame, are also acceptable.

```
>>> import numpy as np
>>> X = np.random.random((10,5))
>>> y = np.array(['M','M','F','F','M','F','M','F','F','F'])
>>> X[X < 0.7] = 0
```

Training And Test Data

```
>>> from sklearn.model_selection import train_test_split
>>> X_train, X_test, y_train, y_test = train_test_split(X,
                                                    y,
                                                    random_state=0)
```

Preprocessing The Data

Standardization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(X_train)
>>> standardized_X = scaler.transform(X_train)
>>> standardized_X_test = scaler.transform(X_test)
```

Normalization

```
>>> from sklearn.preprocessing import Normalizer
>>> scaler = Normalizer().fit(X_train)
>>> normalized_X = scaler.transform(X_train)
>>> normalized_X_test = scaler.transform(X_test)
```

Binarization

```
>>> from sklearn.preprocessing import Binarizer
>>> binarizer = Binarizer(threshold=0.0).fit(X)
>>> binary_X = binarizer.transform(X)
```

Create Your Model

Supervised Learning Estimators

Linear Regression

```
>>> from sklearn.linear_model import LinearRegression
>>> lr = LinearRegression(normalize=True)
```

Support Vector Machines (SVM)

```
>>> from sklearn.svm import SVC
>>> svc = SVC(kernel='linear')
```

Naïve Bayes

```
>>> from sklearn.naive_bayes import GaussianNB
>>> gnb = GaussianNB()
```

KNN

```
>>> from sklearn import neighbors
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
```

Unsupervised Learning Estimators

Principal Component Analysis (PCA)

```
>>> from sklearn.decomposition import PCA
>>> pca = PCA(n_components=0.95)
```

K Means

```
>>> from sklearn.cluster import KMeans
>>> k_means = KMeans(n_clusters=3, random_state=0)
```

Model Fitting

Supervised learning

```
>>> lr.fit(X, y)
>>> knn.fit(X_train, y_train)
>>> svc.fit(X_train, y_train)
```

Fit the model to the data

Unsupervised Learning

```
>>> k_means.fit(X_train)
>>> pca_model = pca.fit_transform(X_train)
```

Fit the model to the data
Fit to data, then transform it

Prediction

Supervised Estimators

```
>>> y_pred = svc.predict(np.random.random((2,5)))
>>> y_pred = lr.predict(X_test)
>>> y_pred = knn.predict_proba(X_test)
```

Predict labels
Predict labels
Estimate probability of a label

Unsupervised Estimators

```
>>> y_pred = k_means.predict(X_test)
```

Predict labels in clustering algos

Evaluate Your Model's Performance

Classification Metrics

Accuracy Score

```
>>> knn.score(X_test, y_test)
>>> from sklearn.metrics import accuracy_score
>>> accuracy_score(y_test, y_pred)
```

Estimator score method
Metric scoring functions

Classification Report

```
>>> from sklearn.metrics import classification_report
>>> print(classification_report(y_test, y_pred))
```

Precision, recall, f1-score
and support

Confusion Matrix

```
>>> from sklearn.metrics import confusion_matrix
>>> print(confusion_matrix(y_test, y_pred))
```

Regression Metrics

Mean Absolute Error

```
>>> from sklearn.metrics import mean_absolute_error
>>> y_true = [3, -0.5, 2]
>>> mean_absolute_error(y_true, y_pred)
```

Mean Squared Error

```
>>> from sklearn.metrics import mean_squared_error
>>> mean_squared_error(y_test, y_pred)
```

R² Score

```
>>> from sklearn.metrics import r2_score
>>> r2_score(y_true, y_pred)
```

Clustering Metrics

Adjusted Rand Index

```
>>> from sklearn.metrics import adjusted_rand_score
>>> adjusted_rand_score(y_true, y_pred)
```

Homogeneity

```
>>> from sklearn.metrics import homogeneity_score
>>> homogeneity_score(y_true, y_pred)
```

V-measure

```
>>> from sklearn.metrics import v_measure_score
>>> metrics.v_measure_score(y_true, y_pred)
```

Cross-Validation

```
>>> from sklearn.cross_validation import cross_val_score
>>> print(cross_val_score(knn, X_train, y_train, cv=4))
>>> print(cross_val_score(lr, X, y, cv=2))
```

Tune Your Model

Grid Search

```
>>> from sklearn.grid_search import GridSearchCV
>>> params = {"n_neighbors": np.arange(1,5),
            "metric": ["euclidean", "cityblock"]}
>>> grid = GridSearchCV(estimator=knn,
                      param_grid=params)
>>> grid.fit(X_train, y_train)
>>> print(grid.best_score_)
>>> print(grid.best_estimator_.n_neighbors)
```

Randomized Parameter Optimization

```
>>> from sklearn.grid_search import RandomizedSearchCV
>>> params = {"n_neighbors": range(1,5),
            "weights": ["uniform", "distance"]}
>>> rsearch = RandomizedSearchCV(estimator=knn,
                               param_distributions=params,
                               cv=4,
                               n_iter=8,
                               random_state=5)
>>> rsearch.fit(X_train, y_train)
>>> print(rsearch.best_score_)
```

DataCamp

Learn Python for Data Science [Interactively](#)



Python For Data Science Cheat Sheet

Matplotlib

Learn Python Interactively at [www.DataCamp.com](https://www.datacamp.com)



Matplotlib

Matplotlib is a Python 2D plotting library which produces publication-quality figures in a variety of hardcopy formats and interactive environments across platforms.



1 Prepare The Data

Also see Lists & NumPy

1D Data

```
>>> import numpy as np
>>> x = np.linspace(0, 10, 100)
>>> y = np.cos(x)
>>> z = np.sin(x)
```

2D Data or Images

```
>>> data = 2 * np.random.random((10, 10))
>>> data2 = 3 * np.random.random((10, 10))
>>> Y, X = np.mgrid[-3:3:100j, -3:3:100j]
>>> U = -1 - X**2 + Y
>>> V = 1 + X - Y**2
>>> from matplotlib.cbook import get_sample_data
>>> img = np.load(get_sample_data('axes_grid/bivariate_normal.npy'))
```

2 Create Plot

```
>>> import matplotlib.pyplot as plt
```

Figure

```
>>> fig = plt.figure()
>>> fig2 = plt.figure(figsize=plt.figaspect(2.0))
```

Axes

All plotting is done with respect to an Axes. In most cases, a subplot will fit your needs. A subplot is an axes on a grid system.

```
>>> fig.add_axes()
>>> ax1 = fig.add_subplot(221) # row-col-num
>>> ax3 = fig.add_subplot(212)
>>> fig3, axes = plt.subplots(nrows=2,ncols=2)
>>> fig4, axes2 = plt.subplots(ncols=3)
```

3 Plotting Routines

1D Data

```
>>> fig, ax = plt.subplots()
>>> lines = ax.plot(x,y)
>>> ax.scatter(x,y)
>>> axes[0,0].bar([1,2,3],[3,4,5])
>>> axes[1,0].barh([0.5,1,2.5],[0,1,2])
>>> axes[1,1].axhline(0.45)
>>> axes[0,1].axvline(0.65)
>>> ax.fill(x,y,color='blue')
>>> ax.fill_between(x,y,color='yellow')
```

Draw points with lines or markers connecting them
Draw unconnected points, scaled or colored
Plot vertical rectangles (constant width)
Plot horizontal rectangles (constant height)
Draw a horizontal line across axes
Draw a vertical line across axes
Draw filled polygons
Fill between y-values and 0


2D Data or Images

```
>>> fig, ax = plt.subplots()
>>> im = ax.imshow(img,
                  cmap='gist_earth',
                  interpolation='nearest',
                  vmin=-2,
                  vmax=2)
```

Colormapped or RGB arrays

Plot Anatomy & Workflow

Plot Anatomy



Workflow

The basic steps to creating plots with matplotlib are:

- 1 Prepare data
- 2 Create plot
- 3 Plot
- 4 Customize plot
- 5 Save plot
- 6 Show plot

```
>>> import matplotlib.pyplot as plt
>>> x = [1,2,3,4]
>>> y = [10,20,25,30]
>>> fig = plt.figure()
>>> ax = fig.add_subplot(111)
>>> ax.plot(x, y, color='lightblue', linewidth=3)
>>> ax.scatter([2,4,6],
              [5,15,25],
              color='darkgreen',
              marker='^')
>>> ax.set_xlim(1, 6.5)
>>> plt.savefig('foo.png')
>>> plt.show()
```

4 Customize Plot

Colors, Color Bars & Color Maps

```
>>> plt.plot(x, x, x, x**2, x, x**3)
>>> ax.plot(x, y, alpha = 0.4)
>>> ax.plot(x, y, c='k')
>>> fig.colorbar(im, orientation='horizontal')
>>> im = ax.imshow(img,
                  cmap='seismic')
```

Markers

```
>>> fig, ax = plt.subplots()
>>> ax.scatter(x,y,marker=".")
>>> ax.plot(x,y,marker="o")
```

Linestyles

```
>>> plt.plot(x,y,linewidth=4.0)
>>> plt.plot(x,y,ls='solid')
>>> plt.plot(x,y,ls='--')
>>> plt.plot(x,y,'--',x**2,y**2,'-.')
>>> plt.setp(lines,color='r',linewidth=4.0)
```

Text & Annotations

```
>>> ax.text(1,
          -2.1,
          'Example Graph',
          style='italic')
>>> ax.annotate("Sine",
              xy=(8, 0),
              xycoords='data',
              xytext=(10.5, 0),
              textcoords='data',
              arrowprops=dict(arrowstyle="->",
                             connectionstyle="arc3"),)
```

Mathtext

```
>>> plt.title(r'$\sigma_i=15$', fontsize=20)
```

Limits, Legends & Layouts

Limits & Autoscaling

```
>>> ax.margins(x=0.0,y=0.1)
>>> ax.axis('equal')
>>> ax.set(xlim=[0,10.5],ylim=[-1.5,1.5])
>>> ax.set_xlim(0,10.5)
```

Legends

```
>>> ax.set(title='An Example Axes',
          ylabel='Y-Axis',
          xlabel='X-Axis')
>>> ax.legend(loc='best')
```

Ticks

```
>>> ax.xaxis.set(ticks=range(1,5),
               ticklabels=[3,100,-12,"foo"])
>>> ax.tick_params(axis='y',
                  direction='inout',
                  length=10)
```

Subplot Spacing

```
>>> fig3.subplots_adjust(wspace=0.5,
                       hspace=0.3,
                       left=0.125,
                       right=0.9,
                       top=0.9,
                       bottom=0.1)
```

```
>>> fig.tight_layout()
```

Axis Spines

```
>>> ax1.spines['top'].set_visible(False)
>>> ax1.spines['bottom'].set_position(('outward',10))
```

Add padding to a plot
Set the aspect ratio of the plot to 1
Set limits for x-and y-axis
Set limits for x-axis

Set a title and x-and y-axis labels

No overlapping plot elements

Manually set x-ticks

Make y-ticks longer and go in and out

Adjust the spacing between subplots

Fit subplot(s) in to the figure area

Make the top axis line for a plot invisible
Move the bottom axis line outward

5 Save Plot

Save figures

```
>>> plt.savefig('foo.png')
```

Save transparent figures

```
>>> plt.savefig('foo.png', transparent=True)
```

6 Show Plot

```
>>> plt.show()
```

Close & Clear

```
>>> plt.cla()
>>> plt.clf()
>>> plt.close()
```

Clear an axis
Clear the entire figure
Close a window





Statistical Data Visualization With Seaborn

The Python visualization library **Seaborn** is based on **matplotlib** and provides a high-level interface for drawing attractive statistical graphics.

Make use of the following aliases to import the libraries:

```
>>> import matplotlib.pyplot as plt
>>> import seaborn as sns
```

The basic steps to creating plots with Seaborn are:

- 1. Prepare some data
- 2. Control figure aesthetics
- 3. Plot with Seaborn
- 4. Further customize your plot

```
>>> import matplotlib.pyplot as plt
>>> import seaborn as sns
>>> tips = sns.load_dataset("tips")
>>> sns.set_style("whitegrid")
>>> g = sns.lmplot(x="tip", y="total_bill", data=tips, aspect=2)
>>> g = (g.set_axis_labels("Tip", "Total bill (USD)")).set(xlim=(0,10),ylim=(0,100))
>>> plt.title("title")
>>> plt.show(g)
```

1 Data

Also see Lists, NumPy & Pandas

```
>>> import pandas as pd
>>> import numpy as np
>>> uniform_data = np.random.rand(10, 12)
>>> data = pd.DataFrame({'x':np.arange(1,101), 'y':np.random.normal(0,4,100)})
```

Seaborn also offers built-in data sets:

```
>>> titanic = sns.load_dataset("titanic")
>>> iris = sns.load_dataset("iris")
```

2 Figure Aesthetics

```
>>> f, ax = plt.subplots(figsize=(5,6))
```

Create a figure and one subplot

Seaborn styles

```
>>> sns.set()
>>> sns.set_style("whitegrid")
>>> sns.set_style("ticks", {'xtick.major.size':8, 'ytick.major.size':8})
>>> sns.axes_style("whitegrid")
```

(Re)set the seaborn default Set the matplotlib parameters Set the matplotlib parameters

Return a dict of params or use with to temporarily set the style

3 Plotting With Seaborn

Axis Grids

```
>>> g = sns.FacetGrid(titanic, col="survived", row="sex")
>>> g = g.map(plt.hist, "age")
>>> sns.factorplot(x="pclass", y="survived", hue="sex", data=titanic)
>>> sns.lmplot(x="sepal_width", y="sepal_length", hue="species", data=iris)
```

Subplot grid for plotting conditional relationships

Draw a categorical plot onto a Facetgrid

Plot data and regression model fits across a FacetGrid

Categorical Plots

```
Scatterplot
>>> sns.stripplot(x="species", y="petal_length", data=iris)
>>> sns.swarmplot(x="species", y="petal_length", data=iris)

Bar Chart
>>> sns.barpplot(x="sex", y="survived", hue="class", data=titanic)

Count Plot
>>> sns.countplot(x="deck", data=titanic, palette="Greens_d")

Point Plot
>>> sns.pointplot(x="class", y="survived", hue="sex", data=titanic, palette={"male": "g", "female": "m"}, markers=["^", "o"], linestyle=["-", "--"])

Boxplot
>>> sns.boxplot(x="alive", y="age", hue="adult_male", data=titanic)
>>> sns.boxplot(data=iris, orient="h")

Violinplot
>>> sns.violinplot(x="age", y="sex", hue="survived", data=titanic)
```

Scatterplot with one categorical variable

Categorical scatterplot with non-overlapping points

Show point estimates and confidence intervals with scatterplot glyphs

Show count of observations

Show point estimates and confidence intervals as rectangular bars

Boxplot

Boxplot with wide-form data

Violin plot

```
>>> h = sns.PairGrid(iris)
>>> h = h.map(plt.scatter)
>>> sns.pairplot(iris)
>>> i = sns.JointGrid(x="x", y="y", data=data)
>>> i = i.plot(sns.regplot, sns.distplot)
>>> sns.jointplot("sepal_length", "sepal_width", data=iris, kind='kde')
```

Subplot grid for plotting pairwise relationships Plot pairwise bivariate distributions Grid for bivariate plot with marginal univariate plots

Plot bivariate distribution

Regression Plots

```
>>> sns.regplot(x="sepal_width", y="sepal_length", data=iris, ax=ax)
```

Plot data and a linear regression model fit

Distribution Plots

```
>>> plot = sns.distplot(data.y, kde=False, color="b")
```

Plot univariate distribution

Matrix Plots

```
>>> sns.heatmap(uniform_data, vmin=0, vmax=1)
```

Heatmap

4 Further Customizations

Also see Matplotlib

Axisgrid Objects

```
>>> g.despine(left=True)
>>> g.set_ylabels("Survived")
>>> g.set_xticklabels(rotation=45)
>>> g.set_axis_labels("Survived", "Sex")
>>> h.set(xlim=(0,5), ylim=(0,5), xticks=[0,2.5,5], yticks=[0,2.5,5])
```

Remove left spine Set the labels of the y-axis Set the tick labels for x Set the axis labels

Set the limit and ticks of the x-and y-axis

Plot

```
>>> plt.title("A Title")
>>> plt.ylabel("Survived")
>>> plt.xlabel("Sex")
>>> plt.ylim(0,100)
>>> plt.xlim(0,10)
>>> plt.setp(ax, yticks=[0,5])
>>> plt.tight_layout()
```

Add plot title Adjust the label of the y-axis Adjust the label of the x-axis Adjust the limits of the y-axis Adjust the limits of the x-axis Adjust a plot property Adjust subplot params

5 Show or Save Plot

Also see Matplotlib

```
>>> plt.show()
>>> plt.savefig("foo.png")
>>> plt.savefig("foo.png", transparent=True)
```

Show the plot Save the plot as a figure Save transparent figure

Close & Clear

Also see Matplotlib

```
>>> plt.cla()
>>> plt.clf()
>>> plt.close()
```

Clear an axis Clear an entire figure Close a window



Bokeh


Learn Bokeh **Interactively** at [www.DataCamp.com](https://www.datacamp.com),
taught by Bryan Van de Ven, core contributor



Plotting With Bokeh

The Python interactive visualization library **Bokeh** enables high-performance visual presentation of large datasets in modern web browsers.

Bokeh's mid-level general purpose `bokeh.plotting` interface is centered around two main components: data and glyphs.



The basic steps to creating plots with the `bokeh.plotting` interface are:

1. Prepare some data:
2. Create a new plot
3. Add renderers for your data, with visual customizations
4. Specify where to generate the output
5. Show or save the results

```
>>> from bokeh.plotting import figure
>>> from bokeh.io import output_file, show
>>> x = [1, 2, 3, 4, 5]
>>> y = [6, 7, 2, 4, 5]
>>> p = figure(title="simple line example",
>>>             x_axis_label='x',
>>>             y_axis_label='y')
>>> p.line(x, y, legend="Temp.", line_width=2)
>>> output_file("lines.html")
>>> show(p)
```

Also see [Lists, NumPy & Pandas](#)

1 Data

Under the hood, your data is converted to Column Data Sources. You can also do this manually:

```
>>> import numpy as np
>>> import pandas as pd
>>> df = pd.DataFrame(np.array([[33.9, 4, 65, 'US'],
>>>                             [32.4, 4, 66, 'Asia'],
>>>                             [21.4, 4, 109, 'Europe']]
>>>                  columns=['mpg', 'cyl', 'hp', 'origin'],
>>>                  index=['Toyota', 'Fiat', 'Volvo'])
>>> from bokeh.models import ColumnDataSource
>>> cds_df = ColumnDataSource(df)
```

2 Plotting

```
>>> from bokeh.plotting import figure
>>> p1 = figure(plot_width=300, tools='pan, box_zoom')
>>> p2 = figure(plot_width=300, plot_height=300,
>>>             x_range=(0, 8), y_range=(0, 8))
>>> p3 = figure()
```

Glyphs

Scatter Markers

```
>>> p1.circle(np.array([1, 2, 3]), np.array([3, 2, 1]),
>>>           fill_color='white')
>>> p2.square(np.array([1.5, 3.5, 5.5]), [1, 4, 3],
>>>          color='blue', size=1)
```

Line Glyphs

```
>>> p1.line([1, 2, 3, 4], [3, 4, 5, 6], line_width=2)
>>> p2.multi_line(pd.DataFrame([[1, 2, 3], [5, 6, 7]]),
>>>               pd.DataFrame([[3, 4, 5], [3, 2, 1]]),
>>>               color="blue")
```

Customized Glyphs

Also see [Data](#)

Selection and Non-Selection Glyphs

```
>>> p = figure(tools='box_select')
>>> p.circle('mpg', 'cyl', source=cds_df,
>>>          selection_color='red',
>>>          nonselection_alpha=0.1)
```

Hover Glyphs

```
>>> from bokeh.models import HoverTool
>>> hover = HoverTool(tooltips=None, mode='vline')
>>> p3.add_tools(hover)
```

Colormapping

```
>>> from bokeh.models import CategoricalColorMapper
>>> color_mapper = CategoricalColorMapper(
>>>               factors=['US', 'Asia', 'Europe'],
>>>               palette=['blue', 'red', 'green'])
>>> p3.circle('mpg', 'cyl', source=cds_df,
>>>           color=dict(field='origin',
>>>                      transform=color_mapper),
>>>           legend='Origin')
```

Legend Location

Inside Plot Area

```
>>> p.legend.location = 'bottom_left'
```

Outside Plot Area

```
>>> from bokeh.models import Legend
>>> r1 = p2.asterisk(np.array([1, 2, 3]), np.array([3, 2, 1]))
>>> r2 = p2.line([1, 2, 3, 4], [3, 4, 5, 6])
>>> legend = Legend(items=[("One", [p1, r1]), ("Two", [r2])],
>>>                  location=(0, -30))
>>> p.add_layout(legend, 'right')
```

Legend Orientation

```
>>> p.legend.orientation = "horizontal"
>>> p.legend.orientation = "vertical"
```

Legend Background & Border

```
>>> p.legend.border_line_color = "navy"
>>> p.legend.background_fill_color = "white"
```

Rows & Columns Layout

Rows

```
>>> from bokeh.layouts import row
>>> layout = row(p1, p2, p3)
```

Columns

```
>>> from bokeh.layouts import columns
>>> layout = column(p1, p2, p3)
```

Nesting Rows & Columns

```
>>> layout = row(column(p1, p2), p3)
```

Grid Layout

```
>>> from bokeh.layouts import gridplot
>>> row1 = [p1, p2]
>>> row2 = [p3]
>>> layout = gridplot([[p1, p2], [p3]])
```

Tabbed Layout

```
>>> from bokeh.models.widgets import Panel, Tabs
>>> tab1 = Panel(child=p1, title="tab1")
>>> tab2 = Panel(child=p2, title="tab2")
>>> layout = Tabs(tabs=[tab1, tab2])
```

Linked Plots

Linked Axes

```
>>> p2.x_range = p1.x_range
>>> p2.y_range = p1.y_range
```

Linked Brushing

```
>>> p4 = figure(plot_width = 100,
>>>             tools='box_select, lasso_select')
>>> p4.circle('mpg', 'cyl', source=cds_df)
>>> p5 = figure(plot_width = 200,
>>>             tools='box_select, lasso_select')
>>> p5.circle('mpg', 'hp', source=cds_df)
>>> layout = row(p4, p5)
```

4 Output & Export

Notebook

```
>>> from bokeh.io import output_notebook, show
>>> output_notebook()
```

HTML

Standalone HTML

```
>>> from bokeh.embed import file_html
>>> from bokeh.resources import CDN
>>> html = file_html(p, CDN, "my_plot")
```

```
>>> from bokeh.io import output_file, show
>>> output_file('my_bar_chart.html', mode='cdn')
```

Components

```
>>> from bokeh.embed import components
>>> script, div = components(p)
```

PNG

```
>>> from bokeh.io import export_png
>>> export_png(p, filename="plot.png")
```

SVG

```
>>> from bokeh.io import export_svgs
>>> p.output_backend = "svg"
>>> export_svgs(p, filename="plot.svg")
```

5 Show or Save Your Plots

```
>>> show(p1)
>>> save(p1)
```

```
>>> show(layout)
>>> save(layout)
```

