



Introduction to **Machine Learning and Data Mining** (Học máy và Khai phá dữ liệu)

Khoat Than

School of Information and Communication Technology
Hanoi University of Science and Technology

Contents

- Introduction to Machine Learning & Data Mining
- Unsupervised learning
- Supervised learning
 - **Evaluation of empirical results**
- Practical advice

1. Assessing performance (1)

- *How can we make a reliable assessment on the performance of an ML method?*
 - Note that performance of a method often improves as more data are available.
 - An assessment is more reliable as more data are used to test prediction.
- *How to choose a good value for a parameter in an ML method?*
- The performance of a method depends on many factors:
 - Class distribution
 - Training size
 - Representativeness of training data over the whole space,...

Assessing performance (2)

- *Theoretical evaluation*: study some theoretical properties of a method/model with some explicit mathematical proofs.
 - Learning rate?
 - How many training instances are enough?
 - What is the expected accuracy of prediction?
 - Noise-resistance? ...
- *Experimental evaluation*: observe the performance of a method in practical situations, using some datasets and a performance measure. Then make a summary from those experiments.
- We will discuss experimental evaluation in this lecture.

Assessing performance (3)

- **Model assessment:** *we need to evaluate the performance of a method/model, only based on a given observed dataset D .*
- Evaluation:
 - Should be done automatically,
 - Does not need any help from users.
- Evaluation strategies:
 - To obtain a reliable assessment on performance.
- Evaluation measures:
 - To measure performance quantitatively.

2. Some evaluation techniques

- Hold-out
- Stratified sampling
- Repeated hold-out
- Cross-validation
 - K-fold
 - Leave-one-out
- Bootstrap sampling

Hold-out (random splitting)

- The observed dataset D is randomly splitted into 2 non-overlapping subsets:
 - D_{train} : used for training
 - D_{test} : used to test performance



- Note that:
 - No instance of D_{test} is used in the training phase.
 - No instance of D_{train} is used in the test phase.
- Popular split: $|D_{\text{train}}| = (2/3) \cdot |D|$, $|D_{\text{test}}| = (1/3) \cdot |D|$
- This technique is suitable when D is of large size.

Stratified sampling

- For small or imbalanced datasets, random splitting might result in a training dataset which are not representative.
 - A class in D_{train} might be empty or have few instances.
- *We should split D so that the class distribution in D_{train} is similar with that in D .*
- Stratified sampling fulfills this need:
 - *We randomly split each class of D into 2 parts: one is for D_{train} , and the other is for D_{test} .*
 - for each class:

D_{train}	D_{test}
--------------------	-------------------
- Note that this technique cannot be applied to regression and unsupervised learning.

Repeated hold-out

- We can do hold-out many times, and then take the average result.
 - Repeat hold-out n times. The i^{th} time will give a performance result p_i . The training data for each hold-out should be different from each other.
 - Take the average $p = \text{mean}(p_1, \dots, p_n)$ as the final quality.
- Advantages?
- Limitations?

Cross-validation

- In repeated hold-out: there are overlapping between two training/testing datasets. It might be redundant.
- *K-fold cross-validation:*
 - Split D into K equal parts which are non-overlapping.
 - Do K runs (folds): at each run, one part is used for testing and the remaining parts are used for training.
 - Take the average as the final quality from K individual runs.



- Popular choices of K : 10 or 5
- It is useful to combine this technique with stratified sampling.
- This technique is suitable for small/average datasets.

Leave-one-out cross-validation

- It is K-fold cross-validation when $K = |D|$.
 - Each testing set consists of only one instance from D .
 - The remaining is for training.
- So all observed instances are exploited as much as possible.
- No randomness appears.
- But it is expensive, and hence is suitable with small datasets.

Bootstrap sampling

- Previous methods do not allow repetitions of an instance in any training part.
- Bootstrap sampling:
 - Assume D having n instances.
 - Build D_{train} by randomly sampling (with replacement/repetition) n instances from D .
 - D_{train} is used for the training phase.
 - $D_{\text{test}} = D \setminus D_{\text{train}}$ is used for testing quality.
 - Note that $D_{\text{test}} = \{z \in D: z \notin D_{\text{train}}\}$
- It can be shown that D_{train} contains nearly 63.2% different instances of D . 36.8% of D are used for testing.
- This technique is suitable for small datasets.

3. Model selection

- An ML method often has a set of hyperparameters that require us to select suitable values a priori.
 - Ridge regression: λ
 - Linear SVM: C
- How to choose a good value?
- **Model selection:** given a dataset D , we need to choose a good setting of the hyperparameters in method (model) A such that the function learned by A generalizes well.
- A validation set T_{valid} is often used to find a good setting.
 - It is a subset of D .
 - A good setting should help the learned function predicts well on T_{valid} .


Model selection: using hold-out

- Given an observed dataset D , we can **select** a good value for hyperparameter λ as follows:
 - *Select a finite set S which contains all potential values of λ .*
 - *Select a performance measure P .*
 - *Randomly split D into 2 non-overlapping subsets: D_{train} and T_{valid}*
 - *For each $\lambda \in S$: train the system given D_{train} and λ . Measure the quality on T_{valid} to get P_λ .*
 - *Select the best λ^* which corresponds to the best P_λ .*
- It is often beneficial to learn again from D given λ^* to get a better function.
- Hold-out can be replaced with other techniques e.g., sampling, cross-validation.

Example: select parameters

- Random forest for news classification
 - Parameter: `n_estimators` (number of trees)
- Dataset: 1135 news, 10 classes, vocabulary of 25199 terms
- 10-fold cross-validation is used

- Độc giả
- Đời sống - Xã hội
- Giải trí
- Khoa học - Công nghệ
- Kinh tế
- Pháp luật
- Sức khỏe
- Thể thao
- Thời sự
- Tin khác



4. Model assessment and selection

- Given an observed dataset D , we need to **select** a good value for hyperparameter λ and **evaluate** the overall performance of a method A :
 - Select a finite set S which contains all potential values of λ .
 - Select a performance measure P .
 - Split D into 3 non-overlapping subsets: D_{train} , T_{valid} and T_{test}
 - For each $\lambda \in S$: train the system given D_{train} and λ . Measure the quality on T_{valid} to get P_{λ} .
 - Select the best λ^* which corresponds to the best P_{λ} .
 - Train the system again from $D_{\text{train}} \cup T_{\text{valid}}$ given λ^* .
 - Test performance of the system on T_{test} .
- Hold-out can be replaced with other techniques.

5. Performance measures

- Accuracy:
 - Percentage of correct predictions on testing data.
- Efficiency:
 - The cost in time and storage when learning/prediction.
- Robustness:
 - The ability to reduce possible affects by noises/errors/missings.
- Scalability:
 - The relation between the performance and training size.
- Complexity:
 - The comlexity of the learned function.
- ...

Accuracy

- Classification:

$$Accuracy = \frac{\text{number of correct predictions}}{\text{Total number of predictions}}$$

- Regression: (MAE – mean absolute error)

$$MAE = \frac{1}{|D_{test}|} \sum_{x \in D_{test}} |o(x) - y(x)|$$

- $o(x)$ is the prediction for an instance x .
- $y(x)$ is the true value.

Precision and Recall (1)

- These two measures are often used for classification

- **Precision** for class c_i :

- Percentage of correct instances, among all that are assigned to c_i .

$$Precision(c_i) = \frac{TP_i}{TP_i + FP_i}$$

- **Recall** for class c_i :

- Percentage of instances in c_i that are correctly assigned to c_i .

$$Recall(c_i) = \frac{TP_i}{TP_i + FN_i}$$

- TP_i : the number of instances that are assigned correctly to class c_i .
- FP_i : the number of instances that are assigned incorrectly to class c_i .
- FN_i : the number of instances inside c_i that are assigned incorrectly to another class.
- TN_i : the number of instances outside c_i that are not assigned to class c_i .

Precision and Recall (1)

- These two measures are often used in information retrieval and classification

- **Precision** for class c_i :

- Percentage of correct instances, among all that are assigned to c_i .

$$Precision(c_i) = \frac{TP_i}{TP_i + FP_i}$$

- **Recall** for class c_i :

- Percentage of instances in c_i that are correctly assigned to c_i .

$$Recall(c_i) = \frac{TP_i}{TP_i + FN_i}$$

Precision and Recall (2)

- To give an overall summary, we can take an average from individual classes.
- Micro-averaging:

$$Precision = \frac{\sum_{i=1}^{|C|} TP_i}{\sum_{i=1}^{|C|} (TP_i + FP_i)}$$

$$Recall = \frac{\sum_{i=1}^{|C|} TP_i}{\sum_{i=1}^{|C|} (TP_i + FN_i)}$$

- Macro-averaging:

$$Precision = \frac{\sum_{i=1}^{|C|} Precision(c_i)}{|C|}$$

$$Recall = \frac{\sum_{i=1}^{|C|} Recall(c_i)}{|C|}$$

F₁



- Precision and recall provide us different views on the performance of a classifier.
- F₁ can provide us a unified view.
- F₁ is the *harmonic mean* of precision and recall, and is computed as:

$$F_1 = \frac{2 \cdot \text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} = \frac{2}{\frac{1}{\text{Precision}} + \frac{1}{\text{Recall}}}$$

- F₁ tends to be close to the smaller value from {precision, recall}
- Large F₁ implies that both precision and recall are large.


Example: compare 2 methods

- Methods: **Random forest** vs **Support vector machines (SVM)**
- Parameter selection: 10-fold cross-validation
 - Random forest: $n_{\text{estimate}} = 250$
 - SVM: regularization constant $C = 1$




Example: effect of data size

- SVM
 - Parameter: size of training data
- Dataset: 1135 news, 10 classes, vocabulary of 25199 terms
- 10-fold cross-validation is used



Example: effect of parameters

- SVM for news classification
 - Parameter C changes
- Dataset: 1135 news, 10 classes, vocabulary of 25199 terms
- 10-fold cross-validation is used



References

- Trevor Hastie, Robert Tibshirani, Jerome Friedman. *The Elements of Statistical Learning*. Springer, 2009.
- Sebastiani, F. (2002). Machine learning in automated text categorization. *ACM computing surveys (CSUR)*, 34(1), 1-47.