



1485

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX2™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1485
Standard



1485NF
No Foam



1485WD
With Padded Dividers



1485TP
With TrekPak Divider System



1485WF
With Foam

DIMENSIONS

Interior (L×W×D)	17.75 x 10.18" x 6.15 (45.1 x 25.9 x 15.6 cm)
Exterior (L×W×D)	19.17 x 12.80" x 6.89 (48.7 x 32.5 x 17.5 cm)
Lid Depth	1.80" (4.6 cm)
Bottom Depth	4.35" (11 cm)
Total Depth	6.15" (15.6 cm)
Int Volume	0.64 ft³ (0.018 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black	Orange	Silver	Yellow
-------	--------	--------	--------


WEIGHT

Weight With Foam	5.39 lbs (2.44 kg)
Weight Empty	4.57 lbs (2.07 kg)
Buoyancy	41.10 lbs (18.64 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES

				
1485AirFS 3 pc. Replacement Foam Set	1485AirDS Padded Divider Set	1485TP-KIT TrekPak Case Divider Kit	1485TPKIT TrekPak Case Divider Kit	1506TSA TSA Lock
				
1500D Desiccant Silica Gel	RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion	1485TPDIV Extra TrekPak Dividers		

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-11-26