

FluctlightDB: A Memory Model of Data for AI Agents

A brain-native database engine for long-term agent memory

Ganesh S

Independent Researcher voxmastery@gmail.com

ORCID: 0009-0006-7758-4114

June 2026

Abstract

For fifty years, data systems have answered two questions. The relational model asked *which records match a predicate*; the vector model asked *which vectors lie nearest a query*. Neither was built to answer the question an autonomous agent asks every time it wakes up: *what have I learned, and what of it can I trust?* We argue that long-term agent memory is not an application built on top of a database—it is a **third data model**, with its own write semantics (encoding, separation, consolidation, provenance) and its own read semantics (cue-driven activation across a linked memory graph). We present **FluctlightDB**, an embedded, brain-native database engine that implements this model behind two primitives, `experience()` and `activate()`. On the official LoCoMo long-conversation benchmark (10 conversations, 1,982 gold evidence spans), FluctlightDB’s hybrid index recalls **98.1%** of gold evidence—warm and cold-start identical. On LongMemEval-S (500 questions, official `session_recall@8`), our retrieval harness scores **96.8%** (484/500), competitive with published hybrid memory systems on the same benchmark. On BEIR SciFact it matches a tuned Chroma + MiniLM baseline on nDCG@10 at equal latency, while agent mode improves Recall@100. On an agent-specific suite (FAMB) it scores 97–98% macro across paraphrase recall, provenance ranking, persistence, and write-time separation. The engine, harnesses, and frozen metrics are released under the MIT license. We claim no new neuroscience and no new transformer; we claim a missing layer of the data stack, and an engine that fills it.

1 Introduction

Every generation of software gets the database it deserves. Business records gave us the relational model [2] and SQL. Embeddings gave us vector databases and approximate nearest-neighbor search. Agents—programs that act, observe, and persist across sessions—have so far been handed *neither*. They are stateless between runs unless a developer hand-assembles a session store, a vector index, a deduplicator, a trust policy, and glue code to keep them consistent. The result is that “memory” for agents lives in application code, re-implemented badly in every project, with no shared abstraction and no benchmark to hold it accountable.

This paper makes a deliberately large claim and then defends it with measurements: **agent memory deserves its own database engine, not a wrapper around someone else’s**. A relational engine is the wrong abstraction because memory is not a set of typed rows joined by keys. A vector engine is the wrong abstraction because recall is not cosine similarity alone—a human, and an agent, retrieve a fact because it was *learned*, *linked* to a context, and *trusted*, not merely because its embedding is close. What is missing is a model whose unit is the *episode*—an

experience with content, context, salience, and provenance—and whose query is a *cue* that spreads through associations.

Contributions.

- **A data model.** We define agent memory as a first-class model of data with explicit write semantics (separation, encoding, consolidation, provenance) and read semantics (cue activation over a memory graph), distinct from the relational and vector models.
- **An engine.** FluctlightDB, an embedded Rust engine exposing `experience()` / `activate()` / `checkpoint()`—one durable store per agent, with no external services.
- **Evidence.** **98.1%** evidence recall on full LoCoMo, **96.8%** session recall@8 on full LongMemEval-S, parity with a tuned vector baseline on BEIR SciFact, and 97–98% macro on an agent-specific benchmark.
- **Reproducibility.** Open harnesses and frozen result JSON so every number here can be re-run with one command.

2 The Third Data Model

2.1 Why rows are not memory

The relational model stores facts whose schema is known in advance and whose truth is uniform. Agent memory is the opposite: heterogeneous, arriving out of order, often contradictory (a chat claim vs. a ledger entry), and valuable precisely *because* of where it came from. SQL has no native notion of provenance-weighted recall or of an experience that should be down-weighted because a more trusted source disagrees.

2.2 Why nearest-neighbor is not recall

Vector search answers “what is similar.” Memory answers “what is relevant given who I am and what I was doing.” Two memories with distant embeddings can be the right answer because they were co-activated during the same episode; a near embedding can be the wrong answer because it is an unverified rumor. Pure ANN has no place to encode association strength, salience decay, or trust.

2.3 The model

We define a memory store as a set of *engrams*. Each engram carries content, an encoding context, a salience weight, optional provenance, and edges to co-activated engrams. The write operation `experience` performs pattern *separation* (near-duplicates are gated, not blindly appended), encodes the engram, registers its semantic vector, and wires graph edges. The read operation `activate` takes a cue, seeds both lexical and semantic indexes, spreads activation through the graph, fuses the scores, and applies provenance boosts so verified sources outrank chat. Consolidation replays and compacts the store offline, the way sleep consolidates biological memory. This is the entire contract; the neuroscience vocabulary is explanatory, not required to use it.

Table 1: Brain-native primitives vs. relational and vector abstractions.

Primitive	Role in FluctlightDB	Relational / vector analogue
Engram	Unit of memory: content, context, salience, provenance, edges	Row; or embedded chunk
<code>experience()</code>	Write: separation, encode, index, wire co-activation	INSERT / upsert
<code>activate(cue)</code>	Read: lexical + semantic seed, graph spread, fusion, trust boost	SELECT / ANN top- <i>k</i>
Consolidation	Offline replay and compaction (<code>checkpoint()</code>)	Vacuum / reindex only
Provenance	Verified sources outrank unverified chat at recall	No native type

3 System Design

3.1 Embedded, one store per agent

Like SQLite, FluctlightDB is a library, not a server: each agent owns a directory on disk and `checkpoint()` commits state. There is nothing to provision and nothing to keep in sync. A thin HTTP server is provided for multi-agent deployments but is not required.

3.2 Write path

Incoming `experience` episodes pass through optional separation gating, dentate-style encoding into engrams, semantic vector registration, and graph wiring. A fast-ingest mode skips heavy graph work for bulk indexing.

3.3 Read path

`activate(cue)` seeds lexical (BM25) and semantic (vector) indexes, spreads activation through the memory graph, fuses scores, and applies provenance boosts. For conversational RAG we merge vector top-*k* with lexical seeds—*hybrid retrieval*—before ranking. A vector-fast mode provides Chroma-class cosine top-*k* for IR comparisons.

3.4 Two explicit modes

`connect()` is the full episodic engine (separation, graph, provenance) for live agents. `connect_index()` is the bulk semantic path for RAG backfills and IR benchmarks. The modes share one engine and one file format.

Figure 1 summarizes how an agent brain is laid out on disk, what each engram stores, and how write and read paths connect the episodic store to the hybrid recall sidecar.




Figure 1: FluctlightDB persistence and recall layout. Each agent owns a brain directory (a) with segmented engram storage, a co-activation graph, and a hybrid recall sidecar (FTS5 + HNSW). The logical engram (b) bundles episode content, provenance, optional RAG keys, and graph wiring. `experience()` (c) gates near-duplicates, encodes, and indexes; `activate()` (d) seeds candidates lexically and semantically, spreads through the graph, and ranks by fused score with provenance boosts.

4 Evaluation

All experiments use `all-MiniLM-L6-v2` (ONNX, CPU) unless noted. Every number below is reproduced by a script in `benchmarks/` and frozen in `benchmarks/results/paper-2026-07-03.json` (LoCoMo, BEIR, FAMB from 2025-06-22; LongMemEval from 2026-07-03).

4.1 BEIR SciFact: parity with a tuned vector baseline

We score standard IR metrics via `pytrec_eval` against official qrels, using identical embeddings for FluctlightDB and Chroma. Index mode is a dead heat on quality and latency—meaning the memory engine costs nothing as a plain vector store—while agent mode, with graph co-activation, improves deep recall.

Table 2: BEIR SciFact (shared MiniLM embeddings).

System	nDCG@10	R@10	R@100	Query (ms)
Chroma	0.645	0.783	0.925	5–7
FluctlightDB (index)	0.645	0.783	0.925	5–7
FluctlightDB (agent)	0.651	0.790	0.941	15




Figure 2: Headline benchmark results (frozen July 2026). LoCoMo and LongMemEval-S use official retrieval metrics; BEIR reports nDCG@10; FAMB reports index-mode macro score.

4.2 LoCoMo: 98.1% evidence recall on the full set

LoCoMo [4] stresses very long, multi-session dialogue. We report the official evidence-recall metric: the fraction of gold `dia_id` evidence spans present in retrieved context. Configuration: `connect_index()`, ingest of dialog *and* observations, $k=150$, hybrid vector+BM25, two CPU threads. The headline result is robust to cold start—clearing every cache and re-ingesting from scratch yields the identical figure—which is the property a production memory engine must have.

Table 3: LoCoMo full set: 10 conversations, 1,982 gold evidence spans.

Metric	Warm	Cold (caches cleared)
Mean evidence recall	98.1%	98.1%
All evidence in context	97.1%	97.1%
Evidence hits	1925/1982	1925/1982
Wall time (s)	271	335

We deliberately separate *retrieval* from *generation*. A verbatim answer-in-context proxy sits near 38%, but this measures string overlap, not correctness—LoCoMo gold answers are usually inferred facts (dates, counts), not quoted spans. A 50-question end-to-end pilot with a hosted reader LLM produced 23.5% category F1 at 99.5% retrieval on the same slice; full end-to-end QA awaits sufficient inference quota and is reported as future work. The engine’s job is to put the evidence in front of the reader, and at that job it scores 98.1%.

4.3 FAMB: the agent-specific suite

Generic IR does not test what agents need. FAMB measures paraphrase recall@1 (real cues never match stored wording), provenance top-1 (verified ledger beats chat claim), persistence (recall

survives checkpoint + reopen), confusion ingest (near-duplicates do not block new facts), and determinism. Index-mode macro is **98%**; agent-mode macro is **97%**.

4.4 LongMemEval-S: 96.8% session recall@8 on the full set

LongMemEval [8] tests six long-horizon abilities across 500 questions. The official *retrieval* metric is `session_recall@K`: whether gold `answer_session_ids` appear in the top- K recalled sessions. This is the fair bar for comparing memory *indexes* before any reader LLM is invoked; end-to-end QA with an LLM judge is a separate, higher layer (TiMem reports $\sim 77\%$ LLJ on LongMemEval-S; PlugMem $\sim 90\%$ Acc).

We run retrieval-only with `connect_index()`, one engram per chat session (LongMemEval “value” granularity), hybrid BM25 + dense recall, dual-key user indexing (CP2), and heuristic query expansion (CP3). Embeddings use `multi-qa-mpnet-base-dot-v1` on GPU (Google Colab); the full 500-question run completes in ~ 53 minutes (6.4 s/question).

Table 4: LongMemEval-S retrieval: session recall@8 (full 500 questions).

System / slice	session@8	Notes
FluctlightDB (full)	96.8%	484/500; hybrid + dual-key + expand
knowledge-update	100%	
multi-session	98.5%	
single-session-user	98.6%	
single-session-assistant	98.2%	
temporal-reasoning	96.2%	
single-session-preference	76.7%	implicit prefs; remaining gap
gbrain (leaderboard)	97.6% @5	hybrid + text-embedding-3-large
YourMemory (leaderboard)	95.8% @5	mpnet + BM25 + graph BFS
M3 Memory (leaderboard)	96.8% @10	FTS5 + vector + MMR

Leaderboard figures use $K=5$ or $K=10$ and different embedders; our $K=8$ run is directly comparable in *protocol* (gold session in top- K) but not a claim of strict SOTA. The headline—96.8% on all 500 questions with a reproducible open harness—places FluctlightDB alongside published hybrid memory systems. The main residual error is **single-session-preference** (23/30 correct): questions ask for recommendations without naming prior facts (e.g. “documentary recommendations?” when the user previously watched *Our Planet*); bridging implicit preference to the right session is the active research frontier. Reproduce via `benchmarks/longmemeval.colab.ipynb` or `benchmarks/longmemeval.bench.py` with `--granularity session --metric session --dual-key --query-expand`.

5 Discussion

The engine is the contribution, not the reader. A memory system should be judged on whether it surfaces the right evidence; 98.1% on full LoCoMo says it does. End-to-end QA additionally depends on the language model and the prompt budget, and we are careful not to launder a retrieval win into a generation claim.

In production. Beyond benchmarks, FluctlightDB backs a continuously running operational agent in a deployed production system, persisting cross-session state for an autonomous service




Figure 3: LongMemEval-S session recall@8 by question type. Preference questions (76.7%) remain the main gap—implicit user context not named in the query.

rather than a research fixture—the durability and cold-start guarantees above are properties we rely on, not only ones we measured.

Hybrid retrieval matters. Lexical seeds materially raised LoCoMo recall over vector-only retrieval at moderate k ; dialogue evidence frequently hinges on named entities and dates that cosine similarity alone misses. This is direct evidence that the memory model benefits from machinery a pure vector DB lacks.

Limitations. LongMemEval preference questions (76.7%) and a handful of temporal misses remain; LLM-based key expansion (LongMemEval CP2) is not yet in the default ingest path. We have not yet evaluated multi-tenant isolation at scale, ANN beyond 10^5 memories, or full end-to-end LLM QA against published Mem0/Zep baselines on LongMemEval (their numbers use reader-LLM judges, not session recall). These are the natural next steps.

6 Related Work

6.1 Vector databases

Systems such as Chroma, Qdrant, and FAISS [6] optimize approximate nearest-neighbor search. They answer *similarity*, not *memory*: there is no native episode, provenance-weighted recall, write-time separation, or cue-driven spreading activation. FluctlightDB’s `connect_index()` mode deliberately exposes a vector-fast path so we can measure parity on BEIR; agent mode adds graph co-activation on top of the same store.

6.2 Agent memory SDKs and layers

Mem0 [1] is the closest contemporary system: it extracts, consolidates, and retrieves salient facts from dialogue, with an optional graph variant (Mem0^g) for relational structure among entities. It reports strong LoCoMo numbers using *LLM-as-a-judge end-to-end QA*—a different metric from the official evidence-recall protocol we adopt for retrieval. **Zep** [9] provides temporal knowledge-graph

memory for assistants, also evaluated with reader-LLM QA on LoCoMo. **Cognee** [7] pipelines vector and graph storage for agent RAG. **MemGPT** [5] (Letta) treats context as an OS resource with explicit memory tiers but does not define a standalone embedded memory *engine contract*. **HippoRAG** [3] draws on associative-retrieval neuroscience for multi-hop QA over a graph index. These systems are valuable *memory layers*: they orchestrate extraction, summarization, and retrieval over general-purpose backends. We position FluctlightDB as the missing *engine* beneath such layers—where the native operations are **experience** and **activate**, not **SQL** or **vector_search**.

6.3 Positioning

To our knowledge, no prior work argues that long-term agent memory is a third data model—peer to the relational [2] and vector models—with engine-level write and read semantics implemented in an embedded store. Enterprise databases adding agent features (e.g. Oracle AI Database unified memory) retrofit memory onto existing engines rather than defining episodes and cues as first-class types. Table 5 summarizes the landscape; direct head-to-head retrieval on LoCoMo evidence recall against Mem0/Zep is future work (different published metrics today).

Table 5: Landscape: memory *layers* vs. FluctlightDB as an embedded *engine*. Benchmark figures are *not* directly comparable across rows unless the metric column matches.

System	Kind	Native contract	con-	Benchmark (cited)	Metric type
Mem0 Mem0 ^g	/ SDK + backend	Extract / consolidate / retrieve facts		~92%+ LLM-J	End-to-end QA
Zep	Managed layer	Temporal + summaries	KG	~75% LLM-J	End-to-end QA
Cognee	Pipeline	Graph + vector ETL		—	Task-specific
MemGPT Letta	/ Agent OS	Context tiers / blocks		—	Session QA
HippoRAG	Graph RAG	Associative graph retrieval		—	Multi-hop QA
Chroma Qdrant	/ Vector DB	ANN top- <i>k</i>		—	IR / similarity
FluctlightDB	Engine	experience / activate		98.1%	LoCoMo evidence
FluctlightDB	Engine	hybrid index + session keys		96.8%	LongMemEval session@8

Benchmarks LoCoMo [4] and LongMemEval [8] measure long-horizon memory; BEIR [6] anchors IR credibility. Our framing—memory as a data model on equal footing with rows and vectors—is the claim this engine and its measurements are built to support.

7 Conclusion

The relational model gave applications a database for *facts*; the vector model gave search a database for *similarity*. Autonomous agents need a database for *memory*, and it should be as boring to adopt and as rigorous to trust as SQLite. FluctlightDB is our argument that this engine can exist today: it matches vector baselines where they are strong, wins where memory semantics matter, recalls 98.1%

of gold evidence on LoCoMo and 96.8% session recall on LongMemEval-S. We release everything needed to reproduce and contest these claims.

Artifacts

Repository: FluctlightDB (MIT). Harnesses: `benchmarks/locomo_eval.py`, `benchmarks/longmemeval_bench.py`, `benchmarks/longmemeval_colab.ipynb`, `benchmarks/beir_bench.py`, `benchmarks/agent_memory_bench.py`. Frozen metrics: `benchmarks/results/paper-2026-07-03.json`. Preprint DOI: <https://doi.org/10.5281/zenodo.20949890>. Source: <https://github.com/voxmastery/FluctlightDB/tree/main/papers/arxiv-v1>.

References

- [1] Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready ai agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*, 2025.
- [2] Edgar F Codd. A relational model of data for large shared data banks. *Communications of the ACM*, 13(6):377–387, 1970.
- [3] Bernardo Gutiérrez, Yiheng Shu, Yu Gu, Peter Pasupat, Barret Liu, Rishabh Shah, Ming-Wei Chang, Ramakanth Pasunuru, Yujia Zhang, Avi Gupta, et al. Hipporag: Neurobiologically inspired long-term memory for large language models. *arXiv preprint arXiv:2405.14831*, 2024.
- [4] Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of llm agents. In *ACL*, 2024.
- [5] Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G Patil, Ion Stoica, and Joseph E Gonzalez. Memgpt: Towards llms as operating systems. *arXiv preprint arXiv:2310.08560*, 2023.
- [6] Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. Beir: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. In *NeurIPS Datasets and Benchmarks*, 2021.
- [7] Topoteretes. Cognee: Memory engine for ai agents. <https://github.com/topoteretes/cognee>, 2024. Vector + knowledge-graph memory pipeline.
- [8] Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. Longmemeval: A benchmark for long-term memory in llm chat assistants. *arXiv preprint arXiv:2410.10813*, 2024.
- [9] Zep AI. Zep: A temporal knowledge graph architecture for agent memory. <https://www.getzep.com>, 2024. Agent memory platform; LoCoMo evaluations in product documentation.