

# Automated Deduction

Laura Kovács

for(synte,  Informatics

# Outline

First-Order Theorem Proving - An Example

First-Order Logic and TPTP

Inference Systems

# First-Order Theorem Proving

We will use the VAMPIRE theorem prover throughout the lecture.

Go to

<https://vprover.github.io/download.html>

and pick the route most suitable to you.

Notes:

- ▶ For Linux users, a binary is probably the easiest route
- ▶ For Mac users, you need to build from source
  - ▶ `run make vampire_rel`
- ▶ For Windows users, the easiest route is a virtual machine and then use Linux
  - ▶ only running Vampire in the browser at <https://tptp.org/cgi-bin/SystemOnTPTP>

# First-Order Theorem Proving

We will use the VAMPIRE theorem prover throughout the lecture.

Go to

<https://vprover.github.io/download.html>

and pick the route most suitable to you.

Notes:

- ▶ For Linux users, a binary is probably the easiest route
- ▶ For Mac users, you need to build from source
  - ▶ `run make vampire_rel`
- ▶ For Windows users, the easiest route is a virtual machine and then use Linux
  - ▶ only running Vampire in the browser at <https://tptp.org/cgi-bin/SystemOnTPTP>

# First-Order Theorem Proving. An Example

**Group theory theorem:** if a group satisfies the identity  $x^2 = 1$ , then it is commutative.

# First-Order Theorem Proving. An Example

group op:  $\cdot$

**Group theory theorem:** if a group satisfies the identity  $x^2 = 1$ , then it is commutative.

**More formally:** in a group “assuming that  $x^2 = 1$  for all  $x$  prove that  $x \cdot y = y \cdot x$  holds for all  $x, y$ .”

# First-Order Theorem Proving. An Example

**Group theory theorem:** if a group satisfies the identity  $x^2 = 1$ , then it is commutative.

**More formally:** in a group “**assuming** that  $x^2 = 1$  for all  $x$  **prove** that  $x \cdot y = y \cdot x$  holds for all  $x, y$ .”

**What is implicit:** axioms of the group theory.

$$\forall x(1 \cdot x = x)$$

$$\forall x(x^{-1} \cdot x = 1)$$

$$\forall x \forall y \forall z((x \cdot y) \cdot z = x \cdot (y \cdot z))$$

# Formulation in First-Order Logic

Axioms (of group theory):	$\forall x(1 \cdot x = x)$	$A_1$
	$\forall x(x^{-1} \cdot x = 1)$	$A_2$
	$\forall x \forall y \forall z((x \cdot y) \cdot z = x \cdot (y \cdot z))$	$A_3$
Assumptions:	$\forall x(x \cdot x = 1)$	$A_4$
Conjecture:	$\forall x \forall y(x \cdot y = y \cdot x)$	$G$

$$A_1 \wedge A_2 \wedge A_3 \wedge A_4 \Rightarrow G$$



# In the TPTP Syntax

The **TPTP** library (**T**housands of **P**roblems for **T**heorem **P**rovers), <http://www.tptp.org> contains a large collection of first-order problems. For representing these problems it uses the **TPTP syntax**, which is understood by all modern theorem provers, including Vampire.

# In the TPTP Syntax

$$\text{\$product}(e, X) = X$$

The **TPTP** library (**T**housands of **P**roblems for **T**heorem **P**rovers), <http://www.tptp.org> contains a large collection of first-order problems. For representing these problems it uses the **TPTP syntax**, which is understood by all modern theorem provers, including Vampire. In the TPTP syntax this group theory problem can be written down as follows:

tf

```
%---- 1 * x = x
fof(left_identity, axiom,
! [X] : mult(e, X) = X).
%---- i(x) * x = 1
fof(left_inverse, axiom,
! [X] : mult(inverse(X), X) = e).
%---- (x * y) * z = x * (y * z)
fof(associativity, axiom,
! [X, Y, Z] : mult(mult(X, Y), Z) = mult(X, mult(Y, Z))).
%---- x * x = 1
fof(group_of_order_2, hypothesis,
! [X] : mult(X, X) = e).
%---- prove x * y = y * x
fof(commutativity, conjecture,
! [X] : mult(X, Y) = mult(Y, X)).
```

$$\forall x : 1 \cdot x = x$$

# Running Vampire on a TPTP file

is easy: simply use

```
vampire <filename>
```

# Running Vampire on a TPTP file

is easy: simply use

```
vampire <filename>
```

One can also run Vampire with various options, some of them will be explained later. For example, save the group theory problem in a file `group.tptp` and try

```
vampire --thanks TUWien group.tptp
```

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

► Each inference derives a formula from zero or more other formulas;

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ **Input**, preprocessing, new symbols introduction, superposition calculus

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus



# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sK0,sK1) != mult(sK1,sK0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sK0,sK1) != mult(sK1,sK0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sK0,sK1) != mult(sK1,sK0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, **new symbols introduction**, superposition calculus

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, **superposition calculus**

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ **Proof by refutation**, generating and simplifying inferences, unused formulas ...

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ Proof by refutation, **generating** and **simplifying** inferences, unused formulas ...

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ Proof by refutation, generating and simplifying inferences, **unused formulas** ...

# Outline

First-Order Theorem Proving - An Example

First-Order Logic and TPTP

Inference Systems

# First-Order Logic and TPTP

- ▶ **Language**: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.

# First-Order Logic and TPTP

- Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.

In TPTP: Variable names start with upper-case letters.

$$\text{HyFunction}(e, X) = X$$



# First-Order Logic and TPTP

- ▶ Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.  
In TPTP: Variable names start with upper-case letters.
- ▶ **Terms**: variables, constants, and expressions  $f(t_1, \dots, t_n)$ , where  $f$  is a function symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms.

# First-Order Logic and TPTP

- ▶ Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.  
In TPTP: Variable names start with upper-case letters.
- ▶ Terms: variables, constants, and expressions  $f(t_1, \dots, t_n)$ , where  $f$  is a function symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Terms denote domain elements.

# First-Order Logic and TPTP

- ▶ Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.  
In TPTP: Variable names start with upper-case letters.
- ▶ Terms: variables, constants, and expressions  $f(t_1, \dots, t_n)$ , where  $f$  is a function symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Terms denote domain elements.
- ▶ **Atomic formula:** expression  $p(t_1, \dots, t_n)$ , where  $p$  is a predicate symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms.

# First-Order Logic and TPTP

- ▶ Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.  
In TPTP: Variable names start with upper-case letters.
- ▶ Terms: variables, constants, and expressions  $f(t_1, \dots, t_n)$ , where  $f$  is a function symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Terms denote domain elements.
- ▶ **Atomic formula:** expression  $p(t_1, \dots, t_n)$ , where  $p$  is a predicate symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Formulas denote **properties of domain elements**.
- ▶ All symbols are uninterpreted, apart from equality  $=$ .

# First-Order Logic and TPTP

- ▶ Language: variables, function and predicate (relation) symbols. A constant symbol is a special case of a function symbol.  
In TPTP: Variable names start with upper-case letters.
- ▶ Terms: variables, constants, and expressions  $f(t_1, \dots, t_n)$ , where  $f$  is a function symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Terms denote domain elements.
- ▶ **Atomic formula:** expression  $p(t_1, \dots, t_n)$ , where  $p$  is a predicate symbol of arity  $n$  and  $t_1, \dots, t_n$  are terms. Formulas denote properties of domain elements.
- ▶ All symbols are uninterpreted, apart from equality  $=$ .

	FOL	TPTP
	$\perp, \top$	<code>\$false, \$true</code>
	$\neg a$	<code>~a</code>
	$a \wedge \dots \wedge a_n$	<code>a1 &amp; ... &amp; an</code>
	$a \vee \dots \vee a_n$	<code>a1   ...   an</code>
	$a_1 \rightarrow a_2$	<code>a1 =&gt; a2</code>
	$(\forall x_1) \dots (\forall x_n) a$	<code>! [X1, ..., Xn] : a</code>
	$(\exists x_1) \dots (\exists x_n) a$	<code>? [X1, ..., Xn] : a</code>

$p(x) \vee q(x)$

$\&$   
 $! [X]: (p(x) \vee q(x))$

$! [X]: p(x) \vee ! [X]: q(x)$

# More on the TPTP Syntax

```
%---- 1 * x = x
fof(left_identity,axiom,(
    ! [X] : mult(e,X) = X )).
%---- i(x) * x = 1
fof(left_inverse,axiom,(
    ! [X] : mult(inverse(X),X) = e )).
%---- (x * y) * z = x * (y * z)
fof(associativity,axiom,(
    ! [X,Y,Z] :
        mult(mult(X,Y),Z) = mult(X,mult(Y,Z)) )).
%---- x * x = 1
fof(group_of_order_2,hypothesis,
    ! [X] : mult(X,X) = e ).
%---- prove x * y = y * x
fof(commutativity,conjecture,
    ! [X,Y] : mult(X,Y) = mult(Y,X) ).
```

# More on the TPTP Syntax

## ► Comments;

```
%---- 1 * x = x
fof(left_identity,axiom,(
    ! [X] : mult(e,X) = X )).
%---- i(x) * x = 1
fof(left_inverse,axiom,(
    ! [X] : mult(inverse(X),X) = e )).
%---- (x * y) * z = x * (y * z)
fof(associativity,axiom,(
    ! [X,Y,Z] :
        mult(mult(X,Y),Z) = mult(X,mult(Y,Z)) )).
%---- x * x = 1
fof(group_of_order_2,hypothesis,
    ! [X] : mult(X,X) = e ).
%---- prove x * y = y * x
fof(commutativity,conjecture,
    ! [X,Y] : mult(X,Y) = mult(Y,X) ).
```

# More on the TPTP Syntax

- Comments;
- Input formula names;

```
%---- 1 * x = x
fof(left_identity, axiom, (
    ! [X] : mult(e, X) = X )).
%---- i(x) * x = 1
fof(left_inverse, axiom, (
    ! [X] : mult(inverse(X), X) = e )).
%---- (x * y) * z = x * (y * z)
fof(associativity, axiom, (
    ! [X, Y, Z] :
        mult(mult(X, Y), Z) = mult(X, mult(Y, Z)) )).
%---- x * x = 1
fof(group_of_order_2, hypothesis,
    ! [X] : mult(X, X) = e ).
%---- prove x * y = y * x
fof(commutativity, conjecture,
    ! [X, Y] : mult(X, Y) = mult(Y, X) ).
```



# More on the TPTP Syntax

- ▶ **Comments**;
- ▶ **Input formula names**;
- ▶ **Input formula roles** (very important);

```
%---- 1 * x = x
fof(left_identity, axiom, (
    ! [X] : mult(e,X) = X )).
%---- i(x) * x = 1
fof(left_inverse, axiom, (
    ! [X] : mult(inverse(X),X) = e )).
%---- (x * y) * z = x * (y * z)
fof(associativity, axiom, (
    ! [X,Y,Z] :
        mult(mult(X,Y),Z) = mult(X,mult(Y,Z)) )).
%---- x * x = 1
fof(group_of_order_2, hypothesis,
    ! [X] : mult(X,X) = e ).
%---- prove x * y = y * x
fof(commutativity, conjecture,
    ! [X,Y] : mult(X,Y) = mult(Y,X) ).
```

# More on the TPTP Syntax

- ▶ Comments;
- ▶ Input formula names;
- ▶ Input formula roles (very important);
- ▶ Equality

```
%---- 1 * x = x
fof(left_identity, axiom, (
    ! [X] : mult(e, X) = X )).
%---- i(x) * x = 1
fof(left_inverse, axiom, (
    ! [X] : mult(inverse(X), X) = e )).
%---- (x * y) * z = x * (y * z)
fof(associativity, axiom, (
    ! [X, Y, Z] :
        mult(mult(X, Y), Z) = mult(X, mult(Y, Z)) )).
%---- x * x = 1
fof(group_of_order_2, hypothesis,
    ! [X] : mult(X, X) = e ).
%---- prove x * y = y * x
fof(commutativity, conjecture,
    ! [X, Y] : mult(X, Y) = mult(Y, X) ).
```

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

► Each inference derives a formula from zero or more other formulas;

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ **Input**, preprocessing, new symbols introduction, superposition calculus

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sK0,sK1) != mult(sK1,sK0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sK0,sK1) != mult(sK1,sK0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sK0,sK1) != mult(sK1,sK0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, **new symbols introduction**, superposition calculus

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult(sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, **superposition calculus**



# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ **Proof by refutation**, generating and simplifying inferences, unused formulas ...

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                                    [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ Proof by refutation, **generating** and **simplifying** inferences, unused formulas ...

# Proof by Vampire (Slightly Modified)

Refutation found.

```
270. $false [trivial inequality removal 269]
269. mult(sk0,sk1) != mult (sk0,sk1) [superposition 14,125]
125. mult(X2,X3) = mult(X3,X2) [superposition 21,90]
90. mult(X4,mult(X3,X4)) = X3 [forward demodulation 75,27]
75. mult(inverse(X3),e) = mult(X4,mult(X3,X4)) [superposition 22,19]
27. mult(inverse(X2),e) = X2 [superposition 21,11]
22. mult(inverse(X4),mult(X4,X5)) = X5 [forward demodulation 17,10]
21. mult(X0,mult(X0,X1)) = X1 [forward demodulation 15,10]
19. e = mult(X0,mult(X1,mult(X0,X1))) [superposition 12,13]
17. mult(e,X5) = mult(inverse(X4),mult(X4,X5)) [superposition 12,11]
15. mult(e,X1) = mult(X0,mult(X0,X1)) [superposition 12,13]
14. mult(sk0,sk1) != mult(sk1,sk0) [cnf transformation 9]
13. e = mult(X0,X0) [cnf transformation 4]
12. mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [cnf transformation 3]
11. e = mult(inverse(X0),X0) [cnf transformation 2]
10. mult(e,X0) = X0 [cnf transformation 1]
9. mult(sk0,sk1) != mult(sk1,sk0) [skolemisation 7,8]
8. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) <=> mult(sk0,sk1) != mult(sk1,sk0)
                                     [choice axiom]
7. ?[X0,X1]: mult(X0,X1) != mult(X1,X0) [ennf transformation 6]
6. ~![X0,X1]: mult(X0,X1) = mult(X1,X0) [negated conjecture 5]
5. ![X0,X1]: mult(X0,X1) = mult(X1,X0) [input]
4. ![X0]: e = mult(X0,X0) [input]
3. ![X0,X1,X2]: mult(X0,mult(X1,X2)) = mult(mult(X0,X1),X2) [input]
2. ![X0]: e = mult(inverse(X0),X0) [input]
1. ![X0]: mult(e,X0) = X0 [input]
```

- ▶ Each inference derives a formula from zero or more other formulas;
- ▶ Input, preprocessing, new symbols introduction, superposition calculus
- ▶ Proof by refutation, generating and simplifying inferences, **unused formulas** ...

# Vampire

- ▶ **Completely automatic:** once you started a proof attempt, it can only be interrupted by terminating the process.

# Vampire

- ▶ **Completely automatic:** once you started a proof attempt, it can only be interrupted by terminating the process.
- ▶ **Champion** of the CASC world-cup in first-order theorem proving: won CASC > 50 times.



# What an Automatic Theorem Prover is Expected to Do

## Input:

- ▶ a set of **axioms** (first order formulas) or clauses;
- ▶ a **conjecture** (first-order formula or set of clauses).

## Output:

- ▶ **proof** (hopefully).

# Proof by Refutation

Given a problem with axioms and assumptions  $F_1, \dots, F_n$  and conjecture  $G$ ,

1. negate the conjecture;
2. establish **unsatisfiability** of the set of formulas  $F_1, \dots, F_n, \neg G$ .

$$\overbrace{F_1 \wedge \dots \wedge F_n}^{\text{axioms}} \Rightarrow \overbrace{G}^{\text{conjecture}}$$



$$\underbrace{F_1 \wedge \dots \wedge F_n \wedge \neg G}_{\text{axioms}} \Rightarrow \perp$$

# Proof by Refutation

Given a problem with axioms and assumptions  $F_1, \dots, F_n$  and conjecture  $G$ ,

1. negate the conjecture;
2. establish **unsatisfiability** of the set of formulas  $F_1, \dots, F_n, \neg G$ .

Thus, we reduce the theorem proving problem to the problem of **checking unsatisfiability**.



# Proof by Refutation

Given a problem with axioms and assumptions  $F_1, \dots, F_n$  and conjecture  $G$ ,

1. negate the conjecture;
2. establish **unsatisfiability** of the set of formulas  $F_1, \dots, F_n, \neg G$ .

Thus, we reduce the theorem proving problem to the problem of **checking unsatisfiability**.

In this formulation the negation of the conjecture  $\neg G$  is treated like any other formula. In fact, Vampire (and other provers) **internally treat conjectures differently, to make proof search more goal-oriented**.

# General Scheme (simplified)


preprocessing

- ▶ Read a problem;
- ▶ Determine proof-search options to be used for this problem;
- ▶ Preprocess the problem;
- ▶ Convert it into CNF;

▶ Run a saturation algorithm on it, try to derive false.

proving

- ▶ If false is derived, report the result, maybe including a refutation.



$$S_0 \Rightarrow S_1 \Rightarrow S_2 \Rightarrow \dots \Rightarrow S_{n+1}$$