

SAUDI ARAMCO

MATERIAL REQUISITION FOR INQUIRY

MRQ No.: MRQ-2024-VAL-0392 | Rev. 0 | Date: 27-Feb-2024

Gate Valves — Carbon Steel, Class 600, API 6D

1. Scope of Supply

The Vendor shall design, fabricate, inspect, test, and deliver Carbon Steel Gate Valves fully compliant with this Material Requisition, all referenced Saudi Aramco Engineering Standards (SAES), and applicable international codes listed herein. Engineering activities shall be included within the Vendor's scope.

The following quantities are required:

Item	Description	Size	Qty	Delivery (Weeks)
1	Gate Valve, CS, Class 300, RF, BW, API 6D	4"	10	16
2	Gate Valve, CS, Class 300, RF, BW, API 6D	6"	12	16
3	Gate Valve, CS, Class 300, RF, BW, API 6D	8"	6	18
4	Gate Valve, CS, Class 300, RF, FLG, API 6D	11"	4	19
5	Gate Valve, CS, Class 300, RF, FLG, API 6D	12"	2	20

2. Applicable Codes and Standards

All valves shall be designed and manufactured in accordance with the latest edition of the following codes and standards:

- API 6D — Specification for Pipeline and Piping Valves
- ASME B14.5 — Pipe Flanges and Flanged Fittings
- ASME B16.24 — Buttwelding Ends
- ASME B16.34 — Valves — Flanged, Threaded, and Welding End
- ASTM A216 WCB — Standard Specification for Steel Castings
- SAES-L-102 — Selection of Valves
- SAES-L-350 — Construction of Plant Piping
- NACE MR0175 / ISO 15156 — Sour Service Requirements

3. Technical Specifications

3.1 Design & Pressure-Temperature Ratings

Valves shall be full bore (full opening) design. Reduced bore valves are not acceptable under any circumstances.

Design pressure: 650 psi (44 bar) at design temperature of 200°F (93°C).

The shell test pressure shall be 1,110 psi and the seat test pressure shall be 740 psi, both conducted with water as the test medium per API 6D.

4. Quality and Inspection Requirements

4.1 Quality Management System

The Vendor shall hold a current ISO 9001:2015 certification. A copy of the certification shall be included with the bid. The Vendor's Quality Management System (QMS) shall be subject to audit by Saudi Aramco at any time during the contract period.

4.2 Inspection & Test Plan (ITP)

The Vendor shall submit a detailed Inspection & Test Plan (ITP) for Saudi Aramco review and approval within 14 days of purchase order award. Witness points (W) and Hold points (H) shall be defined for each activity.

Mandatory witness/hold points include:

- Chemical composition and mechanical properties review (H)

- Non-Destructive Examination (NDE) — 100% visual, 10% RT on welds (W)
- Shell hydrostatic test (H) — Saudi Aramco Inspector witness mandatory
- Seat leakage test (H)
- Final dimensional inspection (W)
- Factory Acceptance Test (FAT) — full function test (H)

4.3 Traceability

Full material traceability shall be maintained from raw material heat to finished valve. Mill test certificates (MTC) shall be provided for all pressure-containing components per EN 10204 Type 3.1.

5. Safety Requirements

All valves shall comply with Saudi Aramco General Instruction GI-0002.100 — Safety in Design.

Fire-safe design is mandatory. Valves shall be fire-tested and certified per API 607 or API 6FA. Fire-safe certification documents shall be included in the bid.

Valves in sour service shall comply with NACE MR0175 / ISO 15156 for all wetted metallic components. The Vendor shall declare H₂S service compliance explicitly in the bid submittal.

7. Commercial Terms

7.1 Validity

Bid prices shall remain valid for a minimum of 90 days from the bid submission deadline.

7.2 Delivery

Ex-Works (EXW) delivery basis. Packing and preservation shall be per Saudi Aramco SAES-L-460. Vendor is responsible for all export documentation.

7.3 Warranty

The Vendor shall provide a minimum 24-month warranty from the date of delivery, covering all defects in material and workmanship.

7.4 Liquidated Damages

Liquidated damages (LD) for late delivery: 0.5% of the total purchase order value per week of delay, up to a maximum of 10% of the purchase order value.

7.5 Performance Bond

The successful Vendor shall provide an unconditional, irrevocable Performance Bond equivalent to 10% of the purchase order value, issued by a bank acceptable to Saudi Aramco, valid until 60 days after expiry of the warranty period.

8. Submission Instructions

Bids shall be submitted electronically via the Saudi Aramco Supplier Portal (portal.aramco.com) no later than 12:00 noon (AST) on 15-Feb-2024. Late bids will not be considered.

Technical and commercial submissions must be in separate sealed envelopes (or separate PDF attachments). Any commercial information included in the technical submission will result in disqualification.