SMART TRAFFIC SIGNAL CONTROLLER

Submitted By:

Name: Patel Dip N.(240280106096)

Patel Vraj M. (240280106113)

Patel Aastha M. (240280106092)

Department: Computer Engineering

College: L.D. College of Engineering, Ahmedabad

Academic Year: 2026–2027

INTRODUCTION

- Traffic congestion is a major problem in urban areas
- Fixed-time traffic signals allocate a predetermined time to each road.
- They may cause unnecessary waiting when traffic density changes.
- A Smart Traffic Signal Controller adjusts signal timing according to traffic conditions.
- Fuzzy Logic is used to make intelligent decisions based on traffic density.
- Python is used to implement and simulate the proposed system.

Aim: To improve traffic flow and reduce unnecessary waiting time.

PROBLEM STATEMENT

- Increasing vehicles cause traffic congestion at intersections.
- Fixed-time signals cannot respond effectively to changing traffic conditions.
- Roads with fewer vehicles may receive unnecessary green time.
- Roads with heavy traffic may experience long queues.
- Traffic delays increase fuel consumption and air pollution.

Proposed Solution: Develop a smart traffic signal controller that uses traffic density and fuzzy logic to determine suitable green signal timing.

OBJECTIVES

- To develop a smart traffic signal control system using Python.
- To estimate traffic conditions using vehicle density.
- To apply fuzzy logic for intelligent decision-making.
- To assign green signal time according to traffic demand.
- To reduce unnecessary waiting time at intersections.
- To improve traffic flow and intersection efficiency.
- To demonstrate the system through computer simulation.

SYSTEM DESIGN

The proposed system consists of the following components:

- Input: Traffic density or number of vehicles on each road.
- Fuzzification: Converts numerical inputs into fuzzy categories.
- Rule Base: Contains predefined fuzzy IF–THEN rules.
- Inference Engine: Evaluates the rules and determines the traffic condition.
- Defuzzification: Converts fuzzy output into a numerical green time.
- Output: Displays the recommended green signal duration.

System Flow:

Traffic Input → Fuzzification → Rule Evaluation → Defuzzification → Green Signal Timing

WORKING PRINCIPLE

- The system receives traffic density values for different roads.
- Each road is classified according to its traffic condition.
- Fuzzy logic evaluates the density using predefined rules.
- The system calculates a suitable green signal duration.
- The road with greater traffic demand can receive a longer green time.
- The controller updates the signal timing according to the evaluated conditions.

Example: A road with heavy traffic may receive more green time than a road with light traffic, subject to minimum and maximum timing limits.

FUZZY LOGIC RULES

The system uses three traffic-density categories:

- Low Traffic: Few vehicles on the road.
- Medium Traffic: A moderate number of vehicles.
- High Traffic: A large number of vehicles.

Sample IF–THEN Rules

- IF traffic density is LOW, THEN green time is SHORT.
- IF traffic density is MEDIUM, THEN green time is MODERATE.
- IF traffic density is HIGH, THEN green time is LONG.
- IF traffic density is VERY HIGH, THEN green time is VERY LONG.
- IF traffic density increases, THEN green time may increase within defined limits.
- These rules help the controller respond to different traffic conditions.

IMPLEMENTATION

Programming Language: Python

Implementation Steps:

- Define traffic density inputs.
- Create fuzzy membership categories.
- Define fuzzy IF–THEN rules.
- Evaluate traffic conditions.
- Calculate the recommended green signal duration.
- Display the results for each road.

Technologies Used:

- Python 3
- Fuzzy Logic concepts
- Conditional statements and functions
- Numerical calculations
- Console-based simulation

The program demonstrates how traffic information can be converted into suitable signal timing.

RESULTS AND OUTPUT

- The simulation demonstrates that green signal timing can change according to traffic density.

Traffic Condition	Expected Green Time
Low Traffic	Short
Medium Traffic	Moderate
High Traffic	Long
Very High Traffic	Very Long

Observations:

- Signal timing responds to changes in traffic demand.
- Heavy traffic can receive additional green time.
- Light traffic can avoid unnecessarily long green phases.
- The simulation demonstrates the basic working of an adaptive traffic signal.

ANALYSIS AND DISCUSSION

Advantages:

- Flexible signal timing.
- Better use of available green time.
- Potential reduction in unnecessary waiting.
- Simple and understandable rule-based logic.
- Easy to modify and extend using Python.

Limitations:

- Results depend on the quality of traffic input data.
- Incorrect rules may produce inefficient signal timings.
- The basic simulation does not represent all real-world traffic conditions.
- Emergency vehicles and pedestrian crossing requirements need additional logic.

APPLICATIONS AND FUTURE SCOPE

Applications:

- Urban road intersections.
- Smart city traffic management.
- Traffic simulation and academic projects.
- Adaptive signal timing research.

Future Improvements:

- Use cameras or sensors to count vehicles.
- Integrate real-time traffic data.
- Add pedestrian crossing and emergency vehicle priority.
- Coordinate multiple intersections.
- Compare fuzzy logic with other adaptive control methods.
- Test the system using realistic traffic simulation software.

CONCLUSION

- The Smart Traffic Signal Controller uses fuzzy logic to evaluate traffic conditions.
- Python provides a practical way to implement and simulate the system.
- The proposed approach adjusts green signal timing according to traffic demand.
- It has the potential to reduce unnecessary waiting and improve traffic flow.
- Further testing with real traffic data is required before real-world deployment.

THANKS