

LAB	PRACTICALS
21	Part – A Create the following table using Query Mode and apply the specified Integrity Constraints. <pre>CREATE TABLE Student_Info (StudentID INT PRIMARY KEY IDENTITY(1,1), Enrollment_No VARCHAR(20) UNIQUE NOT NULL, Name VARCHAR(25) NOT NULL, CPI DECIMAL(5,2) CHECK (CPI <= 10), JoiningDate DATETIME NOT NULL DEFAULT GETDATE(), Bklog INT NOT NULL CHECK (Bklog >= 0), StateName VARCHAR(50) DEFAULT 'Gujarat');</pre> Create the following table using Query Mode and apply the specified Integrity Constraints. Part – B <pre>CREATE TABLE State (StateID INT PRIMARY KEY IDENTITY(1,1), StateName VARCHAR(20) UNIQUE NOT NULL);</pre> <pre>CREATE TABLE City (CityID INT PRIMARY KEY IDENTITY(1,1), CityName VARCHAR(20) UNIQUE NOT NULL, PinCode VARCHAR(10), StateID INT FOREIGN KEY REFERENCES State(StateID));</pre> Part – C Create the tables given in Part-A and Part-B using Design Mode and apply the specified constraints Note: Design Mode Constraints – Practice Yourself
22	Practice to implement Integrity Constraints using both Query Mode and Design Mode. Create the following table and apply the specified Integrity Constraints. Part – A <pre>CREATE TABLE ProductInventory (ProductID INT PRIMARY KEY IDENTITY(1,1), ProductName VARCHAR(100) NOT NULL, CatalogNumber VARCHAR(20) UNIQUE,</pre>

```
UnitPrice DECIMAL(10,2) NOT NULL CHECK (UnitPrice >= 0.50 AND
UnitPrice
<= 5000.00),
QuantityInStock INT NOT NULL CHECK (QuantityInStock >= 0),
IsActive BIT NOT NULL DEFAULT 1
);
```

Part – B

```
CREATE TABLE DepartmentData
(
    DeptID INT PRIMARY KEY,
    DeptName VARCHAR(50) NOT NULL UNIQUE
);
```

```
CREATE TABLE EmployeeData
(
    EmpID INT PRIMARY KEY,
    EmpName VARCHAR(50) NOT NULL,
    Salary DECIMAL(10,2) NOT NULL CHECK (Salary > 30000),
    DeptID INT FOREIGN KEY REFERENCES DepartmentData(DeptID)
);
```

Part – C

```
CREATE TABLE Members
(
    MemberID INT PRIMARY KEY IDENTITY(1,1),
    MemberName VARCHAR(50) NOT NULL,
    Email VARCHAR(100) NOT NULL UNIQUE,
    Phone VARCHAR(15) UNIQUE,
    JoinDate DATETIME NOT NULL DEFAULT GETDATE(),
    City VARCHAR(50) NOT NULL DEFAULT 'Rajkot'
);
```

```
CREATE TABLE Books
(
    BookID INT PRIMARY KEY IDENTITY(100,1),
    Title VARCHAR(100) NOT NULL,
    Author VARCHAR(50) NOT NULL,
    Category VARCHAR(30),
    Price DECIMAL(10,2) NOT NULL CHECK (Price > 0),
    Stock INT NOT NULL CHECK (Stock >= 0)
);
```

```
CREATE TABLE Issue_Return
```

```
(
```

```
    IssueID INT PRIMARY KEY IDENTITY(500,1),
```

```
    MemberID INT NOT NULL FOREIGN KEY REFERENCES Members(MemberID),
```

```
    BookID INT NOT NULL FOREIGN KEY REFERENCES Books(BookID),
```

```
    IssueDate DATE,
```

```
    ReturnDate DATE NOT NULL DEFAULT GETDATE()
```

```
);
```

Note: Design Mode Constraints – Practice Yourself