

Your grade: 100%

Your latest: 100% • Your highest: 100% • To pass you need at least 60%. We keep your highest score.

View item →

1. In Google Cloud, what is the minimum number of IP addresses that a VM instance needs?

1 / 1 point

☐ One: Only an internal IP address☐ Two: One internal and one external IP address☐ Three: One internal, one external and one alias IP address☒ Correct

That's correct! In Google Cloud, each virtual machine needs to have an internal IP address. The external IP address is optional; therefore, a VM instance only needs one IP address.

2. What are the three types of networks offered in Google Cloud?

1 / 1 point

☐ Zonal, regional, and global☐ Gigabit network, 10 gigabit network, and 100 gigabit network☐ Default network, auto network, and custom network☐ IPv4 unicast network, IPv4 multicast network, IPv6 network☒ Correct

The three network types offered by Google Cloud are: default, auto and custom. Each project starts with a default network. The auto-type network uses the same subnet IP range as the default type, with a network name other than default. A custom type allows you to specify the IP range of subnets.

3. What is one benefit of applying firewall rules by tag rather than by address?

1 / 1 point

☐ Tags help organizations track firewall billing.☐ Tags in network traffic help with network sniffing.☐ Tags on firewall rules control which ephemeral IP addresses VMs will receive.☐ When a VM is created with a matching tag, the firewall rules apply irrespective of the IP address it is assigned.☒ Correct

When a VM is created the ephemeral external IP address is assigned from a pool. There is no way to predict which address will be assigned, so there is no way to write a rule that will match that VM's IP address before it is assigned. Tags allow a symbolic assignment that does not depend on order in the IP addresses. It makes for simpler, more general, and easier to maintain, firewall rules.