Cheat Sheet: Web Development Using Flask

0:11 / 3:54

Package/Method	Basic Explain	Code Example
Flask	Used to instantiate an object of this type.	`from flask import Flask` `app = Flask(__name__)`

@app.route decorator	A decorator method used to signify URL-specific functions in a Flask application.	`@app.route('/')`
		`def hello_world():`
		`  return 'Hey, First Flask Application, is active!'`

GUICK states	Flask screen automatically return a 200 OK HTTP status code by default.	`@app.route('/')`
		`def hello_world():`
		`  return ('Hey, First Flask Application, is active!', 200)`

Error 400	**400** indicates an invalid request. This status code is commonly used when the request data is improper or the request cannot be satisfied. Here, **400** indicates the credentials provided in the request are incorrect. The response code **401** is sent to notify the request. **404** Error server is unable to find the resource, it returns a 404 status. **405** indicates that the requested operation is not supported.	`@app.route('/')`
		`def search_response():`
		`  query =`
		`request.args.get('q')`
		`  if not query:`
		`  return`
		`('Serious_Message!', 'Request parameter is wrong!'), 400`
		`  # Fetch the resource from the database`
		`  resource =`
		`fetch_from_database(query)`
		`  if resource:`
		`  return ('Message!', resource)`
		`  else:`
		`  return`
		`('Serious_Message!', 'Resource not found!'), 404`

Error 500	500 (Local Author) this is an error on the server.	`@app.errorhandler(500)`
		`def server_error(error):`
		`  return ('Message!', 'Something went wrong on the server!'), 500`

Author(s)

Joshua Padilla

Other Contributor(s)

Abhishek Gagneja, Eva Nuerk

Back to Unstacked

Like Follow Report an issue