Cheat Sheet: Using Built-in Agents in LangChain

I. Understanding built-in agents

LangChain provides built-in agents that enable LLMs to make decisions, use tools, access memory, and interact with external systems. These agents are typically structured for two ways:

Prebuilt Agent creation	Utilities/functions that bring tools and a model, to a use agent(s) for common use cases (for example, SQL, CSV, Pandas).
LangGraph Agents	Graph-structured agents with explicit reasoning steps and controllable logic.

II. Exploring core agent types

These agent types define the basic way an agent thinks, chooses tools, and performs actions. They are the foundational set used to create both prebuilt and graph agents.

Agent type	Description
`ZERO_SHOT_REACT_DESCRIPTION`	Uses ReAct reasoning (Reflect-Act-Observe) to choose tools dynamically, without any prior examples. Relies on tool descriptions.
`REACT_DOCSTORE`	Uses a ReAct agent with access to a docstore. Ideal for retrieving info from sources, like Wikipedia.
`SELF_ASK_WITH_SEARCH`	Breaks complex questions into simpler ones and answers using a search tool.
`CONVERSATIONAL_REACT_DESCRIPTION`	Maintains conversation history while reasoning and acting.
`CHAT_ZERO_SHOT_REACT_DESCRIPTION`	Like a zero-shot agent but optimized for chat models like GPT-4.
`CHAT_CONVERSATIONAL_REACT_DESCRIPTION`	Chat-based version of conversational ReAct agent.
`STRUCTURED_CHAT_ZERO_SHOT_REACT_DESCRIPTION`	Optimized for chat models and structured tools with multiple inputs.
`OPENAI_FUNCTIONS`	Designed to work with OpenAI's function calling schema.
`OPENAI_MULTI_FUNCTIONS`	Handles multiple tools using OpenAI's multi-function calls format.

III. Model compatibility

Some LLMs may not fully support structured output/parsing required by certain agents (for example, structured chat zero-shot react description). If the model returns ill-formatted or incomplete output, these models might fail with parsing or validation errors.

Description:

You can create an agent using initialize_agent, where you specify the agent type as its first/same according to the agent type. The agent then calls and performs reasoning before acting.

Code:

```
from langchain.agents import initialize_agent
from langchain.agents.agent_types import AgentType

agent = initialize_agent(tools,
                         llm,
                         agent=AgentType.ZERO_SHOT_REACT_DESCRIPTION,
                         verbose=True,
                         handle_parsing_errors=True)
```

#1. Prebuilt agents (task-specific utilities)

These utilities are the ones agent types that find the same tools make it easy to set up agents for specific types of data or tasks.

Function	Purpose	Agent type (Internally used by default)
`create_pandas_dataframe_agent()`	Natural language to DataFrame analysis and visualization	zero-shot-react-description
`create_csv_agent()`	Query CSV files conversationally	zero-shot-react-description
`create_sql_agent()`	Natural language SQL queries	zero-shot-react-description
`create_openai_functions_agent()`	Agent with OpenAI function calling tools	openai-functions
`create_tool_calling_agent()`	Variant agent that invokes structured tools	structured-chat-zero-shot-react-description

Description:

This code shows an example of create_pandas_dataframe_agent where you pass in the LLM, the dataframe you are working on, the agent_type, and verbose. You can see this is a function that performs analysis using natural language.

Code:

```
from langchain_experimental.agents import create_pandas_dataframe_agent

agent_executor = create_pandas_dataframe_agent(
    llm,
    df=df,
    agent_type="zero-shot-react-description",
    verbose=True
)
```

#. LangGraph agents

LangGraph supports building multi-step reasoning agents via a directed graph structure. These agents are ideal for advanced use cases where you would like to control over reasoning steps, looping, or conditional logic.

Description:

The create_react_agent(llm) by constructs a graph agent that performs tool use in a loop with reasoning at each step and for stopping conditions in mind.

Code:

```
from langgraph.prebuilt import create_react_agent
agent_exec = create_react_agent(model=llm, tools=[tool_list])
msgs = agent_exec.invoke({"messages": [("human", "Add the numbers 45, 55, 10")]})
```

Author(s)

IBM Skills Network Team

Mark as completed