Cheat Sheet: LangChain Expression Language (LCEL)

By Professor Maggie, Dr. Kabir Sarin, & 1 other

LangChain Expression Language (LCEL) is a Lite declarative method for assembling chains from modular components with minimal LangChain framework. Rather than years chiling step-by-step instructions, LCEL allows you to specify the outcome, enabling LangChain to optimize execution rules.

This cheat sheet provides an overview of LCEL's key capabilities, patterns, and orchestration strategies.

How let's explore some LCEL's capabilities and their related benefits:

Capability	Benefits
Run optimized parallel execution	Reduced latency and throughput, ensuring application performance by running components concurrently.
Use guaranteed async support	Enables smooth, non-blocking workflows that improve responsiveness and throughput in complex chains.
Stream outputs incrementally	Delivers immediate feedback to users, lowers perceived latency, and provides progressive through each stage of the pipeline.
Trace all steps automatically with LangSmith	Provides visibility into your chain's behavior to quickly debug, monitor performance, and improve reliability.
Call a Python function through a standard LCEL API	Simplifies integration and enables consistent behavior across workflows.
Deploy chains with LangServe	Accelerates the transition from development to production with minimal overhead.
Users can be used anywhere	Makes composability among components fortes Bing reduced duty pipelines.

Runnables

Each component conforms to this core, standardized Runnable interface.

Runnables represent any component from an inventory to a parsing output. The Runnable interface provides a standard and method (.invoke(), .batch(), .stream()) that all components implement, making them interoperable. The following table lists some runnable types, provides a brief description of the runnable type, and lists one example use case.

Runnable type	Description	Example use case
ChatModel	Interfaces with LLM APIs for a fast	Generate conversational responses.
PromptTemplate	Creates formatted prompts from variables	Prepare structured inputs for LLMs.
OutputParser	Converts raw outputs to structured data	Extract structured data from LLM responses.
RunnableLambda	Wraps custom Python functions	Implement custom business logic.
RunnableSequence	Chains multiple Runnables together	Create multi-step processing pipelines.

Next, learn about using runnable chains.

Runnable chains: Use cases, components, and workflows

You can build runnable chains by assembling components from LangChain's standardized Runnable interface. Each component exposes its output/input data for the next component, creating a workflow.

Next, review some runnable chain use cases, their components, and their workflow summaries.

Use cases	Components	Workflow summary
Simple question answering	PromptTemplate → ChatModel → StrOutputParser	Format a question, generate a response, and extract response.
Retrieval-augmented generation (RAG)	Retriever → PromptTemplate → ChatModel → OutputParser	Find relevant documents, combine with prompt, generate response
Function calling	PromptTemplate → ChatModel → Tool	Format prompt, generate function call, parse function parameters, execute function.
Structured output	PromptTemplate → ChatModel → .bind(OutputParser	Format prompt, generate response, parse to JSON object

LCEL function reference

LCEL provides a rich set of functions to create, compose, and configure Runnables. This reference section categorizes LCEL functions into factory operations, composition techniques, data manipulation, advanced patterns, configuration tools, and streaming/batching support. Each function reference how you to use it and control your chains. It's important to note that functions that begin with the prefix runna.asynchronous functions.

Basic operations

Function	Description	Usage
.invoke() / .ainvoke()	Executes a Runnable with a single input	Process one input and get one output
.batch() / .abatch()	Process multiple inputs efficiently (in parallel)	Run the same operation on multiple inputs at once
.stream() / .astream()	Returns incremental results as they're generated	Show partial responses as they're created

Composition patterns

Function	Description	Usage
RunnableSequence or	Create a sequence of Runnables	Chain components where output of one becomes input for the next
RunnableParallel	Executes multiple Runnables with the same input, concurrently	Process the same input in different ways simultaneously
RunnableLambda	Converts Python functions into Runnables	Add custom logic within a chain

Data manipulation patterns

Function	Description	Usage
RunnablePassthrough.assign()	Add new fields to the input dictionary	Augment input with additional data without discarding the original input
RunnablePassthrough()	Returns input unchanged	Include the original input as part of the output
.pick()	Selects specific keys from the dictionary output	Filter output to only needed fields

Advanced patterns

Function	Description	Usage
.bind()	Set default values for parameters	Fix common parameters while leaving others configurable
.with_fallbacks()	Try alternative Runnables if the primary fails	Handle errors by providing backup components
.with_retry()	Add automatic retry capability	Retry operations on failure for example Network issues

Configuration

Function	Description	Usage
.configurable()	Create runtime-reconfigurable	Reuse .bind(), .batch(), .stream() methods with settings that are common, Define runtime configurations
.with_config()	Create Runnables with default configurations	Apply the same configurations to all invocations automatically

Streaming and batching

Function	Description	Usage
.astream_events()	Detailed stream of execution events	Handle the intricate execution of complex chains with intermediate steps
.batch_as_completed() / .abatch_as_completed()	Process inputs in parallel, return as completed	Start processing results as soon as they're available

Next, explore some recommended approaches to orchestration.

Recommended approaches for orchestration

When building LLM applications, you can choose from a hierarchical method based on the complexity of your use case. The following table provides some guidance for when to use a direct call, LCEL, or LangGraph.

Use case	When to use	Recommended tool
Simple (direct call)	• You need to generate one focus a prompt • You're testing or debugging upon a feature is being verified	SDK directly
Simple chains	• You need a straightforward pipeline of components, for example, formatter → LLM → output → Save retrieval • Your application can benefit from parallelized execution and streaming • Your application has a clear, linear flow with minimal branching	LCEL
Complex logic with branching	• Your application requires complex state management • Your application requires conditional flows, loops, or cycles • You are implementing truly multi-agent systems that interact with each other	LangGraph

Author(s)

IBM Skills Network Team

Mark as completed