Tools, Agents, and Function Calling in LangChain

By IBM Skills Network Team, Data Science & Generative AI

0:18 / 10:18

Learning Objectives

By the end of this reading, you will be able to:

- Describe how to define tools and write effective docstrings in LangChain, including how LLMs generate tool calls from function signatures and descriptions.
- Differentiate between tool calling and function calling, and explain how agents utilize tools, memory, and actions to interact with external systems.

This reading explains how large language models (LLMs) interact with external tools through structured "tool calling" or "function calling." It explores key components of tools in LangChain, how agents make decisions using LLMs, and the role of memory in maintaining context. Additionally, it introduces LangGraph as a comprehensive framework for building complex agents, set it and try understanding what each term in LangChain.

Tools

Tools are essentially functions made available to LLMs. For example, a weather tool could be a Python or a JavaScript function with parameters and a description that tells the LLM when it's useful.

A tool in LangChain has several important components that how its schema:

- **Name:** Human-readable for the tool.
- **Description:** Clear explanation of the tool's purpose.
- **Parameters:** The inputs the tool expects to do its function correctly.

This schema enables the LLM to understand when and how to use the tool effectively.

Tool calling

Contrary to the term, in tool calling, LLMs do not execute tools or functions directly. Instead, they generate a structured representation indicating which tool to use and with what parameters.

When you pose a question to the LLM that requires external information or computation, the model evaluates the available tools based on their names and descriptions. If it identifies a relevant tool, the model generates a structured output (typically formatted as a JSON object) that specifies the tool's name and appropriate parameter values. This LLM-generated output is then executed by the framework.

Conversational system then integrates this structured output, executes the actual functions or API call, and returns the result. This result is subsequently fed back to the LLM, which then formulates a comprehensive response.

Here's the workflow and option simplified into:

- Define a weather tool and a question like: "What's the weather like in NY?"
- The model makes a tool call generation and outputs a structured tool call with parameter values e.g., `{"location": "NY"}`.
- Extract the tool name, execute the actual weather checking function, and obtain the weather details.
- Pass the output back to the model to let it generate a complete final answer using the real-time data.

Function calling vs. tool calling

Function calling and tool calling refer to essentially the same concept, with different terminology:

- **Function calling** is the terminology coined by OpenAI's function API documentation.
- **Tool calling** is a more general term used by many models & providers, including Anthropic, and broadly in frameworks like LangChain.

Both terms describe the capability of enabling an LLM to output specific external functions to be executed with structured parameters.

The concepts, workflows, and implementations are functionally identical—the difference is primarily in evolving convention rather than technical distinction.

Tools in LangChain

Tools are utilities designed to be called by a model: their inputs are structured in a way that models can generate, and their outputs are designed to be passed back to models. They help models perform specific actions such as searching the web, querying databases, or executing code.

A **toolkit** is a collection of related tools designed to work together for a common purpose or integration.

Steps to initialize and use tools

LangChain provides a wide array of built-in tools and can be easily:

1. **Using Built-in Tools:** LangChain offers a variety of built-in tools for common tasks. For example, the `WikipediaQueryRun` tool allows you to search Wikipedia.
2. **Loading Tools with Load_tools:** LangChain provides a load_tools function to load multiple tools conveniently. This function can be used to load tools like wikipedia, serpapi, llm-math, etc.
3. **Creating Custom Tools:** You can define your own tools using the `Tool` class or the `@tool` decorator. This allows you to integrate any function or API as a tool for the agent.
4. **Tools as OpenAI Functions:** LangChain tools can be converted into OpenAI functions using the `convert_to_openai_function` utility. This allows you to use LangChain tools with OpenAI's function-calling API, which can be useful for integrating with OpenAI models. You can also bind OpenAI-formatted tools directly to compatible LangChain chat models using the `bind_tools()` method.

LangChain supports a wide range of pre-built tools and third-party tools. These allow LLMs to interact with real-world data sources, APIs, and services. Some popular categories include:

- **Wikipedia:** Search and retrieve information from Wikipedia articles.
- **Search engines:** Integrate with search engines like Bing, Google, and DuckDuckGo to fetch real-time search results.
- **APIs:** Access various APIs for tasks like weather data retrieval, financial data analysis, etc.

and many more!

Agents

Agents are decision-making systems powered by LLMs that can reason, use tools, access memory, and take actions to complete tasks. Unlike a standalone LLM that only generates text, an agent figures out how to respond, with it can call external tools, remember past interactions, and plan multi-step workflows.

An **agent** in LangChain is the framework component that drives the high-level logic. Basically, it encapsulates the LLM itself along with supporting components like tools, memory, and an execution framework. In essence, tool-calling allows agents to be more reliable and capable by connecting them to the real world, while frameworks like LangChain and LangGraph provide the infrastructure to manage the entire process.

Architecture of an agent in LangChain

The following image illustrates the architecture of an **Agent** in LangChain, explains where an LLM is incorporated to make decisions, use tools, access memory, and interact with the external world.

Reference: Overview of LLM-based agents [1]

Let's discuss all the components in the architecture of an Agent in LangChain.

1. AI Agent

This is the core intelligence unit. It includes LLM, tools, memory, and logic to take actions. The agent is responsible for processing inputs, planning and figuring out how to respond, and act with tool. Each by taking actions when needed.

2. Large Language Model (LLM)

All the core reflects agent, the LLM interprets the input and determines what to do next. It may decide to:

- Recall something from memory (via the retrieval-augmented generation or "RAG").
- Use a tool.
- Directly generate a response.

3. Tool(s)

As explained earlier, they are functions or external capabilities that a agent can use. The LLM generates structured requests specifying the function to call and what parameters. The tool is then executed outside the model, and the result is returned.

4. Memory

Memory allows the agent to store and retrieve useful information, enabling long-term context and personalized interactions. It could include:

- Short-term or RAM data
- Structured storage like SQL
- Semantic memory or vector DBs (e.g., for document search)

5. A Plan

When the LLM decides a tool needs to be used, it outputs a structured "action," not a full. Then executed by the system. The outcome of this action is often observation the user or used in further reasoning steps.

6. Connections to the external world

The World represents everything outside the Al agent — the file, internet, APIs, physical devices, etc. The agent can interact with these systems through tools, bridging the gap between this LLM and real-world applications.

Example

Let's see an example of the flow:

1. User asks:

- "What is the weather in New York?"
- The input is received by the Al agent. This is a natural language query requiring real-time information that the LLM doesn't by itself have.

2. LLM processes the query and identifies the need for a tool:

- The LLM understands that it doesn't have real-time weather data and determines that a **weather tool** (e.g., an API) should be used. It prepares a **structured tool call**, specifying the tool name and required parameters (e.g., `location = "New York"`).

3. Tool is invoked as an action:

- The agent passes the structured request to the external weather tool. The tool is executed, reaching out to a weather API to fetch the latest weather for New York. This is the "action" step, where the LLM's plans are put into motion.

4. Memory may be referenced or updated:

- If the user has talked about weather before, the agent might reference this prior context from **memory** to personalize its response. Also, this interaction can also be updated within the new information for future reference.

5. LLM receives tool output and generates a response:

- Once the tool returns the result (e.g., "72°F, sunny with a slight breeze"), this LLM takes this output and uses it to formulate a natural, human-like response.

6. Agent responds and completes the task using real-world data:

- "It's currently 72 degrees and sunny in New York City."
- The task is now complete and the LLM's processing capability and external world data accessed are finished.

Agents in LangChain

LangChain offers several methods to create and utilize agents:

1. **Using Built-in AgentTypes:** LangChain offers predefined agent types such as zero-shot-react-description and chat-zero-shot-react-description. These are useful for simple reasoning tasks where the model decides which tool to use based on the input and tool descriptions.
2. **Creating agents with OpenAI Functions:** LangChain supports agents that use OpenAI's function-calling capabilities. You can create an agent using create_openai_functions_agent, which provides a way to interact with structured inputs in a safer and predictable way.
3. **Building agents with LangGraph:** LangGraph is a framework included on library that provides more flexibility and control. Using the high-level create_react_agent method, you can create agents capable of complex reasoning, action planning, memory integration, and real-time interacting.
4. **Executing agents with AgentExecutor:** Agents are executed using AgentExecutor, which manages the loop of calling the agent, executing the chosen tools, and passing the results back to the agent until the task is ready. This ensures the agent can dynamically react to intermediate results during its reasoning process.
5. **Adding memory:** To keep components like Memory Open, agents can maintain context across multiple interactions. This allows for personalized and context-aware responses, where an agent can remember things like user preferences, past questions, or conversation history.

Summary

In this reading, you learned about:

1. **Tool calling fundamentals:** That LLMs (e.g., OpenAI) do not execute tools directly but instead output structured requests (name + arguments) that your code runs with real parameters, enabling access to real-time or external data.
2. **Components of a tool:** A tool in LangChain includes a **name**, **description**, and **parameters**. This is how the LLM understands when and how to use each tool effectively.
3. **Agents vs. tools:** Agents are reasoning systems powered by LLMs that can make decisions, call tools, access memory, and take actions, enabling dynamic task completion beyond text generation.
4. **Workflow of tool invocation:** When a question requires external data, the LLM outputs a structured tool call. The external system runs the function, retrieves results, and feeds them back to the LLM for a complete answer.
5. **Frameworks (e.g., LangChain):** These libraries provide tools, memory, and agent orchestration. They're powerful technologies, but building "tool calling" in LangChain and other frameworks.

Author(s)

IBM Skills Network Team

Mark as completed