

Back

Quiz: Access Control and Security in Kubernetes and Google Kubernetes Engine

8/100

Your grade: 75%

Score 75% / Your highest 75% / To pass you need at least 75% (Minimum possible score)

Submit

1 / 1 (100%)

1. In a Kubernetes pod, which layer of control do containerized processes use to communicate with the Kubernetes control plane?

☐ A Kubernetes control plane service.

☐ A Google Cloud Service account.

☐ A Kubernetes Service account.

☐ An init container.

☒ None work.

This is the correct answer because Kubernetes Service Accounts are specifically designed to provide an identity for processes running in a pod, allowing them to authenticate to the Kubernetes API server.

2 / 1 (100%)

2. You need to implement access controls to grant your admin user the ability to view details about production clusters and applications, and to fully manage and delete resources from your GKE cluster environments. Which account configuration is best suited for this granular control?

☐ Kubernetes RBAC.

☐ Roles.

☐ IAM.

☐ OAuth.

☒ None work.

This is the correct answer because Kubernetes RBAC allows the fine-grained control of permissions within a cluster, making it possible to grant your admin user only access to production resources and not management rights over test resources.

3 / 1 (100%)

3. Which tool identity is a Kubernetes pod that helps the pod determine what host Google Cloud services?

☐ Google Kubernetes Engine and IAM.

☐ Kubernetes service accounts and IAM service accounts.

☐ Kubernetes and IAM.

☐ Google Compute Engine and IAM.

☒ The agent.

This is the correct answer because the Cloud Identity has a username scope that the pod can request to "authenticate".

4 / 1 (100%)

4. How are you are that control access to control security? Choose all responses that are correct (2 correct responses).

☐ Limit access to Google Cloud services and resources to prevent host access from accessing Cloud Storage objects.

☐ Limit access to some cluster capabilities, the granting certain privileges to processes, but not to all user privileges.

☒ None work.

This is the correct answer because you can grant specific capabilities needed by a process without giving it full root access, enhancing security.

☐ Configure audit logging to restrict all the logs to an external network backend for persistent event auditing.

☐ Enable Application, which uses security profiles to restrict individual program actions.

☒ None work.

This is the correct answer because you can use runtime Application profiles for hosts. Application profiles are additional layer of security by defining what system resources individual applications can access.

https://www.coursera.org/learn/deploying-secure-kubernetes-containers-in-production/assignment-submission/5PM7g/quiz-access-control-and-se... 1/1