



FLIP CHIP MODULES TEST DATA

TYPE: W 051

#001
RELAY DRIVER

TEST	CONDITIONS	MAXIMUM	MINIMUM
V_{CE} (SAT.)	2.5V IN, 100 MA I_C	≤ 200 MV	
LEAKAGE TO -15V	-0.3V IN	≤ 10 μ A	
INPUT CURRENT FROM GROUND	PIN V ONLY	2.7-3.4 MA	
RISE TTT	150 Ω TO -15V LOAD 100 CPS, FF INPUT	≤ 1.5 μ S	
FALL TTT	150 Ω TO -15V LOAD 100 CPS, FF INPUT	$\leq .75$ μ S	
OVERSHOOT	150 Ω , 8 MH IN SERIES. CHECK FOR OVERSHOOT ≤ 2 V.		

TECHNICAL INFORMATION

Instruction literature and technical bulletins are available on all digital products, if you would like to be added to our mailing list for this type of material or if you have any questions about the equipment you have purchased, please contact the nearest Digital Sales Office.

MAINTENANCE INFORMATION

Repair of printed circuitry should be done with a low voltage, fairly cool soldering iron to prevent damage to the transistors and keep the copper from lifting. Oscilloscopes used to troubleshoot a module or system should be grounded to prevent damaging transients.

ELEC. TESTER:



DATE: JAN 14 1966

DAW
12/17/6