



DECUS

PROGRAM LIBRARY

DECUS NO.	FOCAL8-120
TITLE	PFI - PRODUCT FORM OF THE INVERSE
AUTHOR	James H. Christensen
COMPANY	University of Oklahoma Norman, Oklahoma
DATE	October 19, 1970
SOURCE LANGUAGE	FOCAL

ATTENTION

This is a USER program. Other than requiring that it conform to submittal and review standards, no quality control has been imposed upon this program by DECUS.

The DECUS Program Library is a clearing house only; it does not generate or test programs. No warranty, express or implied, is made by the contributor, Digital Equipment Computer Users Society or Digital Equipment Corporation as to the accuracy or functioning of the program or related material, and no responsibility is assumed by these parties in connection therewith.

PFI - PRODUCT FORM OF THE INVERSE

DECUS Program Library Write-up

DECUS No. FOCAL8-120

INTRODUCTION

The product form of the Inverse (PFI) provides a means of inverting a matrix with minimal storage and computation requirements. It is based on the fact that, if we already have the inverse B of an $(n \times n)$ matrix A , we can obtain the inverse $\hat{B}$ of a new matrix $\hat{A}$, formed by replacing column r of A by a vector $\underline{x}$, with the formulae:

$$\left. \begin{aligned} \hat{b}_{ij} &= b_{ij} - \frac{y_i}{y_r} b_{rj}, \quad i \neq r \\ \hat{b}_{rj} &= b_{rj} / y_r \end{aligned} \right\} \quad j = 1, \dots, n,$$

where $\underline{y} = B\underline{x}$. Thus, to obtain A^{-1} , we begin by setting B equal to the identity matrix (or any non-singular matrix), and perform the PFI n times, once for each column of A . We note that this procedure requires storage only for the current value of B and the vector $\underline{y}$; the components of $\underline{x}$ are used only to compute a new $\underline{y}$ (in lines 2.2, 6.3 and 6.4). Note also that the subscripting algorithm $B(I, J) = B(I + N * (J - 1))$ requires few actual multiplications to evaluate the current subscript.

A typical encounter is shown, in which the matrix

$$B = \begin{bmatrix} 1 & 0 & -1 \\ .2 & -1 & 0 \\ 0 & .75 & -1 \end{bmatrix}^{-1}$$

is evaluated; note that a negative column number input gives a printout of the current B matrix. The second example obtains the inverse of

$$\begin{bmatrix} 1 & 0 & -1 \\ 1 & -1 & 0 \\ 0 & .05 & -1 \end{bmatrix}$$

by simply altering the first two columns, while the last example inverts

$$\begin{bmatrix} 1 & 0 & -1 \\ 1 & -1 & 0 \\ 0 & .9 & -1 \end{bmatrix}$$

by altering column 2 only. The ability to do this is especially useful when doing parametric studies or linear programming.

C FOCAL V3A

01.01C JAMES H. CHRISTENSEN

01.02C SCHOOL OF CHEM.ENG. & MATLS.SCI.

01.03C UNIV. OF OKLA.

01.04C 202 W. BOYD #23

01.05C NORMAN , OK. 73069

01.10 T '!!', "PROGRAM TO INVERT A MATRIX USING PRODUCT FORM", !

01.20 A "DIMENSION OF MATRIX" N

01.30 F I=1, N;S B(I)=0

01.35 F I=1, N;S B(I+N*I-N)=1

01.40 A "COLUMN" R; I (R) 1.5, 1.5; D 2.0; G 1.4

01.50 T '!!', "INVERSE IS:"

01.60 F I=1, N;T !;F J=1, N;T %7.06, " ", B(N*I-J-N+I)

01.70 T '!!'; G 1.4

02.10 F J=1, N;S Y(J)=0

02.20 S ISB=-N;F J=1, N;D 6.3

02.30 I (FABS(Y(R))-1.E-10) 6.2;S YR1=1/Y(R)

02.40 S ISB=-N;F J=1, N;S ISB=ISB+N;S BRJ=YR1*B(ISB+R);D 3.0

03.10 F I=1, N;S B(ISB+I)=B(ISB+I)-Y(I)*BRJ

03.20 S B(ISB+R)=BRJ

06.20 T !, "MATRIX IS SINGULAR", '!!';R

06.30 S ISB=ISB+N;A X;I (X)6.4, 6.5, 6.4

06.40 F I=1, N;S Y(I)=Y(I)+X*B(ISB+I)

06.50 RETURN

*,

*

PROGRAM TO INVERT A MATRIX USING PRODUCT FORM

DIMENSION OF MATRIX:3

COLUMN:1:1:.2:0

COLUMN:2:0:-1:.75

COLUMN:3:-1:0:-1

COLUMN:-1

INVERSE IS:

1.176471	-0.882353	-1.176471
0.235294	-1.176471	-0.235294
0.176471	-0.882353	-1.176471

COLUMN:1:1:1:0

COLUMN:2:0:-1:.05

COLUMN:-1

INVERSE IS:

1.052632	-0.052632	-1.052632
1.052632	-1.052632	-1.052632
0.052632	-0.052632	-1.052632

COLUMN:2:0:-1:.9

COLUMN:-1

INVERSE IS:

10.00000	-9.000000	-10.00000
10.00000	-10.00000	-10.00000
9.000000	-9.000000	-10.00000

COLUMN: ↑ P

FOCAL V4A

*W

