

Leetcode Solutions

SVR

August 27, 2025

Contents		21. Merge Two Sorted Lists	45
1. Two Sum	12	25. Reverse Nodes in k-Group	49
2. Add Two Numbers	15	26. Remove Duplicates From Sorted Array	52
3. Longest Substring Without Repeating Characters	18	27. Remove Element	55
4. Median Of Two Sorted Array	21	28. Find the Index of the First Occurrence in a String	58
6. Zigzag Conversion	24	36. Valid Sudoku	61
11. Container with most water	27	42. Trapping Rain Water	65
12. Integer to Roman	29	45. Jump Game II	68
13. Roman To Integer	33	48. Rotate Image	71
14. Longest Common Prefix	36	49. Group Anagrams	74
19. Remove Nth Node From End of List	39	54. Spiral Matrix	78
20. Valid Parentheses	42	55. Jump Game	81

56. Merge Intervals	84	121. Best Time To Buy And Sell Stock	124
57. Insert Interval	87	122. Best Time To Buy And Sell Stock II	126
58. Length of Last Word	90	125. Valid Palindrome	129
61. Rotate List	93	128. Longest Consecutive Sequence	132
68. Text Justification	96	134. Gas Station	135
71. Simplify Path	103	135. Candy	138
73. Set Matrix Zeroes	107	151. Reverse Words In A String	141
80. Remove Duplicates from Sorted Array II	110	167. Two Sum II - Input Array Is Sorted	144
86. Partition List	112	169 Majority Element	147
88. Merge Sorted Array	115	189 Rotate Array	149
100. Same Tree	118	202. Happy Number	152
101. Symmetric Tree	121	205. Isomorphic Strings	155

209. Minimum Size Subarray Sum	159
219. Contains Duplicate II	162
226. Invert Binary Tree	165
228. Summary Ranges	168
238. Product of Array Except Self	171
242. Valid Anagram	174
274. H-Index	176
283. Move Zeros	178
345. Reverse Vowels Of A String	180
392. Is Subsequence	182
394. Decode String	184
443. String Compression	188

Introduction

Following are my solutions for some leetcode problems. The solutions and code are primarily in C++ owing to the fact that I'm already using Python in my research, and C++ for the engineering part. However, C++ is something I'm trying to go deeper owing to the fact that I'm improving my ability to build low latency systems, which primarily use C/C++.

Template Script

Description

The following script is forked each time I want to locally work on a leetcode problem. The subsequent solutions in the later sections also have the functions present in this particular script in their scope. So this script also serves to provide an idea as to the functions, and what not, that are available. Note that the standard practice is to have these functions written in another file and have it included in the main script. However, I often tinker with these functions based on the problem at hand. Thus, the not-so-standard approach.

Template.cpp

```
1 // including header-files
2 #include <algorithm>
3 #include <bitset>
4 #include <climits>
5 #include <cstdint>
6 #include <iostream>
7 #include <limits>
8 #include <map>
9 #include <new>
10 #include <stdlib.h>
11 #include <unordered_map>
12 #include <vector>
13 #include <set>
14 #include <numeric>
15 #include <functional>
16
17
18 // hash-deinfes
19 #define PRINTSPACE std::cout << "\n\n\n" << std::endl;
20 #define PRINTLINE std::cout << "===== " << std::endl;
```

```

21
22 // borrowing from namespace std
23 using std::cout;
24 using std::endl;
25 using std::vector;
26 using std::string;
27 using std::unordered_map;
28 using std::map;
29 using std::format;
30 using std::deque;
31 using std::pair;
32 using std::min;
33 using std::max;
34
35 // vector printing function
36 template<typename T>
37 void fPrintVector(vector<T> input){
38     for(auto x: input) cout << x << ", ";
39     cout << endl;
40 }
41
42 template<typename T>
43 void fpv(vector<T> input){
44     for(auto x: input) cout << x << ", ";
45     cout << endl;
46 }
47
48 template<typename T>
49 void fPrintMatrix(vector<T> input){
50     for(auto x: input){
51         for(auto y: x){
52             cout << y << ", ";
53         }
54         cout << endl;
55     }

```

```

56 }
57
58 template<typename T, typename T1>
59 void fPrintHashmap(unordered_map<T, T1> input){
60     for(auto x: input){
61         cout << format("{}{} | ", x.first, x.second);
62     }
63     cout << endl;
64 }
65
66 struct TreeNode {
67     int val;
68     TreeNode *left;
69     TreeNode *right;
70     TreeNode() : val(0), left(nullptr), right(nullptr) {}
71     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
72     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
73 };
74
75
76 struct ListNode {
77     int val;
78     ListNode *next;
79     ListNode() : val(0), next(nullptr) {}
80     ListNode(int x) : val(x), next(nullptr) {}
81     ListNode(int x, ListNode *next) : val(x), next(next) {}
82 };
83
84 void fPrintBinaryTree(TreeNode* root){
85     // sending it back
86     if (root == nullptr) return;
87
88     // printing
89     PRINTLINE
90     cout << "root->val = " << root->val << endl;

```



```

91
92 // calling the children
93 fPrintBinaryTree(root->left);
94 fPrintBinaryTree(root->right);
95
96 // returning
97 return;
98
99 }
100
101 void fPrintLinkedList(string prefix,
102                      ListNode* root){
103     if (root == nullptr) return;
104     cout << prefix;
105     std::function<void(ListNode*)> runlinkedlist = [&runlinkedlist](ListNode* root){
106         if (root == nullptr) return;
107         cout << root->val << " -> ";
108         runlinkedlist(root->next);
109     };
110     runlinkedlist(root);
111     cout << "|" << endl;
112     return;
113 }
114
115 template<typename T>
116 void fPrintContainer(T input){
117     for(auto x: input) cout << x << ", ";
118     cout << endl;
119     return;
120 }
121
122 struct Timer
123 {
124     std::chrono::time_point<std::chrono::high_resolution_clock> startpoint;
125     std::chrono::time_point<std::chrono::high_resolution_clock> endpoint;

```

```

126 std::chrono::duration<long long, std::nano>          duration;
127
128 // constructor
129 Timer() {startpoint = std::chrono::high_resolution_clock::now();}
130 void start() {startpoint = std::chrono::high_resolution_clock::now();}
131 void stop() {endpoint = std::chrono::high_resolution_clock::now(); fetchtime();}
132
133 void fetchtime(){
134     duration = std::chrono::duration_cast<std::chrono::nanoseconds>(endpoint - startpoint);
135     cout << format("{} nanoseconds \n", duration.count());
136 }
137 void fetchtime(string stringarg){
138     duration = std::chrono::duration_cast<std::chrono::nanoseconds>(endpoint - startpoint);
139     cout << format("{} took {} nanoseconds \n", stringarg, duration.count());
140 }
141 void measure(){
142     auto temp = std::chrono::high_resolution_clock::now();
143     auto nsduration = std::chrono::duration_cast<std::chrono::nanoseconds>(temp - startpoint);
144     auto msduration = std::chrono::duration_cast<std::chrono::microseconds>(temp - startpoint);
145     auto sduration = std::chrono::duration_cast<std::chrono::seconds>(temp - startpoint);
146     cout << format("{} nanoseconds | {} microseconds | {} seconds \n",
147         nsduration.count(), msduration.count(), sduration.count());
148 }
149 ~Timer(){
150     measure();
151 }
152 };
153
154 // main-file =====
155 int main(){
156
157     // starting timer
158     Timer timer;
159
160     // input- configuration

```

```
161
162
163     // setup
164
165
166
167
168
169     // return
170     return(0);
171
172 }
```

1. Two Sum

Given an array of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`. You may assume that each input would have exactly one solution, and you may not use the same element twice. You can return the answer in any order.

Examples

1. Example 1:

- Input: `nums = [2,7,11,15]`, `target = 9`
- Output: `[0,1]`
- Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.

2. Example 2:

- Input: `nums = [3,2,4]`, `target = 6`
- Output: `[1,2]`

3. Example 3:

- Input: `nums = [3,3]`, `target = 6`
- Output: `[0,1]`

Constraints:

- $2 \leq \text{nums.length} \leq 10^4$

- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $-10^9 \leq \text{target} \leq 10^9$
- Only one valid answer exists.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {2, 7, 11, 15};
5     int target {9};
6
7     // setup
8     int complement {0};
9     unordered_map<int, int> number_to_index;
10    vector<int> finaloutput;
11
12    // filling the unordered_map
13    for(int i = 0; i < nums.size(); ++i){
14
15        // calculating complement
16        complement = target - nums[i];
17
18        // checking if complement is present in registry
19        if(number_to_index.find(complement) != number_to_index.end()) [[unlikely]]
20        {
21            finaloutput.push_back(number_to_index[complement]); // adding first index
22            finaloutput.push_back(i); // adding second index
23            break; // breaking out
24        }
25        else [[likely]]
```

```

26     {
27         // check if current element is present
28         if (number_to_index.find(nums[i]) == number_to_index.end()) [[likely]]
29         {
30             // adding the [number, index] pair to the hashmap
31             number_to_index[nums[i]] = i;
32         }
33         else [[unlikely]]
34         {
35             // we'll do nothing since the number and its index is already present
36             continue;
37         }
38     }
39 }
40
41 // printing the final output
42 for(const auto& x : finaloutput) {cout << x << ", ";} cout << endl;
43
44 // return
45 return(0);
46
47 }

```

2. Add Two Numbers

You are given two non-empty linked lists representing two non-negative integers. The digits are stored in reverse order, and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list. You may assume the two numbers do not contain any leading zero, except the number 0 itself.

Examples

1. Example 1:

- Input: $l1 = [2,4,3]$, $l2 = [5,6,4]$
- Output: $[7,0,8]$
- Explanation: $342 + 465 = 807$.

2. Example 2:

- Input: $l1 = [0]$, $l2 = [0]$
- Output: $[0]$

3. Example 3:

- Input: $l1 = [9,9,9,9,9,9,9]$, $l2 = [9,9,9,9]$
- Output: $[8,9,9,9,0,0,0,1]$

Constraints:

- The number of nodes in each linked list is in the range $[1, 100]$.

- $0 \leq \text{Node.val} \leq 9$
- It is guaranteed that the list represents a number that does not have leading zeros.

Code

```
1 int main(){
2
3     // input- configuration
4     ListNode* l1 = new ListNode(2);
5     l1->next = new ListNode(4);
6     l1->next->next = new ListNode(3);
7
8     ListNode* l2 = new ListNode(5);
9     l2->next = new ListNode(6);
10    l2->next->next = new ListNode(4);
11
12    // setup
13    ListNode* traveller_1 = l1;
14    ListNode* traveller_2 = l2;
15    ListNode* finalOutput = new ListNode(-1);
16    ListNode* traveller_fo = finalOutput;
17
18    int sum          {0};
19    int carry        {0};
20    int value_1      {0};
21    int value_2      {0};
22
23    // moving through the two nodes
24    while(traveller_1 != nullptr || traveller_2 != nullptr){
25
26        // adding the two numbers
27        value_1 = traveller_1 == nullptr ? 0 : traveller_1->val;
```



```

28     value_2 = traveller_2 == nullptr ? 0 : traveller_2->val;
29
30     // calculating sum
31     sum      = value_1 + value_2 + carry;
32     if (sum >= 10) [[unlikely]] {sum -= 10; carry = 1;}
33     else      [[likely]]      {carry = 0;}
34
35     // creating node
36     traveller_fo->next = new ListNode(sum);
37     traveller_fo      = traveller_fo->next;
38
39     // updating the two pointers
40     if(traveller_1 != nullptr) [[likely]] {traveller_1 = traveller_1->next;}
41     if(traveller_2 != nullptr) [[likely]] {traveller_2 = traveller_2->next;}
42 }
43
44 // creating a final node if carry is non-zero
45 if (carry == 1) [[unlikely]] {
46     traveller_fo->next = new ListNode(carry);
47 }
48
49 // printing the final output
50 traveller_fo = finalOutput->next;
51 cout << format("final-output = ");
52 while(traveller_fo != nullptr){
53     cout << traveller_fo->val << ", ";
54     traveller_fo = traveller_fo->next;
55 }
56 cout << "\n";
57
58 // return
59 return(0);
60
61 }

```

3. Longest Substring Without Repeating Characters

Given a string s , find the length of the longest substring without duplicate characters.

1. Example 1:

- Input: $s = \text{"abcabcbb"}$
- Output: 3
- Explanation: The answer is "abc", with the length of 3.

2. Example 2:

- Input: $s = \text{"bbbbbb"}$
- Output: 1
- Explanation: The answer is "b", with the length of 1.

3. Example 3:

- Input: $s = \text{"pwwkew"}$
- Output: 3
- Explanation: The answer is "wke", with the length of 3. Notice that the answer must be a substring, "pwke" is a subsequence and not a substring.

Code

```
1 int main(){
2
3     // input- configuration
4     string s {"tmmzuxt"};
5
6     // setup
7     unordered_map<char, int> histogram;
8     int p1 {0};
9     char curr;
10    int finaloutput {-1};
11    int temp_length {-1};
12
13    // going through the thing
14    for(int p2 = 0; p2<s.size(); ++p2){
15
16        // moving to another variable
17        curr = s[p2];
18
19        // checking if current character is in histogram
20        if (histogram.find(curr) == histogram.end()) [[unlikely]]
21        {
22            histogram[curr] = 1;
23        }
24        else [[likely]]
25        {
26            // checking if count is zero
27            if (histogram[curr] == 0)
28            {
29                histogram[curr] = 1;
30            }
31            else
32            {
33                // moving p1 until it arrives at first instance of curr
34                while(s[p1] != curr)
```

```

35     {
36         --histogram[s[p1]];
37         ++p1;
38     }
39     ++p1;
40     histogram[curr] = 1;
41 }
42 }
43
44 // calculating longest length
45 finaloutput = finaloutput > (p2-p1+1) ? finaloutput : (p2-p1+1);
46 }
47
48 // printing
49 cout << format("longest length = {} \n", finaloutput);
50
51 // return
52 return(0);
53 }

```

4. Median Of Two Sorted Array

Given two sorted arrays `nums1` and `nums2` of size `m` and `n` respectively, return the median of the two sorted arrays. The overall run time complexity should be $O(\log(m+n))$.

Examples

1. Example 1:

- Input: `nums1 = [1,3]`, `nums2 = [2]`
- Output: 2.00000
- Explanation: merged array = `[1,2,3]` and median is 2.

2. Example 2:

- Input: `nums1 = [1,2]`, `nums2 = [3,4]`
- Output: 2.50000
- Explanation: merged array = `[1,2,3,4]` and median is $(2 + 3) / 2 = 2.5$.

Constraints:

1. `nums1.length == m`
2. `nums2.length == n`
3. $0 \leq m \leq 1000$

4. $0 \leq n \leq 1000$
5. $1 \leq m + n \leq 2000$
6. $-10^6 \leq \text{nums1}[i], \text{nums2}[i] \leq 10^6$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums1 {1, 2};
5     vector<int> nums2 {3, 4};
6
7
8     // setup
9     vector<int>& first = nums1[0] <= nums2[0] ? nums1 : nums2;
10    vector<int>& second = nums1[0] > nums2[0] ? nums1 : nums2;
11    int left_first {0};
12    int right_first {static_cast<int>(first.size())-1};
13    int left_second {0};
14    int right_second {static_cast<int>(second.size())-1};
15    int left_value = first[left_first] < second[left_second] ? first[left_first] : second[left_second];
16    int right_value = first[right_first] > second[right_second] ? first[right_first] : second[right_second];
17    int numiterations {static_cast<int>((nums1.size() + nums2.size())/2)};
18
19
20    // running for a certain number of iterations
21    for(int i = 0; i<numiterations+1; ++i){
22
23        // updating left
24        if (first[left_first] < second[left_second]) {left_value = first[left_first]; ++left_first;}
25        else {left_value = second[left_second]; ++left_second;}
```

```
26     if (first[right_first] > second[right_second]) {right_value = first[right_first]; --right_first;}
27     else {right_value = second[right_second]; --right_second;}
28
29     // printing
30     cout << format("left-value = {}, right-value = {}\n", left_value, right_value);
31 }
32
33 cout << format("median = {}\n", static_cast<double>(left_value + right_value)/2.0);
34
35
36
37 // return
38 return(0);
39
40 }
```

6. Zigzag Conversion

The string "PAYPALISHIRING" is written in a zigzag pattern on a given number of rows like this: (you may want to display this pattern in a fixed font for better legibility)

P	-	A	-	H	-	N
A	P	L	S	I	I	G
Y	-	I	-	R	-	-

And then read line by line: "PAHNAPLSIIGYIR"

Examples

1. Example 1:

- Input: s = "PAYPALISHIRING", numRows = 3
- Output: "PAHNAPLSIIGYIR"

2. Example 2:

- Input: s = "PAYPALISHIRING", numRows = 4
- Output: "PINALSIGYAHRPI"

3. Example 3:

- Input: s = "A", numRows = 1
- Output: "A"

Constraints:

1. $1 \leq s.length \leq 1000$
2. s consists of English letters (lower-case and upper-case), ',' and '.'.
3. $1 \leq numRows \leq 1000$

Code

```
1 int main(){
2
3     // input- configuration
4     string s {"PAYPALISHIRING"};
5     int numRows {4};
6
7     // trivial case
8     if (numRows == 1) {cout << format("finaloutput = {}\n", s); return 0;}
9
10    // setup
11    int modlength {2*numRows-2};
12    int numblocks {(static_cast<int>(s.size())+ modlength-1)/modlength};
13    int sourceindex {-1};
14    string finaloutput;
15
16    // going through the thing
17    for(int row = 0; row < numRows; ++row){
18        for(int i = 0; i<numblocks; ++i){
19
20            // first column of each block
21            sourceindex = row + modlength * i;
22            if (sourceindex<s.size()) {finaloutput += s[sourceindex];}
23
24        }
```

```
24     // continuing in case of boundary rows
25     if (row == 0 || row == numRows-1) {continue;}
26
27     // taking care of the case where non-boundary rows
28     sourceindex = modlength - row + modlength*i;
29     if (sourceindex < s.size())      {finaloutput += s[sourceindex];}
30 }
31 }
32
33 // printing the final output
34 cout << format("final-output = {}\n", finaloutput);
35
36
37 // return
38 return(0);
39
40 }
```

11. Container with most water

You are given an integer array `height` of length `n`. There are `n` vertical lines drawn such that the two endpoints of the `i`th line are (`i`, 0) and (`i`, `height[i]`). Find two lines that together with the x-axis form a container, such that the container contains the most water. Return the maximum amount of water a container can store. Notice that you may not slant the container.

Examples

1. Example 1:

- Input: `height = [1,8,6,2,5,4,8,3,7]`
- Output: 49
- Explanation: The above vertical lines are represented by array `[1,8,6,2,5,4,8,3,7]`. In this case, the max area of water (blue section) the container can contain is 49.

2. Example 2:

- Input: `height = [1,1]`
- Output: 1

Constraints

- `n == height.length`
- $2 \leq n \leq 10^5$
- $0 \leq \text{height}[i] \leq 10^4$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> height {1,8,6,2,5,4,8,3,7};
5
6     // setup
7     int left      {0};
8     int right     {static_cast<int>(height.size()-1)};
9     int maxvolume {-1};
10    int currvolume {-1};
11
12    // two-pointer approach
13    while(left < right){
14
15        // calculating volumes
16        currvolume = (right - left) * std::min(height[left], height[right]);
17        maxvolume  = maxvolume > currvolume ? maxvolume : currvolume;
18
19        // adjusting left and right based on volume
20        if (height[left] < height[right]) {++left;}
21        else                               {--right;}
22    }
23
24    // printing
25    cout << format("maxvolume = {}\n", maxvolume);
26
27    // return
28    return(0);
29
30 }
```

12. Integer to Roman

Roman numerals are formed by appending the conversions of decimal place values from highest to lowest. Converting a decimal place value into a Roman numeral has the following rules:

- If the value does not start with 4 or 9, select the symbol of the maximal value that can be subtracted from the input, append that symbol to the result, subtract its value, and convert the remainder to a Roman numeral.
- If the value starts with 4 or 9 use the subtractive form representing one symbol subtracted from the following symbol, for example, 4 is 1 (I) less than 5 (V): IV and 9 is 1 (I) less than 10 (X): IX. Only the following subtractive forms are used: 4 (IV), 9 (IX), 40 (XL), 90 (XC), 400 (CD) and 900 (CM).
- Only powers of 10 (I, X, C, M) can be appended consecutively at most 3 times to represent multiples of 10. You cannot append 5 (V), 50 (L), or 500 (D) multiple times. If you need to append a symbol 4 times use the subtractive form.

Given an integer, convert it to a Roman numeral.

Examples

1. Example 1

- Input: num = 3749
- Output: "MMMDCCXLIX"
- Explanation:
 - 3000 = MMM as 1000 (M) + 1000 (M) + 1000 (M)
 - 700 = DCC as 500 (D) + 100 (C) + 100 (C)
 - 40 = XL as 10 (X) less of 50 (L)
 - 9 = IX as 1 (I) less of 10 (X)

- Note: 49 is not 1 (I) less of 50 (L) because the conversion is based on decimal places

2. Example 2:

- Input: num = 58
- Output: "LVIII"
- Explanation:
 - 50 = L
 - 8 = VIII

3. Example 3:

- Input: num = 1994
- Output: "MCMXCIV"
- Explanation:
 - 1000 = M
 - 900 = CM
 - 90 = XC
 - 4 = IV

Constraints

- $1 \leq \text{num} \leq 3999$

Code

```

1  int main(){
2
3      // input- configuration
4      int num    {1994};
5
6      // setup
7      vector<pair<int, string>> numToString {
8          {1, "I"},
9          {4, "IV"},
10         {5, "V"},
11         {9, "IX"},
12         {10, "X"},
13         {40, "XL"},
14         {50, "L"},
15         {90, "XC"},
16         {100, "C"},
17         {400, "CD"},
18         {500, "D"},
19         {900, "CM"},
20         {1000, "M"}
21     };
22     string finaloutput;
23     int    count;
24     auto mulstring = [](const int& count,
25                         const string& inputstring,
26                         string& finaloutput){
27         if (count == 0) {return;}
28         for(int i = 0; i<count; ++i){finaloutput += inputstring;}
29     };
30
31     // going through the hashmap from the end
32     for(int i = numToString.size()-1; i>=0; --i){
33
34         // number-string pairs
35         // variable to hold the final output
36         // variable that will hold the counts
37
38         // lambda-function for int * string

```

```
34 // calculating count
35 count = num / numToString[i].first;
36 num    = num - numToString[i].first*count;
37
38 // adding to final output
39 mulstring(count, numToString[i].second, finaloutput);
40 }
41
42 // printing the final-output
43 cout << format("finaloutput = {}\n", finaloutput);
44
45 // return
46 return(0);
47
48 }
```

13. Roman To Integer

Roman numerals are represented by seven different symbols: I(1), V(5), X(10), L(50), C(100), D(500) and M(1000). For example, 2 is written as II in Roman numeral, just two ones added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II. Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

1. I can be placed before V (5) and X (10) to make 4 and 9.
2. X can be placed before L (50) and C (100) to make 40 and 90.
3. C can be placed before D (500) and M (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Examples

1. Example 1

- Input: s = "III"
- Output: 3
- Explanation: III = 3.

2. Example 2

- Input: s = "LVIII"
- Output: 58

- Explanation: L = 50, V = 5, III = 3.

3. Example 3

- Input: s = "MCMXCIV"
- Output: 1994
- Explanation: M = 1000, CM = 900, XC = 90 and IV = 4.

Constraints

1. $1 \leq s.length \leq 15$
2. s contains only the characters ('I', 'V', 'X', 'L', 'C', 'D', 'M').
3. It is guaranteed that s is a valid roman numeral in the range [1, 3999].

Code

```
1 int main(){
2
3     // input- configuration
4     string s {"MCMXCIV"};
5
6     // setup
7     int finaloutput {0};
8     unordered_map<char, int> charToInt {{'I', 1},
9                                           {'V', 5},
10                                          {'X', 10},
11                                          {'L', 50},
12                                          {'C', 100},
```

```
13         {'D', 500},
14         {'M', 1000}};
15
16 // going through the string
17 for(int i = 0; i<s.size(); ++i){
18     if ((i+1)<s.size() && charToInt[s[i]] < charToInt[s[i+1]]) {finaloutput -= charToInt[s[i]];}
19     else {finaloutput += charToInt[s[i]];}
20 }
21
22 // printing the final output
23 cout << format("finaloutput = {}\n", finaloutput);
24
25 // return
26 return(0);
27
28 }
```

14. Longest Common Prefix

Write a function to find the longest common prefix string amongst an array of strings. If there is no common prefix, return an empty string "".

Examples

1. Example 1:

- Input: `strs = ["flower", "flow", "flight"]`
- Output: `"fl"`

2. Example 2:

- Input: `strs = ["dog", "racecar", "car"]`
- Output: `""`
- Explanation: There is no common prefix among the input strings.

Constraints:

- $1 \leq \text{strs.length} \leq 200$
- $0 \leq \text{strs}[i].\text{length} \leq 200$
- `strs[i]` consists of only lowercase English letters if it is non-empty.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<string> strs {
5         "flower",
6         "flow",
7         "flight"
8     };
9
10    // setup
11    int p          {0};                // index-pointer for boundary
12    int runcondition {true};           // breaking condition
13    string prefix;
14
15    // going through the vector
16    while(runcondition){
17
18        // breaking if it doesn't meet first words length
19        if (p >= strs[0].size())      {++p; runcondition = false; break;}
20
21        // checking if this candidate
22        for(int i = 1; i<strs.size(); ++i){
23
24            // checking if valid
25            if (p >= strs[i].size())   {runcondition = false; break;}
26
27            // checking if same
28            if (strs[i][p] != strs[0][p]) {runcondition = false; break;}
29        }
30
31        // updating p
32        ++p;
33    }
```

```
34
35 // subsetting and printing the prefix
36 prefix = string(strs[0].begin(), strs[0].begin()+p-1);
37 cout << format("finaloutput = {}\n", prefix);
38
39 // return
40 return(0);
41
42 }
```

19. Remove Nth Node From End of List

Given the head of a linked list, remove the nth node from the end of the list and return its head.

Examples

1. **Example 1:**

- Input: head = [1,2,3,4,5], n = 2
- Output: [1,2,3,5]

2. **Example 2:**

- Input: head = [1], n = 1
- Output: []

3. **Example 3:**

- Input: head = [1,2], n = 1
- Output: [1]

Constraints

- The number of nodes in the list is sz.
- $1 \leq sz \leq 30$
- $0 \leq \text{Node.val} \leq 100$
- $1 \leq n \leq sz$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     ListNode* head          = new ListNode(1);
8     head->next               = new ListNode(2);
9     head->next->next          = new ListNode(3);
10    head->next->next->next      = new ListNode(4);
11    head->next->next->next->next = new ListNode(5);
12    auto n {2};
13
14    // trivial case
15    if (!head) {cout << format("final-output = "); fPrintLinkedList(head); cout << endl;}
16
17    // setup
18    auto nodecounter {0};
19    auto prehead      {new ListNode};
20
21    prehead->next      = head;
22    ListNode* traveller = head;
23    ListNode* delayedTraveller = prehead;
24
25    // going through the list
26    while(traveller){
27        if (++nodecounter > n) {delayedTraveller = delayedTraveller->next;}
28        traveller = traveller->next;
29    }
30
31    // reconnecting
32    delayedTraveller->next = delayedTraveller->next->next;
33}
```



```
34 // sending back
35 cout << format("final-output = ");
36 fPrintLinkedList(prehead->next); cout << endl;
37
38
39
40
41
42 // return
43 return(0);
44
45 }
```

20. Valid Parentheses

Given a string *s* containing just the characters '(', ')', '[', ']', '{', and '}', determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Examples

1. Example 1:

- Input: *s* = "()"
- Output: true

2. Example 2:

- Input: *s* = "()[]"
- Output: true

3. Example 3:

- Input: *s* = "(]"
- Output: false

Constraints

- $1 \leq s.length \leq 10^4$
- s consists of parentheses only '()[]'.

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     string s  {"() [] {}"};
8
9     // seutp
10    deque<char> var00;
11
12    // going through the string
13    for(auto x: s){
14        // pushing or poppping
15        if (x == '(' || x == '[' || x == '{') {var00.push_back(x);}
16        else{
17            if (var00.size()==0) {cout << format("final-output = false\n"); return 0;}
18            if (x == ')') && var00.back() == '(') {var00.pop_back(); continue;}
19            if (x == ']') && var00.back() == '[') {var00.pop_back(); continue;}
20            if (x == '}') && var00.back() == '{') {var00.pop_back(); continue;}
21            cout << format("final-output = false\n"); return 0;
22        }
23    }
24
25    // checking if anything is left
```

```
26     if (var00.size()!=0) {cout << format("final-output = false\n"); return 0;}
27
28
29     // true-case
30     cout << format("final-output = true\n"); return 0;
31
32     // return
33     return(0);
34
35 }
```

21. Merge Two Sorted Lists

You are given the heads of two sorted linked lists `list1` and `list2`.

Merge the two lists into one sorted list. The list should be made by splicing together the nodes of the first two lists.

Return the head of the merged linked list.

Examples

1. Example 1:

- Input: `list1 = [1,2,4]`, `list2 = [1,3,4]`
- Output: `[1,1,2,3,4,4]`

2. Example 2:

- Input: `list1 = []`, `list2 = []`
- Output: `[]`

3. Example 3:

- Input: `list1 = []`, `list2 = [0]`
- Output: `[0]`

Constraints

- The number of nodes in both lists is in the range `[0, 50]`.

- $-100 \leq \text{Node.val} \leq 100$
- Both list1 and list2 are sorted in non-decreasing order.

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     ListNode* list1 = new ListNode(1);
8     list1->next      = new ListNode(2);
9     list1->next->next = new ListNode(4);
10
11     ListNode* list2 = new ListNode(1);
12     list2->next      = new ListNode(3);
13     list2->next->next = new ListNode(4);
14
15     // setup
16     ListNode* finalOutput = new ListNode;
17     ListNode* traveller_final = finalOutput;
18     ListNode* traveller_1 = list1;
19     ListNode* traveller_2 = list2;
20
21     // going through the two lists
22     while (traveller_1 != nullptr && traveller_2 != nullptr) {
23
24         // comparing values
25         if (traveller_1->val < traveller_2->val) {
26             traveller_final->next = traveller_1;           // linking node to final
27             traveller_final        = traveller_final->next; // moving node to new link
```

```

28
29     if (traveller_1->next != nullptr)
30         traveller_1          = traveller_1->next;      // updating traveller 1
31     else{
32         traveller_1 = nullptr;
33         break;
34     }
35
36 }
37 else {
38     traveller_final->next = traveller_2;                // linking node to final
39     traveller_final      = traveller_final->next;      // moving node to new link
40     if (traveller_2->next != nullptr)
41         traveller_2      = traveller_2->next;          // updating travel 2
42     else{
43         traveller_2 = nullptr;
44         break;
45     }
46 }
47 }
48
49 // checking if anything is left
50 while (traveller_1 != nullptr){
51     traveller_final->next = traveller_1;
52     traveller_final      = traveller_final->next;
53     traveller_1          = traveller_1->next;
54 }
55
56 while (traveller_2 != nullptr){
57     traveller_final->next = traveller_2;
58     traveller_final      = traveller_final->next;
59     traveller_2          = traveller_2->next;
60 }
61
62 // printing the final-output

```

```
63     cout << format("finaloutput = ");
64     fPrintLinkedList(finalOutput); cout << endl;
65
66     // return
67     return(0);
68 }
```

25. Reverse Nodes in k-Group

Given the head of a linked list, reverse the nodes of the list k at a time, and return the modified list.

k is a positive integer and is less than or equal to the length of the linked list. If the number of nodes is not a multiple of k then left-out nodes, in the end, should remain as it is.

You may not alter the values in the list's nodes, only nodes themselves may be changed.

Examples

1. Example 1:

- Input: head = [1,2,3,4,5], k = 2
- Output: [2,1,4,3,5]

2. Example 2:

- Input: head = [1,2,3,4,5], k = 3
- Output: [3,2,1,4,5]

Constraints

- The number of nodes in the list is n.
- $1 \leq k \leq n \leq 5000$
- $0 \leq \text{Node.val} \leq 1000$

Code

```
1  int main(){
2
3      // starting timer
4      Timer timer;
5
6      // input- configuration
7      ListNode* head          = new ListNode(1);
8      head->next               = new ListNode(2);
9      head->next->next          = new ListNode(3);
10     head->next->next->next      = new ListNode(4);
11     head->next->next->next->next = new ListNode(5);
12     auto k                    {2};
13
14     // setup
15     ListNode* prehead = new ListNode(); prehead->next = head;
16     ListNode* traveller = prehead;
17     vector<ListNode*> memberList(k, nullptr); memberList.reserve(k);
18
19     // runnings
20     while(traveller){
21         // filling up the memberList
22         int counter {0};
23         ListNode* tempotraveller = traveller->next;
24         while(counter < k && tempotraveller != nullptr){
25             memberList[counter] = tempotraveller;
26             tempotraveller       = tempotraveller->next;
27             ++counter;
28         }
29
30         // checking breaking condition
31         if (counter!=k) break;
32
33         // reconnecting
```

```

34     ListNode* beginningOfNextSegment = memberList[memberList.size()-1]->next;
35
36     // reconnecting
37     traveller->next = memberList[memberList.size()-1];
38     for(int i = memberList.size()-1; i>=1; --i) {memberList[i]->next = memberList[i-1];}
39     memberList[0]->next = beginningOfNextSegment;
40
41     // updating traveller
42     traveller = memberList[0];
43 }
44
45 // returning
46 cout << format("final-output = ");
47 fPrintLinkedList(prehead->next); cout << endl;
48
49 // return
50 return(0);
51
52 }

```

26. Remove Duplicates From Sorted Array

Given an integer array `nums` sorted in non-decreasing order, remove the duplicates in-place such that each unique element appears only once. The relative order of the elements should be kept the same. Then return the number of unique elements in `nums`. Consider the number of unique elements of `nums` to be `k`, to get accepted, you need to do the following things:

- Change the array `nums` such that the first `k` elements of `nums` contain the unique elements in the order they were present in `nums` initially. The remaining elements of `nums` are not important as well as the size of `nums`.
- Return `k`.

Examples

1. Example 1:

- Input: `nums = [1,1,2]`
- Output: 2, `nums = [1,2,_]`
- Explanation: Your function should return `k = 2`, with the first two elements of `nums` being 1 and 2 respectively. It does not matter what you leave beyond the returned `k` (hence they are underscores).

2. Example 2:

- Input: `nums = [0,0,1,1,1,2,2,3,3,4]`
- Output: 5, `nums = [0,1,2,3,4,_,_,_,_,_]`
- Explanation: Your function should return `k = 5`, with the first five elements of `nums` being 0, 1, 2, 3, and 4 respectively. It does not matter what you leave beyond the returned `k` (hence they are underscores).

Constraints:

- $1 \leq \text{nums.length} \leq 3 * 10^4$
- $-100 \leq \text{nums}[i] \leq 100$
- nums is sorted in non-decreasing order.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums    {1,1};
5
6     // setup
7     int p    {0};
8     int counter {0};
9
10    // going through the values
11    for(int i = 1; i<nums.size(); ++i){
12
13        // check values
14        if (nums[i] == nums[p]) {continue;}
15
16        // writing values
17        ++p;
18        nums[p] = nums[i];
19        ++counter;
20    }
21
22    // printing the final output
23    cout << format("final-output = {}\n", counter+1);
```

```
24     cout << format("nums = "); fpv(nums);
25
26     // return
27     return(0);
28
29 }
```

27. Remove Element

Given an integer array `nums` and an integer `val`, remove all occurrences of `val` in `nums` in-place. The order of the elements may be changed. Then return the number of elements in `nums` which are not equal to `val`.

Consider the number of elements in `nums` which are not equal to `val` be `k`, to get accepted, you need to do the following things:

Change the array `nums` such that the first `k` elements of `nums` contain the elements which are not equal to `val`. The remaining elements of `nums` are not important as well as the size of `nums`. Return `k`.

Examples

1. Example 1:

- Input: `nums = [3,2,2,3]`, `val = 3`
- Output: `2`, `nums = [2,2,_,_]_`
- Explanation: Your function should return `k = 2`, with the first two elements of `nums` being `2`. It does not matter what you leave beyond the returned `k` (hence they are underscores).

2. Example 2:

- Input: `nums = [0,1,2,2,3,0,4,2]`, `val = 2`
- Output: `5`, `nums = [0,1,4,0,3,_,_,_]_`
- Explanation: Your function should return `k = 5`, with the first five elements of `nums` containing `0`, `0`, `1`, `3`, and `4`. Note that the five elements can be returned in any order. It does not matter what you leave beyond the returned `k` (hence they are underscores).

Constraints

- $0 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 50$
- $0 \leq \text{val} \leq 100$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {0,1,2,2,3,0,4,2};
5     int val         {2};
6
7     // setup
8     int src         {0};
9     int dest        {0};
10    int numwrites {0};
11
12    // going through the indices
13    while(src < nums.size()){
14
15        // moving the dest until we find a val-position
16        while(nums[dest] != val) {++dest;}
17
18        // moving source until we find a non-val position after dest
19        src = std::max(src, dest+1);
20        while(nums[src] == val) {++src;};
21
22        // writing
23        if (dest < nums.size() && src < nums.size()){
```



```
24     nums[dest] = nums[src];
25     ++dest;
26     ++src;
27     ++numwrites;
28 }
29
30 }
31
32 // printing the length
33 cout << format("updated nums = "); fPrintVector(nums);
34 cout << format("finaloutput = {} \n", nums.size()-numwrites-1);
35
36 // return
37 return(0);
38
39 }
```

28. Find the Index of the First Occurrence in a String

Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or -1 if `needle` is not part of `haystack`.

Examples

1. Example 1:

- Input: `haystack = "sadbutsad"`, `needle = "sad"`
- Output: 0
- Explanation: "sad" occurs at index 0 and 6. The first occurrence is at index 0, so we return 0.

2. Example 2:

- Input: `haystack = "leetcode"`, `needle = "leeto"`
- Output: -1
- Explanation: "leeto" did not occur in "leetcode", so we return -1.

Constraints

- $1 \leq \text{haystack.length}, \text{needle.length} \leq 10^4$
- `haystack` and `needle` consist of only lowercase English characters.

Code

```
1 int main(){
2
3     // input- configuration
4     string haystack {"leetcode"};
5     string needle {"leeto"};
6
7
8     // setup
9     int finaloutput {-1};
10    auto beginsearch = [haystack, needle](int currindex){
11        // starting search
12        if(currindex + needle.size() > haystack.size()) {return false;}
13
14        // checking if they're a subset
15        for(int i = 0; i<needle.size(); ++i){
16            if (haystack[currindex + i] != needle[i]) {return false;}
17        }
18
19        return true;
20    };
21
22    // going through
23    for(int i = 0; i < haystack.size(); ++i){
24
25        // begin search at each index
26        auto curroutput = beginsearch(i);
27
28        // writing final output, if a mach
29        if (curroutput) {finaloutput = i; break;}
30    }
31
32    // printing final output
33
```

```
34     cout << format("final-output = {}\n", finaloutput);
35
36     // return
37     return(0);
38
39 }
```

36. Valid Sudoku

Determine if a 9 x 9 Sudoku board is valid. Only the filled cells need to be validated according to the following rules:

1. Each row must contain the digits 1-9 without repetition.
2. Each column must contain the digits 1-9 without repetition.
3. Each of the nine 3 x 3 sub-boxes of the grid must contain the digits 1-9 without repetition.

Examples

1. Example 1

- Input: board =
 - `[["5","3",".",".",".", "7",".",".",".", "."]`
 - `["6",".",".", "1","9","5",".",".", "."]`
 - `[[".", "9","8",".", "6",".", "3"]`
 - `["8",".", "6",".", "3"]`
 - `["4",".", "8",".", "3",".", "1"]`
 - `["7",".", "2",".", "6"]`
 - `[".", "6",".", "2","8","."]`
 - `[".", "4","1","9",".", "5"]`
 - `[".", "8",".", "7","9"]]`

- Output: true

2. Example 2:

- Input: board =
 - `[["8","3",".",".", "7",".",".", "6","."]`
 - `["6",".", "1","9","5",".", "2","."]`
 - `[["9","8",".", "6","."]`
 - `["8",".", "6",".", "3"]`
 - `["4",".", "8",".", "3",".", "1"]`
 - `["7",".", "2",".", "6"]`
 - `[["6",".", "2","8","."]`
 - `[[".", "4","1","9",".", "5"]`
 - `[[".", "8",".", "7","9"]]`
- Output: false
- Explanation: Same as Example 1, except with the 5 in the top left corner being modified to 8. Since there are two 8's in the top left 3x3 sub-box, it is invalid.

Constraints

- `board.length == 9`
- `board[i].length == 9`
- `board[i][j]` is a digit 1-9 or '.'.

Note:

- A Sudoku board (partially filled) could be valid but is not necessarily solvable.
- Only the filled cells need to be validated according to the mentioned rules.

Code

```
1 // main-file
2 int main(){
3
4     // input-configuration
5     vector< vector<char> > board;
6     board.push_back({'5','3','.','.','7','.','.','.','.'});
7     board.push_back({'6','.','.','1','9','5','.','.','.'});
8     board.push_back({'.','9','8','.','.','.','.','6','.'});
9     board.push_back({'8','.','.','.','6','.','.','.','3'});
10    board.push_back({'4','.','.','8','.','3','.','.','1'});
11    board.push_back({'7','.','.','.','2','.','.','.','6'});
12    board.push_back({'.','6','.','.','.','.','2','8','.'});
13    board.push_back({'.','.'.','.','4','1','9','.','.','5'});
14    board.push_back({'.','.'.','.','.','8','.','.','7','9'});
15
16    // basic method
17    int xoffset, yoffset;
18    int row_local, col_local;
19
20    // lambda for converting char to inger
21    auto fConvert = [](char x) -> int {
22        if (x == '.') return -1;
23        else { return static_cast<int>(x - '0');}
24    };
25
26    // checking row and column entries
27    for(int i = 0; i < 9; ++i){
28
29        // register for each jumnn
30        vector<int> rowRegister(9, 0);
31        vector<int> colRegister(9, 0);
32        vector<int> blockRegister(9,0);
33
```

```

34 // going through each jumn
35 for(int j = 0; j<9; ++j){
36
37     // along the row
38     int var00 = fConvert(board[i][j]);
39     if (var00 != -1) {if (++rowRegister[var00-1] > 1) return false;}
40
41     // down the column
42     var00 = fConvert(board[j][i]);
43     if (var00 !=-1) {if (++colRegister[var00-1] > 1) return false;}
44
45     // checking block
46     row_local = j / 3;
47     col_local = j % 3;
48     xoffset = i / 3;
49     yoffset = i % 3;
50
51     // calculating registers
52     var00 = fConvert(board[3*xoffset + row_local][col_local+3*yoffset]);
53     if (var00!=-1) {if (++blockRegister[var00-1]>1) return false;}
54 }
55 }
56
57 // returning true
58 return true;
59 }

```

42. Trapping Rain Water

Given n non-negative integers representing an elevation map where the width of each bar is 1, compute how much water it can trap after raining.

Examples

1. Example 1

- Input: `height = [0,1,0,2,1,0,1,3,2,1,2,1]`
- Output: 6
- Explanation: The above elevation map (black section) is represented by array `[0,1,0,2,1,0,1,3,2,1,2,1]`. In this case, 6 units of rain water (blue section) are being trapped.

2. Example 2

- Input: `height = [4,2,0,3,2,5]`
- Output: 9

Constraints

1. $n == \text{height.length}$
2. $1 \leq n \leq 2 * 10^4$
3. $0 \leq \text{height}[i] \leq 10^5$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> height {0,1,0,2,1,0,1,3,2,1,2,1};
5
6     // setup
7     vector<int> leftmaxes(height.size(), 0);
8     vector<int> rightmaxes(height.size(), 0);
9     int forwardindex {0};
10    int backwardindex {0};
11    int maxleft {-1};
12    int maxright {-1};
13    int finaloutput {0};
14
15    // building left-max
16    for(int i = 1; i<height.size(); ++i){
17
18        // calculating indices
19        forwardindex = i;
20        backwardindex = height.size()-1-i;
21
22        // calculating maxleft
23        maxleft = height[forwardindex-1] > maxleft ?
24                  height[forwardindex-1] : maxleft;
25        leftmaxes[forwardindex] = maxleft;
26
27        // calculating max right
28        maxright = height[backwardindex+1] > maxright ?
29                   height[backwardindex+1] : maxright;
30        rightmaxes[backwardindex] = maxright;
31    }
32
33    // going through the array to calculate maxvolume held by each column
```

```
// vector holding biggest-height to left
// vector holding biggest-height to the right
// for maintaining forward-index
// for maintaining backward-index
// keeping record of biggest left
// keeping record of biggest right
// storing final output
```

```
// forward-index
// backward-index
```

```
// running max-left
// storing to vector
```

```
// running max-right
// storing to vector
```

```

34 for(int i = 0; i < height.size(); ++i){
35
36     // finding max-height of the current column
37     auto minheight    = std::min({leftmaxes[i], rightmaxes[i]}); // finding max-height of borders
38     auto columnheight = minheight - height[i];                 // subtracting to find space
39     columnheight      = columnheight > 0 ? columnheight : 0;    // in case curr-height > max-height
40     finaloutput       += columnheight;                          // accumulating to water content
41 }
42
43 // printing the final output
44 cout << format("finaloutput = {}\n", finaloutput);
45
46 // return
47 return(0);
48
49 }

```

45 Jump Game II

You are given a 0-indexed array of integers `nums` of length `n`. You are initially positioned at index 0. Each element `nums[i]` represents the maximum length of a forward jump from index `i`. In other words, if you are at index `i`, you can jump to any index `(i + j)` where:

- $0 \leq j \leq \text{nums}[i]$
- $i + j \leq n$

Return the minimum number of jumps to reach index `n - 1`. The test cases are generated such that you can reach index `n - 1`.

Examples

1. Example 1

- Input: `nums = [2,3,1,1,4]`
- Output: 2
- Explanation: The minimum number of jumps to reach the last index is 2. Jump 1 step from index 0 to 1, then 3 steps to the last index.

2. Example 2

- Input: `nums = [2,3,0,1,4]`
- Output: 2

Constraints

- $1 \leq \text{nums.length} \leq 10^4$
- $0 \leq \text{nums}[i] \leq 1000$
- It's guaranteed that you can reach $\text{nums}[\text{n} - 1]$.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {2,3,0,1,4};
5
6     // setup
7     Timer timer;
8     vector<int> minjumps(nums.size(),0);
9     int leftboundary {-1};
10    int rightboundary {-1};
11
12    // moving from the back
13    for(int i = nums.size()-2; i>=0; --i){
14
15        // continuign if nums[i] = 0
16        if (nums[i] == 0) {
17            minjumps[i] = std::numeric_limits<int>::max();
18            continue;
19        }
20
21        // range of values it can go from here
22        leftboundary = i+1;
23        rightboundary = i+nums[i];
```

```
// setting a timer
// the dp table
// variable to hold the left-boundary
// variable to hold the right-boundary

// to prevent this from being chosen
// moving to next index

// the starting point of range
// the end point of range
```

```

24     rightboundary = rightboundary < nums.size()-1 ?
25         rightboundary : nums.size()-1;                                // ensuring within vector range
26
27     // calculating smallest element in range
28     auto it = std::min_element(minjumps.begin()+leftboundary,
29                               minjumps.begin()+rightboundary+1);    // finding the minimum value in the range
30
31     // adding min-element to the array
32     if (*it == std::numeric_limits<int>::max())
33         minjumps[i] = std::numeric_limits<int>::max();                // ensuring infity logic
34     else
35         minjumps[i] = (1 + *it);                                       // for regular values
36
37 }
38
39 // printing
40 cout << format("finaloutput = {}\n", minjumps[0]);
41 timer.measure();
42
43 // return
44 return(0);
45
46 }

```

48. Rotate Image

You are given an $n \times n$ 2D matrix representing an image, rotate the image by 90 degrees (clockwise).

You have to rotate the image in-place, which means you have to modify the input 2D matrix directly. DO NOT allocate another 2D matrix and do the rotation.

Examples

1. Example 1

- Input: matrix = `[[1,2,3],[4,5,6],[7,8,9]]`
- Output: `[[7,4,1],[8,5,2],[9,6,3]]`

2. Example 2

- Input: matrix = `[[5,1,9,11],[2,4,8,10],[13,3,6,7],[15,14,12,16]]`
- Output: `[[15,13,2,5],[14,3,4,1],[12,6,8,9],[16,7,10,11]]`

Constraints

- $n == \text{matrix.length} == \text{matrix}[i].\text{length}$
- $1 \leq n \leq 20$
- $-1000 \leq \text{matrix}[i][j] \leq 1000$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     vector<vector<int>> matrix {
8         {5,1,9,11},
9         {2,4,8,10},
10        {13,3,6,7},
11        {15,14,12,16}
12    };
13
14
15    // setup
16    int t_edge = 0;
17    int b_edge = matrix.size()-1;
18    int l_edge = 0;
19    int r_edge = matrix[0].size() -1;
20    int temp;
21
22    // shifting layer by layer.
23    int numlayers = (matrix.size())/2;
24
25    // shifting layer by layer
26    for(int i = 0; i<numlayers; ++i){
27
28        // breaking if they're the same for some reason
29        if(t_edge == b_edge || l_edge == r_edge) break;
30
31        // calculatin width
32        int currwidth = r_edge - l_edge + 1;
33        for(int j = 0; j<currwidth-1; ++j){
```



```

34
35     // shifting the four elements for each
36     temp                = matrix[t_edge][l_edge+j];
37     matrix[t_edge][l_edge+j] = matrix[b_edge-j][l_edge];
38     matrix[b_edge-j][l_edge] = matrix[b_edge][r_edge-j];
39     matrix[b_edge][r_edge-j] = matrix[t_edge+j][r_edge];
40     matrix[t_edge+j][r_edge]  = temp;
41 }
42
43 // updating edge-parameters based on the layer we're working with
44 t_edge += 1;
45 b_edge -= 1;
46 l_edge += 1;
47 r_edge -= 1;
48
49 }
50
51 // printing the matrix
52 cout << "final-matrix = \n";
53 for(const auto& x: matrix){
54     for(const auto& y: x){
55         cout << format("{} ", y);
56     }
57     cout << format("\n");
58 }
59
60 // return
61 return(0);
62
63 }

```

49. Group Anagrams

Given an array of strings `strs`, group the anagrams together. You can return the answer in any order.

Examples

1. Example 1:

- Input: `strs = ["eat","tea","tan","ate","nat","bat"]`
- Output: `[["bat"],["nat","tan"],["ate","eat","tea"]]`
- Explanation:
 - There is no string in `strs` that can be rearranged to form `"bat"`.
 - The strings `"nat"` and `"tan"` are anagrams as they can be rearranged to form each other.
 - The strings `"ate"`, `"eat"`, and `"tea"` are anagrams as they can be rearranged to form each other.

2. Example 2:

- Input: `strs = [""]`
- Output: `[[""]]`

3. Example 3:

- Input: `strs = ["a"]`
- Output: `[["a"]]`

Constraints

- $1 \leq \text{strs.length} \leq 10^4$
- $0 \leq \text{strs}[i].\text{length} \leq 100$
- $\text{strs}[i]$ consists of lowercase English letters.

Code

```
1 // build histogram
2 vector<int> fBuildHist(string input){
3     vector<int> myhist(26, 0);
4     for(auto x: input) {++myhist[static_cast<int>(x - 'a')];}
5     return myhist;
6 }
7
8 // Custom hash function for vector<int>
9 struct VectorHash {
10     std::size_t operator()(const std::vector<int>& v) const {
11         std::size_t hashValue = 0;
12         for (int num : v)
13             hashValue ^= std::hash<int>{}(num) + 0x9e3779b9 + (hashValue << 6) + (hashValue >> 2);
14
15         return hashValue;
16     }
17 };
18 // int main
19 int main(){
20
21     // starting timer
22     Timer timer;
23 }
```

```

24 // input- configuration
25 vector<string> strs{
26     "eat",
27     "tea",
28     "tan",
29     "ate",
30     "nat",
31     "bat"
32 };
33
34 // unordered map for hist to vector of vector of strings
35 unordered_map< vector<int>, vector<string>, VectorHash > histToGroup;
36
37 for(auto x: strs){
38
39     // building hist of current word
40     auto xhist = fBuildHist(x);
41
42     // checking if it exists
43     if (histToGroup.find(xhist) == histToGroup.end())
44         histToGroup[xhist] = vector<string>({x});
45     else
46         histToGroup[xhist].push_back(x);
47
48 }
49
50 // building final output
51 vector<vector<string>> finalOutput;
52 for(auto x: histToGroup) {finalOutput.push_back(x.second);}
53
54 // printing
55 cout << format("final-output = {}\n", finalOutput);
56
57 // return
58 return(0);

```


54. Spiral Matrix

Given an $m \times n$ matrix, return all elements of the matrix in spiral order.

Examples

1. Example 1:

- Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
- Output: [1,2,3,6,9,8,7,4,5]

2. Example 2:

- Input: matrix = [[1,2,3,4],[5,6,7,8],[9,10,11,12]]
- Output: [1,2,3,4,8,12,11,10,9,5,6,7]

Constraints

- $m == \text{matrix.length}$
- $n == \text{matrix}[i].\text{length}$
- $1 \leq m, n \leq 10$
- $-100 \leq \text{matrix}[i][j] \leq 100$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     vector<vector<int>> matrix{
8         {1,2,3,4},
9         {5,6,7,8},
10        {9,10,11,12}
11    };
12
13    // setup
14    int left {0};
15    int right {static_cast<int>(matrix[0].size()-1)};
16    int top {0};
17    int bottom {static_cast<int>(matrix.size()-1)};
18    vector<int> finalOutput;
19
20    // moving through this
21    while(left <= right && top <= bottom){
22
23        // moving on upside
24        for(int i = left; i <= right; ++i) {finalOutput.push_back(matrix[top][i]);}
25
26        // moving through the right side
27        for(int i = top+1; i<=bottom-1; ++i) {finalOutput.push_back(matrix[i][right]);}
28
29        // moving through the bottom
30        for(int i = right; top != bottom && i>= left; --i) {finalOutput.push_back(matrix[bottom][i]);}
31
32        // moving through the left
33        for(int i = bottom-1; left!=right && i>= top+1; --i) {finalOutput.push_back(matrix[i][left]);}
```

```
34
35     // updating boundaries
36     ++left; --right; ++top; --bottom;
37
38 }
39
40 // printing the finaloutput
41 cout << format("final-output = {}\n", finalOutput);
42
43 // return
44 return(0);
45
46 }
```

55. Jump Game

You are given an integer array `nums`. You are initially positioned at the array's first index, and each element in the array represents your maximum jump length at that position. Return `true` if you can reach the last index, or `false` otherwise.

Examples

1. Example 1

- Input: `nums = [2,3,1,1,4]`
- Output: `true`
- Explanation: Jump 1 step from index 0 to 1, then 3 steps to the last index.

2. Example 2

- Input: `nums = [3,2,1,0,4]`
- Output: `false`
- Explanation: You will always arrive at index 3 no matter what. Its maximum jump length is 0, which makes it impossible to reach the last index.

Constraints

- $1 \leq \text{nums.length} \leq 10^4$
- $0 \leq \text{nums}[i] \leq 10^5$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {3,2,1,0,4};
5
6     // setup
7     Timer timer;
8     int maxjumpdistance {0};
9     int currjumpdistance {0};
10    int finaloutput {0};
11
12    // going through the nums
13    for(int i = 0; i<=maxjumpdistance && i<nums.size(); ++i){
14
15        // calculating max-distance we can go from here
16        currjumpdistance = i + nums[i];
17
18        // updating max-jumpdistance
19        maxjumpdistance = currjumpdistance > maxjumpdistance ? \
20            currjumpdistance : maxjumpdistance;
21
22    }
23
24    // updating the final output
25    finaloutput = maxjumpdistance >= nums.size()-1 ? true : false;
26
27    // printing the thing
28    cout << format("final-output = {}\n", finaloutput);
29    timer.measure();
30
31
32    // return
33    return(0);
```

34

35

}

56. Merge Intervals

Given an array of intervals where $\text{intervals}[i] = [\text{start}_i, \text{end}_i]$, merge all overlapping intervals, and return an array of the non-overlapping intervals that cover all the intervals in the input.

Examples

1. Example 1:

- Input: $\text{intervals} = [[1,3],[2,6],[8,10],[15,18]]$
- Output: $[[1,6],[8,10],[15,18]]$
- Explanation: Since intervals $[1,3]$ and $[2,6]$ overlap, merge them into $[1,6]$.

2. Example 2:

- Input: $\text{intervals} = [[1,4],[4,5]]$
- Output: $[[1,5]]$
- Explanation: Intervals $[1,4]$ and $[4,5]$ are considered overlapping.

Constraints

- $1 \leq \text{intervals.length} \leq 10^4$
- $\text{intervals}[i].\text{length} == 2$
- $0 \leq \text{start}_i \leq \text{end}_i \leq 10^4$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     vector<vector<int>> intervals{
8         {1,3},
9         {2,6},
10        {8,10},
11        {15,18}
12    };
13
14    // setup
15    vector<vector<int>> finalOutput;
16
17    // sorting the input
18    std::sort(intervals.begin(), intervals.end(),
19        [](const vector<int>& a, const vector<int>& b){return a[0] < b[0];});
20
21    // going through the intervals
22    vector<int> runninginterval {intervals[0][0], intervals[0][1]};
23    for(int i = 1; i<intervals.size(); ++i){
24        if (runninginterval[1] < intervals[i][0]){
25            finalOutput.push_back(runninginterval);           // pushing the results
26            runninginterval = intervals[i];                   // getting new running interval
27        }
28        else {runninginterval[1] = max(runninginterval[1], intervals[i][1]);}
29    }
30    finalOutput.push_back(runninginterval);                   // pushing the results
31
32    // returning
33    cout << format("final-output = {}\n", finalOutput);
```

```
34
35 // return
36 return(0);
37 }
```

57. Insert Interval

You are given an array of non-overlapping intervals `intervals` where `intervals[i] = [starti, endi]` represent the start and the end of the *i*th interval and `intervals` is sorted in ascending order by `starti`. You are also given an interval `newInterval = [start, end]` that represents the start and end of another interval.

Insert `newInterval` into `intervals` such that `intervals` is still sorted in ascending order by `starti` and `intervals` still does not have any overlapping intervals (merge overlapping intervals if necessary).

Return `intervals` after the insertion.

Note that you don't need to modify `intervals` in-place. You can make a new array and return it.

Examples

1. Example 1:

- Input: `intervals = [[1,3],[6,9]]`, `newInterval = [2,5]`
- Output: `[[1,5],[6,9]]`

2. Example 2:

- Input: `intervals = [[1,2],[3,5],[6,7],[8,10],[12,16]]`, `newInterval = [4,8]`
- Output: `[[1,2],[3,10],[12,16]]`
- Explanation: Because the new interval `[4,8]` overlaps with `[3,5]`, `[6,7]`, `[8,10]`.

Constraints

- $0 \leq \text{intervals.length} \leq 10^4$

- `intervals[i].length == 2`
- $0 \leq \text{start}_i \leq \text{end}_i \leq 10^5$
- `intervals` is sorted by `start_i` in ascending order.
- `newInterval.length == 2`
- $0 \leq \text{start} \leq \text{end} \leq 10^5$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     vector<vector<int>> intervals{
8         {1,2},
9         {3,5},
10        {6,7},
11        {8,10},
12        {12,16}
13    };
14    vector<int> newInterval{4,8};
15
16
17    // setup
18    vector<vector<int>> finalOutput;
19    intervals.push_back(newInterval);
20
21    // sorting the interval
```



```

22     std::sort(intervals.begin(),
23             intervals.end(),
24             [](const vector<int>& a,
25               const vector<int>& b){return a[0] < b[0];});
26     vector<int>      runninginterval {intervals[0]};
27
28     // going through the inputs
29     for(int i = 1; i<intervals.size(); ++i){
30         if (runninginterval[1] < intervals[i][0]){
31             finalOutput.push_back(runninginterval);
32             runninginterval = intervals[i];
33         }
34         else{
35             runninginterval[1] = max(runninginterval[1], intervals[i][1]);
36         }
37     }
38
39     // pushing it back
40     finalOutput.push_back(runninginterval);
41     cout << format("final-output = {}\n", finalOutput);
42
43     // return
44     return(0);
45
46 }

```

58. Length of Last Word

Given a string *s* consisting of words and spaces, return the length of the last word in the string. A word is a maximal substring consisting of non-space characters only.

Example

1. Example 1:

- Input: *s* = "Hello World"
- Output: 5
- Explanation: The last word is "World" with length 5.

2. Example 2:

- Input: *s* = " fly me to the moon "
- Output: 4
- Explanation: The last word is "moon" with length 4.

3. Example 3:

- Input: *s* = "luffy is still joyboy"
- Output: 6
- Explanation: The last word is "joyboy" with length 6.

Constraints

- $1 \leq \text{s.length} \leq 10^4$
- s consists of only English letters and spaces ' '.
- There will be at least one word in s.

Code

```
1 int main(){
2
3     // input- configuration
4     string s  {" fly me to the moon "};
5
6     // setup
7     int p1    {-1};
8     int finaloutput {-1};
9     string laststring;
10
11    // moving from the end
12    for(int i = s.size()-1; i>=0; --i){
13
14        // continuing until you find a non-space character
15        if (s[i] == ' ') {continue;}
16
17        // launch the start of first word
18        p1 = i;
19
20        // moving p1 until we find the first space or nonword thing
21        while(p1>0 && s[p1]!=' '){--p1;}
22
23        // calculating the length
```

```
24     finaloutput = i - p1;
25     laststring = string(s.begin() + p1, s.begin() + i+1);
26
27     // breaking
28     break;
29 }
30
31 // printing
32 cout << format("length = {}, last-word = {}\n", finaloutput, laststring);
33
34 // return
35 return(0);
36
37 }
```

61. Rotate List

Given the head of a linked list, rotate the list to the right by k places.

Examples

1. Example 1:

- Input: head = [1,2,3,4,5], $k = 2$
- Output: [4,5,1,2,3]

2. Example 2:

- Input: head = [0,1,2], $k = 4$
- Output: [2,0,1]

Constraints

- The number of nodes in the list is in the range [0, 500].
- $-100 \leq \text{Node.val} \leq 100$
- $0 \leq k \leq 2 * 10^9$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto head {new ListNode(1)};
8     head->next = new ListNode(2);
9     head->next->next = new ListNode(3);
10    head->next->next->next = new ListNode(4);
11    head->next->next->next->next = new ListNode(5);
12    auto k {2};
13
14    // trivial cases
15    if (head == nullptr) {fPrintLinkedList("head = ", head); return 0;}
16
17    // storing the starting point
18    auto startingpoint {head};
19    auto listsize      {0};
20
21    // connecting the last-node with the first
22    auto traveller {head};
23    while(traveller->next) {traveller = traveller->next; ++listsize;}
24    ++listsize;
25    traveller->next = head;
26
27    // to get rid of cycles
28    k = k % listsize;
29    auto cutoffpoint {listsize - k};
30    auto count       {0};
31    auto finalresult  {static_cast<ListNode*>(nullptr)};
32
33    // finding the cutting off point
```

```

34     traveller = head;
35     while(traveller){
36         ++count;                                // appending count
37         if (count == cutoffpoint){
38             finalresult = traveller->next;        // setting up the new head
39             traveller->next = nullptr;           // setting up last pointer
40             break;                               // breaking up
41         }
42         traveller = traveller->next;              // moving to the next point
43     }
44
45     // printing the linked list
46     fPrintLinkedList("final-result = ", finalresult);
47
48     // return
49     return(0);
50
51 }

```

68. Text Justification

Given an array of strings `words` and a width `maxWidth`, format the text such that each line has exactly `maxWidth` characters and is fully (left and right) justified.

You should pack your words in a greedy approach; that is, pack as many words as you can in each line. Pad extra spaces ' ' when necessary so that each line has exactly `maxWidth` characters.

Extra spaces between words should be distributed as evenly as possible. If the number of spaces on a line does not divide evenly between words, the empty slots on the left will be assigned more spaces than the slots on the right.

For the last line of text, it should be left-justified, and no extra space is inserted between words.

Note:

1. A word is defined as a character sequence consisting of non-space characters only.
2. Each word's length is guaranteed to be greater than 0 and not exceed `maxWidth`.
3. The input array `words` contains at least one word.

Examples

1. Example 1:

- Input: `words = ["This", "is", "an", "example", "of", "text", "justification."], maxWidth = 16`
- Output:
 - [
 - "This is an",
 - "example of text",

- "justification. "
-]

2. Example 2:

- Input: words = ["What","must","be","acknowledgment","shall","be"], maxWidth = 16
- Output:
 - [
 - "What must be",
 - "acknowledgment ",
 - "shall be "
 -]
- Explanation: Note that the last line is "shall be " instead of "shall be", because the last line must be left-justified instead of fully-justified. Note that the second line is also left-justified because it contains only one word.

3. Example 3:

- Input: words = ["Science","is","what","we","understand","well","enough","to","explain","to","a","computer.","Art","is","everything"], maxWidth = 20
- Output:
 - [
 - "Science is what we",
 - "understand well",
 - "enough to explain to",
 - "a computer. Art is",
 - "everything else we",
 - "do "
 -]

Constraints

- $1 \leq \text{words.length} \leq 300$
- $1 \leq \text{words}[i].\text{length} \leq 20$
- $\text{words}[i]$ consists of only English letters and symbols.
- $1 \leq \text{maxWidth} \leq 100$
- $\text{words}[i].\text{length} \leq \text{maxWidth}$

Code

```
1 // function to calculate number of non-space characters
2 int fCalcLengthOfTempWithoutSpaces(std::vector<std::string> temp){
3     int num_nonspaces = 0;
4     for(auto x: temp) num_nonspaces += x.size();
5     return num_nonspaces;
6 }
7
8 // function to calculate words formed with temp
9 int fCalcLengthOfTempWithSpaces(std::vector<std::string> temp){
10     int num_nonspaces = 0;
11     for(auto x: temp) num_nonspaces += 1+ x.size();
12     return num_nonspaces-1;
13 }
14
15 // printing temp
16 void fPrintTemp(std::vector<std::string> temp){
17     // printing temp
18     std::cout << "temp = ";
19     for(auto x: temp) std::cout << x << ", ";
```

```

20     std::cout << std::endl;
21 }
22
23 // main-file =====
24 int main(){
25
26     // input- configuration
27     auto words    = vector<string>({"This", "is", "an", "example", "of", "text", "justification."});
28     auto maxWidth {16};
29
30     // setup
31     std::vector<std::string> finalOutput;
32
33     // going through strings
34     int acc = 0;
35     int numwords = 0;
36     int currwidth = 0;
37     std::vector<std::string> temp;
38
39     for(int i = 0; i<words.size(); ++i){
40
41         // updating temp
42         temp.push_back(words[i]);    // updating words in temp
43
44         // checking if width has been crossed
45         if (fCalcLengthOfTempWithSpaces(temp) >= maxWidth || i == words.size()-1){
46
47             // condition temp based on length
48             if(fCalcLengthOfTempWithSpaces(temp)>maxWidth){
49                 temp.pop_back();    // last words gotta go
50                 --i;                // making sure its taken care of in next iteration
51             }
52
53             // finding length of characters in temp
54             int num_nonspaces = fCalcLengthOfTempWithoutSpaces(temp);

```

```

55
56 // finding number of spaces to add
57 int numspacetofill = maxWidth - num_nonspaces;
58
59 // calculating numspots
60 int numspots = temp.size()-1;
61
62 // calculating ideal number of spaces
63 int idealnumspacesperspot;
64 int remainders;
65 if (numspots!=0){
66     idealnumspacesperspot = numspacetofill/numspots;
67     remainders             = numspacetofill%numspots;
68 }
69 else{
70     idealnumspacesperspot = numspacetofill/1;
71     remainders             = numspacetofill%1;
72 }
73
74 // constructing candidate string
75 std::string candidate;
76
77 // adding each word in temp to the candidate
78 for(int j = 0; j < temp.size(); ++j){
79
80     // fetching word
81     auto x = temp[j];
82
83     // adding word to candidate
84     candidate += x;
85
86     // adding spaces
87     if (j!=temp.size()-1)
88         for(int var00 = 0; var00 < idealnumspacesperspot; ++var00)
89             candidate += " ";

```

```

90
91     // checking if there is any remainder left
92     if (remainders > 0){
93         candidate += " ";
94         --remainders;
95     }
96 }
97
98 // checking if there are remaindeers
99 while (remainders > 0){
100     candidate += " ";
101     --remainders;
102 }
103
104 while (candidate.size() != maxWidth) {candidate += " ";}
105
106 // appending candidate to final output
107 finalOutput.push_back(candidate);
108
109 // getting rid of everything
110 if (i != words.size()-1) {temp.clear();}
111 }
112 }
113
114 // making function left justified
115 std::string lastline;
116 for(int i = 0; i < temp.size(); ++i){
117     lastline += temp[i];
118     if (i != temp.size()-1) {lastline += " ";}
119 }
120
121 // adding spaces until end
122 while(lastline.size() != maxWidth) {lastline += " ";}
123
124 // replacing last line

```

```
125     finalOutput[finalOutput.size()-1] = lastline;
126
127     // return
128     return(0);
129
130 }
```

71. Simplify Path

You are given an absolute path for a Unix-style file system, which always begins with a slash '/'. Your task is to transform this absolute path into its simplified canonical path.

The rules of a Unix-style file system are as follows:

- A single period '.' represents the current directory.
- A double period '..' represents the previous/parent directory.
- Multiple consecutive slashes such as '/' and '//' are treated as a single slash '/'.
- Any sequence of periods that does not match the rules above should be treated as a valid directory or file name. For example, '...' and '....' are valid directory or file names.

The simplified canonical path should follow these rules:

- The path must start with a single slash '/'.
- Directories within the path must be separated by exactly one slash '/'.
- The path must not end with a slash '/', unless it is the root directory.
- The path must not have any single or double periods ('.' and '..') used to denote current or parent directories.

Return the simplified canonical path.

Examples

1. Example 1:

- Input: path = `"/home/"`
- Output: `"/home"`
- Explanation: The trailing slash should be removed.

2. Example 2:

- Input: path = `"/home//foo/"`
- Output: `"/home/foo"`
- Explanation: Multiple consecutive slashes are replaced by a single one.

3. Example 3:

- Input: path = `"/home/user/Documents/../Pictures"`
- Output: `"/home/user/Pictures"`
- Explanation: A double period `".."` refers to the directory up a level (the parent directory).

Constraints

- $1 \leq \text{path.length} \leq 3000$
- path consists of English letters, digits, period `'.'`, slash `'/'` or `'_.'`.
- path is a valid absolute Unix path.

Code

```
1  int main(){
2
3      // starting timer
4      Timer timer;
5
6      // input- configuration
7      string path    {"home/foo/"};
8
9      // setup
10     vector<string> stack;
11
12     // going through the array
13     int i = 0 ;
14     while (i < path.size()){
15
16         // moving until end of string or a /
17         string temp;
18         while(path[i]!='/' && i<path.size()){
19             temp += std::string(1,path[i++]);
20         }
21
22         // continuing if temp size is zero
23         if (temp.size()==0)  {++i; continue;}
24
25         // evaluating the current string
26         if (temp == ".")      {++i; continue;}
27         else if (temp == "..") {
28             if (stack.size()!=0) {stack.pop_back();}
29             ++i;}
30         else {stack.push_back(temp); ++i;}
31     }
32
33 }
```

```
34 // reconstructing final path
35 string finalOutput;
36
37 // reconstructing
38 for(auto x: stack) {finalOutput += "/" + x;}
39
40 // size thing
41 if (finalOutput.size() == 0) {finalOutput += "/";}
42
43 // returning
44 cout << format("finalOutput = {}\n", finalOutput);
45
46 // return
47 return(0);
48
49 }
```

73. Set Matrix Zeroes

Given an $m \times n$ integer matrix `matrix`, if an element is 0, set its entire row and column to 0's. You must do it in place.

Examples

1. Example 1

- Input: `matrix = [[1,1,1],[1,0,1],[1,1,1]]`
- Output: `[[1,0,1],[0,0,0],[1,0,1]]`

2. Example 2

- Input: `matrix = [[0,1,2,0],[3,4,5,2],[1,3,1,5]]`
- Output: `[[0,0,0,0],[0,4,5,0],[0,3,1,0]]`

Constraints

- $m == \text{matrix.length}$
- $n == \text{matrix}[0].\text{length}$
- $1 \leq m, n \leq 200$
- $-231 \leq \text{matrix}[i][j] \leq 231 - 1$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     vector<vector<int>> matrix{
8         {0,1,2,0},
9         {3,4,5,2},
10        {1,3,1,5}
11    };
12
13    // setup
14    vector<bool> colregister(matrix[0].size(), false); colregister.reserve(colregister.size());
15    vector<bool> rowregister(matrix.size(), false); rowregister.reserve(rowregister.size());
16
17    // registering
18    #pragma omp parallel for
19    for(int i = 0; i<matrix.size(); ++i)
20        for(int j = 0; j<matrix[0].size(); ++j)
21            if (matrix[i][j] == 0) {colregister[j] = true; rowregister[i] = true;}
22
23    // rewriting
24    #pragma omp parallel for
25    for(int i = 0; i<matrix.size(); ++i)
26        for(int j = 0; j<matrix[0].size(); ++j)
27            if (colregister[j] == true || rowregister[i] == true) {matrix[i][j] = 0;}
28
29    // printing the final output
30    cout << format("final-output \n");
31    for(const auto& x: matrix){
32        for(const auto& y: x) {cout << format("{}, ", y);}
33        cout << format("\n");
```

```
34     }  
35  
36     // return  
37     return(0);  
38  
39 }
```

80. Remove Duplicates from Sorted Array II

Given an integer array `nums` sorted in non-decreasing order, remove some duplicates in-place such that each unique element appears at most twice. The relative order of the elements should be kept the same.

Since it is impossible to change the length of the array in some languages, you must instead have the result be placed in the first part of the array `nums`. More formally, if there are `k` elements after removing the duplicates, then the first `k` elements of `nums` should hold the final result. It does not matter what you leave beyond the first `k` elements.

Return `k` after placing the final result in the first `k` slots of `nums`.

Do not allocate extra space for another array. You must do this by modifying the input array in-place with $O(1)$ extra memory.

1. Example 1

- Input: `nums = [1,1,1,2,2,3]`
- Output: 5, `nums = [1,1,2,2,3,_]`

2. Example 2

- Input: `nums = [0,0,1,1,1,1,2,3,3]`
- Output: 7, `nums = [0,0,1,1,2,3,3,_,_]`

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {1,1,1,2,2,3};
5 }
```

```

6 // setup
7 int destination {1};
8 int prev {nums[0]};
9 int element_counter {1};
10 int numwrites {1};
11
12 // going through the values
13 for(int i = 1; i < nums.size(); ++i){
14
15     // updating counter
16     if (nums[i-1] == nums[i]) {++element_counter;}
17     else {element_counter = 1;}
18
19     // checking the element counters
20     if (element_counter <=2) {nums[destination++] = nums[i];}
21
22 }
23
24 // printing the final output
25 cout << format("nums = "); fpv(nums);
26 cout << format("return-value = {}\n", destination);
27
28 // return
29 return(0);
30
31 }

```

86. Partition List

Given the head of a linked list and a value x , partition it such that all nodes less than x come before nodes greater than or equal to x . You should preserve the original relative order of the nodes in each of the two partitions.

Examples

1. Example 1:

- Input: head = [1,4,3,2,5,2], $x = 3$
- Output: [1,2,2,4,3,5]

2. Example 2:

- Input: head = [2,1], $x = 2$
- Output: [1,2]

Constraints

- The number of nodes in the list is in the range $[0, 200]$.
- $-100 \leq \text{Node.val} \leq 100$
- $-200 \leq x \leq 200$

Code

```
1  int main(){
2
3      // starting timer
4      Timer timer;
5
6      // input- configuration
7      auto head {new ListNode(1)};
8      head->next = new ListNode(4);
9      head->next->next = new ListNode(3);
10     head->next->next->next = new ListNode(2);
11     head->next->next->next->next = new ListNode(5);
12     head->next->next->next->next->next = new ListNode(2);
13     auto x {3};
14
15     // setup
16     ListNode* traveller      = head;
17     ListNode* lefthead       = new ListNode(-1);
18     ListNode* lefttraveller  = lefthead;
19     ListNode* righthead      = new ListNode(-1);
20     ListNode* righttraveller = righthead;
21
22     // going through the list
23     while(traveller){
24         // checking next-value
25         if (traveller->val < x){
26             lefttraveller->next = new ListNode(traveller->val);
27             lefttraveller       = lefttraveller->next;
28         }
29         else {
30             righttraveller->next = new ListNode(traveller->val);
31             righttraveller       = righttraveller->next;
32         }
33     }
```

```
34     // moving traveller
35     traveller = traveller->next;
36 }
37
38 // connecting
39 lefttraveller->next = righthead->next;
40
41 // returning
42 fPrintLinkedList("Final-output = ", lefthead->next);
43
44 // return
45 return(0);
46
47 }
```

88. Merge Sorted Array

You are given two integer arrays `nums1` and `nums2`, sorted in non-decreasing order, and two integers `m` and `n`, representing the number of elements in `nums1` and `nums2` respectively.

Merge `nums1` and `nums2` into a single array sorted in non-decreasing order.

The final sorted array should not be returned by the function, but instead be stored inside the array `nums1`. To accommodate this, `nums1` has a length of $m + n$, where the first m elements denote the elements that should be merged, and the last n elements are set to 0 and should be ignored. `nums2` has a length of n .

Examples

1. Example 1:

- Input: `nums1 = [1,2,3,0,0,0]`, `m = 3`, `nums2 = [2,5,6]`, `n = 3`
- Output: `[1,2,2,3,5,6]`
- Explanation: The arrays we are merging are `[1,2,3]` and `[2,5,6]`. The result of the merge is `[1,2,2,3,5,6]` with the underlined elements coming from `nums1`.

2. Example 2:

- Input: `nums1 = [1]`, `m = 1`, `nums2 = []`, `n = 0`
- Output: `[1]`
- Explanation: The arrays we are merging are `[1]` and `[]`. The result of the merge is `[1]`.

3. Example 3:

- Input: `nums1 = [0]`, `m = 0`, `nums2 = [1]`, `n = 1`

- Output: [1]
- Explanation: The arrays we are merging are [] and [1]. The result of the merge is [1]. Note that because $m = 0$, there are no elements in `nums1`. The 0 is only there to ensure the merge result can fit in `nums1`.

Constraints:

1. `nums1.length == m + n`
2. `nums2.length == n`
3. $0 \leq m, n \leq 200$
4. $1 \leq m + n \leq 200$
5. $-10^9 \leq \text{nums1}[i], \text{nums2}[j] \leq 10^9$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums1 {1, 2, 3, 0, 0, 0};
5     vector<int> nums2 {2, 5, 6};
6     int m   {3};
7     int n   {3};
8
9     // setup
10    int p1   {m-1};
11    int p2   {n-1};
12    int p3   {m+n-1};
```

```
13
14     int curr1  {-1};
15     int curr2  {-1};
16
17     // going the other way
18     while(p1 >= 0 || p2 >= 0)
19     {
20         // printing the values
21         curr1 = p1 >= 0 ? nums1[p1] : std::numeric_limits<int>::min();
22         curr2 = p2 >= 0 ? nums2[p2] : std::numeric_limits<int>::min();
23
24         // assigning value
25         if (curr1 > curr2) {nums1[p3] = curr1; --p3; --p1;}
26         else               {nums1[p3] = curr2; --p3; --p2;}
27
28     }
29
30     // printing the final output
31     cout << format("finaloutput = "); fPrintVector(nums1);
32
33     // return
34     return(0);
35 }
```

100. Same Tree

Given the roots of two binary trees *p* and *q*, write a function to check if they are the same or not.

Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.

Examples

1. Example 1:

- Input: *p* = [1,2,3], *q* = [1,2,3]
- Output: true

2. Example 2:

- Input: *p* = [1,2], *q* = [1,null,2]
- Output: false

3. Example 3:

- Input: *p* = [1,2,1], *q* = [1,1,2]
- Output: false

Constraints

- The number of nodes in both trees is in the range [0, 100].
- $-10^4 \leq \text{Node.val} \leq 10^4$

Code

```
1  int main(){
2
3      // starting timer
4      Timer timer;
5
6      // input- configuration
7      auto p {new TreeNode(1)};
8      p->left  = new TreeNode(2);
9      p->right = new TreeNode(3);
10
11     auto q {new TreeNode(1)};
12     q->left  = new TreeNode(2);
13     q->right = new TreeNode(3);
14
15     // setup
16     std::function<bool(TreeNode*, TreeNode*)> fCompareTrees = [&fCompareTrees](
17         TreeNode* p, TreeNode* q){
18
19         // basecase
20         if (p == nullptr && q == nullptr) return true;
21         if (p == nullptr && q != nullptr) return false;
22         if (p != nullptr && q == nullptr) return false;
23         if (p->val != q->val) return false;
24
25         // going through the next set of branches
26         return (fCompareTrees(p->left, q->left) && fCompareTrees(p->right, q->right));
27     };
28
29     // going through the two nodes
30     bool finalOutput = fCompareTrees(p, q);
31
32     // returning final output
33     cout << format("final-output = {}\n", finalOutput);
```

```
34
35     // return
36     return(0);
37
38 }
```

101. Symmetric Tree

Given the root of a binary tree, check whether it is a mirror of itself (i.e., symmetric around its center).

Examples

1. Example 1:

- Input: root = [1,2,2,3,4,4,3]
- Output: true

2. Example 2:

- Input: root = [1,2,2,null,3,null,3]
- Output: false

Constraints

- The number of nodes in the tree is in the range [1, 1000].
- $-100 \leq \text{Node.val} \leq 100$

Code

```

1  int main(){
2
3      // starting timer
4      Timer timer;
5
6      // input- configuration
7      auto root      {new TreeNode(1)};
8      root->left      = new TreeNode(2);
9      root->right     = new TreeNode(2);
10     root->left->left  = new TreeNode(3);
11     root->left->right = new TreeNode(4);
12     root->right->left = new TreeNode(4);
13     root->right->right = new TreeNode(3);
14
15     // setup
16     std::function<bool(TreeNode*, TreeNode*)> dfs = [&dfs](
17         TreeNode* leftNode,
18         TreeNode* rightNode){
19
20         // printing the base-cases
21         if (leftNode == nullptr && rightNode == nullptr) return true;
22         if (leftNode == nullptr || rightNode == nullptr) return false;
23
24         // calling the children
25         bool finaloutput = (leftNode->val == rightNode->val)    && \
26                         dfs(leftNode->left, rightNode->right)  && \
27                         dfs(leftNode->right, rightNode->left);
28
29         // returning the value
30         return finaloutput;
31     };
32
33     // running
34     cout << format("final-output = {}\n", dfs(root->left, root->right));

```

```
35
36     // return
37     return(0);
38 }
```

121. Best Time To Buy And Sell Stock

You are given an array `prices` where `prices[i]` is the price of a given stock on the *i*th day. You want to maximize your profit by choosing a single day to buy one stock and choosing a different day in the future to sell that stock. Return the maximum profit you can achieve from this transaction. If you cannot achieve any profit, return 0.

Examples

1. Example 1

- Input: `prices = [7,1,5,3,6,4]`
- Output: 5

2. Example 2

- Input: `prices = [7,6,4,3,1]`
- Output: 0

Constraints:

- $1 \leq \text{prices.length} \leq 10^5$
- $0 \leq \text{prices}[i] \leq 10^4$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> prices {7,6,4,3,1};
5
6     // setup
7     Stopwatch timer;                                // timer-object
8     int p0      {0};                                // first index-pointer
9     int p1      {1};                                // second index-pointer
10    int maxprofit {0};                                // variable to hold max-profit
11    int curr     {-1};                                // variable to hold current-profit
12
13    // going through array
14    while(p1<prices.size()){
15        curr     = prices[p1] - prices[p0];           // calculating current profit
16        maxprofit = curr > maxprofit ? curr : maxprofit; // updating max-profit
17        if (curr < 0) {p0 = p1;}                       // updating p0 if we find lower point
18        ++p1;
19    }
20
21    // printing the final output
22    cout << format("maxprofit = {}\n", maxprofit);
23    timer.stop();
24
25    // return
26    return(0);
27
28 }
```

122. Best Time To Buy And Sell Stock II

You are given an integer array `prices` where `prices[i]` is the price of a given stock on the `i`th day. On each day, you may decide to buy and/or sell the stock. You can only hold at most one share of the stock at any time. However, you can buy it then immediately sell it on the same day. Find and return the maximum profit you can achieve.

Examples

1. Example 1

- Input: `prices = [7,1,5,3,6,4]`
- Output: 7
- Explanation: Buy on day 2 (price = 1) and sell on day 3 (price = 5), profit = $5 - 1 = 4$. Then buy on day 4 (price = 3) and sell on day 5 (price = 6), profit = $6 - 3 = 3$. Total profit is $4 + 3 = 7$.

2. Example 2

- Input: `prices = [1,2,3,4,5]`
- Output: 4
- Explanation: Buy on day 1 (price = 1) and sell on day 5 (price = 5), profit = $5 - 1 = 4$. Total profit is 4.

3. Example 3

- Input: `prices = [7,6,4,3,1]`
- Output: 0
- Explanation: There is no way to make a positive profit, so we never buy the stock to achieve the maximum profit of 0.

Constraints

- $1 \leq \text{prices.length} \leq 3 * 10^4$
- $0 \leq \text{prices}[i] \leq 10^4$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> prices {7,1,5,3,6,4};
5
6     // setup
7     int p1      {0};           // index-pointer to buying
8     int p2      {0};           // index-pointer to selling
9     int accprofit {0};         // variable to accumulate profit
10    int currprofit {std::numeric_limits<int>::min()}; // variable to hold curr-profit
11
12    // going through this
13    while(p2 < prices.size()){
14
15        currprofit = prices[p2] - prices[p1];           // calculating current profit
16
17        if (currprofit > 0){
18            accprofit += currprofit;                   // accumulating the profit
19            p1        = p2++;                           // moving the starting point
20            continue;                                   // moving into the next iteration
21        }
22        else if (currprofit < 0){
23            p1        = p2++;                           // moving the starting point
24            continue;
25        }
26    }
```

```
26         ++p2;
27         // updating p2
28     }
29
30     // printing the max-value
31     cout << format("accprofit = {}\n", accprofit);
32
33     // return
34     return(0);
35
36 }
```

125. Valid Palindrome

A phrase is a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers. Given a string *s*, return true if it is a palindrome, or false otherwise.

Examples

1. Example 1:

- Input: *s* = "A man, a plan, a canal: Panama"
- Output: true
- Explanation: "amanaplanacanalpanama" is a palindrome.

2. Example 2:

- Input: *s* = "race a car"
- Output: false
- Explanation: "raceacar" is not a palindrome.

3. Example 3:

- Input: *s* = ""
- Output: true
- Explanation: *s* is an empty string "" after removing non-alphanumeric characters. Since an empty string reads the same forward and backward, it is a palindrome.

Constraints

- $1 \leq s.length \leq 2 * 10^5$
- s consists only of printable ASCII characters.

Code

```
1 int main(){
2
3     // input- configuration
4     auto s = string("A man, a plan, a canal: Panama");
5
6     // setup
7     auto pleft      {0};
8     auto pright     {static_cast<int>(s.size()-1)};
9     auto finaloutput {true};
10
11     // lambda to check if alphanumeric
12     auto isalphanumeric = [](const int& x){
13         if (x-65 >= 0 && 90-x >= 0) {return true;} // upper-case check
14         if (x-97 >= 0 && 122-x >= 0) {return true;} // lower-case check
15         if (x-48 >= 0 && 57-x >= 0) {return true;} // numeric check
16         return false;
17     };
18
19     // running
20     while(pleft < s.size() && pright >= 0){
21
22         // moving pleft until we find the position
23         while(pleft < s.size() && isalphanumeric(s[pleft]) == false) {++pleft;}
24         while(pright >= 0 && isalphanumeric(s[pright]) == false) {--pright;}
25     }
```

```
26     // checking bounds
27     if (pleft>=pright) {break;}
28
29     // checking if they're the same
30     if (std::tolower(s[pleft]) != std::tolower(s[pright])) {finaloutput = false; break;}
31
32     // updating pointers
33     ++pleft; --pright;
34 }
35
36 // printing
37 cout << format("final-output = {}\n", finaloutput);
38
39 // return
40 return(0);
41
42 }
```

128. Longest Consecutive Sequence

Given an unsorted array of integers `nums`, return the length of the longest consecutive elements sequence.

You must write an algorithm that runs in $O(n)$ time.

Examples

1. Example 1:

- Input: `nums = [100,4,200,1,3,2]`
- Output: 4
- Explanation: The longest consecutive elements sequence is `[1, 2, 3, 4]`. Therefore its length is 4.

2. Example 2:

- Input: `nums = [0,3,7,2,5,8,4,6,0,1]`
- Output: 9

3. Example 3:

- Input: `nums = [1,0,1,2]`
- Output: 3

Constraints

- $0 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto nums = vector<int>({0,3,7,2,5,8,4,6,0,1});
8
9     // setup
10    std::multiset<int> var00;
11
12    // trivial-cases
13    if (nums.size() <= 1) {cout << format("final-output = {}\n", nums.size()); return 0;}
14
15    // going through elements
16    for(auto x: nums) {var00.insert(x);}
17
18    // going through elements
19    int maxlength = std::numeric_limits<int>::min();
20    int temp = 1;
21    std::deque<int> var01;
22
23    for(auto x: var00){
24
25        if (var01.size()<1)          {var01.push_back(x);}
26        else{
27            // comparing previous element and current
28            if (x - var01[0] == 1)  {++temp; var01[0] = x; maxlength = max(maxlength, temp);}
29            else if(x - var01[0] == 0) {maxlength = max(maxlength, temp); continue;}
30            else                    {maxlength = max(maxlength, temp); temp = 1; var01[0] = x;}
31        }
32    }
33}
```

```
34 // returning the max-length
35 cout << format("final-output = {}\n", maxlength);
36
37 // return
38 return(0);
39
40 }
```

134. Gas Station

There are n gas stations along a circular route, where the amount of gas at the i th station is $gas[i]$. You have a car with an unlimited gas tank and it costs $cost[i]$ of gas to travel from the i th station to its next $(i + 1)$ th station. You begin the journey with an empty tank at one of the gas stations. Given two integer arrays gas and $cost$, return the starting gas station's index if you can travel around the circuit once in the clockwise direction, otherwise return -1 . If there exists a solution, it is guaranteed to be unique.

Examples

1. Example 1:

- Input: $gas = [1,2,3,4,5]$, $cost = [3,4,5,1,2]$
- Output: 3

2. Example 2:

- Input: $gas = [2,3,4]$, $cost = [3,4,3]$
- Output: -1

Constraints:

- $n == gas.length == cost.length$
- $1 \leq n \leq 10^5$
- $0 \leq gas[i], cost[i] \leq 10^4$
- The input is generated such that the answer is unique.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> gas   {1,2,3,4,5};
5     vector<int> cost  {3,4,5,1,2};
6
7     // setup
8     auto acc  {0};
9     vector<int> diffvec;
10    auto temp {0};
11    int finaloutput {-1};
12
13    // running through it
14    for(int i = 0; i<cost.size(); ++i){
15        temp  = gas[i] - cost[i];
16        acc   += temp;
17        diffvec.push_back(temp);
18    }
19    if (acc<0) {finaloutput = -1; return 0;}
20
21    // going through the diff-vec
22    acc = 0;
23    for(int i = 0; i<diffvec.size(); ++i){
24        acc += diffvec[i];
25        if (acc<0) {acc = 0; finaloutput = i+1;}
26    }
27
28
29    // printing the acc
30    cout << format("acc = {}\n", finaloutput);
31
32    // return
33    return(0);
```


34

35

}

135. Candy

There are n children standing in a line. Each child is assigned a rating value given in the integer array `ratings`. You are giving candies to these children subjected to the following requirements:

1. Each child must have at least one candy.
2. Children with a higher rating get more candies than their neighbors.
3. Return the minimum number of candies you need to have to distribute the candies to the children.

Examples

- **Example 1**

- Input: `ratings = [1,0,2]`
- Output: 5
- Explanation: You can allocate to the first, second and third child with 2, 1, 2 candies respectively.

- **Example 2**

- Input: `ratings = [1,2,2]`
- Output: 4
- Explanation: You can allocate to the first, second and third child with 1, 2, 1 candies respectively. The third child gets 1 candy because it satisfies the above two conditions.

Constraints

1. $n == \text{ratings.length}$
2. $1 \leq n \leq 2 * 10^4$
3. $0 \leq \text{ratings}[i] \leq 2 * 10^4$

Code

```
1 // main-file =====
2 int main(){
3
4     // input- configuration
5     vector<int> ratings {1,0,2};
6
7     // setup
8     auto candies      {std::vector<int>(ratings.size(),1)};
9     auto finaloutput  {static_cast<int>(candies.size())};
10    int leftrating, currrating, rightrating;
11
12    // left-pass
13    for(int i = 1; i<candies.size(); ++i){
14
15        // fetching the rating
16        leftrating = ratings[i-1];
17        currrating = ratings[i];
18
19        // fetching references to candy counts
20        int& leftcount = candies[i-1];
21        int& currcount = candies[i];
22
23        // updating based on left
```

```

24     if (currrating > leftrating){
25         currcount = leftcount+1;
26     }
27 }
28
29 // right pass
30 for(int i = ratings.size()-2; i>=0; --i){
31
32     // fetching ratings
33     currrating = ratings[i];
34     rightrating = ratings[i+1];
35
36     // fetching references to candies
37     int& curr candies = candies[i];
38     int& rightcandies = candies[i+1];
39
40     // updating based on right
41     if (currrating > rightrating){
42         curr candies = std::max(curr candies,
43                                 rightcandies + 1);
44     }
45 }
46
47 // summing up candies
48 finaloutput = std::accumulate(candies.begin(), candies.end(), 0);
49 cout << format("finaloutput = {}\n", finaloutput);
50
51 // return
52 return(0);
53
54 }

```

151. Reverse Words In A String

Given an input string *s*, reverse the order of the words. A word is defined as a sequence of non-space characters. The words in *s* will be separated by at least one space. Return a string of the words in reverse order concatenated by a single space. Note that *s* may contain leading or trailing spaces or multiple spaces between two words. The returned string should only have a single space separating the words. Do not include any extra spaces.

Examples

1. Example 1

- Input: *s* = "the sky is blue"
- Output: "blue is sky the"

2. Example 2

- Input: *s* = " hello world "
- Output: "world hello"
- Explanation: Your reversed string should not contain leading or trailing spaces.

3. Example 3

- Input: *s* = "a good example"
- Output: "example good a"
- Explanation: You need to reduce multiple spaces between two words to a single space in the reversed string.

Constraints

1. $1 \leq s.length \leq 10^4$
2. s contains English letters (upper-case and lower-case), digits, and spaces ' '.
3. There is at least one word in s.

Code

```
1 int main(){
2
3     // input- configuration
4     string s {"a good example"};
5
6     // setup
7     vector<string> listofwords;
8
9     // creating a list of words
10    int p1 {0};
11    string acc;
12    while(p1 < s.size()){
13
14        // checking if the current character is a non-space
15        if (s[p1] != ' ') {acc += s[p1];}
16        else{
17            // if acc is non-empty, flush
18            if (acc.size() != 0) {listofwords.push_back(acc); acc = "";}
19            else                {};
20        }
21
22        // moving the index-pointer forward
23        p1++;
```

```
24 }
25
26 // check if acc is unflushed
27 if (acc.size() != 0) {listofwords.push_back(acc); acc = "";}
28
29 // building the finaloutput
30 string finaloutput;
31 for(int i = listofwords.size()-1; i>=0; --i){
32     finaloutput += listofwords[i];
33     if (i!=0) [[unlikely]] {finaloutput += " ";}
34 }
35
36 // printing the finaloutput
37 cout << format("finaloutput = {}\n", finaloutput);
38
39
40 // return
41 return(0);
42
43 }
```

167. Two Sum II - Input Array Is Sorted

Given a 1-indexed array of integers `numbers` that is already sorted in non-decreasing order, find two numbers such that they add up to a specific target number. Let these two numbers be `numbers[index1]` and `numbers[index2]` where $1 \leq \text{index1} < \text{index2} \leq \text{numbers.length}$.

Return the indices of the two numbers, `index1` and `index2`, added by one as an integer array `[index1, index2]` of length 2.

The tests are generated such that there is exactly one solution. You may not use the same element twice.

Your solution must use only constant extra space.

Examples

1. Example 1:

- Input: `numbers = [2,7,11,15]`, `target = 9`
- Output: `[1,2]`
- Explanation: The sum of 2 and 7 is 9. Therefore, `index1 = 1`, `index2 = 2`. We return `[1, 2]`.

2. Example 2:

- Input: `numbers = [2,3,4]`, `target = 6`
- Output: `[1,3]`
- Explanation: The sum of 2 and 4 is 6. Therefore `index1 = 1`, `index2 = 3`. We return `[1, 3]`.

3. Example 3:

- Input: `numbers = [-1,0]`, `target = -1`

- Output: [1,2]
- Explanation: The sum of -1 and 0 is -1. Therefore index1 = 1, index2 = 2. We return [1, 2].

Constraints

- $2 \leq \text{numbers.length} \leq 3 * 10^4$
- $-1000 \leq \text{numbers}[i] \leq 1000$
- numbers is sorted in non-decreasing order.
- $-1000 \leq \text{target} \leq 1000$
- The tests are generated such that there is exactly one solution.

Code

```
1 int main(){
2
3     // input- configuration
4     auto numbers = vector<int>{2,7,11,15};
5     auto target  = 9;
6
7     // setup
8     std::vector<int> finalOutput;
9     auto left     {0};
10    auto right    {static_cast<int>(numbers.size()-1)};
11    auto currsum  {0};
12
13    // usual left-right loop
14    while (left < right){
```

```
15
16 // checking sum of two values
17 currsum = numbers[left] + numbers[right];
18
19 // comparing against target
20 if (currsum > target)    {--right;}
21 else if (currsum < target) {++left;}
22 else {
23     finalOutput.push_back( left+1);
24     finalOutput.push_back( right+1);
25     break;
26 }
27 }
28
29 // printign the final output
30 cout << format("finaloutput = {}\n", finalOutput);
31
32 // return
33 return(0);
34
35 }
```

169 Majority Element

Given an array `nums` of size `n`, return the majority element. The majority element is the element that appears more than $\lfloor n/2 \rfloor$ times. You may assume that the majority element always exists in the array.

Examples

- **Example 1**

- Input: `nums = [3,2,3]`
- Output: `3`

- **Example 2**

- Input: `nums = [2,2,1,1,1,2,2]`
- Output: `2`

Constraints:

- `n == nums.length`
- $1 \leq n \leq 5 * 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

Code

```
1  int main(){
2
3      // input- configuration
4      vector<int> nums {2,2,1,1,1,2,2};
5
6      // setup
7      unordered_map<int, int> histogram;
8      int max_element {std::numeric_limits<int>::min()};
9      int max_count {std::numeric_limits<int>::min()};
10     int updated_count {0};
11
12     // going through the elements
13     for(int i = 0; i<nums.size(); ++i){
14
15         // adding to histogram
16         if (histogram.find(nums[i]) == histogram.end()) {histogram[nums[i]] = 1; updated_count = 0;}
17         else {++histogram[nums[i]]; updated_count = histogram[nums[i]];}
18
19         // keeping track of max-element
20         if (updated_count > max_count) {max_element = nums[i]; max_count = updated_count;}
21
22     }
23
24     // printing the final output
25     cout << format("nums = "); fpv(nums);
26     cout << format("max-count = {}\n", max_count);
27
28     // return
29     return(0);
30
31 }
```

189 Rotate Array

Given an integer array `nums`, rotate the array to the right by `k` steps, where `k` is non-negative.

Examples

- **Example 1**
 - Input: `nums = [1,2,3,4,5,6,7]`, `k = 3`
 - Output: `[5,6,7,1,2,3,4]`
- **Example 1**
 - Input: `nums = [-1,-100,3,99]`, `k = 2`
 - Output: `[3,99,-1,-100]`

Constraints

- $1 \leq \text{nums.length} \leq 10^5$
- $-2^31 \leq \text{nums}[i] \leq 2^31 - 1$
- $0 \leq k \leq 10^5$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {-1,-100,3,99};
5     int k {2};
6
7     // setup
8     Stopwatch timer;                                // setting up the timer
9     k = k %static_cast<int>(nums.size());            // to ensure that the value is within range
10
11     int source      {0};
12     int temp_source {nums[source]};
13     int temp        {0};
14     int destination {0};
15
16     vector<bool> sourcelist(nums.size(), false);
17
18     // going through nums
19     for(int i = 0; i < nums.size(); ++i){
20
21         // check if curent-source has been taken care of
22         if (sourcelist[source] == true){
23             source      = (source+1) % nums.size();
24             temp_source = nums[source];
25         }
26
27         source      = source % nums.size(); // code to ensure range
28         destination = (source + k)%nums.size(); // calculating the index we'll be writing to
29         sourcelist[source] = true;           // updating source-list
30
31         temp        = nums[destination]; // safe-keeping the destination value
32         nums[destination] = temp_source;  // storing new value at destination-index
33
34     }
```

```
34     source          = destination;           // updating source-index
35     temp_source      = temp;                 // updating source-value
36 }
37
38 // printing the output
39 cout << format("nums = "); fpv(nums);        // printing the updated array, "nums"
40 timer.stop();                                // printing the time taken
41
42 // return
43 return(0);
44 }
```

202. Happy Number

Write an algorithm to determine if a number n is happy.

A happy number is a number defined by the following process:

1. Starting with any positive integer, replace the number by the sum of the squares of its digits.
2. Repeat the process until the number equals 1 (where it will stay), or it loops endlessly in a cycle which does not include 1.
3. Those numbers for which this process ends in 1 are happy.

Return true if n is a happy number, and false if not.

Examples

1. Example 1:

- Input: $n = 19$
- Output: true
- Explanation:
 - $1^2 + 9^2 = 82$
 - $8^2 + 2^2 = 68$
 - $6^2 + 8^2 = 100$
 - $1^2 + 0^2 + 0^2 = 1$

2. Example 2:

- Input: $n = 2$
- Output: false

Constraints

- $1 \leq n \leq 2^31 - 1$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto n {19};
8
9     // trivial case
10    if (n == 4 || n == 0) {cout << format("final-output = false\n"); return 0;}
11
12    // setting up lambda
13    auto fSumDigitSquares = [](int n) -> int
14    {
15        auto sum {0};
16        auto digit {-1};
17        while(n!=0){
18            digit = n%10;
19            sum += digit*digit;
20            n = n/10;
21        }
22        return sum;
23    };
24
25    // calling the function
26    while (n != 1){
27        // calculating digits sums
```

```
28     n = fSumDigitSquares(n); cout << format("n = {}\n", n);
29     if (n == 4 || n == 0)      {cout << format("final-output = false\n"); return 0;}
30 }
31
32 // printing and returning
33 cout << format("final-output = true \n"); return 0;
34
35 }
```

205. Isomorphic Strings

Given two strings s and t , determine if they are isomorphic.

Two strings s and t are isomorphic if the characters in s can be replaced to get t .

All occurrences of a character must be replaced with another character while preserving the order of characters. No two characters may map to the same character, but a character may map to itself.

Examples

1. Example 1:

- Input: $s = \text{"egg"}, t = \text{"add"}$
- Output: true
- Explanation: The strings s and t can be made identical by:
 - Mapping 'e' to 'a'.
 - Mapping 'g' to 'd'.

2. Example 2:

- Input: $s = \text{"foo"}, t = \text{"bar"}$
- Output: false
- Explanation: The strings s and t can not be made identical as 'o' needs to be mapped to both 'a' and 'r'.

3. Example 3:

- Input: $s = \text{"paper"}, t = \text{"title"}$
- Output: true

Constraints:

- $1 \leq s.length \leq 5 * 10^4$
- $t.length == s.length$
- s and t consist of any valid ascii character.

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     string s = {"egg"};
8     string t = {"add"};
9
10    // making mapping
11    unordered_map<char, char> mapping;
12    std::unordered_set<char> destinations;
13    string      r;
14
15    // going through string
16    for(int i = 0; i<s.size(); ++i){
17
18        // checking if two strings are different
19        if (s[i] != t[i]){
20            // checking if we already have a mapping for this
21            if (mapping.find(s[i]) == mapping.end()){
22
23                // before we add, we need to check if t[i] is already used as a destination
```

```

24     if (destinations.find(t[i]) != destinations.end()) {
25         cout << format("final-output = true \n");
26         return 0;
27     }
28
29     // adding new mapping
30     mapping[s[i]] = t[i];
31     destinations.insert(t[i]);
32 }
33 r.push_back(mapping[s[i]]);
34 }
35 else{
36     // checking if we already have a mapping for this
37     if (mapping.find(s[i]) == mapping.end()){
38
39         // before we add, we need to check if t[i] is already used as a destination
40         if (destinations.find(t[i]) != destinations.end()) {
41             cout << format("final-output = true \n");
42             return 0;
43         }
44
45         // adding new mapping
46         mapping[s[i]] = s[i];
47         destinations.insert(s[i]);
48     }
49     r.push_back(mapping[s[i]]);
50 }
51
52 // if what we have so far is different, we're sending it back
53 string s_subset(t.begin(), t.begin() + r.size());
54 if(s_subset != r) {cout << format("final-output = false \n"); return 0;}
55
56 }
57
58 // return true in the end

```

```
59     cout << format("final-output = true \n");
60
61     // return
62     return(0);
63 }
```

209. Minimum Size Subarray Sum

Given an array of positive integers `nums` and a positive integer `target`, return the minimal length of a subarray whose sum is greater than or equal to `target`. If there is no such subarray, return 0 instead.

Examples

1. Example 1:

- Input: `target = 7`, `nums = [2,3,1,2,4,3]`
- Output: 2
- Explanation: The subarray `[4,3]` has the minimal length under the problem constraint.

2. Example 2:

- Input: `target = 4`, `nums = [1,4,4]`
- Output: 1

3. Example 3:

- Input: `target = 11`, `nums = [1,1,1,1,1,1,1,1]`
- Output: 0

Constraints

- $1 \leq \text{target} \leq 10^9$

- $1 \leq \text{nums.length} \leq 10^5$
- $1 \leq \text{nums}[i] \leq 10^4$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {1,2,3,4,5};
5     auto target {15};
6
7     // setup
8     auto finaloutput {std::numeric_limits<int>::max()};
9     auto pleft {0};
10    auto sum {nums[pleft]};
11    auto i {1};
12
13    // in case the first element itself is greater
14    if (sum > target) {finaloutput = 1;}
15
16    // lambda to update finaloutput
17    auto updatefinaloutput = [&sum,
18                             &target,
19                             &finaloutput,
20                             &i,
21                             &pleft,
22                             &nums]() -> void{
23
24        auto numelements = i - pleft + 1;
25        finaloutput = numelements < finaloutput ? numelements : finaloutput;
26        sum -= nums[pleft++];
27    };
```



```
28
29 // going through the array
30 for(; i<nums.size(); ++i){
31
32     // adding to sum
33     sum += nums[i];
34
35     // updating
36     while (sum>=target) {updatefinaloutput();}
37 }
38
39 // updating
40 if(finaloutput == std::numeric_limits<int>::max()) {finaloutput = 0;}
41
42 // printing the finaloutput
43 cout << format("finaloutput = {}\n", finaloutput);
44
45 // return
46 return(0);
47
48 }
```

219. Contains Duplicate II

Given an integer array `nums` and an integer `k`, return `true` if there are two distinct indices `i` and `j` in the array such that `nums[i] == nums[j]` and $\text{abs}(i - j) \leq k$.

Examples

1. **Example 1:**

- Input: `nums = [1,2,3,1]`, `k = 3`
- Output: `true`

2. **Example 2:**

- Input: `nums = [1,0,1,1]`, `k = 1`
- Output: `true`

3. **Example 3:**

- Input: `nums = [1,2,3,1,2,3]`, `k = 2`
- Output: `false`

Constraints

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $0 \leq k \leq 10^5$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto nums = std::vector<int>({1,2,3,1,2,3});
8     auto k     {2};
9
10    // setup
11    std::unordered_map<int, int> valueToIndex;
12
13    // going through the array
14    for(int i = 0; i<nums.size(); ++i){
15
16        // adding current element to the hamp
17        if (valueToIndex.find(nums[i]) == valueToIndex.end()){
18            // if it doesn't exist, we add to it
19            valueToIndex[nums[i]] = i;
20        }
21        else{
22            // if it already exists, calculating distance from the first index
23            if (i - valueToIndex[nums[i]] <= k) {cout << format("final-output = true\n");}
24            else {valueToIndex[nums[i]] = i;}
25        }
26    }
27
28    // returning false in the final case
29    cout << format("final-output = false\n");
30
31    // return
32    return(0);
33}
```


226. Invert Binary Tree

Given the root of a binary tree, invert the tree, and return its root.

Examples

1. **Example 1:**

- Input: root = [4,2,7,1,3,6,9]
- Output: [4,7,2,9,6,3,1]

2. **Example 2:**

- Input: root = [2,1,3]
- Output: [2,3,1]

3. **Example 3:**

- Input: root = []
- Output: []

Constraints

- The number of nodes in the tree is in the range [0, 100].
- $-100 \leq \text{Node.val} \leq 100$

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto root      {new TreeNode(4)};
8     root->left      = new TreeNode(2);
9     root->right      = new TreeNode(7);
10    root->left->left   = new TreeNode(1);
11    root->left->right  = new TreeNode(3);
12    root->right->left  = new TreeNode(6);
13    root->right->right = new TreeNode(9);
14
15    // setup
16    std::function<void(TreeNode*)> fTwist = [&fTwist](TreeNode* root){
17        // base-case
18        if (root == nullptr) return;
19
20        // switching left and right
21        fTwist(root->left);
22        fTwist(root->right);
23
24        // twisting current branches
25        auto temp = root->left;
26        root->left = root->right;
27        root->right = temp;
28
29        // returning
30        return;
31    };
32
33    // going flipping through everything
```

```
34     fTwist(root);  
35  
36     // return  
37     return(0);  
38  
39 }
```

228. Summary Ranges

You are given a sorted unique integer array `nums`.

A range `[a,b]` is the set of all integers from `a` to `b` (inclusive).

Return the smallest sorted list of ranges that cover all the numbers in the array exactly. That is, each element of `nums` is covered by exactly one of the ranges, and there is no integer `x` such that `x` is in one of the ranges but not in `nums`.

Each range `[a,b]` in the list should be output as:

"a→b" if `a != b`

"a" if `a == b`

Examples

1. Example 1:

- Input: `nums = [0,1,2,4,5,7]`
- Output: `["0→2","4→5","7"]`
- Explanation: The ranges are:
 - `[0,2] ⇒ "0→2"`
 - `[4,5] ⇒ "4→5"`
 - `[7,7] ⇒ "7"`

2. Example 2:

- Input: `nums = [0,2,3,4,6,8,9]`
- Output: `["0","2→4","6","8→9"]`

- Explanation: The ranges are:
 - $[0,0] \implies "0"$
 - $[2,4] \implies "2 \rightarrow 4"$
 - $[6,6] \implies "6"$
 - $[8,9] \implies "8 \rightarrow 9"$

Constraints

- $0 \leq \text{nums.length} \leq 20$
- $-2^31 \leq \text{nums}[i] \leq 2^31 - 1$
- All the values of nums are unique.
- nums is sorted in ascending order.

Code

```

1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     auto nums = vector<int>({0,1,2,4,5,7});
8
9     // trivial-case
10    if (nums.size() == 0) {cout << format("final-output = {}\n", vector<string>()); return 0;}
11
12    // stup

```

```

13 auto arrow {"->"};
14 auto p1 {0};
15 auto p2 {0};
16 vector<string> finalOutput;
17
18 // while loop
19 while (p2<nums.size()){
20
21     // checking prev element
22     if (nums[p2] <= 1 + nums[p2-1]) {++p2;}
23     else{
24         if (p1!=p2-1) {finalOutput.push_back(std::to_string(nums[p1]) + arrow + std::to_string(nums[p2-1]));}
25         else {finalOutput.push_back(std::to_string(nums[p2-1]));}
26         p1 = p2++;
27     }
28 }
29
30 // checking if p1 and p2 areright ne
31 if (p1!=p2-1) {finalOutput.push_back(std::to_string(nums[p1]) + arrow + std::to_string(nums[p2-1]));}
32 else {finalOutput.push_back(std::to_string(nums[p2-1]));}
33
34 // returning restul
35 cout << format("final-output = {}\n", finalOutput);
36
37 // return
38 return(0);
39
40 }

```

238. Product of Array Except Self

Given an integer array `nums`, return an array `answer` such that `answer[i]` is equal to the product of all the elements of `nums` except `nums[i]`. The product of any prefix or suffix of `nums` is guaranteed to fit in a 32-bit integer. You must write an algorithm that runs in $O(n)$ time and without using the division operation.

Examples

1. Example 1

- Input: `nums = [1,2,3,4]`
- Output: `[24,12,8,6]`

2. Example 2

- Input: `nums = [-1,1,0,-3,3]`
- Output: `[0,0,9,0,0]`

Constraints

1. $2 \leq \text{nums.length} \leq 10^5$
2. $-30 \leq \text{nums}[i] \leq 30$
3. The input is generated such that `answer[i]` is guaranteed to fit in a 32-bit integer

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {1,2,3,4};
5
6     // setup
7     vector<int> nums_left(nums.size(), 1);
8     vector<int> nums_right(nums.size(), 1);
9     int acc_left {1};
10    int acc_right {1};
11
12    // runs
13    for(int i = 0; i<nums.size(); ++i){
14
15        // source-indices
16        int source_left {i-1};
17        int source_right {static_cast<int>(nums.size())-i};
18
19        // printing values
20        acc_left  *= source_left == -1      ? 1 : nums[source_left];
21        acc_right *= source_right == nums.size() ? 1 : nums[source_right];
22
23        // writing to the two values
24        nums_left[i] = acc_left;
25        nums_right[nums.size()-i-1] = acc_right;
26    }
27
28    // building the accumulated value
29    vector<int> finaloutput(nums.size(),1);
30    for(int i = 0; i< finaloutput.size(); ++i){
31        finaloutput[i] = nums_left[i] * nums_right[i];
32    }
33}
```

```
34 // printing
35 cout << format("finaloutput = "); fPrintVector(finaloutput);
36
37 // return
38 return(0);
39
40 }
```

242. Valid Anagram

Given two strings s and t , return true if t is an anagram of s , and false otherwise.

Examples

1. Example 1:

- Input: $s = \text{"anagram"}, t = \text{"nagaram"}$
- Output: true

2. Example 2:

- Input: $s = \text{"rat"}, t = \text{"car"}$
- Output: false

Constraints

- $1 \leq s.length, t.length \leq 5 * 10^4$
- s and t consist of lowercase English letters.

Code

```
1 int main(){
2
3     // starting timer
4     Timer timer;
5
6     // input- configuration
7     string s {"anagram"};
8     string t {"nagaram"};
9
10    // setup
11    std::vector<int> s_count(26,0);
12    std::vector<int> t_count(26,0);
13
14    // building count-vector for both
15    for(auto x: s) ++s_count[static_cast<int>(x)-97];
16    for(auto x: t) ++t_count[static_cast<int>(x)-97];
17
18    // comparing the two
19    for (int i = 0; i<s_count.size(); ++i) {
20
21        // element-wise checking
22        if (s_count[i] != t_count[i]) {cout << format("final-output = false \n");}
23
24    }
25
26    // returning
27    cout << format("final-output = true \n");
28
29    // return
30    return(0);
31
32 }
```

274. H-Index

Given an array of integers citations where citations[i] is the number of citations a researcher received for their ith paper, return the researcher's h-index. According to the definition of h-index on Wikipedia: The h-index is defined as the maximum value of h such that the given researcher has published at least h papers that have each been cited at least h times.

Examples

1. Example 1

- Input: citations = [3,0,6,1,5]
- Output: 3
- Explanation: [3,0,6,1,5] means the researcher has 5 papers in total and each of them had received 3, 0, 6, 1, 5 citations respectively. Since the researcher has 3 papers with at least 3 citations each and the remaining two with no more than 3 citations each, their h-index is 3.

2. Example 2

- Input: citations = [1,3,1]
- Output: 1

Constraints

1. $n == \text{citations.length}$
2. $1 \leq n \leq 5000$
3. $0 \leq \text{citations}[i] \leq 1000$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> citations {3,0,6,1,5};
5
6     // sorting the citations first
7     std::sort(citations.begin(), citations.end(),
8               [](const int& a, const int& b) {return a>b;});
9
10    // running accumulations
11    auto hvalue = {0};
12    for(int i = 0; i<citations.size(); ++i){
13        if (citations[i] >= (i+1))    {hvalue = i+1;}
14    }
15
16    // printing citations
17    cout << format("hvalue = {}\n", hvalue);
18
19    // return
20    return(0);
21
22 }
```

283. Move Zeros

Given an integer array `nums`, move all 0's to the end of it while maintaining the relative order of the non-zero elements. Note that you must do this in-place without making a copy of the array.

Examples

1. Example 1:

- Input: `nums = [0,1,0,3,12]`
- Output: `[1,3,12,0,0]`

2. Example 2:

- Input: `nums = [0]`
- Output: `[0]`

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

Code

```
1 int main(){
2
3     // input- configuration
4     vector<int> nums {0,1,0,3,12};
5
6     // setup
7     int explorer {0};
8     int anchor {0};
9
10    // going through the nums
11    while(explorer < nums.size()){
12
13        // moving explorer until we arrive at a non-zero value
14        while(explorer < nums.size() && nums[explorer] == 0) {explorer++;}
15
16        // copying value
17        if (explorer<nums.size() && anchor <nums.size())
18            nums[anchor++] = nums[explorer++];
19    }
20
21    // zeroing out the rest
22    while(anchor < nums.size()) {nums[anchor++] = 0;}
23
24    // printing the finaloutput
25    cout << format("finaloutput = "); fPrintVector(nums);
26
27    // return
28    return(0);
29
30 }
```

345. Reverse Vowels Of A String

Given a string *s*, reverse only all the vowels in the string and return it. The vowels are 'a', 'e', 'i', 'o', and 'u', and they can appear in both lower and upper cases, more than once.

Examples

1. Example 1:

- Input: *s* = "IceCreAm"
- Output: "AceCreIm"
- Explanation: The vowels in *s* are ['I', 'e', 'e', 'A']. On reversing the vowels, *s* becomes "AceCreIm".

2. Example 2:

- Input: *s* = "leetcode"
- Output: "leotcede"

Constraints

- $1 \leq s.length \leq 3 * 10^5$
- *s* consist of printable ASCII characters.

Code

```
1  int main(){
2
3      // input- configuration
4      string s {"leetcode"};
5
6      // going through the string
7      string vowels {"aeiouAEIOU"};
8      vector<int> vowel_indices;
9      string reversed_vowels;
10     string finaloutput = s;
11
12     // going through the string
13     for(int i = 0; i<s.size(); ++i){
14         if (vowels.find(s[i]) != string::npos){
15             reversed_vowels+=s[i];
16             vowel_indices.push_back(i);
17         }
18     }
19
20     // refilling the indices
21     for(int i = 0; i<vowel_indices.size(); ++i){
22         finaloutput[vowel_indices[i]] = reversed_vowels[reversed_vowels.size()-1-i];
23     }
24
25     // printing the final output
26     cout << format("finaloutput = {}\n", finaloutput);
27
28     // return
29     return(0);
30
31 }
```

392. Is Subsequence

Given two strings s and t , return true if s is a subsequence of t , or false otherwise.

A subsequence of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not).

Examples

1. Example 1:

- Input: $s = \text{"abc"}, t = \text{"ahbgdc"}$
- Output: true

2. Example 2:

- Input: $s = \text{"axc"}, t = \text{"ahbgdc"}$
- Output: false

Constraints

- $0 \leq s.length \leq 100$
- $0 \leq t.length \leq 10^4$
- s and t consist only of lowercase English letters.

Code

```
1 int main(){
2
3     // input- configuration
4     string s    {"abc"};
5     string t    {"ahbgdc"};
6
7     // setup
8     int i = 0;
9
10    // going through the elements
11    for(auto x: t) if (x == s[i]) ++i;
12
13    // returning
14    cout << format("final-output = {}\n", static_cast<bool>(i == s.size())) ;
15
16
17    // return
18    return(0);
19
20 }
```

394. Decode String

Given an encoded string, return its decoded string.

The encoding rule is: $k[\text{encoded_string}]$, where the `encoded_string` inside the square brackets is being repeated exactly k times. Note that k is guaranteed to be a positive integer.

You may assume that the input string is always valid; there are no extra white spaces, square brackets are well-formed, etc. Furthermore, you may assume that the original data does not contain any digits and that digits are only for those repeat numbers, k . For example, there will not be input like `3a` or `2[4]`.

The test cases are generated so that the length of the output will never exceed 10^5 .

Examples

1. Example 1:

- Input: `s = "3[a]2[bc]"`
- Output: `"aaabcbc"`

2. Example 2:

- Input: `s = "3[a2[c]]"`
- Output: `"accaccacc"`

3. Example 3:

- Input: `s = "2[abc]3[cd]ef"`
- Output: `"abccabccdcddcdef"`

Constraints:

- $1 \leq s.length \leq 30$
- s consists of lowercase English letters, digits, and square brackets '['].
- s is guaranteed to be a valid input.
- All the integers in s are in the range [1, 300].

Code

```
1 int main(){
2
3     // input- configuration
4     string s {"100[leetcode]"};
5
6     // running
7     std::stack<char> mystack;           // stack
8     string temp;                       // temporary string used for decoding
9     int repcount {1};                 // used for decoding
10
11     // going through the inputs
12     for(int i = 0; i<s.size(); ++i){
13
14         if(s[i] != '[') {mystack.push(s[i]);} // pushing characters to stack until we
15         // arrive at "]"
16         else{
17             temp = ""; // initializing temporary string
18             while(mystack.top() != '[') { // expanding mini-string until we arrive at
19                 temp = mystack.top() + temp;
20                 mystack.pop();
21             }
22             mystack.push(temp);
23         }
24     }
25 }
```

```

20     }
21
22     mystack.pop(); // removing "["
23
24     // calculating the repcount
25     string numberasstring = "";
26     while(mystack.size() != 0 &&
27           mystack.top() - '0' >= 0 && '9' - mystack.top() >= 0)
28     {
29         numberasstring = mystack.top() + numberasstring;
30         mystack.pop();
31     }
32     repcount = std::stoi(numberasstring);
33
34     // mini-decoding
35     int multitempsize = repcount * temp.size(); // calculating size after multiplication
36     for(int j = 0; j<multitempsize; ++j) { // filling up the stack with decoded content
37         mystack.push(temp[j%temp.size()]);
38     }
39 }
40 }
41
42 // creating the final output
43 string finaloutput;
44 while(mystack.size()){
45     finaloutput = mystack.top() + finaloutput;
46     mystack.pop();
47 }
48
49 // printing the final output
50 cout << format("finaloutput = {}\n", finaloutput);
51
52 // return
53 return(0);
54

```


443. String Compression

Given an array of characters `chars`, compress it using the following algorithm:

Begin with an empty string `s`. For each group of consecutive repeating characters in `chars`:

1. If the group's length is 1, append the character to `s`.
2. Otherwise, append the character followed by the group's length.

The compressed string `s` should not be returned separately, but instead, be stored in the input character array `chars`. Note that group lengths that are 10 or longer will be split into multiple characters in `chars`. After you are done modifying the input array, return the new length of the array. You must write an algorithm that uses only constant extra space.

Examples

1. Example 1:

- Input: `chars = ["a","a","b","b","c","c","c"]`
- Output: Return 6, and the first 6 characters of the input array should be: `["a","2","b","2","c","3"]`
- Explanation: The groups are "aa", "bb", and "ccc". This compresses to "a2b2c3".

2. Example 2:

- Input: `chars = ["a"]`
- Output: Return 1, and the first character of the input array should be: `["a"]`
- Explanation: The only group is "a", which remains uncompressed since it's a single character.

3. Example 3:

- Input: chars = ["a","b","b","b","b","b","b","b","b","b","b","b","b"]
- Output: Return 4, and the first 4 characters of the input array should be: ["a","b","1","2"].
- Explanation: The groups are "a" and "bbbbbbbbbbbb". This compresses to "ab12".

Constraints

- $1 \leq \text{chars.length} \leq 2000$
- chars[i] is a lowercase English letter, uppercase English letter, digit, or symbol.

Code

```
1 int main(){
2
3     // input- configuration
4     vector<char> chars {'a','b','b','b','b','b','b','b','b','b','b','b','b'};
5
6     // going through the character
7     int p1          {0};
8     char runningchar {};
9     char curr       {};
10    int count        {0};
11    string finaloutput;
12
13    // going through the inputs
14    while(p1<chars.size()){
15
16        // getting current tchar
```

```

17     curr = chars[p1];
18
19     // increasing count
20     if (count == 0)           {runningchar = chars[p1]; ++count;}
21     else if(curr == runningchar) {++count;}
22     else if(curr != runningchar) {
23         finaloutput += runningchar; // writing character to current pointer
24         if (count != 1)
25             finaloutput += std::to_string(count); // increasing write-pointer
26         runningchar = curr;
27         count = 1;
28     }
29
30     // increasing pointer
31     ++p1;
32 }
33
34 // flushing out
35 if (count != 0){
36     finaloutput += runningchar; // writing character to current pointer
37     if (count != 1)
38         finaloutput += std::to_string(count); // increasing write-pointer
39 }
40
41 // writing to input
42 for(int i = 0; i<finaloutput.size(); ++i){
43     chars[i] = finaloutput[i];
44 }
45
46 // printing the final output
47 cout << format("finaloutput = {}\n", finaloutput);
48 cout << "chars = "; fPrintVector(chars);
49 cout << format("return-value = {}\n", finaloutput.size());
50
51 // return

```

```
52     return(0);
53
54 }
```
