

Website Designing Assignments

Introduction to Website Design and HTML Basics

Theory Assignments ::

1.Explain the structure of an HTML document and the purpose of DOCTYPE.

Answer: (a) The basic structure of an HTML document is defined by nested `<html>`, `<head>`, and `<body>` tags. The `<!DOCTYPE html>` declaration is an instruction to the web browser about the version of HTML the page is written in.

The `<!DOCTYPE html>` declaration ensures the browser renders the page in "standards mode," following modern HTML5 specifications. Without it, the browser might use "quirks mode," which can lead to inconsistent rendering across different browsers.

Within the document, the `<html>` tag is the root element. The `<head>` section contains meta-information about the document, such as the title, links to stylesheets, and scripts. The `<body>` section contains all the visible content of the webpage, such as text, images, and links.

2.List and explain at least five common HTML tags used in website design.

Answer: (a) Five common HTML tags used in website design are `<h1>` to `<h6>`, `<p>`, `<a>`, `<img>`, and `<div>`.

`<h1>` to `<h6>` (Heading tags): Used to define headings and subheadings, with `<h1>` being the most important and `<h6>` the least. They help structure content hierarchically.

`<p>` (Paragraph tag): Defines a block of text as a paragraph, automatically adding space before and after the content.

`<a>` (Anchor tag): Creates hyperlinks to link to other web pages or resources. The `href` attribute specifies the destination URL.

`<img>` (Image tag): Embeds an image into the webpage. The `src` attribute specifies the image source file, and the `alt` attribute provides alternative text for accessibility.

`<div>` (Division tag): A generic container used to group other HTML elements. It is often used with CSS for layout and styling purposes.

3. Describe the difference between block-level and inline elements in HTML.

Answer: (a) Block-level elements always start on a new line and occupy the full available width of the page, while inline elements do not start on a new line and only take up as much width as necessary for their content.

Block-level elements: Examples include `<div>`, `<p>`, `<h1>` to `<h6>`, and `<ul>/<ol>`. They create larger structures and sections of content.

Inline elements: Examples include `<span>`, `<a>`, `<img>`, and `<strong>/<em>`. They are typically used to format text within a block-level element.