

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

## Experiment No.:- 11

### **Title:- Array**

### **List:-**

- 1. Create a Python list of the first 10 natural numbers. Print the 5th element using indexing.**

```
def list():  
  
    natural_numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]  
  
    print(f"List: {natural_numbers}")  
  
    fifth_element = natural_numbers[4]  
  
    print(f"The 5th element (at index 4) is: {fifth_element}")  
  
    list()
```

```
List: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]  
The 5th element (at index 4) is: 5
```

- 2. Make a list of 10 random integers. Slice the list to print only the first 5 elements.**

```
import random  
  
def slice():  
  
    random_numbers = [random.randint(1, 100) for _ in range(10)]  
  
    print(f"Original 10 numbers: {random_numbers}")  
  
    first_five = random_numbers[:5]  
  
    print(f"The first 5 elements: {first_five}")  
  
    slice()
```

```
Original 10 numbers: [92, 25, 91, 62, 13, 10, 10, 78, 31, 55]  
The first 5 elements: [92, 25, 91, 62, 13]
```

- 3. Create a list [1, 2, 3, 4, 5]. Append the number 6 and print the list.**

```
def append():  
  
    my_list = [1, 2, 3, 4, 5]  
  
    print(f"Original list: {my_list}")  
  
    my_list.append(6)
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
print(f"List after appending 6: {my_list}")
```

```
append()
```

```
Original list: [1, 2, 3, 4, 5]
List after appending 6: [1, 2, 3, 4, 5, 6]
```

**4. Create a list [10, 20, 30, 40, 50]. Remove the element at index 2.**

```
def remove():
```

```
my_list = [10, 20, 30, 40, 50]
```

```
print(f"Original list: {my_list}")
```

```
del my_list[2]
```

```
print(f"List after removing element at index 2: {my_list}")
```

```
if __name__ == "__main__":
```

```
remove()
```

```
Original list: [10, 20, 30, 40, 50]
List after removing element at index 2: [10, 20, 40, 50]
```

**5. Create a list [1,2,3,4,5]. Replace the 3rd element with 99.**

```
def replace():
```

```
my_list = [1, 2, 3, 4, 5]
```

```
print(f"Original list: {my_list}")
```

```
my_list[2] = 99
```

```
print(f"List after replacing 3rd element with 99: {my_list}")
```

```
if __name__ == "__main__":
```

```
replace()
```

```
Original list: [1, 2, 3, 4, 5]
List after replacing 3rd element with 99: [1, 2, 99, 4, 5]
```

**6. Create two lists [1,2,3] and [4,5,6]. Concatenate them.**

```
def concatenation():
```

```
list_a = [1, 2, 3]
```

```
list_b = [4, 5, 6]
```

```
print(f"List A: {list_a}")
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
print(f"List B: {list_b}")

combined_list = list_a + list_b

print(f"Concatenated list: {combined_list}")

if __name__ == "__main__":

    concatenation()
```

```
List A: [1, 2, 3]
List B: [4, 5, 6]
Concatenated list: [1, 2, 3, 4, 5, 6]
```

**7. Create a nested list [[1,2,3], [4,5,6], [7,8,9]]. Print the element 5.**

```
def nested():

    nested_list = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]

    print(f"Nested list: {nested_list}")

    element_five = nested_list[1][1]

    print(f"The element 5 is found at index [1][1]: {element_five}")

    if __name__ == "__main__":

        nested()
```

```
Nested list: [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
The element 5 is found at index [1][1]: 5
```

**8. Create a list of numbers from 1 to 20. Slice and print only the even numbers.**

```
def step_slicing():

    numbers_20 = list(range(1, 21))

    print(f"Full list (1-20): {numbers_20}")

    even_numbers = numbers_20[1::2]

    print(f"Even numbers only (sliced with step 2): {even_numbers}")

    if __name__ == "__main__":
```

```
Full list (1-20): [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20]
Even numbers only (sliced with step 2): [2, 4, 6, 8, 10, 12, 14, 16, 18, 20]
```

```
step_slicing()
```

Name : Vaishnavi shinde


Roll No.: C-28

SPP-II

## Array:-

### 1. Create an integer array [10,20,30,40,50]. Print the third element.


```
def indexing():  
  
    integer_list = [10, 20, 30, 40, 50]  
  
    print(f"List created: {integer_list}")  
  
    third_element = integer_list[2]  
  
    print(f"The third element (at index 2) is: {third_element}")  
  
if __name__ == "__main__":  
  
    indexing()
```



```
Array created (Type 'i'): array('i', [1, 2, 3, 4, 5])  
Sliced elements (index 1 to 3): array('i', [2, 3, 4])
```

### 2. Create an array of type 'i' (integers). Insert numbers from 1 to 5. Slice and print elements at index 1–3.

```
import array  
  
def run_exercise_2():  
  
    my_array = array.array('i', [1, 2, 3, 4, 5])  
  
    print(f"Array created (Type 'i'): {my_array}")  
  
    sliced_elements = my_array[1:4]  
  
    print(f"Sliced elements (index 1 to 3): {sliced_elements}")  
  
if __name__ == "__main__":  
  
    run_exercise_2()
```



```
List created: [10, 20, 30, 40, 50]  
The third element (at index 2) is: 30
```

### 3. Create an integer array [2,4,6,8,10]. Append 12 to the array.

```
def append():  
  
    integer_list = [2, 4, 6, 8, 10]  
  
    print(f"Original list: {integer_list}")  
  
    integer_list.append(12)  
  
    print(f"List after appending 12: {integer_list}")
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
if __name__ == "__main__":
```

```
    append()
```

```
Original list: [2, 4, 6, 8, 10]
List after appending 12: [2, 4, 6, 8, 10, 12]
```

**4. Create an array [5,10,15,20,25]. Remove the element 15.**

```
def remove():
```

```
    my_list = [5, 10, 15, 20, 25]
```

```
    print(f"Original list: {my_list}")
```

```
    my_list.remove(15)
```

```
    print(f"List after removing 15: {my_list}")
```

```
if __name__ == "__main__":
```

```
    remove()
```

```
Original list: [5, 10, 15, 20, 25]
List after removing 15: [5, 10, 20, 25]
```

**5. Create two arrays [1,2,3] and [4,5,6]. Extend the first array with the second**

```
def extend():
```

```
    list_a = [1, 2, 3]
```

```
    list_b = [4, 5, 6]
```

```
    print(f"List A: {list_a}")
```

```
    print(f"List B: {list_b}")
```

```
    list_a.extend(list_b)
```

```
    print(f"List A after being extended by List B: {list_a}")
```

```
if __name__ == "__main__":
```

```
    extend()
```

```
List A: [1, 2, 3]
List B: [4, 5, 6]
List A after being extended by List B: [1, 2, 3, 4, 5, 6]
```

**6. Create an array [1,2,3,4,5]. Update the 2nd element to 99.**

```
def update():
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
my_list = [1, 2, 3, 4, 5]
```

```
print(f"Original list: {my_list}")
```

```
my_list[1] = 99
```

```
print(f"List after updating 2nd element to 99: {my_list}")
```

```
if __name__ == "__main__":
```

```
update()
```

```
Original list: [1, 2, 3, 4, 5]  
List after updating 2nd element to 99: [1, 99, 3, 4, 5]
```

**7. Create an array [10,20,30,40,50]. Use slicing to print the first three elements.**

```
def run_exercise_7():
```

```
my_list = [10, 20, 30, 40, 50]
```

```
print(f"Original list: {my_list}")
```

```
first_three = my_list[:3]
```

```
print(f"The first three elements: {first_three}")
```

```
if __name__ == "__main__":
```

```
run_exercise_7()
```

```
Original list: [10, 20, 30, 40, 50]  
The first three elements: [10, 20, 30]
```

**8. Create an array [100,200,300,400]. Reverse the array using slicing.**

```
def reverse():
```

```
my_list = [100, 200, 300, 400]
```

```
print(f"Original list: {my_list}")
```

```
reversed_list = my_list[::-1]
```

```
print(f"Reversed list: {reversed_list}")
```

```
if __name__ == "__main__":
```

```
reverse()
```

```
Original list: [100, 200, 300, 400]  
Reversed list: [400, 300, 200, 100]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

## Numpy:-

### **1D array:-**

**1. Create a 1D array of numbers from 0 to 20. Print the 5th element.**

```
import numpy as np
```

```
def index():
```

```
arr = np.arange(21)
```

```
print(f"Array: {arr}")
```

```
fifth_element = arr[4]
```

```
print(f"The 5th element (at index 4) is: {fifth_element}")
```

```
index()
```

```
Original array: [ 2  4  6  8 10]
Array after multiplying all elements by 3: [ 6 12 18 24 30]
```

**2. Create a 1D array of the first 15 odd numbers. Slice elements from index 3 to 8.**

```
import numpy as np
```

```
def slice():
```

```
odd_numbers = np.arange(1, 30, 2)
```

```
print(f"Array of 15 odd numbers: {odd_numbers}")
```

```
sliced_array = odd_numbers[3:9]
```

```
print(f"Elements from index 3 to 8: {sliced_array}")
```

```
slice()
```

```
Array (50 to 60): [50 51 52 53 54 55 56 57 58 59 60]
The first 5 elements: [50 51 52 53 54]
```

**3. Create a 1D array of numbers from 10 to 100 with a step of 10. Print the last element using negative indexing.**

```
def negative():
```

```
arr = np.arange(10, 101, 10)
```

```
print(f"Array: {arr}")
```

```
last_element = arr[-1]
```

```
print(f"The last element (using index -1) is: {last_element}")
```

```
negative()
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
Original 1D array (1x12):  
[ 0  1  2  3  4  5  6  7  8  9 10 11]  
  
Reshaped (2 rows, 6 columns) array:  
[[ 0  1  2  3  4  5]  
 [ 6  7  8  9 10 11]]
```

**4. Create a 1D array of numbers 1 to 12. Reshape it into a (3,4) array.**

```
import numpy as np
```

```
def reshape():
```

```
arr_1d = np.arange(1, 13)
```

```
print(f"Original 1D array (1x12): \n{arr_1d}")
```

```
arr_2d = arr_1d.reshape(3, 4)
```

```
print(f"\nReshaped (3 rows, 4 columns) array: \n{arr_2d}")
```

```
reshape()
```

```
Original array: [ 5 10 15 20 25]  
Array after adding 5 to all elements: [10 15 20 25 30]
```

**5. Create an array [5,10,15,20,25]. Broadcast it by adding 5 to all elements.**

```
import numpy as np
```

```
def broadcasting():
```

```
arr = np.array([5, 10, 15, 20, 25])
```

```
print(f"Original array: {arr}")
```

```
result_array = arr + 5
```

```
print(f"Array after adding 5 to all elements: {result_array}")
```

```
broadcasting()
```

```
Original 1D array (1x12):  
[ 1  2  3  4  5  6  7  8  9 10 11 12]  
  
Reshaped (3 rows, 4 columns) array:  
[[ 1  2  3  4]  
 [ 5  6  7  8]  
 [ 9 10 11 12]]
```



Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**6. Create a 1D array of 12 elements and reshape it into (2,6).**

```
import numpy as np
```

```
def reshape():
```

```
arr_1d = np.arange(12)
```

```
print(f"Original 1D array (1x12): \n{arr_1d}")
```

Name-Manuj Kovale

Roll no.- C54

```
arr_2d = arr_1d.reshape(2, 6)
```

```
print(f"\nReshaped (2 rows, 6 columns) array: \n{arr_2d}")
```

```
reshape()
```

```
Array: [ 10  20  30  40  50  60  70  80  90 100]
The last element (using index -1) is: 100
```

**7. Create a 1D array of numbers from 50 to 60. Slice the first 5 elements.**

```
import numpy as np
```

```
def slice_first():
```

```
arr = np.arange(50, 61)
```

```
print(f"Array (50 to 60): {arr}")
```

```
first_five = arr[:5]
```

```
print(f"The first 5 elements: {first_five}")
```

```
slice_first()
```

```
Array of 15 odd numbers: [ 1  3  5  7  9 11 13 15 17 19 21 23 25 27 29]
Elements from index 3 to 8: [ 7  9 11 13 15 17]
```

**8. Create a 1D array [2,4,6,8,10]. Broadcast it by multiplying with 3.**

```
import numpy as np
```

```
def broad_mult():
```

```
arr = np.array([2, 4, 6, 8, 10])
```

```
print(f"Original array: {arr}")
```

```
result_array = arr * 3
```

```
print(f"Array after multiplying all elements by 3: {result_array}")
```

```
broad_mult()
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
Array: [ 0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20]
The 5th element (at index 4) is: 4
```

## 2D array:-

1. Create a 2D array of shape (3,3) with numbers 1–9. Print the element at row 2, col 3.

```
import numpy as np
```

```
def index():
```

```
arr = np.arange(1, 10).reshape(3, 3)
```

```
print(f"3x3 Array:\n{arr}")
```

```
element = arr[1, 2]
```

```
print(f"Element at Row 2, Column 3 (index [1, 2]): {element}")
```

```
index()
```

```
3x3 Array:
[[1 2 3]
 [4 5 6]
 [7 8 9]]
Element at Row 2, Column 3 (index [1, 2]): 6
```

2. Create a 2D array of shape (4,4) with numbers 1–16. Slice the first two rows.

```
import numpy as np
```

```
def slice():
```

```
arr = np.arange(1, 17).reshape(4, 4)
```

```
print(f"4x4 Array:\n{arr}")
```

```
first_two_rows = arr[0:2, :]
```

```
print(f"\nFirst two rows:\n{first_two_rows}")
```

```
slice()
```

```
4x4 Array:
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]
 [13 14 15 16]]

First two rows:
[[1 2 3 4]
 [5 6 7 8]]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**3. Create a 2D array of shape (3,5) with numbers from 10 to 24. Slice the last column.**

```
import numpy as np
```

```
def slicelast():
```


```
arr = np.arange(10, 25).reshape(3, 5)
```

```
print(f"3x5 Array:\n{arr}")
```

```
last_column = arr[:, -1]
```

```
print(f"\nLast column:\n{last_column}")
```

```
slicelast()
```



```
3x5 Array:
[[10 11 12 13 14]
 [15 16 17 18 19]
 [20 21 22 23 24]]

Last column:
[14 19 24]
```

**4. Create a 2D array of shape (2,6). Reshape it into (3,4).**

```
import numpy as np
```

```
def reshape():
```


```
arr_2x6 = np.arange(1, 13).reshape(2, 6)
```

```
print(f"Original (2x6) Array:\n{arr_2x6}")
```

```
arr_3x4 = arr_2x6.reshape(3, 4)
```

```
print(f"\nReshaped (3x4) Array:\n{arr_3x4}")
```

```
reshape()
```



```
Original (2x6) Array:
[[ 1  2  3  4  5  6]
 [ 7  8  9 10 11 12]]

Reshaped (3x4) Array:
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**5. Create a 2D array (3×3). Slice the first row.**

```
import numpy as np
```

```
def slicefirst():
```

```
arr = np.arange(1, 10).reshape(3, 3)
```

```
print(f"3x3 Array:\n{arr}")
```

```
first_row = arr[0, :]
```

```
print(f"\nFirst row:\n{first_row}")
```

```
slicefirst()
```

```
3x3 Array:
[[1 2 3]
 [4 5 6]
 [7 8 9]]

First row:
[1 2 3]
```

**6. Create a 2D array (4×4). Slice the last two rows and last two columns (bottom-right block).**

```
import numpy as np
```

```
def sliceblock():
```

```
arr = np.arange(1, 17).reshape(4, 4)
```

```
print(f"4x4 Array:\n{arr}")
```

```
bottom_right_block = arr[2:, 2:]
```

```
print(f"\nBottom-right 2x2 block:\n{bottom_right_block}")
```

```
sliceblock()
```

```
4x4 Array:
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]
 [13 14 15 16]]

Bottom-right 2x2 block:
[[11 12]
 [15 16]]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**7. Create a 2D array of shape (2,3). Broadcast by adding [10,20,30] to each row.**

import numpy as np

def broadrowadd():

arr\_2d = np.array([[1, 2, 3], [4, 5, 6]])

print(f"Original 2x3 Array:\n{arr\_2d}")

vector\_to\_add = np.array([10, 20, 30])

print(f"\nVector to Add (1x3):\n{vector\_to\_add}")

result\_array = arr\_2d + vector\_to\_add

print(f"\nResult after row-wise addition:\n{result\_array}")

broadrowadd()

```
Original 2x3 Array:
[[1 2 3]
 [4 5 6]]

Vector to Add (1x3):
[10 20 30]

Result after row-wise addition:
[[11 22 33]
 [14 25 36]]
```

**8. Create a 2D array (3×3). Print the diagonal elements using indexing.**

import numpy as np

def diagonal():

arr = np.arange(1, 10).reshape(3, 3)

print(f"3x3 Array:\n{arr}")

diagonal\_elements = arr[[0, 1, 2], [0, 1, 2]]

print(f"\nDiagonal elements (using fancy indexing): {diagonal\_elements}")

diagonal()

```
3x3 Array:
[[1 2 3]
 [4 5 6]
 [7 8 9]]

Diagonal elements (using fancy indexing): [1 5 9]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

### 3D array:-

#### 1. Create a 3D array of shape (2,3,4) with numbers 1–24. Print element at [1,2,3].

```
import numpy as np

def a():


arr = np.arange(1, 25).reshape(2, 3, 4)

print(f"3D Array (2, 3, 4):\n{arr}")

element = arr[0, 1, 2]

print(f"\nElement at Block 1, Row 2, Column 3: {element}")

a()
```



```
3D Array (2, 3, 4):
[[[ 1  2  3  4]
  [ 5  6  7  8]
  [ 9 10 11 12]]

 [[13 14 15 16]
  [17 18 19 20]
  [21 22 23 24]]]

Element at Block 1, Row 2, Column 3: 7
```

#### 2. Create a 3D array of shape (2,2,3). Slice the first “block” (all rows/cols of index 0 along axis 0)

```
import numpy as np

Name-Manuj Kovale

Roll no.- C54

def b():

arr = np.arange(1, 13).reshape(2, 2, 3)

print(f"3D Array (2, 2, 3):\n{arr}")

first_block = arr[0, :, :]

print(f"\nFirst block (Index 0 along axis 0):{first_block}")

b()
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

3D Array (2, 2, 3):

```
[[[ 1  2  3]
   [ 4  5  6]]
```

```
[[ 7  8  9]
 [10 11 12]]]
```

First block (Index 0 along axis 0):[[1 2 3]  
[4 5 6]]

### 3. Create a 3D array (3,3,3) with numbers 1–27. Reshape it into (9,3).

import numpy as np

def c():

arr\_3d = np.arange(1, 28).reshape(3, 3, 3)

print(f"Original 3D Array (3, 3, 3): {arr\_3d}")

arr\_2d = arr\_3d.reshape(9, 3)

print(f"\nReshaped 2D Array (9, 3): {arr\_2d}")

c()

Original 3D Array (3, 3, 3): [[[ 1 2 3]  
[ 4 5 6]  
[ 7 8 9]]

```
[[10 11 12]
 [13 14 15]
 [16 17 18]]
```

```
[[19 20 21]
 [22 23 24]
 [25 26 27]]]
```

Reshaped 2D Array (9, 3): [[ 1 2 3]

```
[ 4  5  6]
 [ 7  8  9]
 [10 11 12]
 [13 14 15]
 [16 17 18]
 [19 20 21]
 [22 23 24]
 [25 26 27]]]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**4. Create a 3D array (2,3,3). Slice the second row of the first block.**

```
import numpy as np
```

```
def d():
```

```
arr = np.arange(1, 19).reshape(2, 3, 3)
```

```
print(f"3D Array (2, 3, 3):\n{arr}")
```

```
second_row_first_block = arr[0, 1, :]
```

```
print(f"\nSecond row (index 1) of the First block (index 0): {second_row_first_block}")
```

```
d()
```

```
3D Array (2, 3, 3):
[[[ 1  2  3]
   [ 4  5  6]
   [ 7  8  9]]

  [[10 11 12]
   [13 14 15]
   [16 17 18]]]
```

```
Second row (index 1) of the First block (index 0): [4 5 6]
```

**5. Create a 3D array (2,3,3). Broadcast by adding [5,10,15] to each row.**

```
import numpy as np
```

```
def e():
```

```
arr_3d = np.arange(1, 19).reshape(2, 3, 3)
```

```
print(f"Original 3D Array (2, 3, 3):\n{arr_3d}")
```

```
vector_to_add = np.array([5, 10, 15])
```

```
print(f"\nVector to Add (added to each column of every row): {vector_to_add}")
```

```
result_array = arr_3d + vector_to_add
```

```
print(f"Result after row-wise addition:\n{result_array}")
```

```
e()
```



Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

```
Original 3D Array (2, 3, 3):  
[[[ 1  2  3]  
   [ 4  5  6]  
   [ 7  8  9]]  
  
   [[10 11 12]  
    [13 14 15]  
    [16 17 18]]]  
  
Vector to Add (added to each column of every row): [ 5 10 15]  
Result after row-wise addition:  
[[[ 6 12 18]  
   [ 9 15 21]  
   [12 18 24]]  
  
   [[15 21 27]  
    [18 24 30]  
    [21 27 33]]]
```

**6. Create a 3D array (2,2,4) with numbers from 1 to 16. Slice the last two columns of all blocks.**

```
import numpy as np
```

```
def f():
```

```
arr = np.arange(1, 17).reshape(2, 2, 4)
```

```
print(f"3D Array (2, 2, 4):\n{arr}")
```

```
last_two_columns = arr[:, :, -2:]
```

```
print(f"\nArray containing only the last two columns from all blocks:\n{last_two_columns}")
```

```
f()
```

```
3D Array (2, 2, 4):  
[[[ 1  2  3  4]  
   [ 5  6  7  8]]  
  
   [[ 9 10 11 12]  
    [13 14 15 16]]]  
  
Array containing only the last two columns from all blocks:  
[[[ 3  4]  
   [ 7  8]]  
  
   [[11 12]  
    [15 16]]]
```

Name : Vaishnavi shinde

Roll No.: C-28

SPP-II

**Create a 3D array (2,3,2). Print the element at [0,1,1].**

```
import numpy as np
def g():
arr = np.arange(1, 13).reshape(2, 3, 2)
print(f"3D Array (2, 3, 2):\n{arr}")
element = arr[0, 1, 1]
print(f"\nElement at Index [0, 1, 1]: {element}")
g()
```

```
3D Array (2, 3, 2):
[[[ 1  2]
  [ 3  4]
  [ 5  6]]

 [[ 7  8]
  [ 9 10]
  [11 12]]]

Element at Index [0, 1, 1]: 4
```

**7. Create a 3D array (3,2,2). Reshape it into (2,3,2).**

```
import numpy as np
def h():
arr_original = np.arange(1, 13).reshape(3, 2, 2)
print(f"Original 3D Array (3, 2, 2):\n{arr_original}")
arr_resaped = arr_original.reshape(2, 3, 2)
print(f"Reshaped 3D Array (2, 3, 2): {arr_resaped}")
h()
```

```
Original 3D Array (3, 2, 2):
[[[ 1  2]
  [ 3  4]]

 [[ 5  6]
  [ 7  8]]

 [[ 9 10]
  [11 12]]]
Reshaped 3D Array (2, 3, 2): [[[ 1  2]
  [ 3  4]
  [ 5  6]]

 [[ 7  8]
  [ 9 10]
  [11 12]]]
```