

Module 5: Networking Fundamentals

Agenda

- * **Basic linux native technologies.**
- * **Neutron working**
- * **Neutron Agents**
- * **Virtual Devices in openstack architecture**
- * **Network Packet Flow.**
- * **Managing Network**

Why this session ??

Neutron is a core component

Neutron is a hard to follow component

Understanding is key to troubleshooting

Before we start

Five main concept/linux virtual network devices

- tap devices
- veth pair
- Linux bridge
- Openvswitch
- Network namespaces

What does neutron do ?

- **Allow user to create networks and routers**
- **Provides an api and manages the database**
- **Route L3 traffic**
- **Provide Floating IP's**
- **Switches L2 traffic**
- **Provides DHCP to instances**
- **Provides metadata to instances**

Neutron - Agents

AGENT	FEATURE
L3 agent	Provides external access to the OpenStack environment, including support for floating IP addresses, which allow external access to the instances running on the OpenStack environment.
DHCP agent	Provides support for subnets created using the OpenStack networking service. This agent starts a new DHCP service running in the namespace for each subnet being created. It provides the range of IP addresses this subnet has been created with.
Metadata agent	Provides information services for the instances that are being created to gain information about its configuration.
Open vSwitch agent	Manages the Open vSwitch plug-in for Neutron.

Virtual switches and interfaces


OPEN VSWITCH CONFIGURATION	
br-int	Provides both ingress and egress VLAN tagging for instance traffic.
br-ex	Provides an external bridge and connects to qg of the qrouter via a tap interface.
qg	Connects the router to the gateway.
qr	Connects the router to the integration bridge br-int .
qvo	Connects to the integration bridge.
qvb	Connects the firewall bridge to br-int via qvo .
qbr	Linux bridge to provide OpenStack security groups.

Packet Flow in Neutron ??

- **Instance - Instance, same network**
 - **Instances living on same compute host**
 - **Instances living on different host**
- **Instance - Instance, different Network**
- **Instance - dhcp**
- **Instance - Public Network**
- **End User - Instance using Floating IP**


Instance - to - Instance

- > On Same Compute node





Instance to Instance Different Host



Full Flow

