

CSA0501

DATABASE MANAGEMENT SYSTEMS

LAB EXPERIMENT

V SANDEEP

192525235

EXPERIMENT – 11

AIM

To create and use an **AUTO_INCREMENT sequence** in the Bike Showroom database.

Procedure

1. Open **MySQL Workbench**.
2. Connect to your MySQL server.
3. Select the BikeShowroomDB database.
4. Create a table with an AUTO_INCREMENT primary key.
5. Insert records without specifying the ID.
6. MySQL automatically generates the ID.
7. Verify the generated IDs using SELECT.
8. Manually insert a value into the ID column.
9. Remove the AUTO_INCREMENT property.
10. Verify the table after each operation.

QUESTIONS & OUTPUTS :

1. Populate Bike ID using AUTO_INCREMENT.
2. Manually populate Bike ID.
3. Drop the AUTO_INCREMENT.

1. Populate Bike ID using AUTO_INCREMENT

```
4      Bike_ID INT AUTO_INCREMENT PRIMARY KEY,
5      Bike_Name VARCHAR(50),
6      Brand VARCHAR(50),
7      Price DECIMAL(10,2)
8  );
9  • INSERT INTO auto_bike_data (Bike_Name, Brand, Price)
10 VALUES
11 ('Apache RTR 200', 'TVS', 145000),
12 ('Pulsar NS200', 'Bajaj', 165000),
13 ('Classic 350', 'Royal Enfield', 225000),
14 ('R15 V4', 'Yamaha', 190000);
15 • SELECT * FROM auto_bike_data;
```

Result Grid

Bike_ID	Bike_Name	Brand	Price
1	Apache RTR 200	TVS	145000.00
2	Pulsar NS200	Bajaj	165000.00
3	Classic 350	Royal Enfield	225000.00
4	R15 V4	Yamaha	190000.00
5	Apache RTR 200	TVS	145000.00
6	Pulsar NS200	Bajaj	165000.00
7	Classic 350	Royal Enfield	225000.00

auto_bike_data 2 x

Apply Revert Context Help

Output

Action Output

#	Time	Action	Message
✓ 1	18:09:05	USE BikeShowroomDB	0 row(s) affected
✓ 2	18:09:05	CREATE TABLE auto_bike_data (Bike_ID INT AUTO_INCREMENT PRIMARY KEY, Bike_Name VARCHAR(50), Brand VARCHAR(50), Price...	0 row(s) affected
✓ 3	18:09:05	INSERT INTO auto_bike_data (Bike_Name, Brand, Price) VALUES (Apache RTR 200', 'TVS', 145000), (Pulsar NS200', 'Bajaj', 165000), (Classic 350', '...	4 row(s) affected Records: 4 Duplicates: 0 Warnings: 0
✓ 4	18:09:05	SELECT * FROM auto_bike_data LIMIT 0, 1000	4 row(s) returned

2. Manually populate Bike ID.

```
1 • INSERT INTO auto_bike_data
2 (Bike_ID, Bike_Name, Brand, Price)
3 VALUES
4 (10, 'Duke 390', 'KTM', 325000);
5 • SELECT * FROM auto_bike_data;
```

Result Grid

Bike_ID	Bike_Name	Brand	Price
1	Apache RTR 200	TVS	145000.00
2	Pulsar NS200	Bajaj	165000.00
3	Classic 350	Royal Enfield	225000.00
4	R15 V4	Yamaha	190000.00
5	Apache RTR 200	TVS	145000.00
6	Pulsar NS200	Bajaj	165000.00
7	Classic 350	Royal Enfield	225000.00

auto_bike_data 3 x

Apply Rev

Output

Action Output

#	Time	Action	Message
✓ 1	18:09:55	INSERT INTO auto_bike_data (Bike_ID, Bike_Name, Brand, Price) VALUES (10, 'Duke 390', 'KTM', 325000)	1 row(s) affected
✓ 2	18:09:55	SELECT * FROM auto_bike_data LIMIT 0, 1000	9 row(s) returned

3.Drop the AUTO_INCREMENT

```
1 • ALTER TABLE auto_bike_data
2   MODIFY Bike_ID INT NOT NULL;
3 • SHOW CREATE TABLE auto_bike_data;
4 • SELECT * FROM auto_bike_data;
```

Bike_ID	Bike_Name	Brand	Price
1	Apache RTR 200	TVS	145000.00
2	Pulsar NS200	Bajaj	165000.00
3	Classic 350	Royal Enfield	225000.00
4	R15 V4	Yamaha	190000.00
5	Apache RTR 200	TVS	145000.00
6	Pulsar NS200	Bajaj	165000.00
7	Classic 350	Royal Enfield	225000.00

Result 4 auto_bike_data 5 x Apply Ri

Output

#	Time	Action	Message
✓ 1	18:10:56	ALTER TABLE auto_bike_data MODIFY Bike_ID INT NOT NULL	9 row(s) affected Records: 9 Duplicates: 0 Warnings: 0
✓ 2	18:10:56	SHOW CREATE TABLE auto_bike_data	1 row(s) returned
✓ 3	18:10:56	SELECT * FROM auto_bike_data LIMIT 0, 1000	9 row(s) returned

RESULT

Thus, the **AUTO_INCREMENT sequence** was successfully created, records were populated automatically and manually, and the AUTO_INCREMENT property was removed from the table