

# Knowledge-base import autotests

---

Tests for the knowledge-base import that runs on container startup (PR #168): the `scripts/import_knowledge.sh` gating logic and the entrypoint wiring that triggers it.

- `test_import_knowledge.py` — unit tests for `scripts/import_knowledge.sh`, with the `import-knowledge` binary stubbed on PATH.
- `test_import_knowledge_integration.py` — startup tests that launch the image through `scripts/omegaclaw` and check the entrypoint gating and that a local import lands in the `chroma_db` the agent reads.

## Build the image

---

The integration tests need a locally built image. Build it from the repository root:

```
docker build -t omegaclaw:kb-test .
```

The unit tests need no image.

## Run

---

Unit:

```
cd Autotests
pytest -s import_knowledge/test_import_knowledge.py
```

Integration (point `OMEGACLAW_KB_IMAGE` at the image built above):

```
cd Autotests
OMEGACLAW_KB_IMAGE=omegaclaw:kb-test pytest -s import_knowledge/test_import_knowledge_integration.py
```

The integration tests start and remove the container themselves through `scripts/omegaclaw` (fixed name `omegaclaw`, one at a time), so there is no manual `docker run` step. They are skipped unless `OMEGACLAW_KB_IMAGE` is set and Docker and `scripts/omegaclaw` are available.

## Tests description

---

# Unit: scripts/import\_knowledge.sh

---

The script reads `EMBEDDING_PROVIDER`, runs `import-knowledge` (or `import-knowledge --local`), and writes a per-provider sentinel under `CHROMA_DB_PATH` so a second start skips the import. The stub on `PATH` records how `import-knowledge` was called.

## 1. test\_local\_runs\_import\_and\_writes\_sentinel

Local provider runs the import and leaves the local sentinel behind.

- Checks: exit 0; the stub was called with `--local`; `.import-kb.local.done` exists; stdout reports `Import complete`.

## 2. test\_openai\_with\_key\_runs\_import\_and\_writes\_sentinel

OpenAI with `OPENAI_API_KEY` set runs the import and leaves the OpenAI sentinel.

- Checks: exit 0; the stub was called without `--local`; `.import-kb.openai.done` exists.

## 3. test\_openai\_without\_key\_exit1

OpenAI without a key stops before importing.

- Checks: exit 1; stderr says `OPENAI_API_KEY is required`; the stub was never called.

## 4. test\_unknown\_provider\_exit1

A provider the script doesn't know is rejected.

- Checks: exit 1; stderr says `Unsupported`; the stub was never called.

## 5. test\_provider\_case\_insensitive

The provider name is matched regardless of case (`openai` / `OpenAI` / `OPENAI`, `local` / `Local` / `LOCAL`).

- Checks: exit 0; the sentinel for the matching provider is written. Parametrized over the six spellings.

## 6. test\_existing\_sentinel\_skips\_import

A sentinel already present means the import is skipped.

- Checks: exit 0; stdout says `skipping`; the stub was never called.

## 7. test\_force\_reimports\_despite\_sentinel

`IMPORT_KB_FORCE=1` re-runs the import even with the sentinel present.

- Checks: exit 0; the stub was called with `--local` .

## 8. test\_local\_openai\_sentinels\_independent

Local and OpenAI track separate sentinels, so one being done doesn't block the other.

- Checks: with `.import-kb.local.done` already present, OpenAI still imports and writes `.import-kb.openai.done` .

## 9. test\_custom\_chroma\_path

`CHROMA_DB_PATH` sends the DB directory and its sentinel to a custom location.

- Checks: the custom directory is created; the sentinel lands inside it.

## 10. test\_failed\_import\_does\_not\_write\_sentinel

When `import-knowledge` exits non-zero, no sentinel is written, so the next start retries instead of masking the failure.

- Checks: non-zero exit; the stub was called; `.import-kb.local.done` is absent.

## Integration: container startup

---

They launch the image through `scripts/omegaclaw` , so the real entrypoint runs (nginx, env scrub, import gating).

## 11. test\_entrypoint\_imports\_when\_enabled

With `IMPORT_KB_ON_START=1` the entrypoint starts the import on boot.

- Checks: `[import-kb] Running` appears in the container log within 180 s.

## 12. test\_entrypoint\_skips\_when\_disabled

With `IMPORT_KB_ON_START=0` the entrypoint never touches import-kb.

- Checks: after a 25 s window no `[import-kb]` line appears in the log.

## 13. test\_local\_real\_import\_runs

A real local import runs and lands in the same `chroma_db` the agent reads from.

- Checks: the log shows `Running import-knowledge with local embeddings` and `Generating local` ; inside the container `/PeTTa/chroma_db` resolves to `$MEMORY_DIR/chroma_db` , so the import target is the path the agent queries.