DESCRIPTION:

With high ability to withstand the shock loading of large current, **VSA04-S23** triacs provide high dv/dt rate with strong resistance to electromagnetic interface. With high commutation performances, 3 quadrants products especially recommended for use on inductive load.

MAIN FEATURES



Symbol	Value	Unit
V_{DRM}/V_{RRM}	600/800	V
$I_{T(RMS)}$	1	A

ABSOLUTE MAXIMUM RATINGS

Parameter		Symbol	Value	Unit
Storage junction temperature range		T_{stg}	-40 - 150	℃
Operating junction temperature range		T_j	-40 - 125	℃
Repetitive peak off-state voltage (T_j=25℃)		V_{DRM}	600/800	V
Repetitive peak reverse voltage (T_j=25℃)		V_{RRM}	600/800	V
RMS on-state current	SOT-223/ SOT-223-2L (T_C=70℃)	$I_{T(RMS)}$	1	A
Non repetitive surge peak on-state current (full cycle, F=50Hz)		I_{TSM}	25	A
I^2t value for fusing (tp=10ms)		I^2t	3.1	A^2s
Critical rate of rise of on-state current (I_G =2×I_{GT})		dI/dt	50	A/μs
Peak gate current		I_{GM}	1	A
Average gate power dissipation		$P_{G(AV)}$	0.1	W
Peak gate power		P_{GM}	0.5	W

ELECTRICAL CHARACTERISTICS (T_j=25℃ unless otherwise specified)

Symbol	Test Condition	Quadrant		Value				Unit
				TW	SW	CW	BW	
I_{GT}	V_D =12V R_L =33Ω	Ⅰ-Ⅱ-Ⅲ	MAX	5	10	35	50	mA
V_{GT}		Ⅰ-Ⅱ-Ⅲ	MAX	1.3				V
V_{GD}	V_D =V_{DRM} T_j =125℃ R_L =3.3KΩ	Ⅰ-Ⅱ-Ⅲ	MIN	0.2				V
I_L	I_G =1.2I_{GT}	Ⅰ-Ⅲ	MAX	10	20	50	70	mA
		Ⅱ		15	35	60	80	
I_H	I_T =100mA		MAX	10	15	35	60	mA
dV/dt	V_D=2/3V_{DRM} Gate Open T_j =125℃		MIN	50	100	500	1000	V/μs

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)	Unit
V_{TM}	I_{TM} =5.5A tp=380μs	T_j=25℃	1.5	V
I_{DRM}	V_D =V_{DRM} V_R =V_{RRM}	T_j=25℃	10	μA
I_{RRM}		T_j=125℃	0.75	mA

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	junction to case(AC)	SOT-223/ SOT-223-2L	4.1	℃/W
$R_{th(j-a)}$	junction to ambient		60	

FIG.1: Maximum power dissipation versus RMS on-state current



FIG.2: RMS on-state current versus ambient temperature (printed circuit board FR4, copper thickness:35μm)(full cycle)



FIG.3: Surge peak on-state current versus number of cycles



FIG.4: On-state characteristics (maximum values)



FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp<20ms and corresponding value of I^2t (dI/dt < 50A/μs)



FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature