Description

The series of devices uses **Super Trench II** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g. This device is ideal for high-frequency switching and synchronous rectification.

Application

● DC/DC Converter

● Ideal for high-frequency switching and synchronous rectification

General Features

● V_{DS} =100V, I_D =125A

  $R_{DS(ON)}$=4.2mΩ , typical (TO-220)@ V_{GS}=10V

  $R_{DS(ON)}$=4.0mΩ , typical (TO-263)@ V_{GS}=10V

● Excellent gate charge x $R_{DS(on)}$ product(FOM)

● Very low on-resistance $R_{DS(on)}$

● 175°C operating temperature

● Pb-free lead plating

| TO-263 | TO-220C | Schematic Diagram |

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST10N040-T3	VST10N040	TO-220C	-	-	-
VST10N040-TC	VST10N040	TO-263	-	-	-

Absolute Maximum Ratings (T_C=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	125	A
Drain Current-Continuous(T_C=100℃)	I_D (100℃)	95	A
Pulsed Drain Current	I_{DM}	500	A
Maximum Power Dissipation	P_D	200	W
Derating factor		1.33	W/℃
Single pulse avalanche energy [Note 5]	E_{AS}	871	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 175	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Case[Note 2]	$R_{θJC}$	0.75	℃/W

Electrical Characteristics (T_C=25℃ unless otherwise noted)

Parameter	Symbol	Condition		Min	Typ	Max	Unit
Off Characteristics							
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250µA		100		-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=100V,V_{GS}=0V		-	-	1	µA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V		-	-	±100	nA
On Characteristics [Note 3]							
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250µA		2	3	4	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=60A	TO-220	-	4.2	4.5	mΩ
			TO-263		4.0	4.5	
Forward Transconductance	g_{FS}	V_{DS}=5V,I_D=60A			120	-	S
Dynamic Characteristics [Note4]							
Input Capacitance	C_{Iss}	V_{DS}=50V,V_{GS}=0V, F=1.0MHz		-	5500	-	PF
Output Capacitance	C_{oss}			-	590	-	PF
Reverse Transfer Capacitance	C_{rss}			-	25	-	PF
Switching Characteristics [Note 4]							
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=50V,I_D=60A, V_{GS}=10V,R_G=3Ω		-	21	-	nS
Turn-on Rise Time	t_r			-	13	-	nS
Turn-Off Delay Time	$t_{d(off)}$			-	40	-	nS
Turn-Off Fall Time	t_f			-	12	-	nS
Total Gate Charge	Q_g	V_{DS}=50V,I_D=60A, V_{GS}=10V		-	92	-	nC
Gate-Source Charge	Q_{gs}			-	27		nC
Gate-Drain Charge	Q_{gd}			-	21		nC
Drain-Source Diode Characteristics							
Diode Forward Voltage [Note 3]	V_{SD}	V_{GS}=0V,I_S=60A		-		1.2	V
Diode Forward Current [Note 2]	I_S			-	-	125	A
Reverse Recovery Time	t_{rr}	T_J = 25°C, I_F =60A di/dt = 100A/µs [Note3]		-	72	-	nS
Reverse Recovery Charge	Q_{rr}			-	140	-	nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300µs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production
5. EAS condition : Tj=25℃,V_{DD}=50V,V_G=10V,L=0.5mH,Rg=25Ω

## Typical Electrical and Thermal Characteristics


**Figure 1 Output Characteristics**

**Figure 2 Transfer Characteristics**

Figure 3 Rdson- Drain Current

Figure 4 Rdson-Junction Temperature

Figure 5 Gate Charge

Figure 6 Source- Drain Diode Forward

**Figure 7 Capacitance vs Vds**

Figure 9 Power De-rating

Figure 8 Safe Operation Area

Figure 10 Current De-rating

Figure 11 Normalized Maximum Transient Thermal Impedance