Description

The VSM60P05N uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge .This device is well suited for use as a load switch or in PWM applications.

General Features

- V_{DS} =-60V,I_D =-5A
  $R_{DS(ON)}$ <65mΩ @ V_{GS}=-10V
  $R_{DS(ON)}$ <85mΩ @ V_{GS}=-4.5V
- High density cell design for ultra low Rdson
- Fully characterized avalanche voltage and current
- Excellent package for good heat dissipation

Application

- Load switch
- PWM application



SOT-23-6



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VSM60P05N-S6	VSM60P05N	SOT-23-6	Ø180mm	8 mm	3000 units

Absolute Maximum Ratings (T_C=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	-5	A
Pulsed Drain Current	I_{DM}	-20	A
Maximum Power Dissipation	P_D	3.1	W
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 150	℃

Thermal Characteristic

Thermal Resistance, Junction-to-Ambient(Note 2)	$R_{\theta JA}$	40.3	℃/W

Electrical Characteristics (T_C=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						

Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=-250μA	-60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-60V,V_{GS}=0V	-	-	-1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250μA	-1.0	-1.5	-2.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-5A	-	55	65	mΩ
		V_{GS}=-4.5V, I_D=-5A	-	70	85	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V,I_D=-5A	-	10	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=-30V,V_{GS}=0V, F=1.0MHz	-	1153	-	PF
Output Capacitance	C_{oss}		-	93.7	-	PF
Reverse Transfer Capacitance	C_{rss}		-	77.7	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=-30V, R_L=6Ω, V_{GS}=-10V,R_G=3Ω	-	8	-	nS
Turn-on Rise Time	t_r		-	5	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	32	-	nS
Turn-Off Fall Time	t_f		-	8	-	nS
Total Gate Charge	Q_g	V_{DS}=-30,I_D=-5A, V_{GS}=-10V	-	15.8	-	nC
Gate-Source Charge	Q_{gs}		-	2.7	-	nC
Gate-Drain Charge	Q_{gd}		-	3.5	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=-5A	-		-1.2	V
Diode Forward Current (Note 2)	I_S		-	-	-5	A
Reverse Recovery Time	t_{rr}	T_J = 25°C, I_F =- 5A di/dt = -100A/μs(Note3)	-	27		nS
Reverse Recovery Charge	Qrr		-	32		nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

Test Circuit

1）E_{AS} test Circuit



2）Gate charge test Circuit



3）Switch Time Test Circuit



Typical Electrical and Thermal Characteristics (Curves)



Figure 1 Output Characteristics



Figure 2 Transfer Characteristics



Figure 3 Rdson- Drain Current



Figure 4 Rdson-Junction Temperature



Figure 5 Gate Charge



Figure 6 Source- Drain Diode Forward



Figure 7 Capacitance vs Vds



Figure 8 Safe Operation Area



Figure 9 BV_{DSS} vs Junction Temperature



Figure 10 ID Current De-rating



Figure 11 Normalized Maximum Transient Thermal Impedance