## Description

The VSM2308 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. This device is suitable for use as a Battery protection or in other switching application.

## General Features

- $V_{DS}$ =60V,$I_D$ =2A
  $R_{DS(ON)}$ <140mΩ @ $V_{GS}$=10V
  $R_{DS(ON)}$ < 190mΩ @ $V_{GS}$=4.5V
- High power and current handing capability
- Lead free product is acquired
- Surface mount package

## Application

- Battery switch
- DC/DC converter


SOT-23-3




Schematic Diagram

## Package Marking and Ordering Information

| Device Marking | Device | Device Package | Reel Size | Tape width | Quantity |
|---|---|---|---|---|---|
| VSM2308-S2 | VSM2308 | SOT-23-3 | Ø180mm | 8 mm | 3000 units |

## Absolute Maximum Ratings ($T_A$=25℃unless otherwise noted)

| Parameter | Symbol | Limit | Unit |
|---|---|---|---|
| Drain-Source Voltage | $V_{DS}$ | 60 | V |
| Gate-Source Voltage | $V_{GS}$ | ±20 | V |
| Drain Current-Continuous | $I_D$ | 2.0 | A |
| Drain Current-Pulsed (Note 1) | $I_{DM}$ | 8 | A |
| Maximum Power Dissipation | $P_D$ | 1.6 | W |
| Operating Junction and Storage Temperature Range | $T_J$,$T_{STG}$ | -55 To 150 | ℃ |

## Thermal Characteristic

| | | | |
|---|---|---|---|
| Thermal Resistance,Junction-to-Ambient (Note 2) | $R_{\theta JA}$ | 78 | ℃/W |

## Electrical Characteristics ($T_A$=25℃unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **Off Characteristics** | | | | | | |
| Drain-Source Breakdown Voltage | $BV_{DSS}$ | $V_{GS}$=0V $I_D$=250μA | 60 | - | - | V |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$=60V,$V_{GS}$=0V | - | - | 1 | μA |

| | | | | | | |
|---|---|---|---|---|---|---|
| Gate-Body Leakage Current | $I_{GSS}$ | $V_{GS}$=±20V,$V_{DS}$=0V | - | - | ±100 | nA |
| **On Characteristics** (Note 3) | | | | | | |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}$=$V_{GS}$,$I_D$=250μA | 1.0 | 1.5 | 2.0 | V |
| Drain-Source On-State Resistance | $R_{DS(ON)}$ | $V_{GS}$=10V, $I_D$=2A | - | 125 | 140 | mΩ |
| | | $V_{GS}$=4.5V, $I_D$=2A | - | 150 | 190 | mΩ |
| Forward Transconductance | $g_{FS}$ | $V_{DS}$=5V,$I_D$=2A | - | 3 | - | S |
| **Dynamic Characteristics** (Note4) | | | | | | |
| Input Capacitance | $C_{lss}$ | $V_{DS}$=30V,$V_{GS}$=0V, F=1.0MHz | - | 384 | - | PF |
| Output Capacitance | $C_{oss}$ | | - | 25 | - | PF |
| Reverse Transfer Capacitance | $C_{rss}$ | | - | 20 | - | PF |
| **Switching Characteristics** (Note 4) | | | | | | |
| Turn-on Delay Time | $t_{d(on)}$ | $V_{DD}$=30V,$I_D$=2A $V_{GS}$=10V,$R_{GEN}$=1Ω | - | 8 | - | nS |
| Turn-on Rise Time | $t_r$ | | - | 6 | - | nS |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 12 | - | nS |
| Turn-Off Fall Time | $t_f$ | | - | 4 | - | nS |
| Total Gate Charge | $Q_g$ | $V_{DS}$=30V,$I_D$=2A, $V_{GS}$=10V | - | 11.9 | - | nC |
| Gate-Source Charge | $Q_{gs}$ | | - | 2.0 | - | nC |
| Gate-Drain Charge | $Q_{gd}$ | | - | 1.3 | - | nC |
| **Drain-Source Diode Characteristics** | | | | | | |
| Diode Forward Voltage (Note 3) | $V_{SD}$ | $V_{GS}$=0V,$I_S$=2A | - | - | 1.2 | V |
| Diode Forward Current (Note 2) | $I_S$ | | - | - | 2 | A |

## Notes:

**1.** Repetitive Rating: Pulse width limited by maximum junction temperature.
**2.** Surface Mounted on FR4 Board, t ≤ 10 sec.
**3.** Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
**4.** Guaranteed by design, not subject to production

## Typical Electrical and Thermal Characteristics




**Figure 1:Switching Test Circuit**




**Figure 2:Switching Waveforms**




**Figure 3 Power Dissipation**




**Figure 4 Drain Current**




**Figure 5 Output Characteristics**




**Figure 6 Drain-Source On-Resistance**




**Figure 7 Transfer Characteristics**




**Figure 8 Drain-Source On-Resistance**




**Figure 9 Rdson vs Vgs**




**Figure 10 Capacitance vs Vds**




**Figure 11 Gate Charge**




**Figure 12 Source- Drain Diode Forward**




**Figure 13 Safe Operation Area**




**Figure 14 Normalized Maximum Transient Thermal Impedance**