Description

The VSM3401BY uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a load switch or in PWM applications.

General Features

- V_{DS} = -30V,I_D = -4.4A
  $R_{DS(ON)}$ < 70mΩ @ V_{GS}=-2.5V
  $R_{DS(ON)}$ < 55mΩ @ V_{GS}=-4.5V
  $R_{DS(ON)}$ < 45mΩ @ V_{GS}=-10V
- High power and current handing capability
- Lead free product is acquired
- Surface mount package

Application

- PWM applications
- Load switch
- Power management

SOT-23-3



Schematic Diagram

Package Marking And Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VSM3401BY-S2	VSM3401BY	SOT-23-3	Ø180mm	8 mm	3000 units

Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±12	V
Drain Current-Continuous	I_D	-4.4	A
Drain Current-Continuous(T_C=100℃)	I_D (100℃)	-3.1	A
Drain Current-Pulsed (Note 1)	I_{DM}	-30	A
Maximum Power Dissipation	P_D	1.3	W
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 150	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Ambient (Note 2)	$R_{\theta JA}$	96	℃/W

Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=-250μA	-30		-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-24V,V_{GS}=0V	-	-	-1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±12V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250μA	-0.6	-0.9	-1.2	V

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-4A	-	33	45	mΩ
		V_{GS}=-4.5V, I_D=-3A	-	37.5	55	mΩ
		V_{GS}=-2.5V, I_D=-2A		55	70	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V,I_D=-4A	-	10	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=-15V,V_{GS}=0V, F=1.0MHz	-	909.5	-	PF
Output Capacitance	C_{oss}		-	90.3	-	PF
Reverse Transfer Capacitance	C_{rss}		-	71	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=-15V,I_D=-4A V_{GS}=-10V,R_{GEN}=6Ω	-	7	-	nS
Turn-on Rise Time	t_r		-	3.5	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	35	-	nS
Turn-Off Fall Time	t_f		-	10	-	nS
Total Gate Charge	Q_g	V_{DS}=-15V,I_D=-4A,V_{GS}=-4.5V	-	7.3	-	nC
Gate-Source Charge	Q_{gs}		-	1.1	-	nC
Gate-Drain Charge	Q_{gd}		-	2	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=-4A	-	-	-1.2	V

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

Typical Electrical and Thermal Characteristics



Figure 1:Switching Test Circuit



Figure 2:Switching Waveforms



Figure 3 Power Dissipation



Figure 4 Drain Current



Figure 5 Output Characteristics



Figure 6 Drain-Source On-Resistance



Figure 7 Transfer Characteristics



Figure 8 Drain-Source On-Resistance



Figure 9 Rdson vs Vgs



Figure 10 Capacitance vs Vds



Figure 11 Gate Charge



Figure 12 Source- Drain Diode Forward



-Vds Drain-Source Voltage (V)

Figure 13 Safe Operation Area



Square Wave Pluse Duration(sec)

Figure 14 Normalized Maximum Transient Thermal Impedance