Description

The VST08N088 uses **Super Trench** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g. This device is ideal for high-frequency switching and synchronous rectification.

General Features

- V_{DS} =88V,I_D =14A
  $R_{DS(ON)}$=8.8mΩ (typical) @ V_{GS}=10V
  $R_{DS(ON)}$=9.8mΩ (typical) @ V_{GS}=4.5V
- Excellent gate charge x $R_{DS(on)}$ product(FOM)
- Very low on-resistance $R_{DS(on)}$
- 150 °C operating temperature
- Pb-free lead plating
- 100% UIS tested

Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

SOP-8



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST08N088-S8	VST08N088	SOP-8	Ø330mm	12mm	4000 units

Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	88	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	14	A
Drain Current-Continuous(T_C=100℃)	I_D (100℃)	10	A
Pulsed Drain Current	I_{DM}	56	A
Maximum Power Dissipation	P_D	3.5	W
Single pulse avalanche energy (Note 5)	E_{AS}	230	mJ
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 150	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Ambient(Note 2)	$R_{\theta JA}$	41.7	℃/W

Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250μA	88	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=88V,V_{GS}=0V	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250μA	1.2	1.7	2.2	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=14A	-	8.8	10.2	mΩ
		V_{GS}=4.5V, I_D=10A	-	9.8	11.2	mΩ
Forward Transconductance	g_{FS}	V_{DS}=5V,I_D=14A	-	30	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=40V,V_{GS}=0V, F=1.0MHz	-	3696		PF
Output Capacitance	C_{oss}		-	250		PF
Reverse Transfer Capacitance	C_{rss}		-	40		PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=40V,I_D=14A V_{GS}=10V,R_G=1.6Ω	-	11	-	nS
Turn-on Rise Time	t_r		-	7	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	30	-	nS
Turn-Off Fall Time	t_f		-	4	-	nS
Total Gate Charge	Q_g	V_{DS}=40V,I_D=14A, V_{GS}=10V	-	54	-	nC
Gate-Source Charge	Q_{gs}		-	13	-	nC
Gate-Drain Charge	Q_{gd}		-	7	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=14A	-	-	1.2	V
Diode Forward Current (Note 2)	I_S		-	-	14	A
Reverse Recovery Time	t_{rr}	T_J = 25°C, I_F = I_S di/dt = 100A/μs (Note3)	-	78	-	nS
Reverse Recovery Charge	Qrr		-	149	-	nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

Test Circuit

1) E_{AS} test Circuit



2) Gate charge test Circuit



3) Switch Time Test Circuit



Typical Electrical and Thermal Characteristics



Figure 1 Output Characteristics



Figure 2 Transfer Characteristics



Figure 3 Rdson- Drain Current



Figure 4 Rdson-Junction Temperature



Figure 5 Gate Charge



Figure 6 Source- Drain Diode Forward



Figure 7 Capacitance vs Vds



Figure 9 Power De-rating



Figure 8 Safe Operation Area



Figure 10 Current De-rating



Figure 11 Normalized Maximum Transient Thermal Impedance